
auxjad Documentation

Release 0.6.1

Gilberto Agostinho

May 16, 2020

CONTENTS

1	The auxjad package	1
1.1	auxjad	1
2	auxjad's contents	3
2.1	auxjad.are_containers_equal	4
2.2	auxjad.are_leaves_tieable	5
2.3	auxjad.ArtificialHarmonic	6
2.4	auxjad.CartographyContainer	10
2.5	auxjad.close_container	14
2.6	auxjad.fill_with_rests	17
2.7	auxjad.HarmonicNote	21
2.8	auxjad.is_container_full	24
2.9	auxjad.LeafDynMaker	25
2.10	auxjad.LeafShuffler	29
2.11	auxjad.LoopWindow	38
2.12	auxjad.LoopWindowByElements	48
2.13	auxjad.LoopWindowByList	57
2.14	auxjad.remove_repeated_dynamics	61
2.15	auxjad.remove_repeated_time_signatures	68
2.16	auxjad.rests_to_multimeasure_rest	70
2.17	auxjad.simplified_time_signature_ratio	72
2.18	auxjad.sync_containers	72
2.19	auxjad.TenneysContainer	81
2.20	auxjad.underfull_duration	85
3	Indices and tables	87
	Python Module Index	89
	Index	91

THE AUXJAD PACKAGE

1.1 auxjad

Auxiliary functions and classes for Abjad 3.1. All classes and functions have a `__doc__` attribute with usage instructions.

Documentation is available at <https://gilberthasnofb.github.io/auxjad-docs/>. A pdf version of the documentation is also available in the *docs* directory.

Bugs can be reported to <https://github.com/gilberthasnofb/auxjad/issues>.

This library is published under the MIT License.

AUXJAD'S CONTENTS

Below is a table with all classes and functions included in `auxjad`. Click on their their names or use the left side panel to navigate to the individual documentaion of each class and function.

<code>auxjad.are_containers_equal(container1, ...)</code>	A comparator function returning <code>True</code> when two containers are identical and <code>False</code> when they are not.
<code>auxjad.are_leaves_tieable(leaf1, leaf2)</code>	A comparator function returning <code>True</code> when two leaves have identical pitches and thus can be tied, otherwise returning <code>False</code> .
<code>auxjad.ArtificialHarmonic(*arguments, ...)</code>	Creates an <code>abjad.Chord</code> with a tweaked top note head for notating artificial harmonics.
<code>auxjad.CartographyContainer(container, *, ...)</code>	A container used to store, manipulate, and select objects using a decaying weighted function.
<code>auxjad.close_container(container)</code>	Changes the time signature of the last bar of an under-full <code>abjad.Container</code> in order to make it full, if necessary.
<code>auxjad.fill_with_rests(container)</code>	Fills an <code>abjad.Container</code> with rests in order to make it full.
<code>auxjad.HarmonicNote(*arguments, multiplier, ...)</code>	Creates an <code>abjad.Note</code> with tweaked notehead for harmonics.
<code>auxjad.is_container_full(container)</code>	Checks if an <code>abjad.Container</code> is full.
<code>auxjad.LeafDynMaker(*, increase_monotonic, ...)</code>	An extension of <code>abjad.LeafMaker</code> which can also take optional lists of dynamics and articulations.
<code>auxjad.LeafShuffler(container, *, ...)</code>	Takes an input <code>abjad.Container</code> and shuffles its leaves.
<code>auxjad.LoopingWindow(container, *, window_size, ...)</code>	Using a looping window, this slices an input <code>abjad.Container</code> and output them as containers.
<code>auxjad.LoopingWindowByElements(container, *, ...)</code>	Takes an <code>abjad.Container</code> as input as well as an integer representing the number of elements per looping window, then outputs a container with the elements processed in the looping process.
<code>auxjad.LoopingWindowByList(container, *, ...)</code>	Similar to <code>LoopingWindowByList</code> , but instead of taking an <code>abjad.Container</code> input, it takes a list of arbitrary size.
<code>auxjad.remove_repeated_dynamics(container, ...)</code>	A function which removes all consecutive repeated dynamics.
<code>auxjad.remove_repeated_time_signatures(container, ...)</code>	A function which removes all unnecessary time signatures.
<code>auxjad.rests_to_multimeasure_rest(container, ...)</code>	Takes an <code>abjad.Container</code> and converts all rests into <code>abjad.MultimeasureRest</code> 's when possible.

Continued on next page

Table 1 – continued from previous page

<code>auxjad.simplified_time_signature_ratio</code>	(A function simplifies the ratio of a given time signature respecting a minimum denominator value.
<code>auxjad.sync_containers(*containers, ...)</code>	Takes an arbitrary number of <code>abjad.Container</code> 's (or child classes), finds the longest one and adds rests to all the shorter ones, making them the same length.
<code>auxjad.TenneysContainer(container, *, ...)</code>	TenneysContainer in an implementation of the Dissonant Counterpoint Algorithm by James Tenney.
<code>auxjad.underfull_duration(container)</code>	Checks if an <code>abjad.Container</code> is underfull and returns the missing <code>abjad.Duration</code> .

2.1 auxjad.are_containers_equal

`auxjad.are_containers_equal` (*container1*: `abjad.core.Container.Container`, *container2*: `abjad.core.Container.Container`, *, *include_indicators*: `bool = False`)
→ `bool`

A comparator function returning `True` when two containers are identical and `False` when they are not.

When the pitches and effective durations of all leaves in both containers are identical, this function returns `True`:

```
>>> container1 = abjad.Staff(r"c'4 d'4 e'4 f'4 <g' a'>2 r2")
>>> container2 = abjad.Staff(r"c'4 d'4 e'4 f'4 <g' a'>2 r2")
>>> auxjad.are_containers_equal(container1, container2)
True
```

Even if all leaves of both containers are identical in relation to both pitches and written durations, the function considers the effective durations. This means that situations like the one below do not yield a false positive:

```
>>> container1 = abjad.Staff(r"c'4 d'4 e'4 f'4 <g' a'>2 r2")
>>> container2 = abjad.Staff(r"\times 3/2 {c'4 d'4 e'4} "
...                          "f'4 <g' a'>2 r2")
>>> auxjad.are_containers_equal(container1, container2)
False
```

By default, this function ignores indicators, so the containers in the example below are understood to be identical:

```
>>> container1 = abjad.Staff(r"c'4\pp d'4 e'4-. f'4 <g' a'>2-> r2")
>>> container2 = abjad.Staff(r"c'4 d'4 e'4 f'4 <g' a'>2 r2")
>>> auxjad.are_containers_equal(container1, container2)
True
```

Setting the argument `include_indicators` to `True` forces the function to include indicators in its comparison. In that case, the containers in the example above are not considered identical any longer:

```
>>> container1 = abjad.Staff(r"c'4\pp d'4 e'4-. f'4 <g' a'>2-> r2")
>>> container2 = abjad.Staff(r"c'4 d'4 e'4 f'4 <g' a'>2 r2")
>>> auxjad.are_containers_equal(container1,
...                             container2,
...                             include_indicators=True,
...                             )
True
```

This function also handles grace notes:


```
>>> container1 = abjad.Staff(r"c'4 d'4 e'4 f'4")
>>> container2 = abjad.Staff(r"c'4 \grace{d'4} d'4 e'4 f'4")
>>> auxjad.are_containers_equal(container1, container2)
False
```

```
>>> container1 = abjad.Staff(r"c'4 d'4 e'4 f'4 <g' a'>2 r2")
>>> container2 = abjad.Staff(r"c'4 \grace{c''4} d'4 e'4 "
...                          "f'4 <g' a'>2 r2")
>>> auxjad.are_containers_equal(container1, container2)
False
```

```
>>> container1 = abjad.Staff(r"c'4 \grace{c''4} d'4 e'4 "
...                          "f'4 <g' a'>2 r2")
>>> container2 = abjad.Staff(r"c'4 \grace{c''8} d'4 e'4 "
...                          "f'4 <g' a'>2 r2")
>>> auxjad.are_containers_equal(container1, container2)
False
```

```
>>> container1 = abjad.Staff(r"c'4 \grace{c''16} d'4 e'4 "
...                          "f'4 <g' a'>2 r2")
>>> container2 = abjad.Staff(r"c'4 \grace{c''16} d'4 e'4 "
...                          "f'4 <g' a'>2 r2")
>>> auxjad.are_containers_equal(container1, container2)
True
```

2.2 auxjad.are_leaves_tieable

`auxjad.are_leaves_tieable(leaf1: abjad.core.Leaf.Leaf, leaf2: abjad.core.Leaf.Leaf) → bool`

A comparator function returning True when two leaves have identical pitches and thus can be tied, otherwise returning False.

When the pitches in both leaves are identical, this function returns True:

```
>>> Leaf1 = abjad.Note(r"c'4")
>>> Leaf2 = abjad.Note(r"c'4")
>>> auxjad.are_leaves_tieable(Leaf1, Leaf2)
True
```

Durations do not affect the comparison.

```
>>> Leaf1 = abjad.Note(r"c'2.")
>>> Leaf2 = abjad.Note(r"c'16")
>>> Leaf3 = abjad.Note(r"f''16")
>>> auxjad.are_leaves_tieable(Leaf1, Leaf2)
True
>>> auxjad.are_leaves_tieable(Leaf1, Leaf3)
False
>>> auxjad.are_leaves_tieable(Leaf2, Leaf3)
False
```

Handles chords as well as pitches.

```
>>> chord1 = abjad.Chord(r"<c' e' g'>4")
>>> chord2 = abjad.Chord(r"<c' e' g'>16")
```

(continues on next page)

(continued from previous page)

```
>>> chord3 = abjad.Chord(r"<f'' fs''>16")
>>> auxjad.are_leaves_tieable(chord1, chord2)
True
>>> auxjad.are_leaves_tieable(chord1, chord3)
False
>>> auxjad.are_leaves_tieable(chord2, chord3)
False
```

Leaves can also be part of containers.

```
>>> container = abjad.Container(r"r4 <c' e'>4 <c' e'>2")
>>> auxjad.are_leaves_tieable(container[1], container[2])
True
```

If rests are input, the return value is False.

```
>>> container = abjad.Container(r"r4 g'4 r2")
>>> auxjad.are_leaves_tieable(container[0], container[2])
False
```

2.3 auxjad.ArtificialHarmonic

class `auxjad.ArtificialHarmonic` (*arguments, multiplier: Union[abjad.utilities.Duration.Duration, Tuple[int, int]] = None, tag: abjad.system.Tag.Tag = None, style: str = 'harmonic', is_parenthesized: bool = False)

Creates an `abjad.Chord` with a tweaked top note head for notating artificial harmonics.

Usage is similar to `abjad.Chord`:

```
>>> chord = auxjad.ArtificialHarmonic("<g c'>4")
>>> chord.style
'harmonic'
>>> abjad.f(chord)
<
  g
  \tweak style #'harmonic
  c'
>4
```



And similarly to `abjad.Chord`, pitch and duration can be input in many different ways:

```
>>> chord1 = auxjad.ArtificialHarmonic("<g c'>4")
>>> chord2 = auxjad.ArtificialHarmonic(["g", "c'"], 1/4)
>>> chord3 = auxjad.ArtificialHarmonic([-5, 0], 0.25)
>>> chord4 = auxjad.ArtificialHarmonic([-5, 0], abjad.Duration(1, 4))
>>> staff = abjad.Staff([chord1, chord2, chord3, chord4])
>>> abjad.f(staff)
\new Staff
```

(continues on next page)

(continued from previous page)

```

{
  <
    g
    \tweak style #'harmonic
    c'
  >4
  <
    g
    \tweak style #'harmonic
    c'
  >4
  <
    g
    \tweak style #'harmonic
    c'
  >4
  <
    g
    \tweak style #'harmonic
    c'
  >4
}

```



It is important to note that this class can only be initialised with exactly two pitches. Any other number of pitches will raise a `ValueError`:

```

>>> auxjad.ArtificialHarmonic("<g c' d'>4")
ValueError: 'ArtificialHarmonic' requires exactly two 'note_heads' for
initialisation

```

When creating an `ArtificialHarmonic`, use the keyword argument `style` to set a different type of chord head for the top note, such as `'harmonic-mixed'`:

```

>>> chord = auxjad.ArtificialHarmonic("<g c'>4",
...                                     style='harmonic-mixed',
...                                     )
>>> chord.style
'harmonic-mixed'
>>> abjad.f(chord)
<
  g
  \tweak style #'harmonic-mixed
  c'
>4

```



To notate natural harmonics with a parenthesised pitch for the open string at the bottom of the interval, set the keyword `is_parenthesized` to `True`.

```
>>> chord = auxjad.ArtificialHarmonic("<g c'>4",
...                                     is_parenthesized=True,
...                                     )
>>> chord.is_parenthesized
True
>>> abjad.f(chord)
<
  \parenthesize
  \tweak ParenthesesItem.font-size #-4
  g
  \tweak style #'harmonic
  c'
>4
```



Similarly to `abjad.Chord`, `ArtificialHarmonic` can take multipliers:

```
>>> chord = auxjad.ArtificialHarmonic("<g c'>4",
...                                     multiplier=(2, 3),
...                                     )
>>> chord.multiplier
abjad.Multiplier(2, 3)
>>> abjad.f(chord)
<
  g
  \tweak style #'harmonic
  c'
>4 * 2/3
```



All properties of `abjad.Chord` are also available to be read. This class also includes two new properties named `style` and `is_parenthesized`:

```
>>> chord = auxjad.ArtificialHarmonic("<g c'>4")
>>> chord.written_pitches
"g c'"
>>> chord.written_duration
1/4
>>> chord.style
'harmonic'
>>> chord.is_parenthesized
False
```

All these properties can be set to different values after initialisation:

```
>>> chord.written_pitches = [-5, 2]
>>> chord.written_duration = abjad.Duration(1, 8)
>>> chord.style = 'harmonic-mixed'
>>> chord.is_parenthesized = True
>>> chord.written_pitches
'g d''
>>> chord.written_duration
1/8
>>> chord.style
'harmonic-mixed'
>>> chord.is_parenthesized
True
```

The methods `sounding_pitch()` and `sounding_note()` return the sounding pitch and sounding note, respectively. Their types are `abjad.Pitch` and `abjad.Note`, respectively.

```
>>> harmonics = [ArtificialHarmonic("<g b>4"),
...               ArtificialHarmonic("<g c'>4"),
...               ArtificialHarmonic("<g d'>4"),
...               ArtificialHarmonic("<g e'>4"),
...               ArtificialHarmonic("<g g'>4"),
...               ]
>>> for harmonic in harmonics:
...     print(harmonic.sounding_pitch())
b''
g''
d''
b''
g'
>>> for harmonic in harmonics:
...     print(harmonic.sounding_note())
b''4
g''4
d''4
b''4
g'4
```

The note created by `sounding_note()` inherits all indicators from the `ArtificialHarmonic`.

```
>>> note = auxjad.ArtificialHarmonic(r"<g c'>4-.\pp")
>>> abjad.f(note.sounding_note())
g''4
\pp
- \staccato
```



Both `sounding_pitch()` and `sounding_note()` methods raise a `ValueError` exception when it cannot calculate the sounding pitch for the given interval.

```
>>> ArtificialHarmonic("<g ef'>4").sounding_pitch()
ValueError: cannot calculate sounding pitch for given interval
>>> ArtificialHarmonic("<g ef'>4").sounding_note()
ValueError: cannot calculate sounding pitch for given interval
```

`__init__` (*arguments, multiplier: Union[abjad.utilities.Duration.Duration, Tuple[int, int]] = None, tag: abjad.system.Tag.Tag = None, style: str = 'harmonic', is_parenthesized: bool = False)
Initialize self. See help(type(self)) for accurate signature.

Methods

<code>__init__</code> (*arguments, multiplier, Tuple[int, ...])	Initialize self.
<code>sounding_note</code> ()	
<code>sounding_pitch</code> ()	

Attributes

<code>is_parenthesized</code>	
<code>multiplier</code>	Gets multiplier.
<code>note_heads</code>	Gets note-heads in chord.
<code>style</code>	
<code>tag</code>	Gets component tag.
<code>written_duration</code>	Gets and sets written duration of chord.
<code>written_pitches</code>	Written pitches in chord.

2.4 auxjad.CartographyContainer

class auxjad.CartographyContainer (container: list, *, decay_rate: float = 0.75)

A container used to store, manipulate, and select objects using a decaying weighted function.

The container should be initialised with a list of objects. The contents of the list can be absolutely anything.

```
>>> container = auxjad.CartographyContainer([0, 1, 2, 3, 4])
>>> container.contents
[0, 1, 2, 3, 4]
```

The default decay rate is 0.75; that is, the weight of any given elements is the weight of the previous one multiplied by 0.75. The weights are associated with the index position, not the elements themselves.

```
>>> container.weights
[1.0, 0.75, 0.5625, 0.421875, 0.31640625]
```

Applying the `len()` function to the container will give the length of the container.

```
>>> len(container)
5
```

Calling the container will output one of its elements, selected according to its weight function.

```
>>> result = ''
>>> for _ in range(30):
...     result += str(container())
>>> result
203001402200011111101400310140
```

Calling the container with the optional keyword argument `no_repeat` set to `True` will forbid immediate repetitions among consecutive calls.

```
>>> container = auxjad.CartographyContainer([0, 1, 2, 3, 4])
>>> result = ''
>>> for _ in range(30):
...     result += str(container(no_repeat=True))
>>> result
210421021020304024230120241202
```

The keyword argument `decay_rate` can be used to set a different decay rate when creating a container.

```
>>> container = auxjad.CartographyContainer([0, 1, 2, 3, 4],
...                                         decay_rate=0.5,
...                                         )
>>> cartography_container.weights
[1.0, 0.5, 0.25, 0.125, 0.0625]
```

The decay rate can also be set after the creation of a container, using the property `decay_rate`.

```
>>> container = auxjad.CartographyContainer([0, 1, 2, 3, 4])
>>> container.decay_rate = 0.2
>>> container.weights
[1.0, 0.2, 0.04000000000000001, 0.008000000000000002,
0.0016000000000000003]
>>> result = ''
>>> for _ in range(30):
...     result += str(container())
>>> result
'000001002100000201001030000100'
```

Appending is a type of container transformation. It discards the first element of the container, shifts all others leftwards, and then appends the new element to the rightmost index.

```
>>> container = auxjad.CartographyContainer([0, 1, 2, 3, 4])
>>> container.contents
[0, 1, 2, 3, 4]
>>> container.append(5)
>>> container.contents
[1, 2, 3, 4, 5]
>>> container.append(42)
>>> container.contents
[2, 3, 4, 5, 42]
```

The method `append_keeping_n()` is similar to `append()`, but it keeps the first `n` indices untouched. It thus discards the `n+1`-th element, shifts all the next ones leftwards and then appends the new element at the end of the container.

```
>>> container = auxjad.CartographyContainer([10, 7, 14, 31, 98])
>>> container.contents
[10, 7, 14, 31, 98]
>>> container.append_keeping_n(100, 2)
>>> container.contents
[10, 7, 31, 98, 100]
```

Prepending is another type of container transformation. It discards the last element of the container, shifts all others rightwards, and then prepends the new element to the leftmost index.

```
>>> container = auxjad.CartographyContainer([0, 1, 2, 3, 4])
>>> container.contents
```

(continues on next page)

(continued from previous page)

```
[0, 1, 2, 3, 4]
>>> container.prepend(-1)
>>> container.contents
[-1, 0, 1, 2, 3]
>>> container.prepend(71)
>>> container.contents
[71, -1, 0, 1, 2]
```

Rotation is another type of container transformation. It rotates all elements rightwards, while moving the rightmost element into the leftmost index. It can take the optional keyword argument `anticlockwise` which if set to `True` will rotate in the opposite direction.

```
>>> container = auxjad.CartographyContainer([0, 1, 2, 3, 4])
>>> container.contents
[0, 1, 2, 3, 4]
>>> container.rotate()
>>> container.contents
[1, 2, 3, 4, 0]
>>> container.rotate(anticlockwise=True)
>>> container.contents
[0, 1, 2, 3, 4]
>>> container.rotate(anticlockwise=True)
>>> container.contents
[1, 2, 3, 4, 0]
```

It is also possible to mirror two elements around a pivot at the centre of the container; given an element (selected by its index), this operation will locate and swap it for its complementary element. The complementary element is defined as that one which is at a same distance from the centre pivot but in the opposite direction.

```
>>> container = auxjad.CartographyContainer([0, 1, 2, 3, 4])
>>> container.contents
[0, 1, 2, 3, 4]
>>> container.mirror(0)
>>> container.contents
[4, 1, 2, 3, 0]
>>> container.mirror(0)
>>> container.contents
[0, 1, 2, 3, 4]
>>> container.mirror(3)
>>> container.contents
[0, 3, 2, 1, 4]
>>> container.mirror(2)
>>> container.contents
[0, 3, 2, 1, 4]
```

To mirror a random pair of complementary elements, use the `mirror_random()` method. In case of a container with an odd number of elements, this method will never pick an element at the pivot point since the operation would not change the contents.

```
>>> container = auxjad.CartographyContainer([0, 1, 2, 3, 4])
>>> container.contents
[0, 1, 2, 3, 4]
>>> container.mirror_random()
>>> container.contents
[4, 1, 2, 3, 0]
>>> container.mirror_random()
```

(continues on next page)

(continued from previous page)

```
>>> container.contents
[4, 3, 2, 1, 0]
>>> container.mirror_random()
>>> container.contents
[4, 1, 2, 3, 0]
```

The method `randomise()` will randomise the position of the elements of a container.

```
>>> container = auxjad.CartographyContainer([0, 1, 2, 3, 4])
>>> container.contents
[0, 1, 2, 3, 4]
>>> container.randomise()
>>> container.contents
[1, 4, 3, 0, 2]
```

The contents of a container can also be altered after it has been initialised using the `container` property. The length of the container can change as well.

```
>>> container = auxjad.CartographyContainer([0, 1, 2, 3, 4],
...                                         decay_rate=0.5,
...                                         )
>>> len(container)
5
>>> container.weights
[1.0, 0.5, 0.25, 0.125, 0.0625]
>>> container.contents = [10, 7, 14, 31, 98, 47, 32]
>>> container.contents
[10, 7, 14, 31, 98, 47, 32]
>>> len(container)
7
>>> container.weights
[1.0, 0.5, 0.25, 0.125, 0.0625, 0.03125, 0.015625]
```

This class allows indexing and slicing just like regular lists. This can be used to both access and alter elements.

```
>>> container = auxjad.CartographyContainer([10, 7, 14, 31, 98])
>>> container[1]
7
>>> container[1:4]
[7, 14, 31]
>>> container[:]
[10, 7, 14, 31, 98]
>>> container()
31
>>> previous_index = container.previous_index
>>> previous_index
3
>>> container[previous_index]
31
>>> container.contents
[10, 7, 14, 31, 98]
>>> container[2] = 100
>>> container.contents
[10, 7, 100, 31, 98]
```

__init__ (*container: list, *, decay_rate: float = 0.75*)
Initialize self. See `help(type(self))` for accurate signature.

Methods

<code>__init__(container, *, decay_rate)</code>	Initialize self.
<code>append(new_element)</code>	
<code>append_keeping_n(new_element, n)</code>	
<code>mirror(index)</code>	
<code>mirror_random()</code>	
<code>prepend(new_element)</code>	
<code>randomise()</code>	
<code>rotate([anticlockwise])</code>	

Attributes

<code>contents</code>
<code>decay_rate</code>

2.5 auxjad.close_container

`auxjad.close_container` (*container: abjad.core.Container.Container*)

Changes the time signature of the last bar of an underfull `abjad.Container` in order to make it full, if necessary.

Returns the missing duration of the last bar of any container or child class. If no time signature is encountered, it uses LilyPond's convention and considers the container as in 4/4.

```
>>> container1 = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> container2 = abjad.Container(r"c'4 d'4 e'4")
>>> container3 = abjad.Container(r"c'4 d'4 e'4 f'4 | c'4")
>>> container4 = abjad.Container(r"c'4 d'4 e'4 f'4 | c'4 d'4 e'4 f'4")
>>> auxjad.close_container(container1)
>>> auxjad.close_container(container2)
>>> auxjad.close_container(container3)
>>> auxjad.close_container(container4)
>>> abjad.f(container1)
{
    c'4
    d'4
    e'4
    f'4
}
```



```
>>> abjad.f(container2)
{
    %%% \time 3/4 %%%
    c'4
    d'4
}
```

(continues on next page)

(continued from previous page)

```
e'4
}
```



```
>>> abjad.f(container3)
{
    c'4
    d'4
    e'4
    f'4
    %%% \time 1/4 %%%
    c'4
}
```



```
>>> abjad.f(container4)
{
    c'4
    d'4
    e'4
    f'4
    c'4
    d'4
    e'4
    f'4
}
```



Handles any time signatures as well as changes of time signature.

```
>>> container1 = abjad.Container(r"\time 4/4 c'4 d'4 e'4 f'4 g'")
>>> container2 = abjad.Container(r"\time 3/4 a2. \time 2/4 c'4")
>>> container3 = abjad.Container(r"\time 5/4 g1 ~ g4 \time 4/4 af'2")
>>> auxjad.close_container(container1)
>>> auxjad.close_container(container2)
>>> auxjad.close_container(container3)
>>> abjad.f(container1)
{
    %%% \time 4/4 %%%
    c'4
    d'4
    e'4
```

(continues on next page)

(continued from previous page)

```
f'4
%%% \time 1/4 %%%
g'4
}
```



```
>>> abjad.f(container2)
{
  %%% \time 3/4 %%%
  a2.
  %%% \time 1/4 %%%
  c'4
}
```



```
>>> abjad.f(container3)
{
  %%% \time 5/4 %%%
  g1
  ~
  g4
  %%% \time 2/4 %%%
  af'2
}
```



Note: Notice that the time signatures in the output are commented out with `%%%`. This is because Abjad only applies time signatures to containers that belong to a `abjad.Staff`. The present function works with either `abjad.Container` and `abjad.Staff`.

```
>>> container = abjad.Container(r"\time 4/4 c'4 d'4 e'4 f'4 g'")
>>> auxjad.close_container(container)
>>> abjad.f(container)
{
  %%% \time 4/4 %%%
  c'4
  d'4
  e'4
  f'4
}
```

(continues on next page)

(continued from previous page)

```

    %%% \time 1/4 %%%
    g'4
}
>>> staff = abjad.Staff([container])
>>> abjad.f(container)
{
    \time 4/4
    c'4
    d'4
    e'4
    f'4
    \time 1/4
    g'4
}

```

Correctly handles partial time signatures.

```

>>> container = abjad.Container(r"c'4 d'4 e'4 f'4 g'4")
>>> time_signature = abjad.TimeSignature((3, 4), partial=(1, 4))
>>> abjad.attach(time_signature, container[0])
>>> auxjad.close_container(container)
>>> abjad.f(container)
{
    %%% \partial 4 %%%
    %%% \time 3/4 %%%
    c'4
    d'4
    e'4
    f'4
    %%% \time 1/4 %%%
    g'4
}

```



Warning: If a container is malformed, i.e. it has an underfilled bar before a time signature change, the function raises a `ValueError` exception.

```

>>> container = abjad.Container(r"\time 5/4 g'1 \time 4/4 f'4")
>>> auxjad.close_container(container)
ValueError: 'container' is malformed, with an underfull bar preceeding
a time signature change

```

2.6 auxjad.fill_with_rests

`auxjad.fill_with_rests` (*container: abjad.core.Container.Container*)

Fills an `abjad.Container` with rests in order to make it full.

Returns the missing duration of the last bar of any container or child class. If no time signature is encountered, it uses LilyPond's convention and considers the container as in 4/4.

```
>>> container1 = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> container2 = abjad.Container(r"c'4 d'4 e'4")
>>> container3 = abjad.Container(r"c'4 d'4 e'4 f'4 | c'4")
>>> container4 = abjad.Container(r"c'4 d'4 e'4 f'4 | c'4 d'4 e'4 f'4")
>>> auxjad.fill_with_rests(container1)
>>> auxjad.fill_with_rests(container2)
>>> auxjad.fill_with_rests(container3)
>>> auxjad.fill_with_rests(container4)
>>> abjad.f(container1)
{
    c'4
    d'4
    e'4
    f'4
}
```



```
>>> abjad.f(container2)
{
    c'4
    d'4
    e'4
    r4
}
```



```
>>> abjad.f(container3)
{
    c'4
    d'4
    e'4
    f'4
    c'4
    r2.
}
```



```
>>> abjad.f(container4)
{
    c'4
```

(continues on next page)

(continued from previous page)

```

d'4
e'4
f'4
c'4
d'4
e'4
f'4
}

```



Handles any time signatures as well as changes of time signature.

```

>>> container1 = abjad.Container(r"\time 4/4 c'4 d'4 e'4 f'4 g'")
>>> container2 = abjad.Container(r"\time 3/4 a2. \time 2/4 c'4")
>>> container3 = abjad.Container(r"\time 5/4 g1 ~ g4 \time 4/4 af'2")
>>> auxjad.fill_with_rests(container1)
>>> auxjad.fill_with_rests(container2)
>>> auxjad.fill_with_rests(container3)
>>> abjad.f(container1)
{
    %%% \time 4/4 %%%
    c'4
    d'4
    e'4
    f'4
    g'4
    r2.
}

```



```

>>> abjad.f(container2)
{
    %%% \time 3/4 %%%
    a2.
    %%% \time 2/4 %%%
    c'4
    r4
}

```



```
>>> abjad.f(container3)
{
    %%% \time 5/4 %%%
    g1
    ~
    g4
    %%% \time 4/4 %%%
    af'2
    r2
}
```



Notice that the time signatures in the output are commented out with `%%%`. This is because Abjad only applies time signatures to containers that belong to a `abjad.Staff`. The present function works with either `abjad.Container` and `abjad.Staff`.

```
>>> container = abjad.Container(r"\time 4/4 c'4 d'4 e'4 f'4 g'")
>>> auxjad.fill_with_rests(container)
>>> abjad.f(container)
{
    %%% \time 4/4 %%%
    c'4
    d'4
    e'4
    f'4
    g'4
    r2.
}
>>> staff = abjad.Staff([container])
>>> abjad.f(container)
{
    \time 4/4
    c'4
    d'4
    e'4
    f'4
    g'4
    r2.
}
```

Correctly handles partial time signatures.

```
>>> container = abjad.Container(r"c'4 d'4 e'4 f'4 g'4")
>>> time_signature = abjad.TimeSignature((3, 4), partial=(1, 4))
>>> abjad.attach(time_signature, container[0])
>>> auxjad.fill_with_rests(container)
>>> abjad.f(container)
{
    %%% \partial 4 %%%
    %%% \time 3/4 %%%
    c'4
    d'4
```

(continues on next page)

(continued from previous page)

```

e'4
f'4
g'4
r2
}

```



Warning: If a container is malformed, i.e. it has an underfilled bar before a time signature change, the function raises a `ValueError` exception.

```

>>> container = abjad.Container(r"\time 5/4 g''1 \time 4/4 f'4")
>>> auxjad.fill_with_rests(container)
ValueError: 'container' is malformed, with an underfull bar preceeding
a time signature change

```

2.7 auxjad.HarmonicNote

class `auxjad.HarmonicNote` (*arguments, multiplier: `Union[abjad.utilities.Duration.Duration, Tuple[int, int]]` = None, tag: `abjad.system.Tag.Tag` = None, style: `str` = 'harmonic')

Creates an `abjad.Note` with tweaked notehead for harmonics.

Usage is similar to `abjad.Note`:

```

>>> note = auxjad.HarmonicNote("c''4")
>>> note.style
'harmonic'
>>> abjad.f(note)
\tweak style #'harmonic
c''4

```



And similarly to `abjad.Note`, pitch and duration can be input in many different ways:

```

>>> note1 = auxjad.HarmonicNote("c''4")
>>> note2 = auxjad.HarmonicNote("c''", 1/4)
>>> note3 = auxjad.HarmonicNote(12, 0.25)
>>> note4 = auxjad.HarmonicNote(12, abjad.Duration(1, 4))
>>> staff = abjad.Staff([note1, note2, note3, note4])
>>> abjad.f(staff)
\new Staff
{
    \tweak style #'harmonic

```

(continues on next page)

(continued from previous page)

```

c''4
\tweak style #'harmonic
c''4
\tweak style #'harmonic
c''4
\tweak style #'harmonic
c''4
}

```



When creating an `HarmonicNote`, use the keyword argument `style` to set a different type of note head, such as `'harmonic-mixed'`:

```

>>> note = auxjad.HarmonicNote("c''4",
...                             style='harmonic-mixed',
...                             )
>>> note.style
'harmonic-mixed'
>>> abjad.f(note)
\tweak style #'harmonic-mixed
c''4

```



Similarly to `abjad.Note`, `HarmonicNote` can take multipliers:

```

>>> note = auxjad.HarmonicNote("c''4",
...                             multiplier=(2, 3),
...                             )
>>> note.multiplier
abjad.Multiplier(2, 3)
>>> abjad.f(note)
\tweak style #'harmonic
c''4 * 2/3

```



All properties of `abjad.Note` are also available to be read. This class also includes a new property named `style`:

```

>>> note = auxjad.HarmonicNote("c''4")
>>> note.written_pitch
"c'"
>>> note.written_duration

```

(continues on next page)

(continued from previous page)


```
1/4
>>> note.style
'harmonic'
```

All these properties can be set to different values after initialisation:

```
>>> note.written_pitch = 18
>>> note.written_duration = abjad.Duration(1, 8)
>>> note.style = 'harmonic-mixed'
>>> note.written_pitch
"fs'"
>>> note.written_duration
1/8
>>> note.style
'harmonic-mixed'
```

To create a note with a regular note head and with a flageolet circle above it, use the style 'flageolet':

```
>>> note = auxjad.HarmonicNote("c'1",
...                             style='flageolet',
...                             )
>>> note.style
'flageolet'
>>> abjad.f(note)
c'1
\flageolet
```



`__init__` (*arguments, multiplier: Union[abjad.utilities.Duration.Duration, Tuple[int, int]] = None, tag: abjad.system.Tag.Tag = None, style: str = 'harmonic')
Initialize self. See help(type(self)) for accurate signature.

Methods

<code>__init__</code> (*arguments, multiplier, Tuple[int, ...])	Initialize self.
<code>from_pitch_and_duration</code> (pitch, duration)	Makes note from pitch and duration.

Attributes

<code>multiplier</code>	Gets multiplier.
<code>note_head</code>	Gets and sets note-head.
<code>style</code>	
<code>tag</code>	Gets component tag.
<code>written_duration</code>	Gets and sets written duration.
<code>written_pitch</code>	Gets and sets written pitch.

2.8 auxjad.is_container_full

`auxjad.is_container_full` (*container: abjad.core.Container.Container*) → bool

Checks if an `abjad.Container` is full. Based on `auxjad.underfull_duration`.

Returns `True` if the last bar of any container (or child class) is full, otherwise returns `False`. If no time signature is encountered, it uses LilyPond's convention and considers the container as in 4/4.

```
>>> container1 = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> container2 = abjad.Container(r"c'4 d'4 e'4")
>>> container3 = abjad.Container(r"c'4 d'4 e'4 f'4 | c'4")
>>> container4 = abjad.Container(r"c'4 d'4 e'4 f'4 | c'4 d'4 e'4 f'4")
>>> auxjad.is_container_full(container1)
True
>>> auxjad.is_container_full(container2)
False
>>> auxjad.is_container_full(container3)
False
>>> auxjad.is_container_full(container4)
True
```

Handles any time signatures as well as changes of time signature.

```
>>> container1 = abjad.Container(r"\time 4/4 c'4 d'4 e'4 f'4")
>>> container2 = abjad.Container(r"\time 3/4 a2. \time 2/4 r2")
>>> container3 = abjad.Container(r"\time 5/4 g1 ~ g4 \time 4/4 af'2")
>>> container4 = abjad.Container(r"\time 6/8 c'2 ~ c'8")
>>> auxjad.is_container_full(container1)
True
>>> auxjad.is_container_full(container2)
True
>>> auxjad.is_container_full(container3)
False
>>> auxjad.is_container_full(container4)
False
```

Correctly handles partial time signatures.

```
>>> container = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> time_signature = abjad.TimeSignature((3, 4), partial=(1, 4))
>>> abjad.attach(time_signature, container[0])
>>> auxjad.is_container_full(container)
True
```

It also handles multi-measure rests.

```
>>> container1 = abjad.Container(r"R1")
>>> container2 = abjad.Container(r"\time 3/4 R1*3/4 \time 2/4 r2")
>>> container3 = abjad.Container(r"\time 5/4 R1*5/4 \time 4/4 g'4")
>>> container4 = abjad.Container(r"\time 6/8 R1*1/2")
>>> auxjad.is_container_full(container1)
True
>>> auxjad.is_container_full(container2)
True
>>> auxjad.is_container_full(container3)
False
>>> auxjad.is_container_full(container4)
False
```

Warning: If a container is malformed, i.e. it has an underfilled bar before a time signature change, the function raises a `ValueError` exception.

```
>>> container = abjad.Container(r"\time 5/4 g'1 \time 4/4 f'1")
>>> auxjad.is_container_full(container)
ValueError: 'container' is malformed, with an underfull bar preceeding
a time signature change
```

2.9 auxjad.LeafDynMaker

class `auxjad.LeafDynMaker`(*, *increase_monotonic*: *bool* = *None*, *forbidden_note_duration*: *Union*[*abjad.utilities.Duration.Duration*, *Tuple*[*int*, *int*]] = *None*, *forbidden_rest_duration*: *Union*[*abjad.utilities.Duration.Duration*, *Tuple*[*int*, *int*]] = *None*, *skips_instead_of_rests*: *bool* = *None*, *tag*: *abjad.system.Tag.Tag* = *None*, *use_multimeasure_rests*: *bool* = *None*)

An extension of `abjad.LeafMaker` which can also take optional lists of dynamics and articulations.

Usage is similar to `abjad.LeafMaker`:

```
>>> pitches = [0, 2, 4, 5, 7, 9]
>>> durations = [(1, 32), (2, 32), (3, 32), (4, 32), (5, 32), (6, 32)]
>>> dynamics = ['pp', 'p', 'mp', 'mf', 'f', 'ff']
>>> articulations = ['.', '>', '-', '_', '^', '+']
>>> leaf_dyn_maker = auxjad.LeafDynMaker()
>>> notes = leaf_dyn_maker(pitches, durations, dynamics, articulations)
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    c'32
    \pp
    -\staccato
    d'16
    \p
    -\accent
    e'16.
    \mp
    -\tenuto
    f'8
    \mf
    -\portato
    g'8
    \f
    -\marcato
    ~
    g'32
    a'8.
    \ff
    -\stopped
}
```



Tuple elements in `pitches` result in chords. None-valued elements in `pitches` result in rests:

```
>>> pitches = [5, None, (0, 2, 7)]
>>> durations = [(1, 4), (1, 8), (1, 16)]
>>> dynamics = ['p', None, 'f']
>>> articulations = ['staccato', None, 'tenuto']
>>> leaf_dyn_maker = auxjad.LeafDynMaker()
>>> notes = leaf_dyn_maker(pitches, durations, dynamics, articulations)
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    f'4
    \p
    -\staccato
    r8
    <c' d' g'>16
    \f
    -\tenuto
}
```



Can omit repeated dynamics with the keyword argument `no_repeat`:

```
>>> pitches = [0, 2, 4, 5, 7, 9]
>>> durations = [(1, 32), (2, 32), (3, 32), (4, 32), (5, 32), (6, 32)]
>>> dynamics = ['pp', 'pp', 'mp', 'f', 'f', 'p']
>>> leaf_dyn_maker = auxjad.LeafDynMaker()
>>> notes = leaf_dyn_maker(pitches,
...                        durations,
...                        dynamics,
...                        no_repeat=True,
...                        )
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    c'32
    \pp
    d'16
    e'16.
    \mp
    f'8
    \f
    g'8
}
```

(continues on next page)

(continued from previous page)

```

~
g'32
a'8.
\p
}

```



The lengths of both dynamics and articulations can be shorter than the lengths of pitches and durations (whatever is the greatest):

```

>>> pitches = [0, 2, 4, 5, 7, 9]
>>> durations = (1, 4)
>>> dynamics = ['p', 'f', 'ff']
>>> articulations = ['.', '>']
>>> leaf_dyn_maker = auxjad.LeafDynMaker()
>>> notes = leaf_dyn_maker(pitches, durations, dynamics, articulations)
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
  c'4
  \p
  -\staccato
  d'4
  \f
  -\accent
  e'4
  \ff
  f'4
  g'4
  a'4
}

```



If the length of articulations is 1, it will apply to all elements. If the length of dynamics is 1, it will apply to the first element only:

```

>>> pitches = [0, 2, 4, 5, 7, 9]
>>> durations = (1, 4)
>>> dynamics = 'p'
>>> articulations = '.'
>>> leaf_dyn_maker = auxjad.LeafDynMaker()
>>> notes = leaf_dyn_maker(pitches, durations, dynamics, articulations)
>>> staff = abjad.Staff(notes)

```

(continues on next page)

(continued from previous page)

```
>>> abjad.f(staff)
\new Staff
{
    c'4
    \p
    -\staccato
    d'4
    -\staccato
    e'4
    -\staccato
    f'4
    -\staccato
    g'4
    -\staccato
    a'4
    -\staccato
}
```



Similarly to Abjad's native classes, it accepts many types of elements in its input lists:

```
>>> pitches = [0,
...           "d'",
...           'E4',
...           abjad.NumberedPitch(5),
...           abjad.NamedPitch("g'"),
...           abjad.NamedPitch("A4"),
...           ]
>>> durations = [(1, 32),
...               "2/32",
...               abjad.Duration("3/32"),
...               abjad.Duration(0.125),
...               abjad.Duration(5, 32),
...               abjad.Duration(6/32),
...               ]
>>> leaf_dyn_maker = auxjad.LeafDynMaker()
>>> notes = leaf_dyn_maker(pitches, durations)
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    c'32
    d'16
    e'16.
    f'8
    g'8
    ~
    g'32
    a'8.
}
```




```
__init__(*, increase_monotonic: bool = None, forbidden_note_duration:
Union[abjad.utilities.Duration.Duration, Tuple[int, int]] = None, forbidden_rest_duration:
Union[abjad.utilities.Duration.Duration, Tuple[int, int]] = None, skips_instead_of_rests:
bool = None, tag: abjad.system.Tag.Tag = None, use_multimeasure_rests: bool = None) →
None
Initialize self. See help(type(self)) for accurate signature.
```

Methods

<code>__init__(*, increase_monotonic, ...)</code>	Initialize self.
---	------------------

Attributes

<code>forbidden_note_duration</code>	Gets forbidden written duration.
<code>forbidden_rest_duration</code>	Gets forbidden written duration.
<code>increase_monotonic</code>	Is true when durations increase monotonically.
<code>skips_instead_of_rests</code>	Is true when skips appear in place of rests.
<code>tag</code>	Gets tag.
<code>use_multimeasure_rests</code>	Is true when rests are multimeasure.

2.10 auxjad.LeafShuffler

```
class auxjad.LeafShuffler(container: abjad.core.Container.Container, *, output_single_measure:
bool = False, disable_rewrite_meter: bool = False,
force_time_signatures: bool = False, omit_time_signatures: bool
= False)
```

Takes an input `abjad.Container` and shuffles its leaves. It can shuffle both leaves as well as pitches; it also can rotate pitches. When shuffling or rotating pitches only, tuplets are allowed. Tuplets are not supported when shuffling leaves.

Calling the object will output a shuffled container.

```
>>> container = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> shuffler = auxjad.LeafShuffler(container)
>>> music = shuffler()
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \time 4/4
    d'4
    c'4
    f'4
    e'4
}
```



To get the result of the last operation, use the property `current_container`.

```
>>> music = shuffler.current_container
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \time 4/4
    d'4
    c'4
    f'4
    e'4
}
```



Calling the object outputs the same result as using the method `shuffle_leaves()`.

```
>>> container = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> shuffler = auxjad.LeafShuffler(container)
>>> music = shuffler.shuffle_leaves()
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \time 4/4
    f'4
    c'4
    e'4
    d'4
}
```



This class has many keyword arguments, all of which can be altered after instantiation using properties with the same names as shown below.

```
>>> container = abjad.Container(r"\time 3/4 c'4 d'4 e'4 |"
...                             r"\time 2/4 f'4 g'4 |"
...                             )
>>> shuffler = auxjad.LeafShuffler(container,
...                                   output_single_measure=False,
...                                   disable_rewrite_meter=False,
...                                   force_time_signatures=False,
...                                   omit_time_signatures=False,
```

(continues on next page)

(continued from previous page)

```

...
    )
>>> shuffler.output_single_measure
False
>>> shuffler.disable_rewrite_meter
False
>>> shuffler.force_time_signatures
False
>>> shuffler.omit_time_signatures
False
>>> shuffler.output_single_measure = True
>>> shuffler.disable_rewrite_meter = True
>>> shuffler.force_time_signatures = True
>>> shuffler.omit_time_signatures = True
>>> shuffler.output_single_measure
True
>>> shuffler.disable_rewrite_meter
True
>>> shuffler.force_time_signatures
True
>>> shuffler.omit_time_signatures
True

```

If `output_single_measure` is set to `True`, then the whole container is output as a single measure, having its time signature rewritten.

```

>>> container = abjad.Container(r"\time 3/4 c'4 d'4 e'4 |"
...                             r"\time 2/4 f'4 g'4"
...                             )
>>> shuffler = auxjad.LeafShuffler(container,
...                                 output_single_measure=True,
...                                 )
>>> music = shuffler()
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \time 5/4
    f'4
    d'4
    e'4
    g'4
    c'4
}

```



If `disable_rewrite_meter` is set to `True`, then the automatic behaviour of rewriting the leaves according to the meter is disabled.

```

>>> container = abjad.Container(r"\time 3/4 c'16 d'4.. e'4 |"
...                             r"\time 2/4 f'2"
...                             )
>>> shuffler = auxjad.LeafShuffler(container,

```

(continues on next page)

(continued from previous page)

```
...         output_single_measure=True,
...         disable_rewrite_meter=True,
...     )
>>> music = shuffler()
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \time 5/4
    d'4..
    f'2
    c'16
    e'4
}
```



The first call to the instance will add the correct time signature to the first leaf. Subsequent calls will only add it if its necessary, such as when there is a time signature change in some bar in the container.

```
>>> container = abjad.Container(r"\time 3/4 c'16 d'4.. e'4 | r4 f'2")
>>> shuffler = auxjad.LeafShuffler(container)
>>> music = shuffler()
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \time 3/4
    d'4..
    e'16
    ~
    e'8.
    f'16
    ~
    f'4..
    r16
    r8.
    c'16
}
```



```
>>> music = shuffler()
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    c'16
    e'8.
}
```

(continues on next page)

(continued from previous page)

```

    r16
    d'4..
}

```



To disable time signatures altogether, initialise this class with the keyword argument `omit_time_signatures` set to `True` (default is `False`), or change the `omit_time_signatures` property after initialisation.

```
>>> container = abjad.Container(r"\time 3/4 c'16 d'4.. e'4 | r4 f'2")
>>> shuffler = auxjad.LeafShuffler(container,
...                                omit_time_signatures=True,
...                                )
>>> music = shuffler()
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    d'4..
    e'16
    ~
    e'8.
    f'16
    ~
    f'4..
    r16
    r8.
    c'16
}
```



```
>>> shuffler.omit_time_signatures
True
>>> shuffler.omit_time_signatures = False
>>> shuffler.omit_time_signatures
False
```

To output several shuffled containers at once, use the `output_n` method, inputting the desired number of iterations.

```
>>> container = abjad.Container(r"\time 2/4 c'16 d'4.. | r4 e'8. f'16")
>>> shuffler = auxjad.LeafShuffler(container)
>>> music = shuffler.output_n(3)
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
```

(continues on next page)

(continued from previous page)

```

\time 2/4
d'4..
f'16
c'16
e'8.
r4
d'4..
e'16
~
e'8
f'16
r16
r8.
c'16
r4
d'4
~
d'8.
f'16
c'16
e'8.
}

```



To shuffle only pitches, keeping the durations of the leaves as they are, use the method `shuffle_pitches()`. It handles both notes and chords. Rests will remain at their current location.

```

>>> container = abjad.Container(r"\time 3/4 c'16 d'4.. | r4 e'8. f'16")
>>> shuffler = auxjad.LeafShuffler(container)
>>> music = shuffler.shuffle_pitches()
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
  \time 3/4
  e'16
  c'4..
  r4
  d'8.
  f'16
}

```



When dealing with pitches, it is possible to use containers containing tuplets. And similarly to the method `output_n()`, to output several containers with shuffled pitches, use `output_n_shuffled_pitches()`.

```
>>> container = abjad.Container(r"\times 2/3 {\time 5/4 c'4 d'2}"
...                             r"r4 e'4. f'8"
...                             )
>>> shuffler = auxjad.LeafShuffler(container)
>>> music = shuffler.output_n_shuffled_pitches(3)
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \times 2/3 {
        \time 5/4
        f'4
        e'2
    }
    r4
    d'4.
    c'8
    \times 2/3 {
        d'4
        c'2
    }
    r4
    f'4.
    e'8
    \times 2/3 {
        d'4
        f'2
    }
    r4
    c'4.
    e'8
}
```



To rotate pitches, use the `rotate_pitches()` method.

```
>>> container = abjad.Container(r"\time 3/4 c'16 d'4.. | r4 e'8. f'16")
>>> shuffler = auxjad.LeafShuffler(container)
>>> music = shuffler.rotate_pitches()
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \time 3/4
    d'16
    e'4..
    r4
    f'8.
    c'16
}
```




This method can take two optional keyword arguments: `anticlockwise`, set to `False` by default, and `n_rotations`, set to 1 by default. The first defines the direction of the rotation, while the later sets the number of rotations applied.

```
>>> container = abjad.Container(r"\time 3/4 c'16 d'4.. | r4 e'8. f'16")
>>> shuffler = auxjad.LeafShuffler(container)
>>> music = shuffler.rotate_pitches(anticlockwise=True, n_rotations=2)
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \time 3/4
    e'16
    f'4..
    r4
    c'8.
    d'16
}
```



Similarly to the method `output_n()`, to output several containers with rotated pitches, use `output_n_rotated_pitches()`.

```
>>> container = abjad.Container(r"\times 2/3 {\time 5/4 c'4 d'2}"
...                             r"r4 e'4. f'8"
...                             )
>>> shuffler = auxjad.LeafShuffler(container)
>>> music = shuffler.output_n_rotated_pitches(3)
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \times 2/3 {
        \time 5/4
        d'4
        e'2
    }
    r4
    f'4.
    c'8
    \times 2/3 {
        e'4
        f'2
    }
    r4
    c'4.
    d'8
    \times 2/3 {
```

(continues on next page)

(continued from previous page)



```

__init__(container: abjad.core.Container.Container, *, output_single_measure: bool =
    False, disable_rewrite_meter: bool = False, force_time_signatures: bool = False,
    omit_time_signatures: bool = False)
    Initialize self. See help(type(self)) for accurate signature.

```

Methods

<code>__init__(container, *, ...)</code>	Initialize self.
<code>output_n(n)</code>	
<code>output_n_rotated_pitches(n, *, n_rotations, ...)</code>	
<code>output_n_shuffled_pitches(n)</code>	
<code>rotate_pitches(*, n_rotations, anticlockwise)</code>	
<code>shuffle_leaves()</code>	
<code>shuffle_pitches()</code>	

Attributes

current_container
disable_rewrite_meter
force_time_signatures
omit_time_signatures
output_single_measure

2.11 auxjad.LoopWindow

```
class auxjad.LoopWindow(container: abjad.core.Container.Container, *, window_size: (<class 'tuple'>, <class 'abjad.meter.Meter'>) = (4, 4), step_size: (<class 'int'>, <class 'float'>, <class 'tuple'>, <class 'str'>, <class 'abjad.utilities.Duration.Duration'>) = (1, 16), max_steps: int = 1, repetition_chance: float = 0.0, forward_bias: float = 1.0, head_position: (<class 'int'>, <class 'float'>, <class 'tuple'>, <class 'str'>, <class 'abjad.utilities.Duration.Duration'>) = 0, omit_time_signature: bool = False, move_window_on_first_call: bool = False)
```

Using a looping window, this slices an input `abjad.Container` and output them as containers.

Usage is similar to other factory classes. It takes a container (or child class equivalent) as argument. Each call

of the object, in this case `looper()`, will move the window forwards and output the sliced window. If no `window_size` nor `step_size` are entered as arguments, they are set to the following default values, respectively: (4, 4), i.e. a window of the size of a 4/4 bar, and (1, 16), i.e. a step of the length of a sixteenth-note.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> looper = auxjad.LoopWindow(input_music)
>>> notes = looper()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    \time 4/4
    c'4
    d'2
    e'4
}
```



```
>>> notes = looper()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    c'8.
    d'16
    ~
    d'4..
    e'16
    ~
    e'8.
    f'16
}
```



The property `current_window` can be used to access the current window without moving the head forwards.

```
>>> notes = looper.current_window()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    c'8.
    d'16
    ~
    d'4..
    e'16
    ~
    e'8.
}
```

(continues on next page)

(continued from previous page)

```
f'16
}
```



The very first call will output the input container without processing it. To disable this behaviour and have the looping window move on the very first call, initialise the class with the keyword argument `move_window_on_first_call` set to `True`.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> loopier = auxjad.LoopWindow(input_music,
...                             move_window_on_first_call=True,
...                             )
>>> notes = loopier()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    \time 4/4
    c'8.
    d'16
    ~
    d'4..
    e'16
    ~
    e'8.
    f'16
}
```



The optional arguments `window_size` and `step_size` can be used to set different window and step sizes. `window_size` can take a tuple or an `abjad.Meter` as input, while `step_size` takes a tuple or an `abjad.Duration`.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> loopier = auxjad.LoopWindow(input_music,
...                             window_size=(3, 4),
...                             step_size=(1, 4),
...                             )
>>> notes = loopier()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    \time 3/4
    c'4
    d'2
}
```



```
>>> notes = looper()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    d'2
    e'4
}
```



The instances of `LoopWindow` can also be used as an iterator, which can then be used in a for loop to exhaust all windows. Notice how it appends rests at the end of the container, until it is totally exhausted.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4")
>>> looper = auxjad.LoopWindow(input_music,
...                             window_size=(3, 4),
...                             step_size=(1, 8),
...                             )
>>> staff = abjad.Staff()
>>> for window in looper:
...     staff.append(window)
>>> abjad.f(staff)
\new Staff
{
    \time 3/4
    c'4
    d'2
    c'8
    d'8
    ~
    d'4.
    e'8
    d'2
    e'4
    d'4.
    e'8
    ~
    e'8
    r8
    d'4
    e'4
    r4
    d'8
    e'8
    ~
    e'8
    r4.
    e'4
}
```

(continues on next page)

(continued from previous page)

```

    r2
    e'8
    r8
    r2
}

```



This class can take many optional keyword arguments during its creation, besides `window_size` and `step_size`. `max_steps` sets the maximum number of steps that the window can advance when the object is called, ranging between 1 and the input value (default is also 1). `repetition_chance` sets the chance of a window result repeating itself (that is, the window not moving forwards when called). It should range from 0.0 to 1.0 (default 0.0, i.e. no repetition). `forward_bias` sets the chance of the window moving forward instead of backwards. It should range from 0.0 to 1.0 (default 1.0, which means the window can only move forwards. A value of 0.5 gives 50% chance of moving forwards while a value of 0.0 will move the window only backwards). Finally, `head_position` can be used to offset the starting position of the looping window. It must be a tuple or an `abjad.Duration`, and its default value is 0.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> looper = auxjad.LoopWindow(input_music,
...                             window_size=(3, 4),
...                             step_size=(5, 8),
...                             max_steps=2,
...                             repetition_chance=0.25,
...                             forward_bias=0.2,
...                             head_position=(2, 8),
...                             omit_time_signature=False,
...                             )
>>> looper.window_size
3/4
>>> looper.step_size
5/8
>>> looper.repetition_chance
0.25
>>> looper.forward_bias
0.2
>>> looper.max_steps
2
>>> looper.head_position
1/4
>>> looper.omit_time_signature
False
```

Use the properties below to change these values after initialisation.

```
>>> looper.window_size = (5, 4)
>>> looper.step_size = (1, 4)
>>> looper.max_steps = 3
>>> looper.repetition_chance = 0.1
>>> looper.forward_bias = 0.8
>>> looper.head_position = 0
>>> looper.omit_time_signature = True
```

(continues on next page)

(continued from previous page)

```
>>> looper.window_size
5/4
>>> looper.step_size
1/4
>>> looper.max_steps
3
>>> looper.repetition_chance
0.1
>>> looper.forward_bias
0.8
>>> looper.head_position
0
>>> looper.omit_time_signature
True
```

To run through the whole process and output it as a single container, from the initial head position until the process outputs the single last element, use the method `output_all()`.

```
>>> input_music = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> looper = auxjad.LoopWindow(input_music,
...                             window_size=(3, 4),
...                             step_size=(1, 4),
...                             )
>>> music = looper.output_all()
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \time 3/4
    c'4
    d'4
    e'4
    d'4
    e'4
    f'4
    e'4
    f'4
    r4
    f'4
    r2
}
```



When using `output_all()`, set the keyword argument `tie_identical_pitches` to `True` in order to tie identical notes or chords at the end and beginning of consecutive windows.

```
>>> input_music = abjad.Container(r"c'4 <e' f' g'>2 r4 f'2.")
>>> looper = auxjad.LoopWindow(input_music,
...                             window_size=(3, 4),
...                             step_size=(1, 4),
...                             )
>>> music = looper.output_all(tie_identical_pitches=True)
```

(continues on next page)

(continued from previous page)

```

>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
  \time 3/4
  c'4
  <e' f' g'>2
  ~
  <e' f' g'>2
  r4
  <e' f' g'>4
  r4
  f'4
  r4
  f'2
  ~
  f'2.
  ~
  f'2
  r4
  f'4
  r2
}

```



To run through just part of the process and output it as a single container, starting from the initial head position, use the method `output_n()` and pass the number of iterations as argument. Similarly to `output_all()`, the keyword argument `tie_identical_pitches` is available for tying pitches.

```

>>> input_music = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> looper = auxjad.Window(input_music,
...                         window_size=(3, 4),
...                         step_size=(1, 4),
...                         )
>>> music = looper.output_n(2)
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
  \time 3/4
  c'4
  d'4
  e'4
  d'4
  e'4
  f'4
}

```



To change the size of the looping window after instantiation, use the property `window_size`. In the example below, the initial window is of size (4, 4), but changes to (3, 8) after three calls. Notice how the very first call attaches a time signature equivalent to the window size to the output window; subsequent calls will not have time signatures unless the size of the looping window changes.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> looper = auxjad.LoopWindow(input_music)
>>> staff = abjad.Staff()
>>> for _ in range(3):
...     notes = looper()
...     staff.append(notes)
>>> abjad.f(staff)
\new Staff
{
    \time 4/4
    c'4
    d'2
    e'4
    c'8.
    d'16
    ~
    d'4..
    e'16
    ~
    e'8.
    f'16
    c'8
    d'8
    ~
    d'4.
    e'8
    ~
    e'8
    f'8
}
```



```
>>> looper.window_size = (3, 8)
>>> staff = abjad.Staff()
>>> for _ in range(3):
...     notes = looper()
...     staff.append(notes)
>>> abjad.f(staff)
\new Staff
{
    \time 3/8
    c'16
    d'16
    ~
    d'4
    d'4.
    d'4.
}
```



To disable time signatures altogether, initialise `LoopWindow` with the keyword argument `omit_time_signature` set to `True` (default is `False`), or use the `omit_time_signature` property after initialisation.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> looper = auxjad.LoopWindow(input_music, omit_time_signature=True)
>>> notes = looper()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    c'4
    d'2
    e'4
}
```



This class can handle dynamics and articulations too. When a leaf is shortened by the looping window's movement, the dynamics and articulations are still applied to it.

```
>>> input_music = abjad.Container(
... r"c'4-. \p< d'2-- \f e'4-> \ppp f'2 ~ f'8")
>>> looper = auxjad.LoopWindow(input_music)
>>> staff = abjad.Staff()
>>> for _ in range(2):
...     music = looper()
...     staff.append(music)
>>> abjad.f(staff)
\new Staff
{
    \time 4/4
    c'4
    \p
    - \staccato
    \<
    d'2
    \f
    - \tenuto
    e'4
    \ppp
    - \accent
    c'8.
    \p
    - \staccato
    \<
    d'16
    \f
    - \tenuto
```

(continues on next page)

(continued from previous page)

```

~
d'4..
e'16
\ppp
- \accent
~
e'8.
f'16
}

```



This class can handle tuplets, but this functionality should be considered experimental.

```

>>> input_music = abjad.Container(r"\times 2/3 {c'8 d'8 e'} d'2.")
>>> looper = auxjad.Window(input_music,
...                         window_size=(3, 4),
...                         step_size=(1, 16))
>>> staff = abjad.Staff()
>>> for _ in range(3):
...     window = looper()
...     staff.append(window)
>>> abjad.f(staff)
\new Staff
{
  \times 2/3 {
    \time 3/4
    c'8
    d'8
    e'8
  }
  d'2
  \times 2/3 {
    c'32
    d'16
    ~
    d'16
    e'8
  }
  d'16
  ~
  d'2
  \times 2/3 {
    d'16
    e'8
  }
  d'8
  ~
  d'2
}

```



```
__init__(container: abjad.core.Container.Container, *, window_size: (<class 'tuple'>, <class 'abjad.meter.Meter'>) = (4, 4), step_size: (<class 'int'>, <class 'float'>, <class 'tuple'>, <class 'str'>, <class 'abjad.utilities.Duration.Duration'>) = (1, 16), max_steps: int = 1, repetition_chance: float = 0.0, forward_bias: float = 1.0, head_position: (<class 'int'>, <class 'float'>, <class 'tuple'>, <class 'str'>, <class 'abjad.utilities.Duration.Duration'>) = 0, omit_time_signature: bool = False, move_window_on_first_call: bool = False)
Initialize self. See help(type(self)) for accurate signature.
```

Methods

<code>__init__(container, *, window_size, ...)</code>	Initialize self.
<code>output_all(*, tie_identical_pitches)</code>	
<code>output_n(n, *, tie_identical_pitches)</code>	

Attributes

<code>current_window</code>
<code>forward_bias</code>
<code>head_position</code>
<code>max_steps</code>
<code>omit_time_signature</code>
<code>repetition_chance</code>
<code>step_size</code>
<code>window_size</code>

2.12 auxjad.LoopingWindowByElements

```
class auxjad.LoopingWindowByElements (container: abjad.core.Container.Container, *, window_size: int, step_size: int = 1, max_steps: int = 1, repetition_chance: float = 0.0, forward_bias: float = 1.0, head_position: int = 0, omit_all_time_signatures: bool = False, force_identical_time_signatures: bool = False, move_window_on_first_call: bool = False)
```

Takes an `abjad.Container` as input as well as an integer representing the number of elements per looping window, then outputs a container with the elements processed in the looping process. For instance, if the initial container had the leaves `[A, B, C, D, E, F]` and the looping window was size three, the output would be:

```
A B C B C D C D E D E F E F F
```

This can be better visualised as:

```
A B C
  B C D
    C D E
      D E F
```

(continues on next page)

(continued from previous page)

```
E F
  F
```

Usage is similar to other factory classes. It takes a container (or child class equivalent) and the number of elements of the window as arguments. Each call of the object, in this case `looper()`, will move the window forwards and output the result.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> looper = auxjad.LoopWindowByElements(input_music,
...                                     window_size=3,
...                                     )
>>> notes = looper()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    \time 4/4
    c'4
    d'2
    e'4
}
```



```
>>> notes = looper()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    \time 11/8
    d'2
    e'4
    f'2
    ~
    f'8
}
```



The property `current_window` can be used to access the current window without moving the head forwards.

```
>>> notes = looper.current_window
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    \time 11/8
    d'2
    e'4
}
```

(continues on next page)

(continued from previous page)

```
f'2
~
f'8
}
```



The very first call will output the input container without processing it. To disable this behaviour and have the looping window move on the very first call, initialise the class with the keyword argument `move_window_on_first_call` set to `True`.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> looper = auxjad.WindowByElements(
...     input_music,
...     window_size=3,
...     move_window_on_first_call=True,
... )
>>> notes = looper()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    \time 11/8
    d'2
    e'4
    f'2
    ~
    f'8
}
```



The instances of `WindowByElements` can also be used as an iterator, which can then be used in a for loop to exhaust all windows.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4")
>>> looper = auxjad.WindowByElements(input_music,
...                                 window_size=2,
...                                 )
>>> staff = abjad.Staff()
>>> for window in looper:
...     staff.append(window)
>>> abjad.f(staff)
\new Staff
{
    \time 3/4
    c'4
    d'2
    d'2
}
```

(continues on next page)

(continued from previous page)

```

e'4
\time 1/4
e'4
}

```



Notice how the second staff in the example above does not have a time signature. This is because consecutive identical time signatures are omitted by default. To change this behaviour, instantiate this class with the keyword argument `force_identical_time_signatures` set to `True`, or change the `force_identical_time_signatures` property to alter its value after the initialisation.

This class can take many optional keyword arguments during its creation. `step_size` dictates the size of each individual step in number of elements (default value is 1). `max_steps` sets the maximum number of steps that the window can advance when the object is called, ranging between 1 and the input value (default is also 1). `repetition_chance` sets the chance of a window result repeating itself (that is, the window not moving forwards when called). It should range from 0.0 to 1.0 (default 0.0, i.e. no repetition). `forward_bias` sets the chance of the window moving forward instead of backwards. It should range from 0.0 to 1.0 (default 1.0, which means the window can only move forwards. A value of 0.5 gives 50% chance of moving forwards while a value of 0.0 will move the window only backwards). Finally, `head_position` can be used to offset the starting position of the looping window. It must be an integer and its default value is 0.

```

>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> looper = auxjad.WindowByElements(
...     input_music,
...     window_size=3,
...     step_size=1,
...     max_steps=2,
...     repetition_chance=0.25,
...     forward_bias=0.2,
...     head_position=0,
...     omit_all_time_signatures=False,
...     force_identical_time_signatures=False,
... )
>>> looper.window_size
3
>>> looper.step_size
1
>>> looper.repetition_chance
0.25
>>> looper.forward_bias
0.2
>>> looper.max_steps
2
>>> looper.head_position
0
>>> looper.omit_all_time_signatures
False
>>> looper.force_identical_time_signatures
False

```

Use the properties below to change these values after initialisation.

```
>>> looper.window_size = 2
>>> looper.step_size = 2
>>> looper.max_steps = 3
>>> looper.repetition_chance = 0.1
>>> looper.forward_bias = 0.8
>>> looper.head_position = 2
>>> looper.omit_all_time_signatures = True
>>> looper.force_identical_time_signatures = True
>>> looper.window_size
2
>>> looper.step_size
2
>>> looper.max_steps
3
>>> looper.repetition_chance
0.1
>>> looper.forward_bias
0.8
>>> looper.head_position
2
>>> looper.omit_all_time_signatures
True
>>> looper.force_identical_time_signatures
True
```

To disable time signatures altogether, initialise `LoopWindowByElements` with the keyword argument `omit_all_time_signatures` set to `True` (default is `False`), or use the `omit_time_signature` property after initialisation.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> looper = auxjad.LoopWindowByElements(input_music,
...                                     window_size=3,
...                                     omit_all_time_signatures=True,
...                                     )
>>> notes = looper()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    c'4
    d'2
    e'4
}
```



The function `len()` can be used to get the total number of elements in the container.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> looper = auxjad.LoopWindowByElements(input_music,
...                                     window_size=3,
...                                     )
>>> len(looper)
5
```


To run through the whole process and output it as a single container, from the initial head position until the process outputs the single last element, use the method `output_all()`.

```
>>> input_music = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> looper = auxjad.LoopWindowByElements(input_music,
...                                     window_size=2,
...                                     )
>>> window = looper.output_all()
>>> staff = abjad.Staff(window)
>>> abjad.f(staff)
\new Staff
{
    \time 2/4
    c'4
    d'4
    \time 2/4
    d'4
    e'4
    \time 2/4
    e'4
    f'4
    \time 1/4
    f'4
}
```



When using `output_all()`, set the keyword argument `tie_identical_pitches` to `True` in order to tie identical notes or chords at the end and beginning of consecutive windows.

```
>>> input_music = abjad.Container(r"c'4 d'2 r8 d'4 <e' g'>8 r4 f'2. "
...                               "<e' g'>16")
>>> looper = auxjad.LoopWindowByElements(input_music,
...                                     window_size=4,
...                                     )
>>> music = looper.output_all(tie_identical_pitches=True)
>>> staff = abjad.Staff(music)
>>> abjad.f(staff)
\new Staff
{
    \time 9/8
    c'4
    d'2
    r8
    d'4
    ~
    \time 4/4
    d'2
    r8
    d'4
    <e' g'>8
    \time 3/4
    r8
    d'4
}
```

(continues on next page)

(continued from previous page)

```

    <e' g'>8
    r4
    \time 11/8
    d'4
    <e' g'>8
    r4
    f'2.
    \time 19/16
    <e' g'>8
    r4
    f'2.
    <e' g'>16
    \time 17/16
    r4
    f'2.
    <e' g'>16
    \time 13/16
    f'2.
    <e' g'>16
    ~
    \time 1/16
    <e' g'>16
  }

```



To run through just part of the process and output it as a single container, starting from the initial head position, use the method `output_n()` and pass the number of iterations as argument. Similarly to `output_all()`, the keyword argument `tie_identical_pitches` is available for tying pitches.

```

>>> input_music = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> looper = auxjad.WindowByElements(input_music,
...                                 window_size=2,
...                                 )
>>> window = looper.output_n(2)
>>> staff = abjad.Staff(window)
>>> abjad.f(staff)
\new Staff
{
  \time 2/4
  c'4
  d'4
  \time 2/4
  d'4
  e'4
}

```



To change the size of the looping window after instantiation, use the property `window_size`. In the example below, the initial window is of size 3, and so the first call of the `looper` object outputs the first, second, and third leaves. The window size is then set to 4, and the `looper` is called again, moving to the leaf in the next position, thus outputting the second, third, fourth, and fifth leaves.

```
>>> input_music = abjad.Container(r"c'4 d'2 e'4 f'2 ~ f'8 g'1")
>>> looper = auxjad.WindowByElements(input_music,
...                                 window_size=3,
...                                 )
>>> notes = looper()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    \time 4/4
    c'4
    d'2
    e'4
}
```



```
>>> looper.window_size = 4
>>> notes = looper()
>>> staff = abjad.Staff(notes)
>>> abjad.f(staff)
\new Staff
{
    \time 19/8
    d'2
    e'4
    f'2
    ~
    f'8
    g'1
}
```



This class can handle tuplets, but the output is not ideal and so this functionality should be considered experimental. Time signatures will be correct when dealing with partial tuplets (thus having non-standard values in their denominators), but each individual note of a triplet will have the ratio printed above it.

```
>>> input_music = abjad.Container(r"c'4 d'8 \times 2/3 {a4 g2}")
>>> looper = auxjad.WindowByElements(input_music,
```

(continues on next page)

(continued from previous page)

```

...                               window_size=2,
...                               )
>>> window = looper.output_all()
>>> staff = abjad.Staff(window)
>>> abjad.f(staff)
\new Staff
{
    \time 3/8
    c'4
    d'8
    #(ly:expect-warning "strange time signature found")
    \time 7/24
    d'8
    \tweak edge-height #'(0.7 . 0)
    \times 2/3 {
        a4
    }
    \tweak edge-height #'(0.7 . 0)
    \times 2/3 {
        \time 2/4
        a4
    }
    \tweak edge-height #'(0.7 . 0)
    \times 2/3 {
        g2
    }
    \tweak edge-height #'(0.7 . 0)
    \times 2/3 {
        #(ly:expect-warning "strange time signature found")
        \time 2/6
        g2
    }
}

```



__init__ (container: *abjad.core.Container.Container*, *, window_size: *int*, step_size: *int* = 1, max_steps: *int* = 1, repetition_chance: *float* = 0.0, forward_bias: *float* = 1.0, head_position: *int* = 0, omit_all_time_signatures: *bool* = False, force_identical_time_signatures: *bool* = False, move_window_on_first_call: *bool* = False)
Initialize self. See help(type(self)) for accurate signature.

Methods

<code>__init__</code> (container, *, window_size, ...)	Initialize self.
<code>output_all</code> (*, tie_identical_pitches)	
<code>output_n</code> (n, *, tie_identical_pitches)	

Attributes

current_window
force_identical_time_signatures
forward_bias
head_position
max_steps
omit_all_time_signatures
repetition_chance
step_size
window_size

2.13 auxjad.LoopWindowByList

class auxjad.LoopWindowByList (*container: list, *, window_size: int, step_size: int = 1, max_steps: int = 1, repetition_chance: float = 0.0, forward_bias: float = 1.0, head_position: int = 0, move_window_on_first_call: bool = False*)

Similar to LoopWindowByList, but instead of taking an abjad.Container input, it takes a list of arbitrary size. It then outputs the list elements, whatever they may be. The list elements can be abjad.Container's, but they can also be anything else, thus being more general. Takes a list as input as well as an integer representing the number of elements per looping window, then outputs individual elements according to the looping process. For instance, if the initial list had the elements [A, B, C, D, E, F] and the looping window was size three, the output would be:

```
A B C B C D C D E D E F E F F
```

This can be better visualised as:

```
A B C
  B C D
    C D E
      D E F
        E F
          F
```

It takes a list and the number of elements of the window as arguments. Each call of the object, in this case `looper()`, will move the window forwards and output the result:

```
>>> input_list = ['A', 'B', 'C', 'D', 'E', 'F']
>>> looper = auxjad.LoopWindowByList(input_list, window_size=3)
>>> looper()
['A', 'B', 'C']
>>> looper()
['B', 'C', 'D']
```

The property `current_window` can be used to access the current window without moving the head forwards.

```
>>> looper.current_window
['B', 'C', 'D']
```

The very first call will output the input list without processing it. To disable this behaviour and have the looping window move on the very first call, initialise the class with the keyword argument `move_window_on_first_call` set to `True`.

```
>>> input_list = ['A', 'B', 'C', 'D', 'E', 'F']
>>> looper = auxjad.WindowByList(input_list,
...                               window_size=3,
...                               move_window_on_first_call=True,
...                               )
>>> looper()
['B', 'C', 'D']
```

The instances of `WindowByList` can also be used as an iterator, which can then be used in a for loop to exhaust all windows.

```
>>> input_list = ['A', 'B', 'C', 'D', 'E', 'F']
>>> looper = auxjad.WindowByList(input_list,
...                               window_size=3,
...                               )
>>> for window in looper:
...     print(window)
['A', 'B', 'C']
['B', 'C', 'D']
['C', 'D', 'E']
['D', 'E', 'F']
['E', 'F']
['F']
```

This class can take many optional keyword arguments during its creation. `step_size` dictates the size of each individual step in number of elements (default value is 1). `max_steps` sets the maximum number of steps that the window can advance when the object is called, ranging between 1 and the input value (default is also 1). `repetition_chance` sets the chance of a window result repeating itself (that is, the window not moving forwards when called). It should range from 0.0 to 1.0 (default 0.0, i.e. no repetition). `forward_bias` sets the chance of the window moving forward instead of backwards. It should range from 0.0 to 1.0 (default 1.0, which means the window can only move forwards. A value of 0.5 gives 50% chance of moving forwards while a value of 0.0 will move the window only backwards). Finally, `head_position` can be used to offset the starting position of the looping window (default is 0).

```
>>> input_list = ['A', 'B', 'C', 'D', 'E', 'F']
>>> looper = auxjad.WindowByList(input_list,
...                               window_size=3,
...                               step_size=1,
...                               max_steps=2,
...                               repetition_chance=0.25,
...                               forward_bias=0.2,
...                               head_position=0,
...                               )
>>> looper.window_size
3
>>> looper.step_size
1
>>> looper.repetition_chance
0.25
>>> looper.forward_bias
0.2
>>> looper.max_steps
2
>>> looper.head_position
0
```

Use the properties below to change these values after initialisation.

```

>>> looper.window_size = 2
>>> looper.step_size = 2
>>> looper.max_steps = 3
>>> looper.repetition_chance = 0.1
>>> looper.forward_bias = 0.8
>>> looper.head_position = 2
>>> looper.window_size
2
>>> looper.step_size
2
>>> looper.max_steps
3
>>> looper.repetition_chance
0.1
>>> looper.forward_bias
0.8
>>> looper.head_position
2

```

The function `len()` can be used to get the total number of elements in the container.

```

>>> input_list = ['A', 'B', 'C', 'D', 'E', 'F']
>>> looper = auxjad.LoopWindowByList(input_list, window_size=3)
>>> len(looper)
6

```

To run through just part of the process and output it as a single list, starting from the initial head position, use the method `output_n()` and pass the number of iterations as argument.

```

>>> input_list = ['A', 'B', 'C', 'D']
>>> looper = auxjad.LoopWindowByList(input_list, window_size=3)
>>> looper.output_n(2)
['A', 'B', 'C', 'B', 'C', 'D']

```

To run through the whole process and output it as a single list, from the initial head position until the process outputs the single last element, use the method `output_all()`.

```

>>> input_list = ['A', 'B', 'C', 'D']
>>> looper = auxjad.LoopWindowByList(input_list, window_size=3)
>>> looper.output_all()
['A', 'B', 'C', 'B', 'C', 'D', 'C', 'D', 'D']

```

To change the size of the looping window after instantiation, use the property `window_size`. In the example below, the initial window is of size 3, and so the first call of the `looper` object outputs the first, second, and third elements of the list. The window size is then set to 4, and the `looper` is called again, moving to the element in the next position, thus outputting the second, third, fourth, and fifth elements.

```

>>> input_list = ['A', 'B', 'C', 'D', 'E', 'F']
>>> looper = auxjad.LoopWindowByList(input_list, window_size=3)
>>> looper()
['A', 'B', 'C']
>>> looper.window_size = 4
>>> looper()
['B', 'C', 'D', 'E']

```

It should be clear that the list can contain any types of elements:

```
>>> input_list = [123, 'foo', (3, 4), 3.14]
>>> looper = auxjad.LoopWindowByList(input_list, window_size=3)
>>> looper()
[123, 'foo', (3, 4)]
```

This also include Abjad's types. Abjad's exclusive membership requirement is respected since each call returns a `copy.deepcopy` of the window. The same is true to the `output_all()` method.

```
>>> import abjad
>>> import copy
>>> input_list = [
...     abjad.Container(r"c'4 d'4 e'4 f'4"),
...     abjad.Container(r"fs'1"),
...     abjad.Container(r"r2 bf4 c'4"),
...     abjad.Container(r"c''2. r4"),
... ]
>>> looper = auxjad.LoopWindowByList(input_list, window_size=3)
>>> staff = abjad.Staff()
>>> for element in looper.output_all():
...     staff.append(element)
>>> abjad.f(staff)
\new Staff
{
    {
        c'4
        d'4
        e'4
        f'4
    }
    {
        fs'1
    }
    {
        r2
        bf4
        c'4
    }
    {
        fs'1
    }
    {
        r2
        bf4
        c'4
    }
    {
        c''2.
        r4
    }
    {
        r2
        bf4
        c'4
    }
    {
        c''2.
        r4
    }
}
```

(continues on next page)


```

    }
    {
        c''2.
        r4
    }
}

```

```
>>> staff = abjad.Staff(r"\time 3/8 c'4\pp d'8\pp | c'4\f d'8\f")
>>> abjad.f(staff)
\nnew Staff
{
    \time 3/8
    c'4
    \pp
    d'8
    \pp
    c'4
    \f
    d'8
    \f
}
```



```
>>> auxjad.remove_repeated_dynamics(staff)
>>> abjad.f(staff)
\nnew Staff
{
    \time 3/8
    c'4
    \pp
    d'8
    c'4
    \f
    d'8
}
```



The function also removes dynamics that are separated by an arbitrary number of leaves without dynamics:

```
>>> staff = abjad.Staff(r"\time 3/8 c'4\p d'8 | e'4.\p | c'4\p d'8\f")
>>> abjad.f(staff)
\nnew Staff
{
    \time 3/8
    c'4
    \p
    d'8
    e'4.
    \p
    c'4
    \p
    d'8
}
```

(continues on next page)

(continued from previous page)

```
\f
}
```



```
>>> auxjad.remove_repeated_dynamics(staff)
>>> abjad.f(staff)
\new Staff
{
    \time 3/8
    c'4
    \p
    d'8
    e'4.
    c'4
    d'8
    \f
}
```



The input container can also handle subcontainers:

```
>>> staff = abjad.Staff([abjad.Note("c'2"),
...                      abjad.Chord("<d' f'>2"),
...                      abjad.Tuplet((2, 3), "g2 a2 b2"),
...                      ])
>>> abjad.attach(abjad.Dynamic('ppp'), staff[0])
>>> abjad.attach(abjad.Dynamic('ppp'), staff[1])
>>> abjad.attach(abjad.Dynamic('ppp'), staff[2][0])
>>> abjad.f(staff)
\new Staff
{
    c'2
    \ppp
    <d' f'>2
    \ppp
    \times 2/3 {
        g2
        \ppp
        a2
        b2
    }
}
```



```
>>> auxjad.remove_repeated_dynamics(staff)
>>> abjad.f(staff)
\new Staff
{
  c'2
  \ppp
  <d' f'>2
  \times 2/3 {
    g2
    a2
    b2
  }
}
```



By default, repeated dynamics with hairpins in between are not removed, but consecutive ones will.

```
>>> staff = abjad.Staff(r"c'2\p< d'2\f\> | c'2\f d'2\f | e'1\p")
>>> abjad.f(staff)
\new Staff
{
  c'1
  \p
  \<
  d'1
  \f
  \>
  c'1
  \f
  d'1
  \f
  e'1
  \p
}
```



```
>>> auxjad.remove_repeated_dynamics(staff)
>>> abjad.f(staff)
```

(continues on next page)

(continued from previous page)

```
\new Staff
{
  c'1
  \p
  \<
  d'1
  \f
  \>
  c'1
  \f
  d'1
  e'1
  \p
}
```



To override the previous behaviour, set `ignore_hairpins=True` and hairpins will be ignored.

```
>>> staff = abjad.Staff(r"c'2\p\< d'2\f\> | c'2\f d'2\f | e'1\p")
>>> abjad.f(staff)
\new Staff
{
  c'1
  \p
  \<
  d'1
  \f
  \>
  c'1
  \f
  d'1
  \f
  e'1
  \p
}
```



```
>>> auxjad.remove_repeated_dynamics(staff, ignore_hairpins=True)
>>> abjad.f(staff)
\new Staff
{
  c'1
  \p
  \<

```

(continues on next page)

(continued from previous page)

```
d'1
\ f
\ >
c'1
d'1
e'1
\ p
}
```



By default, rests are treated just like any other leaf and thus notes with an identical dynamic separated by an arbitrary number of rests will be considered as repeated and the second dynamic will be removed.

```
>>> staff = abjad.Staff(r"c'4\pp r2. | c'4\pp")
>>> auxjad.remove_repeated_dynamics(staff)
>>> abjad.f(staff)
\new Staff
{
  c'4
  \pp
  r2.
  c'4
}
```



To override the previous behaviour, set `reset_after_rests=True` and dynamics will always be restated after a rest.

```
>>> staff = abjad.Staff(r"c'4\pp r2. | c'4\pp")
>>> auxjad.remove_repeated_dynamics(staff, reset_after_rests=True)
>>> abjad.f(staff)
\new Staff
{
  c'4
  \pp
  r2.
  c'4
  \pp
}
```



The argument `reset_after_rests` takes not only boolean values but also duration (`abjad.Duration`, tuple, float, etc.). This sets the maximum length of rests before which identical dynamics are restated. If the total length of rests falls below that value, then repeated dynamics are removed.

In the case below, a rest of `r2.` is shorter than a duration of `(4, 4)`, so the repeated dynamic is removed.

```
>>> staff = abjad.Staff(r"c'4\pp r2. | c'4\pp")
>>> auxjad.remove_repeated_dynamics(staff, reset_after_rests=(4, 4))
>>> abjad.f(staff)
\new Staff
{
    c'4
    \pp
    r2.
    c'4
}
```



But setting the duration to `2/4` forces the dynamic to be restated.

```
>>> staff = abjad.Staff(r"c'4\pp r2. | c'4\pp")
>>> auxjad.remove_repeated_dynamics(staff, reset_after_rests=2/4)
>>> abjad.f(staff)
\new Staff
{
    c'4
    \pp
    r2.
    c'4
    \pp
}
```



The function also handles measure rests with `reset_after_rests`.

```
>>> staff = abjad.Staff(r"c'4\pp r2. | c'4\pp r2. |R1 | c'4\pp")
>>> auxjad.remove_repeated_dynamics(
...     staff,
...     reset_after_rests=abjad.Duration(4, 4),
... )
>>> abjad.f(staff)
\new Staff
{
    c'4
    \pp
    r2.
    c'4
}
```

(continues on next page)

(continued from previous page)

```

r2.
R1
c'4
\pp
}

```



2.15 auxjad.remove_repeated_time_signatures

`auxjad.remove_repeated_time_signatures` (*container: abjad.core.Container.Container*) → *abjad.core.Container.Container*

A function which removes all unnecessary time signatures. It removes consecutive effective time signatures, even if separated by any number of bars with no time signature.

When two consecutive bars have identical time signatures, the second one is removed:

```

>>> staff = abjad.Staff(r"c'4 d'8 | c'4 d'8")
>>> abjad.attach(abjad.TimeSignature((3, 8)), staff[0])
>>> abjad.attach(abjad.TimeSignature((3, 8)), staff[2])
>>> abjad.f(staff)
\new Staff
{
    \time 3/8
    c'4
    d'8
    \time 3/8
    c'4
    d'8
}

```



```

>>> staff = auxjad.remove_repeated_time_signatures(staff)
>>> abjad.f(staff)
\new Staff
{
    \time 3/8
    c'4
    d'8
    c'4
    d'8
}

```



The function also removes time signatures that are separated by an arbitrary number of bars without one:

```
>>> staff = abjad.Staff(r"c'4 d'8 e'4. c'4 d'8")
>>> abjad.attach(abjad.TimeSignature((3, 8)), staff[0])
>>> abjad.attach(abjad.TimeSignature((3, 8)), staff[3])
>>> abjad.f(staff)
\new Staff
{
    \time 3/8
    c'4
    d'8
    e'4.
    \time 3/8
    c'4
    d'8
}
```



```
>>> staff = auxjad.remove_repeated_time_signatures(staff)
>>> abjad.f(staff)
\new Staff
{
    \time 3/8
    c'4
    d'8
    e'4.
    c'4
    d'8
}
```



The input container can also handle subcontainers, including cases in which the time signatures are attached to leaves of subcontainers:

```
>>> staff = abjad.Staff([abjad.Note("c'2"),
...                      abjad.Chord("<d' f'>2"),
...                      abjad.Tuplet((2, 3), "g2 a2 b2"),
...                      ])
>>> abjad.attach(abjad.TimeSignature((2, 2)), staff[0])
>>> abjad.attach(abjad.TimeSignature((2, 2)), staff[2][0])
>>> abjad.f(staff)
\new Staff
{
    \time 2/2
    c'2
    <d' f'>2
    \times 2/3 {
        \time 2/2
```

(continues on next page)

(continued from previous page)

```

    g2
    a2
    b2
  }
}

```



```

>>> staff = auxjad.remove_repeated_time_signatures(staff)
>>> abjad.f(staff)
\new Staff
{
  \time 2/2
  c'2
  <d' f'>2
  \times 2/3 {
    g2
    a2
    b2
  }
}

```



2.16 auxjad.rests_to_multimeasure_rest

`auxjad.rests_to_multimeasure_rest` (*container: abjad.core.Container.Container*)

Takes an `abjad.Container` and converts all rests into `abjad.MultimeasureRest`'s when possible.

Converts any measure filled with regular rests into a measure with a single multi-measure rest.

```

>>> container = abjad.Container(r"r1")
>>> auxjad.rests_to_multimeasure_rest(container)
>>> abjad.f(container)
{
  R1
}

```



Works with measures with multiple regular rests.

```
>>> container = abjad.Container(r"\time 3/4 r4 r8.. r32 r4")
>>> auxjad.rests_to_multimeasure_rest(container)
>>> abjad.f(container)
{
    %%% \time 3/4 %%%
    R1 * 3/4
}
```



Note: Notice that the time signatures in the output are commented out with %%. This is because Abjad only applies time signatures to containers that belong to a `abjad.Staff`. The present function works with either `abjad.Container` and `abjad.Staff`.

```
>>> container = abjad.Container(r"\time 3/4 r4 r8.. r32 r4")
>>> auxjad.rests_to_multimeasure_rest(container)
>>> abjad.f(container)
{
    %%% \time 3/4 %%%
    R1 * 3/4
}
>>> staff = abjad.Staff([container])
>>> abjad.f(container)
{
    %%% \time 3/4 %%%
    R1 * 3/4
}
```

Works with containers with multiple time signatures as well as notes.

```
>>> container = abjad.Container(r"\time 3/4 r2. | "
...                               "\time 6/8 r2. | "
...                               "\time 5/4 c'1 ~ c'4 | r1 r4"
...                               )
>>> auxjad.rests_to_multimeasure_rest(container)
>>> abjad.f(container)
{
    %%% \time 3/4 %%%
    R1 * 3/4
    %%% \time 6/8 %%%
    R1 * 3/4
    %%% \time 5/4 %%%
    c'1
    ~
    c'4
    R1 * 5/4
}
```



2.17 auxjad.simplified_time_signature_ratio

`auxjad.simplified_time_signature_ratio` (*ratio*: (`<class 'tuple'>`, `<class 'abjad.utilities.Duration.Duration'>`, `<class 'abjad.indicators.TimeSignature.TimeSignature'>`), ***, *min_denominator*: `int = 4`) \rightarrow `tuple`

A function simplifies the ratio of a given time signature respecting a minimum denominator value. Input is a tuple of two integers.

By default, the function simplifies the ratio of numerator/denominator using a minimum denominator value of 4 (that is, the denominator will not get smaller than 4). In the case below, (2, 4) is the simplest representation of the ratio (4, 8) with a denominator equal to or larger than 4.

```
>>> ratio = auxjad.simplified_time_signature_ratio((4, 8))
>>> time_signature = abjad.TimeSignature(ratio)
>>> format(time_signature)
abjad.TimeSignature((2, 4))
>>> ratio = auxjad.simplified_time_signature_ratio((1, 1))
>>> time_signature = abjad.TimeSignature(ratio)
>>> format(time_signature)
abjad.TimeSignature((4, 4))
```

If a ratio cannot be simplified at all, the function returns the original values.

```
>>> ratio = auxjad.simplified_time_signature_ratio((7, 8))
>>> time_signature = abjad.TimeSignature(ratio)
>>> format(time_signature)
abjad.TimeSignature((7, 8))
```

The `min_denominator` can be set to values other than 4. If set to 2, the simplest representation of the ratio (4, 8) becomes (1, 2).

```
>>> ratio = auxjad.simplified_time_signature_ratio((4, 8),
...                                              min_denominator=2
...                                              )
>>> time_signature = abjad.TimeSignature(ratio)
>>> format(time_signature)
abjad.TimeSignature((1, 2))
>>> ratio = auxjad.simplified_time_signature_ratio((1, 1),
...                                              min_denominator=1
...                                              )
>>> time_signature = abjad.TimeSignature(ratio)
>>> format(time_signature)
abjad.TimeSignature((1, 1))
```

2.18 auxjad.sync_containers

`auxjad.sync_containers` (**containers*, *use_multimeasure_rests*: `bool = True`, *adjust_last_time_signature*: `bool = True`)

Takes an arbitrary number of `abjad.Container`'s (or child classes), finds the longest one and adds rests to all the shorter ones, making them the same length. By default, it rewrites the last time signature if necessary, and uses multi-measure rests whenever possible.

Input two or more containers. This function will fill the shortest ones with rests ensuring all their lengths become the same.

```
>>> container1 = abjad.Container(r"\time 4/4 g'2.")
>>> container2 = abjad.Container(r"\time 4/4 c'1")
>>> auxjad.sync_containers(container1, container2)
>>> abjad.f(container1)
{
    %%% \time 4/4 %%%
    g'2.
    r4
}
```



```
>>> abjad.f(container2)
{
    %%% \time 4/4 %%%
    c'1
}
```



Note: Notice that the time signatures in the output are commented out with %%%. This is because Abjad only applies time signatures to containers that belong to a `abjad.Staff`. The present function works with either `abjad.Container` and `abjad.Staff`.

```
>>> container1 = abjad.Container(r"\time 4/4 g'2.")
>>> container2 = abjad.Container(r"\time 4/4 c'1")
>>> auxjad.sync_containers(container1, container2)
>>> abjad.f(container1)
{
    %%% \time 4/4 %%%
    g'2.
    r4
}
>>> staff = abjad.Staff([container1])
>>> abjad.f(container1)
{
    \time 4/4
    g'2.
    r4
}
```

If all containers have the same size, no modification is applied.

```
>>> container1 = abjad.Container(r"\time 3/4 g'2.")
>>> container2 = abjad.Container(r"\time 3/4 c'2.")
>>> auxjad.sync_containers(container1, container2)
>>> abjad.f(container1)
```

(continues on next page)

(continued from previous page)

```
{
    %%% \time 3/4 %%%
    g'2.
}
```



```
>>> abjad.f(container2)
{
    %%% \time 3/4 %%%
    c'2.
}
```



By default, this function closes the longest container by rewriting the time signature of its last bar if necessary (if it is underfull), and uses multi-measure rests whenever possible.

```
>>> container1 = abjad.Container(r"\time 4/4 g'1 | f'4")
>>> container2 = abjad.Container(r"\time 4/4 c'1")
>>> auxjad.sync_containers(container1, container2)
>>> abjad.f(container1)
{
    %%% \time 4/4 %%%
    g'1
    %%% \time 1/4 %%%
    f'4
}
```



```
>>> abjad.f(container2)
{
    %%% \time 4/4 %%%
    c'1
    %%% \time 1/4 %%%
    R1*1/4
}
```



To disable multi-measure rests, set the keyword argument `use_multimeasure_rests` to `False`.

```
>>> container1 = abjad.Container(r"\time 4/4 g'1 | f'4")
>>> container2 = abjad.Container(r"\time 4/4 c'1")
>>> auxjad.sync_containers(container1,
...                          container2,
...                          use_multimeasure_rests=False,
...                          )
>>> abjad.f(container1)
{
    %%% \time 4/4 %%%
    g'1
    %%% \time 1/4 %%%
    f'4
}
```



```
>>> abjad.f(container2)
{
    %%% \time 4/4 %%%
    c'1
    %%% \time 1/4 %%%
    r4
}
```



To allow containers to be left open (with underfull bars), set the keyword argument `adjust_last_time_signature` to `False`.

```
>>> container1 = abjad.Container(r"\time 4/4 g'1 | f'4")
>>> container2 = abjad.Container(r"\time 4/4 c'1")
>>> auxjad.sync_containers(container1,
...                          container2,
...                          adjust_last_time_signature=False,
...                          )
>>> abjad.f(container1)
{
    %%% \time 4/4 %%%
    g'1
    f'4
}
```



```
>>> abjad.f(container2)
{
```

(continues on next page)

(continued from previous page)

```

    %%% \time 4/4 %%%
    c'1
    r4
}

```



This function can take an arbitrary number of containers.

```

>>> container1 = abjad.Container(r"\time 4/4 c'1 | g'4")
>>> container2 = abjad.Container(r"\time 4/4 c'1 | g'2")
>>> container3 = abjad.Container(r"\time 4/4 c'1 | g'2.")
>>> container4 = abjad.Container(r"\time 4/4 c'1")
>>> auxjad.sync_containers(container1,
...                          container2,
...                          container3,
...                          container4,
...                          )
>>> abjad.f(container1)
{
    %%% \time 4/4 %%%
    c'1
    %%% \time 3/4 %%%
    g'4
    r2
}

```



```

>>> abjad.f(container2)
{
    %%% \time 4/4 %%%
    c'1
    %%% \time 3/4 %%%
    g'2
    r4
}

```



```

>>> abjad.f(container3)
{
    %%% \time 4/4 %%%
    c'1
    %%% \time 3/4 %%%

```

(continues on next page)

(continued from previous page)

```

    g'2.
}

```



```

>>> abjad.f(container4)
{
    %%% \time 4/4 %%%
    c'1
    %%% \time 3/4 %%%
    R1*3/4
}

```



The containers can be of different length, can have different time signatures, and can contain time signature changes as well.

```

>>> container1 = abjad.Container(r"\time 4/4 c'4 d'4 e'4 f'4")
>>> container2 = abjad.Container(r"\time 3/4 a2. \time 4/4 c'4")
>>> container3 = abjad.Container(r"\time 5/4 g'1 ~ g'4")
>>> container4 = abjad.Container(r"\time 6/8 c'2")
>>> auxjad.sync_containers(container1,
...                          container2,
...                          container3,
...                          container4,
...                          )
>>> abjad.f(container1)
{
    %%% \time 4/4 %%%
    c'4
    d'4
    e'4
    f'4
    %%% \time 1/4 %%%
    R1*1/4
}

```



```

>>> abjad.f(container2)
{
    %%% \time 3/4 %%%
    a2.
    %%% \time 2/4 %%%
}

```

(continues on next page)

(continued from previous page)

```
c'4
r4
}
```



```
>>> abjad.f(container3)
{
    %%% \time 5/4 %%%
    g''1
    ~
    g''4
}
```



```
>>> abjad.f(container4)
{
    %%% \time 6/8 %%%
    c'2
    r4
    %%% \time 2/4 %%%
    R1*1/2
}
```



It's important to note that LilyPond does not support simultaneous staves with different time signatures (i.e. polymetric notation) by default. In order to enable it, the "Timing_translator" and "Default_bar_line_engraver" must be removed from the Score context and added to the Staff context. Below is a full example of how this can be accomplished using Abjad.

```
>>> container1 = abjad.Container(r"\time 4/4 c'4 d'4 e'4 f'4")
>>> container2 = abjad.Container(r"\time 3/4 a2. \time 4/4 c'4")
>>> container3 = abjad.Container(r"\time 5/4 g''1 ~ g''4")
>>> container4 = abjad.Container(r"\time 6/8 c'2")
>>> auxjad.sync_containers(container1,
...                          container2,
...                          container3,
...                          container4,
...                          )
>>> staves = [abjad.Staff([container1]),
...            abjad.Staff([container2]),
...            abjad.Staff([container3]),
```

(continues on next page)

(continued from previous page)

```

...         abjad.Staff([container4]),
...     ]
>>> score = abjad.Score(staves)
>>> lilypond_file = abjad.LilyPondFile.new()
>>> score_block = abjad.Block(name='score')
>>> layout_block = abjad.Block(name='layout')
>>> score_block.items.append(score)
>>> score_block.items.append(layout_block)
>>> lilypond_file.items.append(score_block)
>>> layout_block.items.append(
...     r'''
...     \context {
...         \Score
...         \remove "Timing_translator"
...         \remove "Default_bar_line_engraver"
...     }
...     \context {
...         \Staff
...         \consists "Timing_translator"
...         \consists "Default_bar_line_engraver"
...     }
...     '''
>>> abjad.f(lilypond_file)
\score { %! abjad.LilyPondFile._get_formatted_blocks()
  \new Score
  <<
    \new Staff
    {
      {
        \time 4/4
        c'4
        d'4
        e'4
        f'4
        \time 1/4
        R1 * 1/4
      }
    }
    \new Staff
    {
      {
        \time 3/4
        a2.
        \time 2/4
        c'4
        r4
      }
    }
    \new Staff
    {
      {
        \time 5/4
        g''1
        ~
        g''4
      }
    }
  }
}

```

(continues on next page)

(continued from previous page)

```

\new Staff
{
  {
    \time 6/8
    c'2
    r4
    \time 2/4
    R1 * 1/2
  }
}
>>
\layout {
  \context {
    \Score
    \remove "Timing_translator"
    \remove "Default_bar_line_engraver"
  }
  \context {
    \Staff
    \consists "Timing_translator"
    \consists "Default_bar_line_engraver"
  }
}
} %! abjad.LilyPondFile._get_formatted_blocks()

```



Warning: If one or more containers is malformed, i.e. it has an underfilled bar before a time signature change, the function raises a `ValueError` exception.

```

>>> container1 = abjad.Container(r"\time 4/4 g'1 | f'4")
>>> container2 = abjad.Container(r"\time 5/4 c'1 | \time 4/4 d'4")
>>> auxjad.sync_containers(container1, container2)
ValueError: at least one 'container' is malformed, with an underfull
bar preceeding a time signature change

```

2.19 auxjad.TenneysContainer

class auxjad.TenneysContainer (*container: list*, *, *weights: list = None*, *curvature: float = 1.0*)

TenneysContainer is an implementation of the Dissonant Counterpoint Algorithm by James Tenney. This class can be used to randomly select elements from an input list, giving more weight to elements which have not been selected in recent iterations. In other words, Tenney's algorithm uses feedback in order to lower the weight of recently selected elements.

This implementation is based on the paper: Polansky, L., A. Barnett, and M. Winter (2011). 'A Few More Words About James Tenney: Dissonant Counterpoint and Statistical Feedback'. In: Journal of Mathematics and Music 5(2). pp. 63–82.

The container should be initialised with a list of objects. The contents of the list can be absolutely anything.

```
>>> container = auxjad.TenneysContainer(['A', 'B', 'C', 'D', 'E', 'F'])
>>> container.contents
['A', 'B', 'C', 'D', 'E', 'F']
```

Applying the `len()` function to the container will give the length of the container.

```
>>> len(container)
6
```

When no other keyword arguments are used, the default probabilities of each element in the list is 1.0. Probabilities are not normalised. Use the `previous_index` attribute to check the previously selected index (default is `None`).

```
>>> container.probabilities
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
>>> container.previous_index
None
```

Calling the container will output one of its elements, selected according to the current probability values. After each call, the object updates all probability values, setting the previously selected element's probability at 0.0 and raising all other probabilities according to a growth function (more on this below).

```
>>> result = ''
>>> for _ in range(30):
...     result += container()
>>> result
'EDFACEABAFDCEDAFADCBFEDABEDFEC'
```

From the result above it is possible to see that there are no immediate repetitions of elements (since once selected, their probability is always set to 0.0 and will take at least one iteration to grow to a non-zero value). Checking the probabilities and `previous_index` attributes will give us their current values.

```
>>> container.probabilities
[6.0, 5.0, 0.0, 3.0, 1.0, 2.0]
>>> container.previous_index
2
```

This class can take two optional keyword arguments during its instantiation, namely `weights` and `curvature`. `weights` takes a list of floats with the individual weights of each element; by default, all weights are set to 1.0. These weights affect the effective probability of each element. The other argument, `curvature`, is the exponent of the growth function for all elements. The growth function takes as input the number of iterations since an element has been last selected, and raises this number to the curvature value. If `curvature` is set to 1.0 (which is its default value), the growth is linear with each iteration. If set to a value

larger than 0.0 and less than 1.0, the growth is negative (or concave), so that the chances of an element which is not being selected will grow at ever smaller rates as the number of iterations it has not been selected increase. If the `curvature` is set to 1.0, the growth is linear with the number of iterations. If the `curvature` is larger than 1.0, the curvature is positive (or convex) and the growth will accelerate as the number of iterations an element has not been selected grows. Setting the curvature to 0.0 will result in an static probability vector with all values set to 1.0, except for the previously selected one which will be set to 0.0; this will result in a uniformly random selection without repetition.

With linear curvature (default value of 1.0):

```
>>> container = auxjad.TenneysContainer(['A', 'B', 'C', 'D', 'E', 'F'])
>>> container.curvature
1.0
>>> container.weights
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
>>> container.probabilities
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
>>> container()
'B'
>>> container.curvature
1.0
>>> container.weights
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
>>> container.probabilities
[2.0, 0.0, 2.0, 2.0, 2.0, 2.0]
```

Using a convex curvature:

```
>>> container = auxjad.TenneysContainer(['A', 'B', 'C', 'D', 'E', 'F'],
...                                     curvature=0.2,
...                                     )
>>> container.curvature
0.2
>>> container.weights
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
>>> container.probabilities
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
>>> container()
'C'
>>> container.curvature
0.2
>>> container.weights
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
>>> container.probabilities
[1.148698354997035, 1.148698354997035, 0.0, 1.148698354997035,
1.148698354997035, 1.148698354997035]
```

With a convex curvature, the growth of the probability of each non-selected term gets smaller as the number of times it is not selected increases. The smaller the curvature is, the less difference there will be between any non-previously selected elements. This results in sequences which have more chances of a same element being near each other. In the sequence below, note how there are many cases of a same element being separated only by a single other one, such as 'ACA' in index 6.

```
>>> result = ''
>>> for _ in range(30):
...     result += container()
>>> result
'DACBEDFACABDACECBFAEDBAFBABFD'
```

Checking the probability values at this point outputs:

```
>>> container.probabilities
[1.2457309396155174, 1.148698354997035, 1.6952182030724354, 0.0,
1.5518455739153598, 1.0]
```

As we can see, all non-zero values are relatively close to each other, which is why there is a high chance of an element being selected again just two iterations apart.

Using a concave curvature:

```
>>> container = auxjad.TenneysContainer(['A', 'B', 'C', 'D', 'E', 'F'],
...                                     curvature=15.2,
...                                     )
>>> container.curvature
0.2
>>> container.weights
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
>>> container.probabilities
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
>>> container()
'C'
>>> container.curvature
0.2
>>> container.weights
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
>>> container.probabilities
[37640.547696542824, 37640.547696542824, 37640.547696542824, 0.0,
37640.547696542824, 37640.547696542824]
```

With a concave curvature, the growth of the probability of each non-selected term gets larger as the number of times it is not selected increases. The larger the curvature is, the larger the difference there will be between any non-previously selected elements. This results in sequences which have less chances of a same element being near each other. In the sequence below, with a curvature of 15.2, note how the elements are as far apart from each other, resulting in a repeating string of 'DFAECB'.

```
>>> result = ''
>>> for _ in range(30):
...     result += container()
>>> result
'DFAECBDFAECEBDFAECEBDFAECEBDFAECEB'
```

Checking the probability values at this point outputs:

```
>>> container.probabilities
[17874877.39956566, 0.0, 1.0, 42106007735.02238,
37640.547696542824, 1416810830.8957152]
```

As we can see, the non-zero values vary wildly. The higher the curvature, the higher the difference between these values, making some of them much more likely to be selected.

Each element can also have a fixed weight to themselves. This will affect the probability calculation. The example below uses the default linear curvature.

```
>>> container = auxjad.TenneysContainer(
...     ['A', 'B', 'C', 'D', 'E', 'F'],
...     weights=[1.0, 1.0, 5.0, 5.0, 10.0, 20.0],
>>> )
```

(continues on next page)

(continued from previous page)

```
>>> container.weights
[1.0, 1.0, 5.0, 5.0, 10.0, 20.0]
>>> container.probabilities
[1.0, 1.0, 5.0, 5.0, 10.0, 20.0]
>>> result = ''
>>> for _ in range(30):
...     result += container()
>>> result
'FBFEFECFDEADFEDFEDBFECDAFCEDCFE'
>>> container.weights
[1.0, 1.0, 5.0, 5.0, 10.0, 20.0]
>>> container.probabilities
[7.0, 12.0, 10.0, 15.0, 0.0, 20.0]
```

To reset the probability to its initial value, use the method `reset_probabilities()`.

```
>>> container = auxjad.TenneysContainer(['A', 'B', 'C', 'D', 'E', 'F'])
>>> for _ in range(30):
...     container()
>>> container.probabilities
[4.0, 3.0, 1.0, 0.0, 5.0, 2.0]
>>> container.reset_probabilities()
>>> container.probabilities
[1.0, 1.0, 1.0, 1.0, 1.0, 1.0]
```

This class allows slicing to get and set values in the container. This will not affect the current probability vector, and the new element will have the same probability as the one it replaced.

```
>>> container = auxjad.TenneysContainer(['A', 'B', 'C', 'D', 'E', 'F'])
>>> for _ in range(30):
...     container()
>>> container.probabilities
[3.0, 2.0, 1.0, 7.0, 5.0, 0.0]
>>> container[2]
'C'
>>> container[1:4]
['B', 'C', 'D']
>>> container[2] = 'foo'
>>> container.contents
['A', 'B', 'foo', 'D', 'E', 'F']
>>> container[:] = ['foo', 'bar', 'X', 'Y', 'Z', '...']
>>> container.contents
['foo', 'bar', 'X', 'Y', 'Z', '...']
>>> container.probabilities
[3.0, 2.0, 1.0, 7.0, 5.0, 0.0]
```

You can also check if the object contains a specific element. In the case of the container above, we have:

```
>>> 'foo' in container
True
>>> 'A' in container
False
```

A new container of an arbitrary length can be set at any point using the property `contents`. Do notice that the probabilities will be reset at that point. This method can take the optional keyword argument `weights` similarly to when instantiating the class.


```

>>> container = auxjad.TenneysContainer(['A', 'B', 'C', 'D', 'E', 'F'])
>>> for _ in range(30):
...     container()
>>> container.probabilities
[2.0, 1.0, 4.0, 3.0, 0.0, 5.0]
>>> container.contents
['A', 'B', 'C', 'D', 'E', 'F']
>>> container.contents = [2, 4, 6, 8]
>>> container.contents
[2, 4, 6, 8]
>>> len(container)
4
>>> container.weights
[1.0, 1.0, 1.0, 1.0]
>>> container.probabilities
[1.0, 1.0, 1.0, 1.0]

```

To change the curvature value at any point, simply set the property `curvature` to a different value.

```

>>> container = auxjad.TenneysContainer(['A', 'B', 'C', 'D', 'E', 'F'])
>>> container.curvature
1.0
>>> container.curvature = 0.25
>>> container.curvature
0.25

```

`__init__` (*container: list, *, weights: list = None, curvature: float = 1.0*)
 Initialize self. See help(type(self)) for accurate signature.

Methods

<code>__init__</code> (container, *, weights, curvature)	Initialize self.
<code>reset_probabilities</code> ()	

Attributes

<code>contents</code>	
<code>curvature</code>	
<code>weights</code>	

2.20 auxjad.underfull_duration

`auxjad.underfull_duration` (*container: abjad.core.Container.Container*) → *abjad.utilities.Duration.Duration*

Checks if an `abjad.Container` is underfull and returns the missing `abjad.Duration`.

Returns the missing duration of the last bar of any container or child class. If no time signature is encountered, it uses LilyPond's convention and considers the container as in 4/4.

```

>>> container1 = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> container2 = abjad.Container(r"c'4 d'4 e'4")
>>> container3 = abjad.Container(r"c'4 d'4 e'4 f'4 | c'4")

```

(continues on next page)

(continued from previous page)

```
>>> container4 = abjad.Container(r"c'4 d'4 e'4 f'4 | c'4 d'4 e'4 f'4")
>>> auxjad.underfull_duration(container1)
0
>>> auxjad.underfull_duration(container2)
1/4
>>> auxjad.underfull_duration(container3)
3/4
>>> auxjad.underfull_duration(container4)
0
```

Handles any time signatures as well as changes of time signature.

```
>>> container1 = abjad.Container(r"\time 4/4 c'4 d'4 e'4 f'4")
>>> container2 = abjad.Container(r"\time 3/4 a2. \time 2/4 r2")
>>> container3 = abjad.Container(r"\time 5/4 g1 ~ g4 \time 4/4 af'2")
>>> container4 = abjad.Container(r"\time 6/8 c'2 ~ c'8")
>>> auxjad.underfull_duration(container1)
0
>>> auxjad.underfull_duration(container2)
0
>>> auxjad.underfull_duration(container3)
1/2
>>> auxjad.underfull_duration(container4)
1/8
```

Correctly handles partial time signatures.

```
>>> container = abjad.Container(r"c'4 d'4 e'4 f'4")
>>> time_signature = abjad.TimeSignature((3, 4), partial=(1, 4))
>>> abjad.attach(time_signature, container[0])
>>> auxjad.underfull_duration(container)
0
```

It also handles multi-measure rests.

```
>>> container1 = abjad.Container(r"R1")
>>> container2 = abjad.Container(r"\time 3/4 R1*3/4 \time 2/4 r2")
>>> container3 = abjad.Container(r"\time 5/4 R1*5/4 \time 4/4 g'4")
>>> container4 = abjad.Container(r"\time 6/8 R1*1/2")
>>> auxjad.underfull_duration(container1)
0
>>> auxjad.underfull_duration(container2)
0
>>> auxjad.underfull_duration(container3)
3/4
>>> auxjad.underfull_duration(container4)
1/4
```

Warning: If a container is malformed, i.e. it has an underfilled bar before a time signature change, the function raises a `ValueError` exception.

```
>>> container = abjad.Container(r"\time 5/4 g'1 \time 4/4 f'1")
>>> auxjad.underfull_duration(container)
ValueError: 'container' is malformed, with an underfull bar preceeding
a time signature change
```

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

a

auxjad, [1](#)

Symbols

[__init__\(\)](#) (auxjad.ArtificialHarmonic method), 9
[__init__\(\)](#) (auxjad.CartographyContainer method), 13
[__init__\(\)](#) (auxjad.HarmonicNote method), 23
[__init__\(\)](#) (auxjad.LeafDynMaker method), 29
[__init__\(\)](#) (auxjad.LeafShuffler method), 38
[__init__\(\)](#) (auxjad.LoopWindow method), 48
[__init__\(\)](#) (auxjad.LoopWindowByElements method), 56
[__init__\(\)](#) (auxjad.LoopWindowByList method), 61
[__init__\(\)](#) (auxjad.TenneysContainer method), 85

A

[are_containers_equal\(\)](#) (in module auxjad), 4
[are_leaves_tieable\(\)](#) (in module auxjad), 5
 ArtificialHarmonic (class in auxjad), 6
 auxjad (module), 1

C

CartographyContainer (class in auxjad), 10
[close_container\(\)](#) (in module auxjad), 14

F

[fill_with_rests\(\)](#) (in module auxjad), 17

H

HarmonicNote (class in auxjad), 21

I

[is_container_full\(\)](#) (in module auxjad), 24

L

LeafDynMaker (class in auxjad), 25
 LeafShuffler (class in auxjad), 29
 LoopWindow (class in auxjad), 38
 LoopWindowByElements (class in auxjad), 48
 LoopWindowByList (class in auxjad), 57

R

[remove_repeated_dynamics\(\)](#) (in module auxjad), 61
[remove_repeated_time_signatures\(\)](#) (in module auxjad), 68

[rests_to_multimeasure_rest\(\)](#) (in module auxjad), 70

S

[simplified_time_signature_ratio\(\)](#) (in module auxjad), 72
[sync_containers\(\)](#) (in module auxjad), 72

T

TenneysContainer (class in auxjad), 81

U

[underfull_duration\(\)](#) (in module auxjad), 85