
listools Documentation

Release 2.1.2

Gilberto Agostinho

Dec 03, 2018

CONTENTS:

1	The <i>listools</i> package	1
2	<i>flatools</i> module	3
3	<i>iterz</i> module	11
4	<i>listutils</i> module	19
5	<i>llogic</i> module	21
	Python Module Index	27
	Index	29

THE *LISTTOOLS* PACKAGE

listools is a Python 3 package of which provides utility functions for dealing with lists in Python 3. *listools* supports Python version 3.5 and newer. You can install it using *pip install listools*.

This package contains four modules: *flatools*, *iterz*, *listutils* and *llogic*. The complete list of functions available is:

- *flatools.flatten_index(element, input_list)*
- *flatools.flatten_join(*input_lists)*
- *flatools.flatten_len(input_list)*
- *flatools.flatten_max(input_list, *, key, default)*
- *flatools.flatten_min(input_list, *, key, default)*
- *flatools.flatten_mixed_type(input_list)*
- *flatools.flatten_reverse(input_list)*
- *flatools.flatten_single_type(input_list)*
- *flatools.flatten_sorted(input_list, *, key, reverse)*
- *flatools.flatten_sum(input_list[, start])*
- *flatools.flatten_zip_cycle(*input_lists)*
- *flatools.flatten(input_list)*
- *flatools.pflatten(input_list[, depth])*
- *iterz.cycle_until_index(input_iter, i)*
- *iterz.inf_cycle(input_iter)*
- *iterz.iter_mask(input_iter, mask)*
- *iterz.ncycles(input_iter, n)*
- *iterz.zip_cycle(*input_iters)*
- *iterz.zip_inf_cycle(*input_iters)*
- *iterz.zip_longest(*input_iters[, default])*
- *iterz.zip_syzygy(*input_iters)*
- *listutils.list_lcm(input_list)*
- *listutils.list_mask(input_list, mask)*
- *listutils.list_mask_cycle(input_list, mask)*
- *listutils.list_gcd(input_list)*

- `llogic.difference(list_1, list_2)`
- `llogic.intersection(list_1, list_2)`
- `llogic.is_contained(list_1, list_2)`
- `llogic.mixed_type(input_list)`
- `llogic.single_type(input_list)`
- `llogic.symmetric_difference(list_1, list_2)`
- `llogic.union(list_1, list_2)`

All functions have a `__doc__` attribute with usage instructions.

Documentation is available at <https://gilberthasnofb.github.io/listools-docs/>.

A pdf version of the documentation is also available in the `docs` directory.

Bugs can be reported to <https://github.com/gilberthasnofb/listools/issues>.

This library is published under the MIT License.

FLATOOLS MODULE

The module *flatools* contains functions that deal with flatten lists. The full list of available functions is:

- *flatools.flatten_index(element, input_list)*
- *flatools.flatten_join(*input_lists)*
- *flatools.flatten_len(input_list)*
- *flatools.flatten_max(input_list, *, key, default)*
- *flatools.flatten_min(input_list, *, key, default)*
- *flatools.flatten_mixed_type(input_list)*
- *flatools.flatten_reverse(input_list)*
- *flatools.flatten_single_type(input_list)*
- *flatools.flatten_sorted(input_list, *, key, reverse)*
- *flatools.flatten_sum(input_list[, start])*
- *flatools.flatten_zip_cycle(*input_lists)*
- *flatools.flatten(input_list)*
- *flatools.pflatten(input_list[, depth])*

All functions have a `__doc__` attribute with usage instructions.

This library is published under the MIT License.

`listools.flatools.flatten(input_list)`

Completely flattens a list containing any number of nested sublists into a one dimensional list. It is equivalent to `flatools.pflatten()` with an infinitely large depth. Usage:

```
>>> alist = [[1, 2], [3, 4], [5], [6, 7, 8], [9, 10]]
>>> flatools.flatten(alist)
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
```

```
>>> alist = [1, 2, [3, [4, 5]]]
>>> flatools.flatten(alist)
[1, 2, 3, 4, 5]
```

Notice that the list themselves can be made out of any datatypes:

```
>>> alist = [1, [2.2, True], ['foo', [(1, 4), None]], [3+2j, {'a': 1}]]
>>> flatools.flatten(alist)
[1, 2.2, True, 'foo', (1, 4), None, 3+2j, {'a': 1}]
```

`listools.flatools.flatten_index(input_list)`

Returns the length of a flatten list (that is, it counts all elements in all of its sublists). Usage:

```
>>> alist = [[1, 2], [3, 4], [5, 6]]
>>> flatools.flatten_index(3, alist)
2
```

The datatypes of the elements of the list do not matter:

```
>>> alist = [1, [2.2, True], ['foo', [(1, 4), None]], [3+2j, {'a': 1}]]
>>> flatools.flatten_index(None, alist)
5
```

Just like the default behaviour of the `flatten_index()` method of a list, `flatten_index` raises a `ValueError` if an element is not found in a list:

```
>>> alist = [[1, 2], [3, 4], [5, 6]]
>>> flatools.flatten_index(7, alist)
ValueError: 7 is not in list
```

`listools.flatools.flatten_join(*input_lists)`

Completely flattens and concatenates an arbitrary number of input lists containing any number of nested sublists. Usage:

```
>>> alist = [[1, 2], [3, 4]]
>>> blist = [[5, 6], [7, 8]]
>>> flatools.flatten_join(alist, blist)
[1, 2, 3, 4, 5, 6, 7, 8]
```

```
>>> alist = [1, [2, [3]]]
>>> blist = [[[4], 5], 6]
>>> flatools.flatten_join(alist, blist)
[1, 2, 3, 4, 5, 6]
```

```
>>> alist = [[1, 2], [3, 4]]
>>> blist = [[5, 6], [7, 8]]
>>> clist = [[[9], 10], 11]
>>> flatools.flatten_join(alist, blist, clist)
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11]
```

Notice that the list themselves can be made out of any datatypes:

```
>>> alist = [1, [2.2, True]]
>>> blist = ['foo', [(1, 4), None]]
>>> clist = [3+2j, {'a': 1}]
>>> flatools.flatten_join(alist, blist, clist)
[1, 2.2, True, 'foo', (1, 4), None, 3+2j, {'a': 1}]
```

`listools.flatools.flatten_len(input_list)`

Returns the `flatten_length` of a flatten list (that is, it counts all elements in all of its sublists). Usage:

```
>>> alist = [[1, 2], [3, 4], [5, 6]]
>>> flatools.flatten_len(alist)
6
```

The datatypes of the elements of the list do not matter:


```
>>> alist = [1, [2.2, True], ['foo', [(1, 4), None]], [3+2j, {'a': 1}]]
>>> flatools.flatten_len(alist)
8
```

`listools.flatools.flatten_max(input_list, *[, key, default])`

Finds the largest element of a flattened list containing any number of nested sublists. Usage:

```
>>> alist = [[1, 4], [5, 7], [2], [9, 6, 10], [8, 3]]
>>> flatools.flatten_max(alist)
10
```

```
>>> alist = [3, 4, [1, [5, 2]]]
>>> flatools.flatten_max(alist)
5
```

The list can also be made out of floats:

```
>>> alist = [[1.73, -3.14, 9.41], [5.56, -1.03]]
>>> flatools.flatten_max(alist)
9.41
```

Or it can be made out of a mixture of integers and floats:

```
>>> alist = [[3, 1.4], [5, 7.8], [-3.1, 6.6]]
>>> flatools.flatten_max(alist)
7.8
```

There are two optional arguments that can be used. The first is a called ‘key’ and takes a function that serves as a key for the sort comparison.

```
>>> alist = [-1, -5, [3, [-2, 4]]]
>>> print(flatten_max(alist))
4
>>> print(flatten_max(alist, key=abs))
-5
```

The second is ‘default’, which is the value that the function defaults to when the input is an empty list:

```
>>> alist = [1, 2, 3]
>>> blist = []
>>> print(flatten_max(alist, default=-100))
3
>>> print(flatten_max(blist, default=-100))
-100
```

`listools.flatools.flatten_min(input_list, *[, key, default])`

Finds the smallest element of a flattened list containing any number of nested sublists. Usage:

```
>>> alist = [[1, 4], [5, 7], [2], [9, 6, 10], [8, 3]]
>>> flatools.flatten_min(alist)
1
```

```
>>> alist = [3, 4, [1, [5, 2]]]
>>> flatools.flatten_min(alist)
1
```

The list can also be made out of floats:

```
>>> alist = [[1.73, -3.14, 9.41], [5.56, -1.03]]
>>> flatools.flatten_min(alist)
-3.14
```

Or it can be made out of a mixture of integers and floats:

```
>>> alist = [[3, 1.4], [5, 7.8], [-3.1, 6.6]]
>>> flatools.flatten_min(alist)
-3.1
```

There are two optional arguments that can be used. The first is a called ‘key’ and takes a function that serves as a key for the sort comparison.

```
>>> alist = [-1, -5, [3, [-2, 4]]]
>>> print(flatten_min(alist))
-5
>>> print(flatten_min(alist, key=abs))
-1
```

The second is ‘default’, which is the value that the function defaults to when the input is an empty list:

```
>>> alist = [1, 2, 3]
>>> blist = []
>>> print(flatten_min(alist, default=-100))
1
>>> print(flatten_min(blist, default=-100))
-100
```

`listools.flatools.flatten_mixed_type(input_list)`

Returns False if all elements of the flattened `input_list` are of the same type and True if they are not. Usage:

```
>>> alist = [[1, 4], [5, 7], [2], [9, 6, 10], [8, 3]]
>>> flatools.flatten_mixed_type(alist)
False
```

```
>>> alist = [3, 4, [1, [5, 2]]]
>>> flatools.flatten_mixed_type(alist)
False
```

```
>>> alist = [[1.73, -3.14, 9.41], [5.56, -1.03]]
>>> flatools.flatten_mixed_type(alist)
False
```

```
>>> alist = [[3, 1.4], [5, 7.8], [-3.1, 6.6]]
>>> flatools.flatten_mixed_type(alist)
True
```

```
>>> alist = ['foo', ['bar', ('foo', 'bar')]]
>>> flatools.flatten_mixed_type(alist)
True
```

Note that empty lists return False:

```
>>> alist = []
>>> flatools.flatten_mixed_type(alist)
False
```

`listools.flatools.flatten_reverse(input_list)`

Completely flattens a list containing any number of nested sublists into a `flatten_reversely` sorted one dimensional list. Usage:

```
>>> alist = [[1, 4], [5, 7], [2], [9, 6, 10], [8, 3]]
>>> flatools.flatten_reverse(alist)
[10, 9, 8, 7, 6, 5, 4, 3, 2, 1]
```

```
>>> alist = [1, 5, [3, [2, 4]]]
>>> flatools.flatten_reverse(alist)
[5, 4, 3, 2, 1]
```

The list can also be made out of floats:

```
>>> alist = [[1.73, -3.14, 9.41], [5.56, -1.03]]
>>> flatools.flatten_reverse(alist)
[9.41, 5.56, 1.73, -1.03, -3.14]
```

Or it can be made out of a mixture of integers and floats:

```
>>> alist = [[3, 1.4], [5, 7.8], [-3.1, 6.6]]
>>> flatools.flatten_reverse(alist)
[7.8, 6.6, 5, 3, 1.4, -3.1]
```

`listools.flatools.flatten_single_type(input_list)`

Returns True if all elements of the flattened `input_list` are of the same type and False if they are not. Usage:

```
>>> alist = [[1, 4], [5, 7], [2], [9, 6, 10], [8, 3]]
>>> flatools.flatten_single_type(alist)
True
```

```
>>> alist = [3, 4, [1, [5, 2]]]
>>> flatools.flatten_single_type(alist)
True
```

```
>>> alist = [[1.73, -3.14, 9.41], [5.56, -1.03]]
>>> flatools.flatten_single_type(alist)
True
```

```
>>> alist = [[3, 1.4], [5, 7.8], [-3.1, 6.6]]
>>> flatools.flatten_single_type(alist)
False
```

```
>>> alist = ['foo', ['bar', ('foo', 'bar')]]
>>> flatools.flatten_single_type(alist)
False
```

Note that empty lists return False:

```
>>> alist = []
>>> flatools.flatten_single_type(alist)
False
```

`listools.flatools.flatten_sorted(input_list, *[, key, reverse])`

Completely flattens a list containing any number of nested sublists into a `flatten_sorted` one dimensional list. Usage:

```
>>> alist = [[1, 4], [5, 7], [2], [9, 6, 10], [8, 3]]
>>> flattools.flatten_sorted(alist)
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
```

```
>>> alist = [1, 5, [3, [2, 4]]]
>>> flattools.flatten_sorted(alist)
[1, 2, 3, 4, 5]
```

The list can also be made out of floats:

```
>>> alist = [[1.73, -3.14, 9.41], [5.56, -1.03]]
>>> flattools.flatten_sorted(alist)
[-3.14, -1.03, 1.73, 5.56, 9.41]
```

Or it can be made out of a mixture of integers and floats:

```
>>> alist = [[3, 1.4], [5, 7.8], [-3.1, 6.6]]
>>> flattools.flatten_sorted(alist)
[-3.1, 1.4, 3, 5, 6.6, 7.8]
```

There are two optional arguments that can be used. The first is a called ‘key’ and takes a function that serves as a key for the sort comparison.

```
>>> alist = [-1, -5, [3, [-2, 4]]]
>>> print(flatten_sorted(alist))
[-5, -2, -1, 3, 4]
>>> print(flatten_sorted(alist, key=abs))
[-1, -2, 3, 4, -5]
```

The second is ‘reverse’, which reverses the order of the output list:

```
>>> alist = [1, 5, [3, [2, 4]]]
>>> print(flatten_sorted(alist, reverse=True))
[5, 4, 3, 2, 1]
```

`listools.flattools.flatten_sum(input_list[, start])`

Sums all values of the list, including any nested sublists. Usage:

```
>>> alist = [[1, 2], [3, 4], [5, 6]]
>>> flattools.flatten_sum(alist)
21
```

```
>>> alist = [1, [2, [3]]]
>>> flattools.flatten_sum(alist)
6
```

The list can also be made out of floats:

```
>>> alist = [1.1, [2.2, [3.3]]]
>>> flattools.flatten_sum(alist)
6.6
```

Or it can contain a mix of integers and floats:

```
>>> alist = [1, [2.1, [3, [4.1]]]]
>>> flattools.flatten_sum(alist)
10.2
```

It can also take an optional argument named 'start' which defines the starting value of the sum.

```
>>> alist = [1, [2, [3]]]
>>> flatools.flatten_sum(alist, start=4)
10
```

`listools.flatools.flatten_zip_cycle(*input_lists)`

This function is very nearly identical to `flatools.flatten_zip_cycle` except that it also flattens all lists before zipping and cycling them. Usage:

```
>>> alist = [1, 2]
>>> blist = [4, [5, 6, 7], 8]
>>> for i, j in flatools.flatten_zip_cycle(alist, blist):
...     print(i, j)
1 4
2 5
1 6
2 7
1 8
```

It also works with multiple lists:

```
>>> a = [1, 2]
>>> b = [1, [2, 3]]
>>> c = [[1], 2, 3], 4]
>>> d = [1, [2, [3, 4]], 5]
>>> for i, j, k, l in flatools.flatten_zip_cycle(a, b, c, d):
...     print(i, j, k, l)
1 1 1 1
2 2 2 2
1 3 3 3
2 1 4 4
1 2 1 5
```

It also works with lists containing any datatypes:

```
>>> alist = [1, 2.0, 'foo', True, None]
>>> blist = [False, 'bar', (1, 4)]
>>> for i, j in flatools.flatten_zip_cycle(alist, blist):
...     print(i, j)
1 False
2.0 bar
foo (1, 4)
True False
None bar
```

Note that unlike `flatools.flatten_zip_cycle()`, this function accepts only lists as input due to its flattening function.

`listools.flatools.pflatten(input_list[, depth])`

Partially flattens a list containing sublists as elements. Usage:

```
>>> alist = [[1, 2], [3, 4], [5], [6, 7, 8], [9, 10]]
>>> flatools.pflatten(alist)
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
```

```
>>> alist = [1, 2, [3, [[4], 5]]]
>>> flatools.pflatten(alist)
[1, 2, 3, [[4], 5]]
```

Use the `depth` argument (which should always be an integer) when wanting to flatten nested sublists:

```
>>> alist = [1, 2, [3, [4, 5]]]
>>> flatools.pflatten(alist, depth=2)
[1, 2, 3, [4], 5]
```

```
>>> alist = [1, 2, [3, [4, 5]]]
>>> flatools.pflatten(alist, depth=3)
[1, 2, 3, 4, 5]
```

```
>>> alist = [1, 2, [3, [4, 5]]]
>>> flatools.pflatten(alist, depth=4)
[1, 2, 3, 4, 5]
```

Notice that the list themselves can be made out of any datatypes:

```
>>> alist = [1, [2.2, True], ['foo', [(1, 4), None]], [3+2j, {'a': 1}]]
>>> flatools.flatten(alist, depth=3)
[1, 2.2, True, 'foo', (1, 4), None, 3+2j, {'a': 1}]
```

ITERZ MODULE

The module *iterz* contains functions that manipulate lists as iterators. The full list of available functions is:

- *iterz.cycle_until_index(input_iter, i)*
- *iterz.inf_cycle(input_iter)*
- *iterz.iter_mask(input_iter, mask)*
- *iterz.ncycles(input_iter, n)*
- *iterz.zip_cycle(*input_iters)*
- *iterz.zip_inf_cycle(*input_iters)*
- *iterz.zip_longest(*input_iters[, default])*
- *iterz.zip_syzygy(*input_iters)*

All functions have a `__doc__` attribute with usage instructions.

This library is published under the MIT License.

`listools.iterz.cycle_until_index(input_iter, i)`

This will cycle an iterator up to a certain index (inclusive). Usage:

```
>>> alist = [1, 2, 4, 8, 16, 32]
>>> for item in iterz.cycle_until_index(atuple, 4):
...     print(item)
1
2
4
8
16
```

In fact, it works with any iterable containing any datatypes:

```
>>> atuple = (1, 'foo', 3.0, 3+2j, [0.0])
>>> for item in iterz.cycle_until_index(atuple, 3):
...     print(item)
1
foo
3.0
3+2j
```

`listools.iterz.inf_cycle(input_iter)`

This will cycle an iterator indefinitely. Usage:

```
>>> alist = [1, 2, 4, 8]
>>> inf_cycle_iter = iterz.inf_cycle(alist)
>>> for i in range(9):
...     print(inf_cycle_iter.__next__())
1
2
4
8
1
2
4
8
1
```

In fact, it works with any iterable containing any datatypes:

```
>>> atuple = (1, 'foo', 3.0)
>>> inf_cycle_iter = iterz.inf_cycle(atuple)
>>> for i in range(5):
...     print(inf_cycle_iter.__next__())
1
foo
3.0
1
foo
```

`listools.iterz.iter_mask(input_iter, mask)`

This function takes an input iterator and applies a mask to it, yielding values according to the mask. The mask should be a list containing 1's and 0's, or alternatively True's and False's. Usage:

```
>>> alist = [1, 2, 3]
>>> mask = [True, False, True]
>>> for item in listutils.iter_mask(alist, mask):
...     print(item)
1
3
```

```
>>> alist = [1, 2, 3, 4, 5]
>>> mask = [1, 0, 0, 1, 0]
>>> for item in listutils.iter_mask(alist, mask):
...     print(item)
1
4
```

If the mask is shorter than the input iterator, it loops:

```
>>> alist = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
>>> mask = [1, 0]
>>> for item in listutils.iter_mask(alist, mask):
...     print(item)
1
3
5
7
9
```

The input iterator can contain any datatypes:


```
>>> alist = [1, 2.2, True, 'foo', (1, 4), None, 3+2j, {'a': 1}]
>>> mask = [True, False, True]
>>> for item in listutils.iter_mask(alist, mask):
...     print(item)
1
True
'foo'
None
3+2j
```

`listools.iterz.ncycle(input_iter)`

This will cycle an iterator a certain number of times. Usage:

```
>>> alist = [1, 2, 4, 8]
>>> for item in iterz.ncycle(alist, 2)
...     print(item)
1
2
4
8
1
2
4
8
```

In fact, it works with any iterable containing any datatypes:

```
>>> atuple = (1, 'foo', 3.0)
>>> for item in iterz.ncycle(atuple, 3):
...     print(item)
1
foo
3.0
1
foo
3.0
1
foo
3.0
```

`listools.iterz.zip_cycle(*input_iters)`

Similar to zip but cycles smaller lists or iterables until the longest one is output. Usage:

```
>>> alist = [1, 2]
>>> blist = [4, 5, 6, 7, 8]
>>> for i, j in iterz.zip_cycle(alist, blist):
...     print(i, j)
1 4
2 5
1 6
2 7
1 8
```

It also works with multiple lists:

```
>>> alist = [1, 2]
>>> blist = [1, 2, 3]
```

(continues on next page)

(continued from previous page)

```

>>> clist = [1, 2, 3, 4]
>>> dlist = [1, 2, 3, 4, 5]
>>> for i, j, k, l in iterz.zip_cycle(alist, blist, clist, dlist):
...     print(i, j, k, l)
1 1 1 1
2 2 2 2
1 3 3 3
2 1 4 4
1 2 1 5

```

In fact, it works with any iterable containing any datatypes:

```

>>> a = (1, 2, 3)
>>> b = [1.0, 2.0, 3.0, 4.0, 5.0, 6.0, 7.0]
>>> c = 'abcde'
>>> for i, j, k in iterz.zip_cycle(a, b, c):
...     print(i, j, k)
1 1.0 a
2 2.0 b
3 3.0 c
1 4.0 d
2 5.0 e
3 6.0 a
1 7.0 b

```

`listools.iterz.zip_inf_cycle(*input_iters)`

Similar to `zip` but cycles all lists indefinitely. Usage:

```

>>> alist = [1, 2]
>>> blist = [4, 5, 6, 7, 8]
>>> zip_inf_cycle_iter = iterz.zip_inf_cycle(alist, blist)
>>> for i in range(9):
...     print(zip_inf_cycle_iter.__next__())
1 4
2 5
1 6
2 7
1 8
2 4
1 5
2 6
1 7

```

It also works with multiple lists:

```

>>> alist = [1, 2]
>>> blist = [1, 2, 3]
>>> clist = [1, 2, 3, 4]
>>> dlist = [1, 2, 3, 4, 5]
>>> zip_inf_cycle_iter = iterz.zip_inf_cycle(alist, blist, clist, dlist)
>>> for i in range(7):
...     print(zip_inf_cycle_iter.__next__())
1 1 1 1
2 2 2 2
1 3 3 3
2 1 4 4

```

(continues on next page)

(continued from previous page)

```
1 2 1 5
1 3 2 1
2 1 3 2
```

In fact, it works with any iterable containing any datatypes:

```
>>> a = (1, 2, 3)
>>> b = [1.0, 2.0, 3.0, 4.0, 5.0, 6.0, 7.0]
>>> c = 'abcde'
>>> zip_inf_cycle_iter = iterz.zip_inf_cycle(a, b, c)
>>> for i in range(10):
...     print(zip_inf_cycle_iter.__next__())
1 1.0 a
2 2.0 b
3 3.0 c
1 4.0 d
2 5.0 e
3 6.0 a
1 7.0 b
2 1.0 c
3 2.0 d
1 3.0 e
```

`listools.iterz.zip_longest(*input_iters[, default])`

Similar to `zip_cycle` but yields values until the longest of the input iterators is exhausted. Shorter iterators yields `None` when exhausted. Usage:

```
>>> alist = [1, 2]
>>> blist = [4, 5, 6, 7, 8]
>>> for i, j in iterz.zip_longest(alist, blist):
...     print(i, j)
1 4
2 5
None 6
None 7
None 8
```

It also works with multiple lists:

```
>>> alist = [1, 2]
>>> blist = [1, 2, 3]
>>> clist = [1, 2, 3, 4]
>>> dlist = [1, 2, 3, 4, 5]
>>> for i, j, k, l in iterz.zip_longest(alist, blist, clist, dlist):
...     print(i, j, k, l)
1 1 1 1
2 2 2 2
None 3 3 3
None None 4 4
None None None 5
```

In fact, it works with any iterable containing any datatypes:

```
>>> a = (1, 2, 3)
>>> b = [1.0, 2.0, 3.0, 4.0, 5.0, 6.0, 7.0]
>>> c = 'abcde'
```

(continues on next page)

(continued from previous page)

```
>>> for i, j, k in iterz.zip_longest(a, b, c):
...     print(i, j, k)
1 1.0 a
2 2.0 b
3 3.0 c
None 4.0 d
None 5.0 e
None 6.0 None
None 7.0 None
```

The value None can be changed using the keyword argument default:

```
>>> alist = [1, 2]
>>> blist = [1, 2, 3, 4]
>>> clist = [1, 2, 3, 4, 5, 6]
>>> for i, j, k, l in iterz.zip_longest(alist, blist, clist, default=0):
...     print(i, j, k, l)
1 1 1
2 2 2
0 3 3
0 4 4
0 0 5
0 0 6
```

`listools.iterz.zip_syzygy(*input_iters)`

Similar to zip but cycles lists until all of them are exhausted at the same time (that is, when the next output tuple would be the same as the very first yielded one). Usage:

```
>>> alist = [1, 2]
>>> blist = [4, 5, 6, 7, 8]
>>> for i, j in iterz.zip_syzygy(alist, blist):
...     print(i, j)
1 4
2 5
1 6
2 7
1 8
2 4
1 5
2 6
1 7
2 8
```

It also works with multiple lists:

```
>>> alist = [1, 2]
>>> blist = [1, 2, 3]
>>> clist = [1, 2, 3, 4]
>>> dlist = [4, 5, 6]
>>> for i, j, k, l in iterz.zip_syzygy(alist, blist, clist, dlist):
...     print(i, j, k, l)
1 1 1 4
2 2 2 5
1 3 3 6
2 1 4 4
1 2 1 5
```

(continues on next page)

(continued from previous page)

```
2 3 2 6
1 1 3 4
2 2 4 5
1 3 1 6
2 1 2 4
1 2 3 5
2 3 4 6
```

In fact, it works with any iterable containing any datatypes:

```
>>> a = (1, 2)
>>> b = [1.0, 2.0, 3.0]
>>> c = 'abc'
>>> for i, j, k in iterz.zip_syzygy(a, b, c):
...     print(i, j, k)
1 1.0 a
2 2.0 b
1 3.0 c
2 1.0 a
1 2.0 b
2 3.0 c
```


LISTUTILS MODULE

The module *listutils* contains functions that apply simple mathematical operations to lists. The full list of available functions is:

- *listutils.list_lcm(input_list)*
- *listutils.list_mask(input_list, mask)*
- *listutils.list_mask_cycle(input_list, mask)*
- *listutils.list_gcd(input_list)*

All functions have a `__doc__` attribute with usage instructions.

This library is published under the MIT License.

`listutils.listutils.list_gcd(input_list)`

This function returns the greatest common divisor of a list of integers. Usage:

```
>>> alist = [8, 12]
>>> listutils.list_gcd(alist)
4
```

```
>>> alist = [74, 259, 185, 333]
>>> listutils.list_gcd(alist)
37
```

`listutils.listutils.list_lcm(input_list)`

This function returns the least common multiple of a list of integers. Usage:

```
>>> alist = [1, 2, 3]
>>> listutils.list_lcm(alist)
6
```

```
>>> alist = [7, 8, 4, 3]
>>> listutils.list_lcm(alist)
168
```

`listutils.listutils.list_mask(input_list, mask)`

This function takes an input list and applies a mask to it, outputting a new list. The mask should be a list containing 1's and 0's, or alternatively True's and False's. If the mask is shorter than the input list then the input list will be considered only up to the mask length. Usage:

```
>>> alist = [1, 2, 3]
>>> mask = [True, False, True]
>>> listutils.list_mask(alist, mask)
[1, 3]
```

```
>>> alist = [1, 2, 3, 4, 5]
>>> mask = [1, 0, 0, 1, 0]
>>> listutils.list_mask(alist, mask)
[1, 4]
```

If the mask is shorter than the list, the :

```
>>> alist = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
>>> mask = [1, 0]
>>> listutils.list_mask(alist, mask)
[1]
```

If the mask is shorter than the input list then the input list will be considered only up to the mask length:

```
>>> alist = [1, 2.2, True, 'foo', (1, 4), None, 3+2j, {'a': 1}]
>>> mask = [True, False, True]
>>> listutils.list_mask(alist, mask)
[1, True]
```

The input list can be empty, in which case an empty list is return. On the other hand, the mask argument cannot be an empty list.

`listutils.listutils.list_mask_cycle(input_list, mask)`

This function takes an input list and applies a mask to it, outputting a new list. The mask should be a list containing 1's and 0's, or alternatively True's and False's. If the mask is shorter than the list, the mask is cycled. Usage:

```
>>> alist = [1, 2, 3]
>>> mask = [True, False, True]
>>> listutils.list_mask_cycle(alist, mask)
[1, 3]
```

```
>>> alist = [1, 2, 3, 4, 5]
>>> mask = [1, 0, 0, 1, 0]
>>> listutils.list_mask_cycle(alist, mask)
[1, 4]
```

If the mask is shorter than the list, it loops:

```
>>> alist = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
>>> mask = [1, 0]
>>> listutils.list_mask_cycle(alist, mask)
[1, 3, 5, 7, 9]
```

The input list can contain any datatypes:

```
>>> alist = [1, 2.2, True, 'foo', (1, 4), None, 3+2j, {'a': 1}]
>>> mask = [True, False, True]
>>> listutils.list_mask_cycle(alist, mask)
[1, True, 'foo', None, 3+2j]
```

The input list can be empty, in which case an empty list is return. On the other hand, the mask argument cannot be an empty list.

LLOGIC MODULE

The module *llogic* contains functions that deal with logic operations on lists. The full list of available functions is:

- *llogic.difference(list_1, list_2)*
- *llogic.intersection(list_1, list_2)*
- *llogic.is_contained(list_1, list_2)*
- *llogic.mixed_type(input_list)*
- *llogic.single_type(input_list)*
- *llogic.symmetric_difference(list_1, list_2)*
- *llogic.union(list_1, list_2)*

All functions have a `__doc__` attribute with usage instructions.

This library is published under the MIT License.

`listools.llogic.difference(list_1, list_2)`

Returns the difference of two lists (omitting repetitions). The order of the elements of the output depends on their order in the lists. The order of the inputs lists does affect the result. Usage:

```
>>> alist = [1, 2, 3, 4, 5]
>>> blist = [7, 6, 5, 4, 3]
>>> llogic.difference(alist, blist)
[1, 2]
>>> llogic.difference(blist, alist)
[7, 6]
```

```
>>> alist = [1, 2, 3, 3, 4, 4, 5, 5, 5]
>>> blist = [3, 3, 4, 5, 5, 6]
>>> llogic.difference(alist, blist)
[1, 2]
```

Note that `llogic.difference` does not flatten the lists so nested lists are of type list:

```
>>> alist = [3, 4, 1, 5, 2]
>>> blist = [1, 2, 3, 4, 5]
>>> llogic.difference(alist, blist)
[]
>>> alist = [3, 4, [1, [5, 2]]]
>>> blist = [1, 2, 3, 4, 5]
>>> llogic.difference(alist, blist)
[[1, [5, 2]]]
```

The lists can contain any datatype:

```
>>> alist = [1, 2.3, 'foo', (3, 7)]
>>> blist = ['foo', 7+3j, (3, 7)]
>>> llogic.difference(alist, blist)
[1, 2.3]
```

`listools.lllogic.intersection(list_1, list_2)`

Returns the intersection of two lists (omitting repetitions). The order of the elements of the output depends on the order they are found in the first list. Usage:

```
>>> alist = [1, 2, 3, 4, 5]
>>> blist = [7, 6, 5, 4, 3]
>>> llogic.intersection(alist, blist)
[3, 4, 5]
```

```
>>> alist = [1, 2, 3, 3, 4, 4, 5, 5, 5]
>>> blist = [3, 3, 4, 5, 5, 6]
>>> llogic.intersection(alist, blist)
[3, 4, 5]
```

Note that `lllogic.intersection` does not flatten the lists so nested lists are of type list:

```
>>> alist = [3, 4, [1, [5, 2]]]
>>> blist = [1, 2, 3, 4, 5]
>>> llogic.intersection(alist, blist)
[3, 4]
```

The lists can contain any datatype:

```
>>> alist = [1, 2.3, 'foo', (3, 7)]
>>> blist = ['foo', 7+3j, (3, 7)]
>>> llogic.intersection(alist, blist)
['foo', (3, 7)]
```

If either list is empty then the result is an empty list:

```
>>> alist = [1, 2, 3, 4, 5]
>>> blist = []
>>> llogic.intersection(alist, blist)
[]
```

`listools.lllogic.is_contained(list_1, list_2)`

Returns True if all unique elements of `list_1` are also present in `list_2` and returns False when that's not the case. Usage:

```
>>> alist = [1, 2, 3, 4, 5]
>>> blist = [2, 3, 4]
>>> llogic.is_contained(blist, alist)
True
>>> llogic.is_contained(alist, blist)
False
```

```
>>> alist = [1, 2, 3, 3, 4, 4, 5, 5, 5, 6, 7]
>>> blist = [3, 3, 4, 5, 5, 6]
>>> llogic.is_contained(blist, alist)
True
```

Lists are not flattened, so sublists are considered as a single element:

```
>>> alist = [3, 4, [1, [5, 2]]]
>>> blist = [1, 2]
>>> llogic.is_contained(blist, alist)
False
```

The lists can contain any datatype:

```
>>> alist = [1, 2.3, 'foo', (3, 7), 7+3j]
>>> blist = ['foo', 7+3j, (3, 7)]
>>> llogic.is_contained(blist, alist)
True
```

`listools.llogic.mixed_type(input_list)`

Returns False if all elements of an input_list are of the same type and True if they are not. Usage:

```
>>> alist = [3, 4, 1, 5, 2]
>>> llogic.single_type(alist)
False
```

```
>>> alist = [3.1, 4, 1, 5, '2']
>>> llogic.single_type(alist)
True
```

Note that `lllogic.mixed_type` does not flatten the lists so nested lists are of type list:

```
>>> alist = [3, 4, [1, [5, 2]]]
>>> llogic.single_type(alist)
True
```

```
>>> alist = [[1, 4], [5, 7], [2], [9, 6, 10], [8, 3]]
>>> llogic.single_type(alist)
False
```

Also note that empty lists return False:

```
>>> alist = []
>>> llogic.single_type(alist)
False
```

`listools.llogic.single_type(input_list)`

Returns True if all elements of an input_list are of the same type and False if they are not. Usage:

```
>>> alist = [3, 4, 1, 5, 2]
>>> llogic.single_type(alist)
True
```

```
>>> alist = [3.1, 4, 1, 5, '2']
>>> llogic.single_type(alist)
False
```

Note that `lllogic.single_type` does not flatten the lists so nested lists are of type list:

```
>>> alist = [3, 4, [1, [5, 2]]]
>>> llogic.single_type(alist)
False
```

```
>>> alist = [[1, 4], [5, 7], [2], [9, 6, 10], [8, 3]]
>>> llogic.single_type(alist)
True
```

Also note that empty lists return False:

```
>>> alist = []
>>> llogic.single_type(alist)
False
```

`listools.llogic.symmetric_difference(list_1, list_2)`

Returns the symmetric difference of two lists (omitting repetitions). The order of the elements of the output depends on their order in the lists. The order of the inputs lists does affect the result. Usage:

```
>>> alist = [1, 2, 3, 4, 5]
>>> blist = [7, 6, 5, 4, 3]
>>> llogic.symmetric_difference(alist, blist)
[1, 2, 7, 6]
>>> llogic.symmetric_difference(blist, alist)
[7, 6, 1, 2]
```

```
>>> alist = [1, 2, 3, 3, 4, 4, 5, 5, 5]
>>> blist = [3, 3, 4, 5, 5, 6]
>>> llogic.symmetric_difference(alist, blist)
[1, 2, 6]
```

Note that `lllogic.symmetric_difference` does not flatten the lists so nested lists are of type list:

```
>>> alist = [3, 4, 1, 5, 2]
>>> blist = [1, 2, 3, 4, 5]
>>> llogic.symmetric_difference(alist, blist)
[]
>>> alist = [3, 4, [1, [5, 2]]]
>>> blist = [1, 2, 3, 4, 5]
>>> llogic.symmetric_difference(alist, blist)
[[1, [5, 2]], 1, 2, 5]
```

The lists can contain any datatype:

```
>>> alist = [1, 2.3, 'foo', (3, 7)]
>>> blist = ['foo', 7+3j, (3, 7)]
>>> llogic.symmetric_difference(alist, blist)
[1, 2.3, 7+3j]
```

`listools.llogic.union(list_1, list_2)`

Returns the union of two lists (omitting repetitions). The order of the elements of the output depends on the order they are found in the first and then in the second lists. Usage:

```
>>> alist = [1, 2, 3, 4, 5]
>>> blist = [7, 6, 5, 4, 3]
>>> llogic.union(alist, blist)
[1, 2, 3, 4, 5, 7, 6]
```

```
>>> alist = [1, 2, 3, 3, 4, 4, 5, 5, 5]
>>> blist = [7, 6, 6, 5, 5, 5, 4]
>>> llogic.union(alist, blist)
[1, 2, 3, 4, 5, 7, 6]
```

Note that `llogic.union` does not flatten the lists so nested lists are of type list:

```
>>> alist = [3, 4, [1, [5, 2]]]
>>> blist = [1, 2, 3, 4, 5]
>>> llogic.union(alist, blist)
[3, 4, [1, [5, 2]], 1, 2, 5]
```

The lists can contain any datatype:

```
>>> alist = [1, 2.3, 'foo', (3, 7)]
>>> blist = ['foo', 7+3j, (3, 7)]
>>> llogic.union(alist, blist)
[1, 2.3, 'foo', (3, 7), 7+3j]
```


PYTHON MODULE INDEX

I

- `listools`, [1](#)
- `listools.flatools`, [3](#)
- `listools.iterz`, [11](#)
- `listools.listutils`, [19](#)
- `listools.llogic`, [21](#)

C

cycle_until_index() (in module listools.iterz), 11

D

difference() (in module listools.llogic), 21

F

flatten() (in module listools.flatools), 3
 flatten_index() (in module listools.flatools), 3
 flatten_join() (in module listools.flatools), 4
 flatten_len() (in module listools.flatools), 4
 flatten_max() (in module listools.flatools), 5
 flatten_min() (in module listools.flatools), 5
 flatten_mixed_type() (in module listools.flatools), 6
 flatten_reverse() (in module listools.flatools), 6
 flatten_single_type() (in module listools.flatools), 7
 flatten_sorted() (in module listools.flatools), 7
 flatten_sum() (in module listools.flatools), 8
 flatten_zip_cycle() (in module listools.flatools), 9

I

inf_cycle() (in module listools.iterz), 11
 intersection() (in module listools.llogic), 22
 is_contained() (in module listools.llogic), 22
 iter_mask() (in module listools.iterz), 12

L

list_gcd() (in module listools.listutils), 19
 list_lcm() (in module listools.listutils), 19
 list_mask() (in module listools.listutils), 19
 list_mask_cycle() (in module listools.listutils), 20
 listools (module), 1
 listools.flatools (module), 3
 listools.iterz (module), 11
 listools.listutils (module), 19
 listools.llogic (module), 21

M

mixed_type() (in module listools.llogic), 23

N

ncycle() (in module listools.iterz), 13

P

pflatten() (in module listools.flatools), 9

S

single_type() (in module listools.llogic), 23
 symmetric_difference() (in module listools.llogic), 24

U

union() (in module listools.llogic), 24

Z

zip_cycle() (in module listools.iterz), 13
 zip_inf_cycle() (in module listools.iterz), 14
 zip_longest() (in module listools.iterz), 15
 zip_syzygy() (in module listools.iterz), 16