Housing Price Prediction

Group 4
Clement, Gilbert, Kah Beng

Introduction


Context

We are tasked to assist property agents in **creating models** for predicting the **house prices** in Ames (Iowa, USA) in order to generate baseline pricing for valuation of the house.

Problem Statement

- Which **regularization** (L1, L2, ENet) resulted in the **best model**?
- Which features can best predict house prices?
- Investigate trade-off between complexity versus the accuracy (R2)
- How to improve upon the initial model

Process



Data Cleaning

Dealing with 2 types of missing values

- Missing value because **the feature does not exist** (Garage, Fireplace, Fence)
 - These were imputed using 'NA' or 0 depending on the feature type
- "Genuine" missing values like Lot Frontage was imputed using mean, mode, or through linear regression

Removing non-informational dimensions like PID

KEY FACT - NO FEATURE WAS DROPPED DUE TO MISSING VALUES

EDA


Checking for multicollinearity



GarageCars was removed


The burning question: What correlates to SalePrice?

```
Top 10 correlated features: 'OverallQual', 'ExterQual', 'GrLivArea', 'KitchenQual', 'BsmtQual', 'GarageArea', 'TotalBsmtSF', '1stFlrSF', 'YearBuilt', 'GarageFinish'
```



Distribution of SalePrice

Our target variable exhibits a normal distribution shape, slightly skewed by extremely high value houses



The main benefit of having a normally distributed variable is that it gets easier to describe we see here that the mode, mean and median almost overlap

Feature Engineering

Categorical variables

Mapping ordinal variables to numbers

Ex: quality features like BsmtQuality got assigned numerical values

E.g.: 'poor' / 'fair' / 'good' ⇒ 1 / 2 / 3

One-Hot Encoding the remaining (nominal) variables

Ex: features not following any order ('Neighborhood', 'LotShape', etc)

Modelling

Focused on models with regularisation techniques applied. **Best models** from **cross-validated grid search**:

Lasso: penalty (α) = 0.00681

Ridge: $\alpha = 464.16$

Elasticnet: $\alpha = 0.1$; I1_ratio = 0.05 (penalty combination is mostly Ridge)

Standardisation of features was done using **standard scalar** to ensure penalty is applied equally to all features

Train-Test split ratio of 70/30 was used for all models

Models are evaluated on MAE, RMSE, R2, R2_adj when predicting test dataset


Model Comparison


Lasso model has the smallest residual and highest R2 with least features

Regression Type	Non-Zero Variables	Non-Zero Features	MAE	RMSE	R2 (test)	R2_adj (test)
Baseline (mean)	0	0	0.725	0.966	-0.001	-0.001
Simple Linear Regression	195	77	9.4e+07	1.7e+09	-2.7e+18	-3.0e+18
Ridge	191	76	0.233	0.328	0.884	0.872
ElasticNet	126	59	0.230	0.323	0.887	0.880
Lasso	103	57	0.226	0.316	0.892	0.887

Accuracy-Complexity Trade-off


- A property for LASSO is that it is able to reduce the number less relevant features to 0 based on the α
- By varying α , we can examine the variations in number of features selected, and the resulting R2






Selected Features





EDA Part 2: Feature Importance

Features with highest regression coeff. can be broadly categorised into house size (square area of various rooms) and house quality (quality of rooms and facilities)





1. Above-Ground Living Area

Distribution of above-ground living area is skewed to the right similar to sales price

Scatter plot for above-ground living area and sale price shows positive relationship

2 outliers in the above-ground living area feature






1. Above-Ground Living Area

Distribution of sale price per square feet resembles a normal distribution

Dataset median is also close to the **actual median prices**





2. Overall Quality

Distribution of overall quality is also skewed to the right


Skew is reasonable since poor quality houses are unlikely to be purchased

Relationship with sale price does not seem linear






The rest of the top 8 features:



Improving the Model

Based on the 2nd EDA, we observed potential methods for improving our model:






Combining Both Methods

1. Non-Linearity for Ordinal Variables

The ordinal variables (e.g.: Quality and Condition) are scored on a linear scale:

- Overall: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10
- Others: NA, Po, Fa, TA, Gd, Ex ⇒ 0, 1, 2, 3, 4, 5

However, the response of these scores (against Sale Price) are **NOT LINEAR**




1. Non-Linearity for Ordinal Variables

Looking at the distribution of the data, we can estimate the response of OverallQuality (and other quality-related columns) to be quadratic (i.e.: $y \sim x^2$)

Therefore, we will now **square**ALL **quality-related columns**and re-run the regression model

Result:

Regression Type	Non-Zero Features	R2_adj
Lasso	57	0.887
Lasso (non-linear ordinal variables)	56 (-1)	0.897 (+0.010)




2. Removing Outliers

Observing the scatter plot between SalePrice and GrLivArea, we can see that there are **two outliers** Regression-based models are typically very sensitive to outliers

We will now re-run the regression model after removing the outliers

Result:

Regression Type	Non-Zero Features	R2_adj
Lasso	57	0.887
Lasso (removed outliers)	55 (-2)	0.910 (+0.023)




Model Summary

Regression Type	Non-Zero Variables	Non-Zero Features	MAE	RMSE	R2	R2_adj
Baseline (mean)	0	0	0.725	0.966	-0.001	-0.001
Simple Linear Regression	195	77	9.4e+07	1.7e+09	-2.7e+18	-3.0e+18
Ridge	191	76	0.233	0.328	0.884	0.872
ElasticNet	126	59	0.230	0.323	0.887	0.880
Lasso	103	57	0.226	0.316	0.892	0.887
Lasso (non-linear ordinal variables)	98 (-5)	56 (-1)	0.218	0.302	0.902 (+0.010)	0.897 (+0.010)
Lasso (removed outliers)	92 (-11)	55 (-2)	0.219	0.307	0.914 (+0.022)	0.910 (+0.023)
Lasso (non-linear + outliers)	91 (-12)	52 (- 5)	0.215	0.298	0.919 (+0.027)	0.915 (+0.028)

Which model to choose?

Short answer: Lasso...

Long answer:



Summary

- Lasso resulted in the highest accuracy and the lowest complexity out of all the tested regularization methods (L1, L2, ENet).
- Main predictor of house pricing:
 - Above-Ground Square Footage
 - Overall Quality
 - Other area- and quality- related metrics for specific locations / sections
- Diminishing return between number of features included (complexity) and R2_adjusted (accuracy)
- Methods for improving predictions:
 - adding non-linearity
 - removing outliers

Future Works

The following items may be investigated for future works:

- Comparing selected variables from Lasso against those from SelectKBest
- Add **interaction terms** for several variables
- Use of more complex models to improve accuracy, such as using Tree-Based models
- Adjusting SalePrice for inflation (depending on the YearSold)
- See impact of housing bubble, if any
 - o (compare prices of house sold before and after 2008)

Thank You