

# Algorithms, AI & Data Science II

**Prof. Dr. Ingo Scholtes**

Chair of Machine Learning for Complex Networks  
Center for Artificial Intelligence and Data Science (CAIDAS)  
Julius-Maximilians-Universität Würzburg


[ingo.scholtes@uni-wuerzburg.de](mailto:ingo.scholtes@uni-wuerzburg.de)

## Notes:

- **L02: Formal Foundations of Computing** 30.04.2025
- **Educational objective:** We introduce foundational mathematical concepts like sets and relations, study formal languages and grammars and introduce the Chomsky hierarchy of formal languages.
  - Basic Set Theory
  - Relations and Functions
  - Formal Languages and Grammars
  - Chomsky Hierarchy of Formal Languages
- **Handout version:** *May 5, 2025*


# Motivation

- ▶ deep understanding of algorithms and artificial intelligence requires to **formalize “computation”**
- ▶ how can we **formally state a problem** such that a machine can give an answer?
- ▶ we explore **formal languages** and study **automata models** to address **word decision problems**
- ▶ we define **Turing machines** and investigate **computability and “machine intelligence”**
- ▶ we start with basic **mathematical foundations of computer science**
  1. set theory and set operations
  2. relations and functions
  3. notational conventions



response from large language model ChatGPT

image credit: OpenAI screenshot, taken on 12/04/2023




Physical model of a **Turing machine**

image credit: Rocky Acosta, Wikimedia Commons, CC-BY-SA

## Notes:

# Set theory

- ▶ **set theory** = mathematical study of relationships between **collections of objects**
- ▶ important foundation of discrete mathematics, formal logics and computer science → G Cantor, 1874
- ▶ sets are **unordered** collections of **distinguishable** objects
- ▶ sets can be **finite or infinite**
- ▶ we can unambiguously determine whether an **object is element of a set or not**



Georg Cantor (1845 – 1918)




image credit: Wikimedia Commons, public domain

**Notes:**

# Foundational set theory

## definitions

- ▶ A **set** is an unordered collection of distinguishable objects, which are called **elements** or **members** of the set.
- ▶ For any object  $x$  we can unambiguously determine whether it is element of a set  $S$ . If  $x$  is member of  $S$  we write  $x \in S$  and  $x \notin S$  otherwise.
- ▶ The **cardinality**  $|S|$  is defined as the number of elements in  $S$ .
- ▶ We denote the **empty set** (without elements) as  $\emptyset$  with  $|\emptyset| = 0$ .
- ▶ We can define sets in (finite or infinite) **enumeration notation**, i.e.  $S = \{e_1, e_2, e_3, \dots\}$ .
- ▶ We can define sets in **set-builder notation**, i.e.  $\{x | p(x)\}$  where  $p$  is a condition (or logical predicate) that holds for all members  $x \in S$
- ▶  **$S_1$  is subset of  $S_2$**  ( $S_1 \subseteq S_2$ ) iff for each  $x \in S_1$  we have  $x \in S_2$
- ▶  **$S_1$  and  $S_2$  are equal** ( $S_1 = S_2$ ) iff for each  $x \in S_1$  we have  $x \in S_2$  and vice-versa, i.e.  $S_1 \subseteq S_2$  and  $S_2 \subseteq S_1$
- ▶  **$S_1$  is proper subset of  $S_2$**  ( $S_1 \subset S_2$ ) iff for each  $x \in S_1$  we have  $x \in S_2$  and  $S_1 \neq S_2$

## examples

- ▶  $S = \{1, 'Cat', 42.5\}$  is a set with  $|S| = 3$
- ▶  $S = \{1, 2, 3, 2\}$  is not a valid set
- ▶  $\mathbb{N} = \{1, 2, 3, 4, \dots\}$  is an (infinite) set
- ▶  $\mathbb{N} = \{x | x \text{ is natural number}\}$
- ▶  $S_1 = \{1, 2, 3\} \subseteq \{1, 2, 3, 4\} = S_2$
- ▶  $\emptyset \subseteq S$  for any set  $S$
- ▶  $S_1 = \{1, 2, 3\} = \{3, 2, 1\} = S_2$
- ▶  $S_1 = \{1, 2, 3\} \subset \{1, 2, 3, 4\} = S_2$

**Notes:**



# Set operations, complement, and power set

## definitions

Let  $S_1$  and  $S_2$  be arbitrary sets. We define the following binary operations:

- ▶  $S_1 \cup S_2 := \{x | x \in S_1 \text{ or } x \in S_2\}$  **union**
- ▶  $S_1 \cap S_2 := \{x | x \in S_1 \text{ and } x \in S_2\}$  **intersection**
- ▶  $S_1 - S_2 := \{x | x \in S_1 \text{ and } x \notin S_2\}$  **difference**
- ▶  $S_1 \triangle S_2 := (S_1 \cup S_2) - (S_2 \cap S_2) = \{x | x \in S_1 \text{ xor } x \in S_2\}$  **symmetric difference**
- ▶  $S_1 \times S_2 := \{(x, y) | x \in S_1 \text{ and } y \in S_2\}$  **product**

- ▶ for given set  $S$  we define **complement**  $S^C$  (relative to some “universe”) as the set of all elements in the universe that are not element of  $S$
- ▶ for given set  $S$  we define **power set**  $2^S$  as the set of all subsets of  $S$ , i.e.  $2^S := \{S' : S' \subseteq S\}$

## examples

Let  $S_1 = \{1, 2, 3\}$  and  $S_2 = \{2, 3, 4, 5\}$ .

- ▶  $S_1 \cup S_2 = \{1, 2, 3, 4, 5\}$
- ▶  $S_1 \cap S_2 = \{2, 3\}$
- ▶  $S_1 - S_2 = \{1\}$
- ▶  $S_1 \triangle S_2 = \{1, 4, 5\}$
- ▶  $S_1 \times S_2 = \{(1, 2), (1, 3), (1, 4), (1, 5), (2, 2), (2, 3), (2, 4), (2, 5), (3, 2), (3, 3), (3, 4), (3, 5)\}$

with  $|S_1 \times S_2| = 12$

- ▶ For  $S = \{1, 2, 3\}$  we have


$$2^S = \{\emptyset, \{1\}, \{2\}, \{3\}, \{1, 2\}, \{1, 3\}, \{2, 3\}, \{1, 2, 3\}\}$$

with  $|2^S| = 2^{|S|} = 8$


## Notes:

# Venn diagrams


we can use **Venn diagrams** to visually represent operations on sets




$$S_1 \cup S_2$$




$$S_1 \cap S_2$$



$$S_1 - S_2$$



$$S_1 \triangle S_2$$



$$S^C$$

## Notes:

# Relations

- ▶ elements of sets often exhibit **relationships** that we can capture mathematically

## definition

- ▶ Let  $S_1$  and  $S_2$  be arbitrary sets. A (binary) relation  $R$  between  $S_1$  and  $S_2$  is a subset of the product set  $S_1 \times S_2$ , i.e.  $R \subseteq S_1 \times S_2$  and  $R \in 2^{S_1 \times S_2}$
  - ▶ Instead of  $(a, b) \in R$  we can write  $R(a, b)$  or  $aRb$ .
- 
- ▶ relations  $R \subseteq S_1 \times S_2$  can be between elements of **different sets**  $S_1 \neq S_2$
  - ▶ we can define relations  $R \subseteq S \times S$  between elements of a **single set**, in which case we call  $R$  a **relation on  $S$**

## examples

- ▶ For  $S_1 = \{\text{Peter, Anna}\}$  and  $S_2 = \{\text{C++, python}\}$

$$R = \{(\text{Peter}, \text{C++}), \\ (\text{Anna}, \text{python}), \\ (\text{Anna}, \text{C++})\}$$

is a relation

- ▶  $\emptyset$  is an (empty) relation between any pair of sets
- ▶ comparator  $<$  is a relation on natural numbers  $\mathbb{N}$  with  $(2, 5) \in <$  and  $(5, 2) \notin <$
- ▶  $R = \{(x, y) \in \mathbb{N} \times \mathbb{N} \mid y = x^2\}$  is a relation on natural numbers  $\mathbb{N}$

## Notes:

# Properties of relations

## definitions

- ▶ relation  $R$  on  $S$  is **reflexive** iff  $xRx$  for any  $x \in S$
  - ▶ relation  $R$  on  $S$  is **symmetric** iff for all  $x, y \in S$  with  $xRy$  we also have  $yRx$
  - ▶ relation  $R$  on  $S$  is **transitive** iff for all  $x, y, z \in S$  with  $xRy$  and  $yRz$  we also have  $xRz$
  - ▶ a relation  $R$  between sets  $X, Y$  is called **functional** (or right-unique) iff for all  $x \in X$  and  $y, y' \in Y$  with  $R(x, y)$  and  $R(x, y')$  we have  $y = y'$
  - ▶ relation  $R$  between  $X, Y$  is called **injective** (or left-unique) iff for all  $x, x' \in X$  and  $y \in Y$  with  $R(x, y)$  and  $R(x', y)$  we have  $x = x'$
- 
- ▶ we call functional relation  $R \subseteq X \times Y$  a **function**  $R : X \rightarrow Y$  and write  $R(x) = y$  instead of  $R(x, y)$
  - ▶ we call a functional relation  $R \subseteq X \times Y$  that is injective **one-to-one mapping**

## examples

- ▶ comparator  $<$  on  $\mathbb{N}$  is neither reflexive nor symmetric
- ▶ comparator  $\leq$  on  $\mathbb{N}$  is reflexive but not symmetric
- ▶  $<$  and  $\leq$  on  $\mathbb{N}$  are transitive
- ▶  $R = \{(x, x), (y, y), (z, z), (y, z), (z, y)\}$  is reflexive, symmetric, and transitive
- ▶  $<$  and  $\leq$  on  $\mathbb{N}$  are not functional
- ▶  $R(x) = x^2$  is functional
- ▶  $R(x) = x^2$  is not injective
- ▶  $R(x) = x + 1$  is a one-to-one mapping that maps every  $x \in \mathbb{N}$  to  $x + 1$

## Notes:



# Operations on relations

- ▶ Let  $R \subseteq S_1 \times S_2$  be a relation. The **inverse of  $R$**  is defined as

$$R^{-1} := \{(y, x) \in S_2 \times S_1 \mid (x, y) \in R\}$$

- ▶ Let  $R_1 \subseteq S_1 \times S_2$  and  $R_2 \subseteq S_3 \times S_4$  be relations. The **inner product of  $R_1$  and  $R_2$**  is defined as

$$R_1 \otimes R_2 := \{((a, c), (b, d)) \in (S_1 \times S_3) \times (S_2 \times S_4) \mid aR_1b \text{ and } cR_2d\}$$

- ▶ Let  $R_1 \subseteq S_1 \times S_2$  and  $R_2 \subseteq S_2 \times S_3$  relations. The **composition of  $R_1$  and  $R_2$**  is defined as

$$R_1 \circ R_2 := \{(a, c) \in (S_1 \times S_3) \mid aR_1b \text{ and } bR_2c \text{ for some } b\}$$

## Notes:

## Group Exercise 02-01

1. Consider the “smaller than” relation  $<$  on  $\mathbb{R}$  and let  $<^{-1}$  be the inverse of  $<$ . Provide a set builder definition for the elements in the inner product  $< \otimes <^{-1}$ . Give an example for elements of the resulting relation.

We first have  $<^{-1} = >$

We then have  $< \otimes > = \{((a, c), (b, d)) \in \mathbb{R}^2 \times \mathbb{R}^2 \mid a < b \text{ and } c > d\}$

example:  $((1, 4), (2, 3)) \in < \otimes >$

2. Prove that  $(R \cup S)^{-1} = R^{-1} \cup S^{-1}$

To prove equality of the two sets, we must prove that (i) for  $(x, y) \in (R \cup S)^{-1}$  we also have  $(x, y) \in R^{-1} \cup S^{-1}$ , and (ii) for  $(x, y) \in R^{-1} \cup S^{-1}$  we also have  $(x, y) \in (R \cup S)^{-1}$ .

Let  $(x, y) \in (R \cup S)^{-1}$ . By definition, we have  $(y, x) \in R \cup S$  and thus  $(y, x) \in R$  or  $(y, x) \in S$  (or both). By definition we then have  $(x, y) \in R^{-1}$  or  $(x, y) \in S^{-1}$  and thus  $(x, y) \in R^{-1} \cup S^{-1}$ .

Let  $(x, y) \in R^{-1} \cup S^{-1}$ . We then have  $(x, y) \in R^{-1}$  or  $(x, y) \in S^{-1}$  (or both). By definition we then have  $(y, x) \in R$  or  $(y, x) \in S$  and thus  $(y, x) \in R \cup S$ . We thus have  $(x, y) \in (R \cup S)^{-1}$ .

## Notes:

# Languages and computers

► humans use **natural languages** (like German, English, French) to communicate


► in natural language, meaning is often **ambiguous or depends on context**, e.g.

“She saw the man with the telescope.”

► to communicate with machines, we (generally) **formalize languages** such that the meaning of statements is precisely defined

## examples of formal languages

1. programming languages (C, C++, python)
2. arithmetic expressions
3. Boolean algebra → L03 - Propositional Logic and Boolean Algebra



output of large language model **ChatGPT**

image credit: OpenAI screenshot, created 29/03/2023

## Notes:

# What is a formal language?

## definition

Let  $\Sigma$  be a **finite alphabet**, i.e. a set of symbols.

- ▶ We call a finite sequence  $w \in \Sigma^i$  of  $i$  symbols a **word** with length  $|w| := i$ . We denote the set of all words of length  $i$  as  $\Sigma^i$ .
- ▶ We call  $\epsilon$  the **empty word** (with length zero).
- ▶ We use  $w^R$  to denote the word that we get by reversing the sequence of symbols.
- ▶ With  $\Sigma^0 = \{\epsilon\}$  we recursively define

$$\Sigma^{i+1} := \{w \mid w = xy \text{ with } x \in \Sigma^i \text{ and } y \in \Sigma\}$$

- ▶ We define  $\Sigma^* := \bigcup_{i \geq 0} \Sigma^i$  and  $\Sigma^+ := \bigcup_{i > 0} \Sigma^i$
- ▶ A **formal language**  $L \subseteq \Sigma^*$  is a (possibly infinite) set of words over alphabet  $\Sigma$ .

## examples

- ▶  $L = \{aa, bb, abba\}$  is a (finite) formal language over alphabet  $\Sigma = \{a, b\}$
- ▶  $L = \{x \in \Sigma^* \mid x = x^R\}$  is an (infinite) formal language of palindroms over alphabet  $\Sigma = \{a, b\}$
- ▶  $L = \{x \mid x \text{ is syntactically correct python program}\}$  is a formal language over the alphabet of ASCII characters

how can we define **syntax** (“ $\sigma\nu\nu - \tau\alpha\xi$ ”) of words of a formal language  $L$ ?

## Notes:



# Grammars

- ▶ we can use **grammars** to define formal languages based on **production rules**

## definition

A **grammar**  $G$  is a four-tuple  $G = (V, \Sigma, P, S)$  where

- ▶  $V$  is a finite set of **variables** used in production rules,
- ▶  $\Sigma$  is a finite alphabet of **terminal symbols** with  $V \cap \Sigma = \emptyset$ ,
- ▶  $P$  is a finite set of **production rules** with  $P \subseteq (V \cup \Sigma)^+ \times (V \cup \Sigma)^*$ , and
- ▶  $S \in V$  is a **start symbol**.

For  $(X, Y) \in P$  we write  $X \rightarrow Y$  to denote that  $X$  can be substituted by  $Y$ . We use  $X \rightarrow^* Y$  to denote that there is a (possibly transitive) application of production rules that allows to substitute  $X$  by  $Y$ .

We say that  $L(G) = \{w \in \Sigma^* \mid S \rightarrow^* w\}$  is the **language generated by grammar  $G$** .

- ▶  $P$  is a relation that is **not necessarily functional**, i.e. we can have  $X \rightarrow Y \in P$  and  $X \rightarrow Y' \in P$ , which we denote as  $X \rightarrow Y \mid Y'$

## example

$G = (\{A, B\}, \{a, b\}, P, S)$  with

$$P = \{S \rightarrow AB, \\ A \rightarrow aA \mid \epsilon, \\ B \rightarrow bB \mid \epsilon \}$$

Starting with  $S$  we can apply the following substitutions:

$$\begin{aligned} S &\rightarrow AB \\ AB &\rightarrow aAB \\ aAb &\rightarrow aaAB \\ aaAB &\rightarrow aaAbB \\ aaAbB &\rightarrow aabB \\ aabB &\rightarrow aab \end{aligned}$$

Due to  $S \rightarrow^* aab$  we have  $aab \in L(G)$ .

## Notes:

## Group Exercise 02-02

Write a grammar for the formal language  $L = \{a^n b^n c^n \mid n \geq 1\}$ . Explain how the production rules are used to produce the word *aaabbbcccc*.

$$\Sigma = \{a, b, c\}, V = \{S, A, B\}$$

Possible production rules  $P$ :

$S \rightarrow aSBC \mid aBC,$   
 $CB \rightarrow BC,$   
 $aB \rightarrow ab,$   
 $bB \rightarrow bb,$   
 $bC \rightarrow bc,$   
 $cC \rightarrow cc$

production of word *aaabbbcccc*:

$S \rightarrow aSBC \rightarrow aaSBCBC$   
 $\rightarrow aaaB\textcolor{red}{C}BCBC \rightarrow aaaBBC\textcolor{red}{C}BC \rightarrow aaaBB\textcolor{red}{C}BCC$   
 $\rightarrow aa\textcolor{red}{a}BBCCCC$   
 $\rightarrow aaa\textcolor{red}{b}BCCCC \rightarrow aaab\textcolor{red}{b}BCCC$   
 $\rightarrow aaabb\textcolor{red}{b}CCC$   
 $\rightarrow aaabbb\textcolor{red}{c}CC \rightarrow aaabbb\textcolor{red}{c}C$   
 $\rightarrow aaabbbcccc$

## Notes:

# Chomsky hierarchy

- ▶ we **categorize grammars into a hierarchy** based on constraints that must be satisfied by production rules


## definition

Let  $G = (V, \Sigma, P, S)$  be a grammar.

- ▶ Every grammar  $G$  is **recursively enumerable (type 0)**
- ▶ Grammar  $G$  is **context-sensitive (type 1)**, iff for all production rules  $w_1 \rightarrow w_2 \in P : |w_1| \leq |w_2|$  (or rule has the form  $S \rightarrow \epsilon$ )
- ▶ Grammar  $G$  of type 1 is **context-free (type 2)**, iff for all rules  $w_1 \rightarrow w_2 \in P : w_1 \in V$
- ▶ Grammar  $G$  of type 2 is **regular (type 3)**, iff for all rules  $w_1 \rightarrow w_2 \in P : w_2 \in \Sigma \cup \Sigma V \cup \{\epsilon\}$

We say that a formal language  $L \subseteq \Sigma^*$  is of type 0, 1, 2 or 3 iff a type 0, 1, 2 or 3 grammar  $G$  exists with  $L(G)$ , respectively.

- ▶ higher type = stricter rules = **less expressive**



Venn diagram of Chomsky hierarchy

## Notes:

## Group Exercise 02-03

Consider the grammar from group exercise 02-02 and determine its type according to the Chomsky hierarchy.

Consider grammar  $G = (V, \Sigma, P, S)$  with  $V = \{S, B, C\}$ ,  $\Sigma = \{a, b\}$  and production rules

$$\begin{aligned} P = \{ & S \rightarrow aSBC \mid aBC, \\ & CB \rightarrow BC, \\ & aB \rightarrow ab, \\ & bB \rightarrow bb, \\ & bC \rightarrow bc, \\ & cC \rightarrow cc \} \end{aligned}$$


$G$  is necessarily of type 0 (i.e. recursively enumerable). Since we have  $|w_1| \leq |w_2|$  for all  $w_1 \rightarrow w_2 \in P$  the grammar  $G$  is of type 1 (i.e. it is context-sensitive). For  $aB \rightarrow ab \in P$  we have  $aB \notin V$  and thus  $G$  is not of type 2 (i.e. it is not context-free).

## Notes:



# In summary ...

- ▶ we have covered **formal foundations of computing**
- ▶ we introduced **formal languages**, which are defined as (possibly infinite) sets of words over finite alphabet
- ▶ we can specify the syntax of formal languages based on **grammars with production rules**
- ▶ we use the **Chomsky hierarchy** to categorize grammars (and the languages that they produce) based on their production rules
- ▶ formal languages allow us to formalize **which problems are decidable** by an algorithm
- ▶ how can we **algorithmically decide** whether a given word  $w$  is in a language  $L$ ?



**Notes:**

# Exercise sheet 01

- ▶ **first exercise sheet** will be released next Monday
- ▶ solutions are due **May 12th** (via WueCampus)
- ▶ present your solution to earn bonus points



Algorithmen für KI und Data Science II  
SoSe 2023

Prof. Dr. Ingo Scholtes  
Chair of Informatics XV  
University of Würzburg

## Exercise Sheet 01

Published: April 26, 2023

Due: May 3, 2023

Total points: 10

Please upload your solutions to WueCampus as a scanned document (image format or pdf), a typesetted PDF document, and/or as a jupyter notebook.

### 1. Set theory

(a) Solve the following:

- a) What's the power set of  $\{x, y, x\}$ ?
- b) What is the intuitive explanation of the power set of the natural numbers  $\mathcal{P}(\mathbb{N})$ ?
- c) Give an example of the pair  $(a, b) \in X$  but  $(b, a) \notin X$ ?
- d) Prove that  $X \cup (\emptyset \cap Y) = X$

1P

(b) Show that the following statements are equivalent:

- (i)  $A \subseteq B$
- (ii)  $A \cap B = A$
- (iii)  $A \cup B = B$

2P

### 2. Relations

Prove the following:

(a) A relation is called equivalence relation if it is reflexive, symmetric and transitive.

Let  $R$  be a relation on a group  $G$ , where  $xRy$  for  $x, y \in G$  if and only if there exists  $g \in G$  such that  $y = g^{-1}xg$ .

(A group  $G$  is a non-empty set of elements together with a binary operation  $+$  :  $G \times G \rightarrow G$  with the following properties:

- There exists neutral element  $1 \in G$  with  $g1 = g$  and  $1g = g$  for all  $g \in G$  and  $1^{-1} = 1$ .
- For all  $g \in G$  there exists  $g^{-1} \in G$  such that  $gg^{-1} = g^{-1}g = 1$ .
- $G$  is associative, i.e.  $(gh)i = g(hi)$  for all  $g, h, i \in G$ .

Here we wrote  $gh$  instead of  $g + h$ .)

(b) Prove that an equivalence relation which is also a function is necessarily the identity function?

The identity  $I : A \rightarrow A$  is defined by  $I(a) = a$  for all  $a \in A$ .

2P

1P

### 3. Formal Languages and Automata

(a) Write a context-free grammar for the following languages:

- 1.  $L_1 = \{a^m b^n \mid m \geq n, n > 0\}$
- 2.  $L_2 = \{a^i b^j c^{i+k} \mid i, k \in \mathbb{N}\}$

2P

**Notes:**

# Self-study questions

1. Explain the difference between a relation and a function.
2. Give an example for a relation  $R$  on  $\mathbb{N}$  that is reflexive, symmetric, and transitive.
3. Show that your relation  $R$  from above defines a partition of  $\mathbb{N}$ , i.e. a partition of  $\mathbb{N}$  in pair-wise non-overlapping subsets of  $\mathbb{N}$ .
4. Give an example for a relation  $R$  that is not functional but injective.
5. Provide the formal definition of a grammar. What is the difference between  $V$  and  $\Sigma$  in the definition?
6. Give an example for a grammar where the production rules never terminate (thus not a language without any words).
7. Give a grammar for the language of all bit strings that correspond to even natural numbers.
8. Using the production rules of the previous question, test whether a large language model like ChatGPT can correctly derive the resulting language.
9. What is the difference between a content-sensitive and context-free language?
10. Give an example for a language that is regular.
11. Write a grammar for the language of correctly bracketed arithmetic formulas with arithmetic operations  $+$  and  $*$ . For simplicity consider formulas with two variables  $a, b$  only.

**Notes:**

# References


## reading list

- ▶ G Cantor: **Ueber eine Eigenschaft des Inbegriffes aller reellen algebraischen Zahlen**, Journal über die Reine und Angewandte Mathematik, 1874
- ▶ N Chomsky: **Three models for the description of language**, 1956
- ▶ N Chomsky: **The Logical Structure of Linguistic Theory**, 1975

## acknowledgments

some examples are based on the following books and lectures:

- ▶ U Schöning: **Theoretische Informatik - kurzgefasst**, Spektrum Akadem. Verlag, 2001
- ▶ J Esparza: **Automata theory: An algorithmic approach**, lecture notes, 2020



## Notes: