



Data Engineering

SNOWFLAKE

ALL CONCEPTS TO GET STARTED



Shwetank Singh
GritSetGrow - GSGLearn.com

Cloud Data Warehouse

A cloud-based platform for storing and analyzing data, which offers scalability, flexibility, and cost-efficiency compared to traditional on-premises data warehouses.

Snowflake provides a fully managed service with separate compute, storage, and cloud services layers, making it easier to scale and manage data operations.



Shwetank Singh
GritSetGrow - GSGLearn.com

Snowflake Architecture

Snowflake's architecture separates storage and compute, allowing for independent scaling and efficient data management. This design eliminates many limitations of traditional data warehouses.

Snowflake uses a multi-cluster shared data architecture, where storage is centralized, and compute resources can be scaled up or down independently based on workload.



Shwetank Singh
GritSetGrow - GSGLearn.com

Virtual Warehouse

A virtual warehouse is a cluster of compute resources in Snowflake. Each virtual warehouse can be scaled independently to match the workload, providing the necessary compute power for query execution without affecting other warehouses.

If a company needs to run a heavy analytical query during peak business hours, they can scale up the virtual warehouse to a larger size, ensuring faster query performance. After the peak hours, the warehouse can be scaled down to save costs.



Shwetank Singh
GritSetGrow - GSGLearn.com

Database

A logical grouping of schemas, tables, and other database objects. It provides a namespace for organizing and managing data.

Creating a new database in Snowflake:
`CREATE DATABASE sales_data;`
This command sets up a new database where all sales-related schemas and tables can be organized.



Shwetank Singh
GritSetGrow - GSGLearn.com

Schema

A logical grouping of database objects such as tables, views, and stored procedures. Schemas help organize objects within a database.

Creating a new schema in a database:
`CREATE SCHEMA sales_data.january;`
This schema can contain all tables related to January's sales data.



Shwetank Singh
GritSetGrow - GSGLearn.com

Table

A structured set of data elements (values) organized in rows and columns. Tables are fundamental storage objects in a database.

Creating a new table:

```
CREATE TABLE customers  
(id INT, name STRING, email STRING);
```

This table stores customer information.



Shwetank Singh
GritSetGrow - GSGLearn.com

View

A virtual table based on the result-set of a SQL query. Views do not store data themselves but provide a way to represent data stored in tables.

Creating a new view:

```
CREATE VIEW vip_customers  
AS SELECT * FROM customers  
WHERE status = 'VIP';
```

This view shows only VIP customers.



Shwetank Singh
GritSetGrow - GSGLearn.com

Stage

A location where data files are stored temporarily before being loaded into Snowflake tables. Stages can be internal or external (e.g., S3, Azure Blob Storage).

Creating an internal stage:

`CREATE STAGE my_stage;`

This stage can be used to store data files before loading them into tables.



Shwetank Singh
GritSetGrow - GSGLearn.com

File Format

Defines the format of data files to be loaded into Snowflake (e.g., CSV, JSON, Avro). File formats specify how Snowflake should interpret the contents of the files.

Creating a file format for CSV files:

CREATE FILE FORMAT my_csv_format

TYPE = 'CSV'

FIELD_OPTIONALLY_ENCLOSED_BY = "";



Shwetank Singh
GritSetGrow - GSGLearn.com

Warehouse Size

Snowflake offers different sizes for virtual warehouses (e.g., X-Small, Small, Medium, Large) to accommodate various workloads. Larger sizes provide more compute resources.

A Small warehouse might be sufficient for routine queries, while a Large warehouse can handle complex analytical queries. Adjust the size based on workload demands.



Shwetank Singh
GritSetGrow - GSGLearn.com

Scaling Up

Increasing the size of a virtual warehouse to provide more compute resources for a specific workload.

Scaling up a virtual warehouse:

```
ALTER WAREHOUSE my_warehouse  
SET WAREHOUSE_SIZE = 'LARGE';
```

This increases the compute power available for queries.



Shwetank Singh
GritSetGrow - GSGLearn.com

Scaling Out

Adding more compute clusters to a virtual warehouse to handle increased concurrency and workload demands.

Enabling auto-scaling for a warehouse:

```
ALTER WAREHOUSE my_warehouse  
SET MAX_CLUSTER_COUNT = 5;.
```

Snowflake will add clusters as needed to handle concurrent queries.



Shwetank Singh
GritSetGrow - GSGLearn.com

Auto-Suspend

Automatically suspends a virtual warehouse when it is idle for a specified period, saving costs.

Setting auto-suspend for a warehouse:

```
ALTER WAREHOUSE my_warehouse  
SET AUTO_SUSPEND = 300;
```

The warehouse will suspend after 5 minutes of inactivity.



Shwetank Singh
GritSetGrow - GSGLearn.com

Auto-Resume

Automatically resumes a suspended virtual warehouse when a query is submitted, ensuring availability without manual intervention.

Enabling auto-resume for a warehouse:

```
ALTER WAREHOUSE my_warehouse  
SET AUTO_RESUME = TRUE;
```

The warehouse will resume automatically when a query is submitted.



Shwetank Singh
GritSetGrow - GSGLearn.com

Query Caching

Snowflake caches the results of queries to speed up repeated query executions, reducing the need for re-computation and saving compute resources.

Running the same query twice will utilize the cached result if the underlying data has not changed, improving performance and efficiency.



Shwetank Singh
GritSetGrow - GSGLearn.com

Result Cache

Stores the results of queries executed within the past 24 hours. The cache is accessible to all users within the account, reducing compute costs and speeding up query performance.

If a query is run and then re-run within 24 hours without changes to the underlying data, the result is fetched from the result cache, saving compute resources.



Shwetank Singh
GritSetGrow - GSGLearn.com

Metadata Cache

Stores metadata about database objects to speed up query parsing and planning. This cache helps optimize query execution by reducing the time needed to access metadata.

Metadata about tables, columns, and statistics is cached, allowing faster query planning and execution. This helps Snowflake optimize performance for complex queries.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Caching

Snowflake caches data in the local storage of virtual warehouses to improve query performance. This cache is independent for each virtual warehouse.

Frequently accessed data is stored in the local disk cache of a virtual warehouse, reducing the need to fetch data from remote storage repeatedly, thus improving performance.



Shwetank Singh
GritSetGrow - GSGLearn.com

Stages

Locations in Snowflake where data files can be stored before being loaded into tables. Stages can be internal (within Snowflake) or external (e.g., AWS S3).

An internal stage can be created using `CREATE STAGE my_stage;`. Data files can be uploaded to this stage before being loaded into a table.



Shwetank Singh
GritSetGrow - GSGLearn.com

COPY INTO Command

Used to load data from a stage into a Snowflake table. The command specifies the target table and the source file(s) along with optional transformations.

Loading data from a stage into a table:

```
COPY INTO my_table  
FROM @my_stage/file.csv  
FILE_FORMAT = (FORMAT_NAME =  
'my_csv_format');
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Time Travel

Allows users to query, clone, or restore data to a previous state within a defined retention period. This feature aids in data recovery and auditing.

Querying a table as it was at a specific point in time:

```
SELECT * FROM my_table  
AT (TIMESTAMP => '2022-06-01T00:00:00');
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Zero-Copy Cloning

Enables creating a clone of a database, schema, or table without copying the data. Changes to the clone do not affect the original, and vice versa.

Creating a clone of a table:

```
CREATE CLONE my_table_clone  
OF my_table;
```

This allows working with a snapshot of the data without additional storage costs.



Shwetank Singh
GritSetGrow - GSGLearn.com

Secure Data Sharing

Allows sharing of data across different Snowflake accounts without moving or copying the data. Consumers can query shared data in real-time.

Sharing data with another Snowflake account:

```
CREATE SHARE my_share;  
GRANT SELECT ON TABLE my_table TO  
SHARE my_share;
```

The recipient can access the shared data directly.



Shwetank Singh
GritSetGrow - GSGLearn.com

Snowsight

Snowflake's new web user interface that enhances the user experience with features like integrated dashboards, interactive visualizations, and an improved SQL editor.

Users can create and manage interactive dashboards within Snowsight, allowing them to visualize data trends and share insights with their team. For example, a sales team can use Snowsight to build a dashboard that tracks monthly sales performance across different regions.



Shwetank Singh
GritSetGrow - GSGLearn.com

Snowflake Community

A vibrant network of users, experts, and partners who share knowledge, best practices, and support each other in using Snowflake. It includes user groups, forums, and special interest groups.

Joining the Snowflake Community allows users to participate in discussions, attend meetups, and access valuable resources. For instance, a data analyst can join a virtual special interest group focused on data warehousing to learn from others' experiences and share their own insights.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Marketplace

The Snowflake Data Marketplace is a platform where users can discover, access, and share live data sets from various providers. It facilitates data collaboration and allows users to enrich their own data with external data sources.

A marketing team can access demographic data from a third-party provider through the Data Marketplace to enhance their customer analysis. They can integrate this data with their internal sales data to gain deeper insights into customer behavior and preferences.



Shwetank Singh
GritSetGrow - GSGLearn.com

Multi-Cluster Warehouses

Multi-Cluster Warehouses allow Snowflake to automatically manage the number of compute clusters needed to handle varying workloads. This ensures optimal performance and resource utilization without manual intervention.

A retail company can set up a multi-cluster warehouse to handle the high concurrency of queries during Black Friday sales. Snowflake automatically adds clusters to manage the increased load and removes them when the load decreases, ensuring efficient use of resources and cost management.



Shwetank Singh
GritSetGrow - GSGLearn.com

Materialized Views

Materialized views store the result set of a query physically and automatically update when the underlying data changes. They improve query performance by providing pre-computed results.

Creating a materialized view:

```
CREATE MATERIALIZED VIEW mv_sales  
AS SELECT * FROM sales  
WHERE year = 2022;
```

Queries on this view are faster since the results are pre-computed.



Shwetank Singh
GritSetGrow - GSGLearn.com

Task

Tasks are used to automate the execution of SQL statements, including procedural logic, at specified intervals or upon completion of other tasks.

Creating a task to run a query every hour:

```
CREATE TASK hourly_task
WAREHOUSE = 'my_warehouse'
SCHEDULE = '1 HOUR'
AS
INSERT INTO daily_sales
SELECT * FROM sales
WHERE sales_date = CURRENT_DATE;;
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Stream

Streams track changes to a table (inserts, updates, deletes) and provide a change data capture (CDC) mechanism for efficient data processing.

Creating a stream:

```
CREATE STREAM sales_stream ON TABLE  
sales;
```

The stream captures changes to the sales table, which can be processed later.



Shwetank Singh
GritSetGrow - GSGLearn.com

Pipe

Pipes automate data loading by continuously ingesting data from external stages (e.g., AWS S3, Azure Blob Storage) into Snowflake tables.

Creating a pipe to load data from an S3 bucket:

```
CREATE PIPE my_pipe  
AS COPY INTO my_table  
FROM @my_stage/file.csv  
FILE_FORMAT = (FORMAT_NAME =  
'my_csv_format');
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Warehouse Monitoring

Snowflake provides tools to monitor the performance and usage of virtual warehouses, helping users optimize resource allocation and manage costs.

Using the `WAREHOUSE_METERING_HISTORY` view to monitor warehouse usage and costs:

```
SELECT * FROM  
WAREHOUSE_METERING_HISTORY  
WHERE WAREHOUSE_NAME =  
'my_warehouse';
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Role-Based Access Control (RBAC)

A security model that restricts access to data and resources based on the roles assigned to users. Snowflake allows fine-grained control over access permissions.

Creating a role and granting privileges:

CREATE ROLE analyst_role;

*GRANT SELECT ON DATABASE sales_data TO
ROLE analyst_role;*

Assigning the role to a user:

GRANT ROLE analyst_role TO USER john_doe;



Shwetank Singh
GritSetGrow - GSGLearn.com

Dynamic Data Masking

Dynamic Data Masking allows Snowflake to hide sensitive data in query results based on the role of the user accessing the data. This enhances data security and privacy.

Masking sensitive data:

```
CREATE MASKING POLICY ssn_mask  
AS (val STRING)  
RETURNS STRING -> CASE
```

```
WHEN CURRENT_ROLE() IN ('analyst_role')  
THEN 'XXX-XX-XXXX'  
ELSE val END;
```

Applying the policy:

```
ALTER TABLE customers  
MODIFY COLUMN ssn  
SET MASKING POLICY ssn_mask;.
```



Shwetank Singh
GritSetGrow - GSGLearn.com

External Tables

External tables allow Snowflake to query data stored in external locations (e.g., AWS S3, Azure Blob Storage) without loading it into Snowflake.

Creating an external table:

```
CREATE EXTERNAL TABLE my_ext_table WITH  
LOCATION = '@my_external_stage'  
FILE_FORMAT = (FORMAT_NAME =  
'my_csv_format');
```

This table allows querying data directly from the external stage.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Replication

Snowflake's data replication feature allows for the replication of databases across different regions and cloud providers to enhance data availability and disaster recovery.

Setting up data replication:
*CREATE REPLICATION GROUP
my_replication AS REPLICATION
TO REGION 'aws_us_west_2';*

This replicates the database to a different AWS region.



Shwetank Singh
GritSetGrow - GSGLearn.com

Failover and Failback

Snowflake provides failover and fallback capabilities to ensure high availability and disaster recovery. Failover allows switching to a replica in case of a failure, and fallback switches back once the original is restored.

Configuring failover for a database:

```
ALTER DATABASE my_database
```

```
SET FAILOVER GROUP = my_failover_group;
```

This ensures that the database can switch to a replica in case of a failure.



Shwetank Singh
GritSetGrow - GSGLearn.com

Search Optimization Service

A Snowflake feature that improves the performance of searches on large tables by creating and maintaining search optimization structures.

Enabling search optimization for a table:

```
ALTER TABLE my_table SET SEARCH  
OPTIMIZATION = TRUE;
```

This improves the performance of search queries on the table.



Shwetank Singh
GritSetGrow - GSGLearn.com

Snowflake Data Exchange

A platform that allows Snowflake users to share and access live data securely. It facilitates data collaboration and monetization by providing a marketplace for data providers and consumers.

Publishing data to the Data Exchange:
CREATE EXCHANGE my_exchange;
GRANT SELECT ON TABLE my_table TO EXCHANGE my_exchange;
Other users can subscribe to and query the shared data.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Masking

Data masking provides a way to protect sensitive data by masking it in query results, based on user roles. This ensures that sensitive information is not exposed to unauthorized users.

Creating a data masking policy:

```
CREATE MASKING POLICY email_mask  
AS (val STRING)  
RETURNS STRING -> CASE  
WHEN CURRENT_ROLE() IN ('analyst_role')  
THEN '*****@domain.com' ELSE val END;
```

Applying the policy to a column:

```
ALTER TABLE users  
MODIFY COLUMN email SET MASKING POLICY  
email_mask;
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Snowpipe

Snowpipe is Snowflake's continuous data ingestion service, which allows for the automated loading of data from external stages into Snowflake tables.

Creating a Snowpipe to load data:

```
CREATE PIPE my_pipe  
AS COPY INTO my_table  
FROM @my_stage  
FILE_FORMAT = (FORMAT_NAME =  
'my_csv_format');
```

Snowpipe will automatically load new data files as they arrive in the stage.



Shwetank Singh
GritSetGrow - GSGLearn.com

External Functions

External functions allow Snowflake to call external services and integrate with external systems directly from SQL queries. This enables advanced data processing and integration capabilities.

Creating an external function:

```
CREATE EXTERNAL FUNCTION
```

```
my_ext_function()
```

```
RETURNS STRING API_INTEGRATION =
```

```
my_api_integration;
```

This function can call an external API and return the result to Snowflake.



Shwetank Singh

GritSetGrow - GSGLearn.com

Streams and Tasks

Streams track changes to tables, and tasks automate the execution of SQL based on schedules or events. Together, they enable efficient change data capture and automation.

Creating a stream and task:

```
CREATE STREAM my_stream  
ON TABLE my_table;  
CREATE TASK my_task WAREHOUSE =  
'my_warehouse' SCHEDULE = '1 HOUR'  
AS  
INSERT INTO my_target_table  
SELECT * FROM my_stream;.
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Snowflake Organizations

Snowflake Organizations provide a way to manage multiple Snowflake accounts within an organization. This enables better resource allocation, cost management, and governance.

Creating an organization:

`CREATE ORGANIZATION my_org;`
and adding accounts to it. This allows central management of multiple Snowflake accounts.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Governance

Snowflake offers features for data governance, including access controls, data masking, and audit logging, to ensure data security, privacy, and compliance.

Implementing data governance:
`CREATE ROW ACCESS POLICY my_policy AS
(val STRING)
RETURNS BOOLEAN -> CURRENT_ROLE()
IN ('data_governance_role');`
and applying it to a table.



Shwetank Singh
GritSetGrow - GSGLearn.com

Account Usage

Snowflake provides account usage views to track and analyze resource usage, query performance, and cost management. These views help in monitoring and optimizing Snowflake usage.

Querying account usage:

```
SELECT * FROM  
ACCOUNT_USAGE.QUERY_HISTORY WHERE  
QUERY_TEXT ILIKE '%SELECT%';
```

This retrieves the history of SELECT queries executed in the account.



Shwetank Singh
GritSetGrow - GSGLearn.com

Resource Monitors

Resource monitors allow administrators to manage and control compute resource usage by setting thresholds and triggering actions when limits are reached.

Creating a resource monitor:

*CREATE RESOURCE MONITOR my_monitor
WITH CREDIT_QUOTA = 1000;*

and assigning it to a warehouse. This monitor will track the compute credits used by the warehouse and take action if the quota is exceeded.



Shwetank Singh
GritSetGrow - GSGLearn.com

Query Optimization

Snowflake provides various tools and techniques to optimize query performance, including using the Query Profiler, optimizing table structures, and leveraging caching.

Using the Query Profiler:

```
SELECT * FROM  
TABLE(QUERY_HISTORY_BY_SESSION(SESSI  
ON_ID => 'my_session'));
```

This helps identify and optimize slow-running queries.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Sharing

Snowflake allows secure sharing of data between different accounts without data movement. Shared data can be accessed in real-time, ensuring consistency and reducing latency.

Creating a share: `CREATE SHARE my_share;` and adding tables to it. Other Snowflake accounts can access the shared data directly.



Shwetank Singh
GritSetGrow - GSGLearn.com

Cloning

Cloning in Snowflake creates a copy of a database, schema, or table without duplicating the data. This is useful for creating test environments and for backup purposes.

Cloning a table:

```
CREATE CLONE my_table_clone OF  
my_table;
```

This allows working with a snapshot of the data without additional storage costs.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Load and Unload

Snowflake provides various methods for loading and unloading data, including bulk loading with the COPY command, using Snowpipe for continuous loading, and unloading data to external stages.

Loading data:

```
COPY INTO my_table  
FROM @my_stage FILE_FORMAT =  
(FORMAT_NAME = 'my_csv_format');
```

and unloading data:

```
COPY INTO @my_stage FROM my_table;
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Encryption

Snowflake encrypts data at rest and in transit to ensure data security. Encryption keys are managed automatically, and users can also provide their own keys for additional security.

Enabling encryption for a table:

```
ALTER TABLE my_table SET  
DATA_RETENTION_TIME_IN_DAYS = 90;
```

This ensures that data is encrypted and retained for a specified period.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Retention

Snowflake provides data retention policies to manage how long data is kept in the system. This includes Time Travel and Fail-safe periods for data recovery.

Setting data retention:

```
ALTER TABLE my_table SET  
DATA_RETENTION_TIME_IN_DAYS = 7;
```

This configures the table to retain historical data for 7 days.



Shwetank Singh
GritSetGrow - GSGLearn.com

Fail-Safe

Fail-Safe is a Snowflake feature that provides an additional 7-day period for recovering data after the Time Travel retention period has expired. This ensures data recovery in case of failures.

Accessing Fail-Safe data:

```
SELECT * FROM my_table BEFORE  
(END_TIME => '2022-06-01T00:00:00');
```

This retrieves data that is in the Fail-Safe period.



Shwetank Singh
GritSetGrow - GSGLearn.com

User-Defined Functions (UDFs)

UDFs allow users to define their own functions in SQL or JavaScript, extending Snowflake's built-in functionality with custom logic.

Creating a SQL UDF:

```
CREATE FUNCTION my_udf(x INT)
RETURNS INT
LANGUAGE SQL
AS
'RETURN x * 2';
```

This function multiplies the input by 2.



Shwetank Singh
GritSetGrow - GSGLearn.com

Stored Procedures

Stored procedures in Snowflake allow for procedural logic and complex operations to be encapsulated in SQL or JavaScript, enabling automation and reusable code.

Creating a stored procedure:

```
CREATE PROCEDURE my_proc()  
RETURNS STRING LANGUAGE JAVASCRIPT  
AS $$ return 'Hello, World!';  
$$;
```

and calling it:

```
CALL my_proc();
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Privileges and Grants

Snowflake's security model uses privileges and grants to control access to database objects. Roles are assigned privileges, and users are assigned roles.

Granting privileges:

```
GRANT SELECT ON TABLE my_table  
TO ROLE analyst_role;
```

This allows users with the analyst_role to query the table.



Shwetank Singh
GritSetGrow - GSGLearn.com

Roles and Role Hierarchies

Roles in Snowflake define a set of privileges and can be assigned to users. Role hierarchies allow roles to inherit privileges from other roles, simplifying access management.

Creating a role hierarchy:

```
CREATE ROLE senior_analyst;
```

```
GRANT ROLE analyst_role TO ROLE  
senior_analyst;
```

Users with the `senior_analyst` role inherit privileges from the `analyst_role`.



Shwetank Singh
GritSetGrow - GSGLearn.com

Session Variables

Session variables in Snowflake store values that can be used within a session. They allow for dynamic SQL and reusable code.

Setting and using a session variable:

SET my_var = 'Hello, World!';

and *SELECT \$my_var;*

This returns the value of the variable.



Shwetank Singh
GritSetGrow - GSGLearn.com

Parameter Management

Snowflake allows configuration of various parameters at the account, session, and object levels to customize behavior and optimize performance.

Setting a session parameter:

```
ALTER SESSION SET QUERY_TAG =  
'MyQuery';
```

This tags queries within the session for easier tracking.



Shwetank Singh
GritSetGrow - GSGLearn.com

Semi-Structured Data

Snowflake supports semi-structured data formats such as JSON, Avro, Parquet, and XML. This allows for flexible data modeling and integration with modern data sources.

Querying JSON data: `SELECT json_data:id FROM my_table;` This retrieves the "id" field from JSON data stored in a column.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Compression

Snowflake automatically compresses data to reduce storage costs and improve query performance. Different compression algorithms are used based on the data type.

Snowflake's automatic compression means users don't need to manually configure compression settings, as the platform optimizes storage efficiency.



Shwetank Singh
GritSetGrow - GSGLearn.com

Cost Management

Snowflake provides tools and practices to manage and optimize costs, including resource monitors, usage views, and best practices for query optimization.

Using resource monitors to control costs:
*CREATE RESOURCE MONITOR my_monitor
WITH CREDIT_QUOTA = 1000;*
and setting up alerts for budget thresholds.



Shwetank Singh
GritSetGrow - GSGLearn.com

Query History

Snowflake tracks query history, allowing users to review and analyze past queries for performance optimization and troubleshooting.

Accessing query history:

`SELECT * FROM QUERY_HISTORY
WHERE QUERY_TEXT ILIKE '%SELECT%';` This retrieves a history of SELECT queries executed in the account.



Shwetank Singh
GritSetGrow - GSGLearn.com

Metadata Management

Snowflake manages metadata for all database objects, providing detailed information about tables, columns, and other objects. This metadata is used for query optimization and data governance.

Querying metadata:

```
SELECT * FROM  
INFORMATION_SCHEMA.TABLES  
WHERE TABLE_SCHEMA = 'PUBLIC';
```

This retrieves information about all tables in the PUBLIC schema.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Import/Export

Snowflake supports various methods for importing and exporting data, including bulk loading with the COPY command and unloading to external stages.

Importing data:

```
COPY INTO my_table  
FROM @my_stage FILE_FORMAT =  
(FORMAT_NAME = 'my_csv_format');
```

and exporting data:

```
COPY INTO @my_stage FROM my_table;
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Quality

Snowflake provides features to ensure data quality, including constraints, data validation, and profiling.

Implementing data quality checks:

```
CREATE TABLE my_table (  
id INT PRIMARY KEY,  
name STRING NOT NULL);
```

This ensures that the "id" column is unique and the "name" column is not null.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Lineage

Data lineage tracks the flow of data through Snowflake, from ingestion to transformation to analysis, providing visibility into data dependencies and transformations.

Using views and tasks to track data lineage:

```
CREATE VIEW my_view  
AS  
SELECT * FROM my_table;  
and  
CREATE TASK my_task  
AS  
INSERT INTO my_table  
SELECT * FROM my_view;
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Business Continuity

Snowflake's features for business continuity include data replication, failover, and fail-safe, ensuring that data is always available and recoverable in case of disasters.

Setting up a failover group:

```
CREATE FAILOVER GROUP my_group  
AS FAILOVER TO REGION 'aws_us_west_2';
```

This ensures that the database can switch to a replica in case of a failure.



Shwetank Singh
GritSetGrow - GSGLearn.com

Governance and Compliance

Snowflake provides tools for data governance and compliance, including access controls, data masking, and audit logging, to ensure data security and regulatory compliance.

Implementing compliance policies:
`CREATE ROW ACCESS POLICY
compliance_policy AS (val STRING)
RETURNS BOOLEAN -> CURRENT_ROLE()
IN ('compliance_role');`
and applying it to a table.



Shwetank Singh
GritSetGrow - GSGLearn.com

Advanced Analytics

Snowflake supports advanced analytics capabilities, including machine learning integration, geospatial data processing, and complex data transformations.

Integrating with machine learning models:

```
CREATE FUNCTION predict_sales(x FLOAT)  
RETURNS FLOAT
```

```
LANGUAGE PYTHON RUNTIME = '3.8'
```

```
HANDLER = 'my_model.predict';
```

This function calls a Python model for sales prediction.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Monetization

Snowflake's data marketplace and secure data sharing enable organizations to monetize their data assets by sharing or selling data to other Snowflake users.

Publishing data for monetization:
CREATE EXCHANGE my_exchange;
and adding data to it for other users to access and purchase.



Shwetank Singh
GritSetGrow - GSGLearn.com

Geospatial Data

Snowflake supports geospatial data types and functions, allowing users to store, query, and analyze spatial data such as points, polygons, and geometries.

Querying geospatial data:

```
SELECT ST_DISTANCE(point1, point2)  
FROM my_table;
```

This calculates the distance between two points stored in a table.



Shwetank Singh
GritSetGrow - GSGLearn.com

IoT Data Processing

Snowflake's scalable architecture and support for semi-structured data make it well-suited for processing and analyzing IoT (Internet of Things) data.

Loading IoT data:

```
COPY INTO my_table  
FROM @iot_stage  
FILE_FORMAT = (FORMAT_NAME =  
'json_format');
```

This ingests JSON data from IoT devices.



Shwetank Singh
GritSetGrow - GSGLearn.com

Real-Time Analytics

Snowflake supports real-time analytics by allowing continuous data ingestion and immediate querying of fresh data.

Using Snowpipe for real-time data ingestion:

```
CREATE PIPE my_pipe  
AS COPY INTO my_table  
FROM @my_stage  
FILE_FORMAT = (FORMAT_NAME =  
'my_csv_format');
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Federation

Snowflake's external tables and data sharing features enable data federation, allowing users to query and combine data from multiple sources without moving the data.

Creating an external table to federate data:

```
CREATE EXTERNAL TABLE my_ext_table WITH  
LOCATION = '@my_external_stage'  
FILE_FORMAT = (FORMAT_NAME =  
'my_csv_format');
```

This table allows querying data directly from the external stage.



Shwetank Singh
GritSetGrow - GSGLearn.com

Security Integrations

Snowflake integrates with security tools and frameworks, including single sign-on (SSO), multi-factor authentication (MFA), and encryption key management, to enhance data security.

Configuring SSO:

```
ALTER ACCOUNT SET SSO_LOGIN_PAGE =  
'https://mycompany.com/sso';
```

This enables single sign-on for Snowflake users.



Shwetank Singh
GritSetGrow - GSGLearn.com

Continuous Data Protection

Snowflake's continuous data protection features include Time Travel, Fail-safe, and data replication, ensuring data integrity and availability at all times.

Setting up data replication:
*CREATE REPLICATION GROUP
my_replication
AS REPLICATION TO REGION
'aws_us_west_2';*

This replicates the database to a different AWS region.



Shwetank Singh
GritSetGrow - GSGLearn.com

Custom Data Types

Snowflake allows users to define custom data types and enforce data integrity through constraints and validation rules.

Creating a custom data type:

```
CREATE DOMAIN email_type  
AS STRING CHECK (VALUE LIKE '%@%.%');
```

This enforces email format validation.



Shwetank Singh
GritSetGrow - GSGLearn.com

Hybrid Tables

Hybrid tables in Snowflake combine the benefits of transactional and analytical processing, allowing for efficient real-time data analysis.

Creating a hybrid table:

```
CREATE HYBRID TABLE my_table  
(id INT, data STRING);
```

This table supports both transactional and analytical workloads.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Archiving

Snowflake's data retention and archiving features help manage long-term storage of historical data, ensuring that it is available for compliance and analysis.

Setting data retention:

```
ALTER TABLE my_table  
SET DATA_RETENTION_TIME_IN_DAYS = 365;
```

This configures the table to retain historical data for one year.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Classification

Data classification in Snowflake helps categorize data based on sensitivity and importance, enabling better data governance and security.

Classifying data:

```
ALTER TABLE my_table SET TAG  
classification = 'sensitive';
```

This tags the table as containing sensitive data.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Masking Policies

Data masking policies in Snowflake provide dynamic masking of sensitive data based on user roles, ensuring that only authorized users can see the actual data.

Creating a data masking policy:

```
CREATE MASKING POLICY ssn_mask  
AS (val STRING)
```

```
RETURNS STRING -> CASE  
WHEN CURRENT_ROLE() IN ('analyst_role')  
THEN 'XXX-XX-XXXX' ELSE val END;
```

Applying the policy:

```
ALTER TABLE customers MODIFY COLUMN ssn  
SET MASKING POLICY ssn_mask;
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Row Access Policies

Row access policies allow Snowflake to restrict access to specific rows in a table based on user roles and other criteria, enhancing data security and compliance.

Creating a row access policy:

```
CREATE ROW ACCESS POLICY row_policy  
AS (val STRING)
```

```
RETURNS BOOLEAN -> CURRENT_ROLE() IN  
('analyst_role');
```

Applying the policy:

```
ALTER TABLE my_table MODIFY ROW  
ACCESS POLICY row_policy;
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Cross-Cloud Replication

Snowflake supports cross-cloud replication, allowing data to be replicated across different cloud providers (e.g., AWS, Azure, Google Cloud) for high availability and disaster recovery.

Setting up cross-cloud replication:

CREATE REPLICATION GROUP

my_replication

AS REPLICATION TO REGION 'azure_eastus';

This replicates the database to an Azure region.



Shwetank Singh

GritSetGrow - GSGLearn.com

Event-Driven Data Processing

Snowflake's tasks and streams enable event-driven data processing, allowing actions to be triggered based on changes in data or scheduled intervals.

Creating an event-driven task:

```
CREATE TASK my_task  
WAREHOUSE = 'my_warehouse'  
AFTER INSERT ON my_table  
AS  
  INSERT INTO audit_table  
  SELECT * FROM my_table;
```



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Encryption Key Management

Snowflake allows users to manage their own encryption keys for added security, providing control over data encryption and compliance with regulatory requirements.

Setting a customer-managed key:

```
ALTER DATABASE my_database  
SET ENCRYPTION = 'my_custom_key';
```

This uses a user-provided key for data encryption.



Shwetank Singh
GritSetGrow - GSGLearn.com

Geospatial Functions

Snowflake provides geospatial functions to perform spatial analysis and operations on geographic data, such as distance calculations and spatial joins.

Using a geospatial function:

```
SELECT ST_DISTANCE(point1, point2)  
FROM my_table;
```

This calculates the distance between two geographic points stored in a table.



Shwetank Singh
GritSetGrow - GSGLearn.com

Graph Analytics

Snowflake supports graph analytics, enabling users to model and analyze relationships between data points using graph structures and algorithms.

Performing graph analytics:
*CREATE TABLE graph_edges
(src INT, dst INT);*
and running graph queries to analyze relationships.



Shwetank Singh
GritSetGrow - GSGLearn.com

Data Versioning

Snowflake's Time Travel and Zero-Copy Cloning features enable data versioning, allowing users to create, manage, and query different versions of data for analysis and auditing.

Creating a version of a table:

```
CREATE CLONE my_table_clone  
OF my_table;
```

This clone represents a version of the original table that can be queried and analyzed separately.



Shwetank Singh
GritSetGrow - GSGLearn.com

API Integration

Snowflake supports integration with external APIs, allowing users to call external services and incorporate real-time data into Snowflake queries and workflows.

Creating an external function to call an API:

```
CREATE EXTERNAL FUNCTION  
my_ext_function() RETURNS STRING  
API_INTEGRATION = my_api_integration;
```

This function can call an external API and return the result to Snowflake.



Shwetank Singh
GritSetGrow - GSGLearn.com



THANK YOU