

Table Of Contents:

List of Splunk Queries	5
1. Query to identify failed login attempts	5
2. Query to identify potential security threats	5
3. Query to identify privilege escalation attempts.....	5
4. Query to identify failed SSH attempts	5
5. Query to identify successful SSH attempts	5
6. Query to identify unusual network traffic	5
7. Query to identify suspicious processes	5
8. Query to identify brute force attacks	5
9. Query to identify privilege escalation attempts on Windows systems	6
10. Query to identify abnormal user activity.....	6
11. Query to identify potential DNS tunneling activity	6
12. Query to identify suspicious PowerShell activity	6
13. Query to identify unusual file access.....	6
14. Query to identify network port scans	6
15. Query to identify suspicious email activity	6
16. Query to identify potential data exfiltration.....	6
17. Query to identify failed VPN attempts	7
18. Query to identify successful VPN attempts	7
19. Query to identify successful login attempts from new or unknown IP addresses	7
20. Query to identify potential SQL injection attempts	7
21. Query to identify unusual file extensions.....	7
22. Query to identify potential phishing attacks.....	7
23. Query to identify traffic to known malicious IP addresses	7
24. Query to identify unusual login times	7
25. Query to identify privilege escalation attempts on Linux systems.....	7
26. Query to identify potential brute force attacks against a specific user	8
27. Query to identify unusual DNS requests	8
28. Query to identify potential spear-phishing attempts.....	8
29. Query to identify potential malware infections	8
30. Query to identify unusual user activity	8

LIST OF SPLUNK QUERIES – SOC

31. Query to identify potential DDoS attacks	8
32. Query to identify potential ransomware activity	8
33. Query to identify potential insider threats	8
34. Query to identify successful authentication attempts from unknown IP addresses.....	9
35. Query to identify potential brute force attacks on a specific service.....	9
36. Query to identify successful SSH logins from unusual countries	9
37. Query to identify potential attempts to exploit known vulnerabilities	9
38. Query to identify potential brute force attacks on a specific user	9
39. Query to identify potential man-in-the-middle attacks.....	9
40. Query to identify potential data exfiltration.....	9
41. Query to identify potential ransomware activity on Windows systems.....	10
42. Query to identify unusual network traffic patterns	10
43. Query to identify potential brute force attacks on a specific protocol	10
44. Query to identify potential account takeover attempts.....	10
45. Query to identify potential DNS tunneling activity	10
46. Query to identify potential SQL injection attempts on web servers	10
47. Query to identify potential brute force attacks on a specific domain.....	10
48. Query to identify potential brute force attacks on a specific application	11
49. Query to identify potential phishing attempts through email attachments.....	11
50. Query to identify potential exploitation attempts on vulnerable services.....	11
51. Query to identify potential reconnaissance activity.....	11
52. Query to identify potential cross-site scripting (XSS) attacks on web servers	11
53. Query to identify potential privilege escalation attempts.....	11
54. Query to identify potential web application attacks	11
55. Query to identify potential lateral movement attempts.....	11
56. Query to identify potential unauthorized changes to critical files	12
57. Query to identify potential port scanning activity	12
58. Query to identify potential malicious PowerShell activity on Windows systems.....	12
59. Query to identify potential SQL injection attempts on web servers	12
60. Query to identify potential brute force attacks on a specific domain controller	12
61. Query to identify potential DDoS attacks	12
62. Query to identify potential web shell activity.....	12
63. Query to identify potential brute force attacks on a specific network device.....	12

LIST OF SPLUNK QUERIES – SOC

64. Query to identify potential privilege escalation attempts on Linux systems.....	13
65. Query to identify potential DNS tunneling activity	13
66. Query to identify potential lateral movement attempts using RDP.....	13
67. Query to identify potential command and control (C2) traffic	13
68. Query to identify potential PowerShell Empire activity	13
69. Query to identify potential ransomware activity	13
70. Query to identify potential malicious traffic from a specific IP address.....	13
71. Query to identify potential brute force attacks on web applications.....	13
72. Query to identify potential unauthorized access attempts to sensitive files.....	14
73. Query to identify potential lateral movement attempts using SMB	14
74. Query to identify potential brute force attacks on SSH servers.....	14
75. Query to identify potential phishing attacks.....	14
76. Query to identify potential command injection attempts on web servers.....	14
77. Query to identify potential lateral movement attempts using WinRM.....	14
78. Query to identify potential brute force attacks on FTP servers	14
79. Query to identify potential privilege escalation attempts on Windows systems	14
80. Query to identify potential beaconing activity from a compromised host.....	15
81. Query to identify potential brute force attacks on SSH servers (failed login attempts).....	15
82. Query to identify potential data exfiltration attempts over HTTP	15
83. Query to identify potential lateral movement attempts using WMI.....	15
84. Query to identify potential brute force attacks on MSSQL servers.....	15
85. Query to identify potential privilege escalation attempts using PowerShell	15
86. Query to identify potential brute force attacks on email accounts	15
87. Query to identify potential lateral movement attempts using RDP (successful logins)	15
88. Query to identify potential brute force attacks on MSSQL servers (successful logins)	16
89. Query to identify potential data exfiltration attempts over FTP.....	16
90. Query to identify potential lateral movement attempts using SMB (successful connections)	16
91. Query to identify potential brute force attacks on RDP	16
92. Query to identify potential brute force attacks on web applications.....	16
93. Query to identify potential lateral movement attempts using Remote Registry Service	16
94. Query to identify potential privilege escalation attempts on Linux systems (sudo usage)	16
95. Query to identify potential data exfiltration attempts over DNS.....	16
96. Query to identify potential lateral movement attempts using SMB (failed connections)	17

LIST OF SPLUNK QUERIES – SOC

97. Query to identify potential brute force attacks on MSSQL servers (failed logins)	17
98. Query to identify potential data exfiltration attempts over SMTP	17
99. Query to identify potential lateral movement attempts using NetBIOS	17
100. Query to identify potential brute force attacks on Telnet servers.....	17
101. Query to identify potential data exfiltration attempts over FTP.....	17
102. Query to identify potential lateral movement attempts using WMI (failed connections)	17
103. Query to identify potential brute force attacks on SSH servers.....	17
104. Query to identify potential privilege escalation attempts on Windows systems (services configuration changes).....	18
105. Query to identify potential brute force attacks on SNMP	18
106. Query to identify potential data exfiltration attempts over HTTP	18
107. Query to identify potential lateral movement attempts using DCOM (failed connections).....	18
108. Query to identify potential brute force attacks on MySQL servers.....	18
109. Query to identify potential privilege escalation attempts on Windows systems (scheduled tasks creation)	18
110. Query to identify potential data exfiltration attempts over HTTPS	18

List of Splunk Queries

1. Query to identify failed login attempts:

```
sourcetype=auth* "authentication failure"  
| stats count by user  
| sort -count
```

2. Query to identify potential security threats:

```
sourcetype=access_* method=POST status=200  
| rex field=_raw "password=(?<password>[^&]+)"  
| eval password_length=length(password)  
| where password_length >= 8
```

3. Query to identify privilege escalation attempts:

```
sourcetype=linux_secure su*  
| where user!=root AND user!=""
```

4. Query to identify failed SSH attempts:

```
sourcetype=linux_secure "Failed password for"  
| stats count by src_ip  
| sort -count
```

5. Query to identify successful SSH attempts:

```
sourcetype=linux_secure "Accepted publickey for"  
| stats count by src_ip  
| sort -count
```

6. Query to identify unusual network traffic:

```
sourcetype=network_traffic  
| stats sum(bytes) as total_bytes by src_ip, dest_ip  
| where total_bytes > 1000000
```

7. Query to identify suspicious processes:

```
sourcetype=processes  
| search "lsass.exe" OR "svchost.exe" OR "explorer.exe"  
| stats count by user  
| sort -count
```

8. Query to identify brute force attacks:

```
sourcetype=access_* | stats count by clientip, action | where action="failure" AND count>=5
```

9. Query to identify privilege escalation attempts on Windows systems:

```
sourcetype="WinEventLog:Security" EventCode=4672  
| eval user_account=mvindex(Account_Name,1)  
| search "Security ID" NOT IN ("SYSTEM","LOCAL SERVICE","NETWORK SERVICE")
```

10. Query to identify abnormal user activity:

```
sourcetype=access_* action=purchase  
| stats count by clientip, user  
| where count > 50
```

11. Query to identify potential DNS tunneling activity:

```
sourcetype=dns  
| rex field=answer "data\"s*:\s*\"(?<data>[^\"]+)"  
| eval data_length=len(data)  
| where data_length > 32 AND (data_length % 4) == 0
```

12. Query to identify suspicious PowerShell activity:

```
sourcetype="WinEventLog:Microsoft-Windows-PowerShell/Operational" EventCode=4103  
| eval script_block=mvindex(Message,3)  
| search script_block="*Start-Process"
```

13. Query to identify unusual file access:

```
sourcetype=access_* action=file_delete OR action=file_rename  
| stats count by user  
| where count > 10
```

14. Query to identify network port scans:

```
sourcetype=network_traffic  
| stats count by src_ip, dest_port  
| where count > 100
```

15. Query to identify suspicious email activity:

```
sourcetype=email  
| search "phishing" OR "malware" OR "suspicious link"
```

16. Query to identify potential data exfiltration:

```
sourcetype=access_* action=file_download  
| stats count by user, dest_ip, dest_port  
| where count > 10
```

17. Query to identify failed VPN attempts:

```
sourcetype=access_* VPN AND action="failure"
```

18. Query to identify successful VPN attempts:

```
sourcetype=access_* VPN AND action="success"
```

19. Query to identify successful login attempts from new or unknown IP addresses:

```
sourcetype=access_* action=login
```

```
| stats count by user, src_ip
```

```
| where count=1
```

20. Query to identify potential SQL injection attempts:

```
sourcetype=access_* method=POST
```

```
| rex field=_raw "SELECT\s+(?<query>[^\s;]+)"
```

```
| eval query_length=length(query)
```

```
| where query_length > 50 AND query_length < 100
```

21. Query to identify unusual file extensions:

```
sourcetype=access_* action=file_upload
```

```
| rex field=file_path "\.*(?<extension>[^\s.]+)"
```

```
| stats count by extension
```

```
| where count > 10
```

22. Query to identify potential phishing attacks:

```
sourcetype=email
```

```
| search "password" OR "reset" OR "verify" OR "login"
```

23. Query to identify traffic to known malicious IP addresses:

```
sourcetype=network_traffic dest_ip=malicious_ip
```

24. Query to identify unusual login times:

```
sourcetype=access_* action=login
```

```
| eval hour=strftime(_time,"%H")
```

```
| stats count by user, hour
```

```
| where count < 3
```

25. Query to identify privilege escalation attempts on Linux systems:

```
sourcetype=linux_secure "sudo:"
```

```
| where user!="root" AND user!=""
```

26. Query to identify potential brute force attacks against a specific user:

```
sourcetype=access_* user=username AND action=failure  
| stats count by src_ip  
| where count >= 5
```

27. Query to identify unusual DNS requests:

```
sourcetype=dns  
| stats count by query  
| where count > 10
```

28. Query to identify potential spear-phishing attempts:

```
sourcetype=email  
| search "CEO" OR "CFO" OR "Finance" OR "Accounting" OR "Payment"
```

29. Query to identify potential malware infections:

```
sourcetype=access_* action=file_download  
| rex field=file_path ".*\.(?<extension>[^\.]*)"   
| search extension="exe" OR extension="dll"
```

30. Query to identify unusual user activity:

```
sourcetype=access_* action=purchase  
| stats count by user  
| where count > 100
```

31. Query to identify potential DDoS attacks:

```
sourcetype=network_traffic  
| stats sum(bytes) as total_bytes by src_ip  
| where total_bytes > 100000000
```

32. Query to identify potential ransomware activity:

```
sourcetype=access_* action=file_delete  
| rex field=file_path ".*\.(?<extension>[^\.]*)"   
| search extension="encrypted" OR extension="locked" OR extension="ransom"
```

33. Query to identify potential insider threats:

```
sourcetype=access_* action=file_upload  
| stats count by user, file_path  
| where count > 10
```


LIST OF SPLUNK QUERIES – SOC

34. Query to identify successful authentication attempts from unknown IP addresses:

```
sourcetype=access_* action=login  
| stats count by src_ip  
| where count >= 5 AND NOT src_ip IN (192.168.0.0/16, 10.0.0.0/8)
```

35. Query to identify potential brute force attacks on a specific service:

```
sourcetype=network_traffic service=ssh  
| stats count by src_ip  
| where count >= 10
```

36. Query to identify successful SSH logins from unusual countries:

```
sourcetype=access_* action=login service=ssh  
| iplocation src_ip  
| stats count by src_country  
| where count > 10 AND NOT src_country="United States"
```

37. Query to identify potential attempts to exploit known vulnerabilities:

```
sourcetype=access_* method=POST  
| rex field=_raw "(?<exploit>CVE-\d{4}-\d+)"  
| stats count by exploit  
| where count > 5
```

38. Query to identify potential brute force attacks on a specific user:

```
sourcetype=access_* user=username AND action=failure  
| stats count by src_ip  
| where count >= 5
```

39. Query to identify potential man-in-the-middle attacks:

```
sourcetype=network_traffic protocol=tcp  
| stats count by dest_ip  
| where count > 100
```

40. Query to identify potential data exfiltration:

```
sourcetype=access_* action=file_upload  
| stats count by user, file_path  
| where count > 10
```

41. Query to identify potential ransomware activity on Windows systems:

```
sourcetype=WinEventLog:Security EventCode=4663  
| rex field=Object_Name "\\.*\\\\(?!<filename>.+)"  
| rex field=filename ".*\\.(?!<extension>[^\.]+)"  
| search extension="encrypted" OR extension="locked" OR extension="ransom"
```

42. Query to identify unusual network traffic patterns:

```
sourcetype=network_traffic  
| stats count by dest_ip, dest_port  
| where count > 100 AND NOT dest_ip="192.168.0.1"
```

43. Query to identify potential brute force attacks on a specific protocol:

```
sourcetype=network_traffic protocol=http  
| stats count by src_ip  
| where count >= 50
```

44. Query to identify potential account takeover attempts:

```
sourcetype=access_* action=login  
| stats count by user  
| where count > 10
```

45. Query to identify potential DNS tunneling activity:

```
sourcetype=dns  
| stats count by query  
| where count > 5 AND NOT match(query, "\\.")
```

46. Query to identify potential SQL injection attempts on web servers:

```
sourcetype=access_* method=POST uri_path="*.php"  
| rex field=_raw "SELECT\s+(?!<query>[^\s;]+)"  
| eval query_length=length(query)  
| where query_length > 50 AND query_length < 100
```

47. Query to identify potential brute force attacks on a specific domain:

```
sourcetype=access_* host=example.com AND action=failure  
| stats count by src_ip  
| where count >= 10
```

48. Query to identify potential brute force attacks on a specific application:

```
sourcetype=access_* uri_path="/app/login" AND action=failure  
| stats count by src_ip  
| where count >= 5
```

49. Query to identify potential phishing attempts through email attachments:

```
sourcetype=email  
| search attachment="*.exe" OR attachment="*.zip"
```

50. Query to identify potential exploitation attempts on vulnerable services:

```
sourcetype=network_traffic  
| stats count by src_ip, dest_port  
| where count > 10 AND dest_port IN (22, 3389, 1433, 3306, 8080)
```

51. Query to identify potential reconnaissance activity:

```
sourcetype=access_* method=GET  
| stats count by uri_path  
| where count > 100
```

52. Query to identify potential cross-site scripting (XSS) attacks on web servers:

```
sourcetype=access_* method=POST uri_path="*.php"  
| rex field=_raw "document\.write\('(?'<payload>[^\']+')'\)"  
| search payload="<script>"
```

53. Query to identify potential privilege escalation attempts:

```
sourcetype=access_* action=privilege_escalation  
| stats count by user  
| where count > 5
```

54. Query to identify potential web application attacks:

```
sourcetype=access_* method=POST uri_path="*.php"  
| rex field=_raw "(?<attack>sql_injection|xss|csrf)"  
| stats count by attack  
| where count > 5
```

55. Query to identify potential lateral movement attempts:

```
sourcetype=network_traffic protocol=tcp dest_port=445  
| stats count by src_ip, dest_ip  
| where count > 10
```

LIST OF SPLUNK QUERIES – SOC

56. Query to identify potential unauthorized changes to critical files:

```
sourcetype=access_* action=file_write  
| search file_path="*/etc/*" OR file_path="*/var/*"
```

57. Query to identify potential port scanning activity:

```
sourcetype=network_traffic protocol=tcp  
| stats count by src_ip, dest_port  
| where count > 20 AND NOT dest_port IN (22, 3389, 1433, 3306, 8080)
```

58. Query to identify potential malicious PowerShell activity on Windows systems:

```
sourcetype=WinEventLog:Windows PowerShell EventCode=4104  
| search (New-Object System.Net.WebClient).DownloadString OR (Invoke-WebRequest -Uri)
```

59. Query to identify potential SQL injection attempts on web servers:

```
sourcetype=access_* method=POST uri_path="*.php"  
| rex field=_raw "SELECT\s+(?<query>[^;]+)"  
| eval query_length=length(query)  
| where query_length > 100 AND query_length < 200
```

60. Query to identify potential brute force attacks on a specific domain controller:

```
sourcetype=WinEventLog:Security EventCode=4625 domain_controller="DC01"  
| stats count by src_ip  
| where count >= 5
```

61. Query to identify potential DDoS attacks:

```
sourcetype=network_traffic  
| stats count by src_ip  
| where count > 1000
```

62. Query to identify potential web shell activity:

```
sourcetype=access_* action=command_execution  
| search (echo|print|printf)\s+(base64_decode|eval|gzinflate|str_rot13)
```

63. Query to identify potential brute force attacks on a specific network device:

```
sourcetype=cisco:asa  
| stats count by src_ip  
| where count >= 10
```

64. Query to identify potential privilege escalation attempts on Linux systems:

```
sourcetype=access_* action="sudo command"
| stats count by user
| where count >= 10
```

65. Query to identify potential DNS tunneling activity:

```
sourcetype=dns
| rex field=_raw "\d{1,3}\.\d{1,3}\.\d{1,3}\.\d{1,3}#(?<query>.+)\s+(\d+)\s+type:
(?<type>.+)\s+class: (?<class>.+)\s+[\d\s]+flags: (?<flags>.+)\s+;[\s\S]+response:\s+no error"
| search type="A" AND class="IN" AND flags="rd"
```

66. Query to identify potential lateral movement attempts using RDP:

```
sourcetype=WinEventLog:Security EventCode=4624 OR EventCode=4625
| search Logon_Type=10
```

67. Query to identify potential command and control (C2) traffic:

```
sourcetype=network_traffic
| stats count by dest_ip
| where count > 500 AND NOT dest_ip IN (192.168.0.0/16, 10.0.0.0/8)
```

68. Query to identify potential PowerShell Empire activity:

```
sourcetype=WinEventLog:Windows PowerShell
| search (powershell.exe -nop -w hidden -ep bypass -c) | (iex(new-object
net.webclient).downloadstring)
```

69. Query to identify potential ransomware activity:

```
sourcetype=access_* action=file_write
| search file_path="*.crypt" OR file_path="*.locky"
```

70. Query to identify potential malicious traffic from a specific IP address:

```
sourcetype=network_traffic src_ip=10.1.1.1
| stats count by dest_ip
| where count > 10
```

71. Query to identify potential brute force attacks on web applications:

```
sourcetype=access_* method=POST uri_path="*.php"
| stats count by src_ip
| where count >= 50
```

72. Query to identify potential unauthorized access attempts to sensitive files:

```
sourcetype=access_* action=file_read  
| search file_path="*/etc/shadow" OR file_path="*/etc/passwd"
```

73. Query to identify potential lateral movement attempts using SMB:

```
sourcetype=WinEventLog:Security EventCode=5140  
| search Object_Name="*\\ADMIN$" OR Object_Name="*\\C$"
```

74. Query to identify potential brute force attacks on SSH servers:

```
sourcetype=linux_secure action=invalid  
| stats count by src_ip  
| where count >= 10
```

75. Query to identify potential phishing attacks:

```
sourcetype=access_* method=POST uri_path="*.php"  
| search form_action="http://www.evilsite.com/login.php" AND (input_password=* OR  
input_password=*)
```

76. Query to identify potential command injection attempts on web servers:

```
sourcetype=access_* method=POST uri_path="*.php"  
| rex field=_raw "(?<command>cat|ls|dir)\s+(?<argument>[^;]+)"  
| where isnotnull(command) AND isnotnull(argument)
```

77. Query to identify potential lateral movement attempts using WinRM:

```
sourcetype=WinEventLog:Microsoft-Windows-WinRM/Operational EventCode=146  
| search "winrs: client" AND "is starting a command" AND NOT user="NETWORK SERVICE" AND  
NOT user="LocalSystem"
```

78. Query to identify potential brute force attacks on FTP servers:

```
sourcetype=access_* method=POST uri_path="*/wp-login.php"  
| stats count by src_ip  
| where count >= 20
```

79. Query to identify potential privilege escalation attempts on Windows systems:

```
sourcetype=WinEventLog:Security EventCode=4688  
| search (New_Process_Name="*\\runas.exe" OR New_Process_Name="*\\psexec.exe") AND  
NOT User="SYSTEM"
```

LIST OF SPLUNK QUERIES – SOC

80. Query to identify potential beaconing activity from a compromised host:

```
sourcetype=network_traffic src_ip=10.1.1.1  
| stats count by dest_port  
| where count > 1000
```

81. Query to identify potential brute force attacks on SSH servers (failed login attempts):

```
sourcetype=linux_secure action=failed  
| stats count by src_ip  
| where count >= 10
```

82. Query to identify potential data exfiltration attempts over HTTP:

```
sourcetype=access_* action=file_download  
| search uri_path="*.zip" OR uri_path="*.rar" OR uri_path="*.tgz" OR uri_path="*.tar.gz"
```

83. Query to identify potential lateral movement attempts using WMI:

```
sourcetype=WinEventLog:Security EventCode=5861  
| search (Operation="ExecQuery" AND QueryLanguage="WQL") OR (Operation="MethodCall"  
AND NOT MethodName="GetSecurityDescriptor" AND NOT  
MethodName="SetSecurityDescriptor")
```

84. Query to identify potential brute force attacks on MSSQL servers:

```
sourcetype=mssql_access action=failed  
| stats count by src_ip  
| where count >= 10
```

85. Query to identify potential privilege escalation attempts using PowerShell:

```
sourcetype=WinEventLog:Microsoft-Windows-PowerShell/Operational EventCode=400  
| search "PowerShell pipeline execution details" AND NOT "UserPrincipalName=SYSTEM@*"  
AND NOT "UserPrincipalName=NETWORK SERVICE@*"
```

86. Query to identify potential brute force attacks on email accounts:

```
sourcetype=exchangeops  
| stats count by src_ip  
| where count >= 10
```

87. Query to identify potential lateral movement attempts using RDP (successful logins):

```
sourcetype=WinEventLog:Security EventCode=4624  
| search Logon_Type=10
```

LIST OF SPLUNK QUERIES – SOC

88. Query to identify potential brute force attacks on MSSQL servers (successful logins):

```
sourcetype=mssql_access action=success  
| stats count by src_ip  
| where count >= 10
```

89. Query to identify potential data exfiltration attempts over FTP:

```
sourcetype=access_* action=file_upload  
| search uri_path="*/ftp" OR uri_path="*/sftp"
```

90. Query to identify potential lateral movement attempts using SMB (successful connections):

```
sourcetype=WinEventLog:Security EventCode=5140  
| search Object_Name="*\\ADMIN$" OR Object_Name="*\\C$"
```

91. Query to identify potential brute force attacks on RDP:

```
sourcetype=WinEventLog:Security EventCode=4625  
| search Logon_Type=10 AND Status="0xC000006D"
```

92. Query to identify potential brute force attacks on web applications:

```
sourcetype=access_* method=POST  
| stats count by src_ip, uri_path  
| where count >= 100
```

93. Query to identify potential lateral movement attempts using Remote Registry Service:

```
sourcetype=WinEventLog:Security EventCode=4663  
| search Object_Name="*\\REGISTRY\\MACHINE\\SOFTWARE" AND NOT User="SYSTEM" AND  
NOT User="NETWORK SERVICE" AND NOT User="LOCAL SERVICE"
```

94. Query to identify potential privilege escalation attempts on Linux systems (sudo usage):

```
sourcetype=linux_secure "sudo:"
```

95. Query to identify potential data exfiltration attempts over DNS:

```
sourcetype=dns  
| search query_type=A AND query != "*.google.com" AND query != "*.facebook.com" AND query  
!= "*.twitter.com" AND query != "*.microsoft.com"
```


LIST OF SPLUNK QUERIES – SOC

96. Query to identify potential lateral movement attempts using SMB (failed connections):

```
sourcetype=WinEventLog:Security EventCode=5152  
| search Object_Name="*\ADMIN$" OR Object_Name="*\C$" AND Status="0xC000006D"
```

97. Query to identify potential brute force attacks on MSSQL servers (failed logins):

```
sourcetype=mssql_access action=failed  
| stats count by src_ip  
| where count >= 10
```

98. Query to identify potential data exfiltration attempts over SMTP:

```
sourcetype=smtp action=send_message  
| search recipient!="*@gmail.com" AND recipient!="*@yahoo.com" AND  
recipient!="*@hotmail.com" AND recipient!="*@aol.com"
```

99. Query to identify potential lateral movement attempts using NetBIOS:

```
sourcetype=WinEventLog:Security EventCode=5719  
| search "No Domain Controller is available" OR "This computer was not able to set up a secure  
session with a domain controller"
```

100. Query to identify potential brute force attacks on Telnet servers:

```
sourcetype=access_* method=POST uri_path="*/telnet"  
| stats count by src_ip  
| where count >= 10
```

101. Query to identify potential data exfiltration attempts over FTP:

```
sourcetype=ftp action=putfile  
| stats count by src_ip  
| where count >= 10
```

102. Query to identify potential lateral movement attempts using WMI (failed connections):

```
sourcetype=WinEventLog:Security EventCode=5605  
| search Object_Name="*\ROOT\CIMV2" AND NOT User="SYSTEM"
```

103. Query to identify potential brute force attacks on SSH servers:

```
sourcetype=access_* method=POST uri_path="*/ssh"  
| stats count by src_ip  
| where count >= 10
```

LIST OF SPLUNK QUERIES – SOC

104. Query to identify potential privilege escalation attempts on Windows systems (services configuration changes):

```
sourcetype=WinEventLog:Security EventCode=4697 OR EventCode=7045  
| search Image_Path="*\\System32\\" AND NOT User="SYSTEM"
```

105. Query to identify potential brute force attacks on SNMP:

```
sourcetype=snmptrap  
| stats count by src_ip  
| where count >= 10
```

106. Query to identify potential data exfiltration attempts over HTTP:

```
sourcetype=access_* method=POST uri_path="/upload"  
| stats count by src_ip  
| where count >= 10
```

107. Query to identify potential lateral movement attempts using DCOM (failed connections):

```
sourcetype=WinEventLog:Security EventCode=10009  
| search "DCOM was unable to communicate with the computer" AND NOT User="SYSTEM"
```

108. Query to identify potential brute force attacks on MySQL servers:

```
sourcetype=mysql_access action=failed  
| stats count by src_ip  
| where count >= 10
```

109. Query to identify potential privilege escalation attempts on Windows systems (scheduled tasks creation):

```
sourcetype=WinEventLog:Security EventCode=4698  
| search "Task Scheduler service found a misconfiguration" AND NOT User="SYSTEM"
```

110. Query to identify potential data exfiltration attempts over HTTPS:

```
sourcetype=ssl method=POST  
| stats count by src_ip, dest_ip  
| where count >= 10
```