User Manual



F3

Faculty of Electrical Engineering Department of Mathematics

Manual for LATEX class ctuthesis

Tomáš Hejda et al.

Supervisor: Prof. Krutoš Spravedlivý

April 2015

Acknowledgements

The Author would like to thank Professor Jiri Novak for his thorough guidance and tutelage - it has been an honor working on this topic under his supervision.

Declaration

I declare that this work is all my own work and I have cited all the sources I have used in the bibliography.

In Prague, 16. April 2015

Prohlašuji, že jsem předloženou práci vypracoval samostatně, a že jsem uvedl veškerou použitou literaturu.

V Praze, 16. April 2015

Abstract

In this dissertation we will survey the current methods of measuring the progression of home grade beer fermentation processes. In addition, we will implement an automatic solution to monitor the gradual accumulation of ethanol in the process of beer fermentation.

Keywords: manual, degree project,

 $E\!\!\!/T\!\!\!\!/E\!X$

Supervisor: Prof. Krutoš Spravedlivý

Abstrakt

Abstract in Czech

Klíčová slova: manuál, závěrečnná

práce, LATEX

Překlad názvu: Manuál ke třídě

ctuthesis pro \LaTeX

Contents

1 Introduction	1
Why was this project created	1
2 User Guide	3
2.1 Installing the class	3
2.2 Minimal example	4
2.3 Setting up the class	5
2.3.1 Options to \backslash documentclass	5
2.3.2 Parameters to \land ctusetup	6
2.3.3 Text environments used in the	
preamble	8
2.4 Various parts of the document	8
2.4.1 Frontmatter	8
2.4.2 Mainmatter and backmatter.	
Sectioning	8
2.4.3 Bibliography	9
2.4.4 Index	9
2.4.5 List of notation. Nomenclature	10
2.4.6 Floating objects: Figures and	
tables	10
2.4.7 Mathematics	11
2.4.8 Colors	11
2.5 Features not described in this	
manual. Troubleshooting	12
3 Creating and modifying	
templates	13

Figures

Tables

2.1 The files of the class ctuthesis. . . $\,3\,$

Chapter 1

Introduction

In this dissertation we will provide a brief overview of the way beer is made by home brewers today - we will follow the process from grains to beer and observe a few issues with the common way this process is done today. Then, we will explore the various ways by which ethanol is currently being measured in home-grade brewing processes and evaluate the advantages and disadvantages of each method.

We will examine the different ways ethanol is measured in liquids, and discuss why and how the method suggested by this paper is the most suitable. We will then establish and justify an automatic, low cost solution to the issue of accurate and safe ethanol measurement, followed by rigorous testing.

- basic user guide;
- reference manual;
- guide for template authors.

Students and other 'users' of the class should carefully read the basic user guide (Chapter 2), and visit the reference when needed (Chapter ??).

Why was this project created

The ctuthesis LATEX template was written by Tomáš Hejda because there is wider demand for it at CTU. The aim has been to provide a LATEX tool to students and their advisors for writing qualification theses (e.g., bachelor, master, Ph.D.). LATEX as a tool for professional typesetting has had a significant group of users at CTU. The ctuthesis template can be selected and used voluntarily, i.e., if the student and the advisor agree on this.

There were several more local attempts in creating LATEX templates for qualification theses at CTU. Let us give only two examples. First, the package ctu, https://github.com/kyrcore/ctu-latex¹. Its development

¹All URLs in this section were retrived on March 15, 2015.

1. Introduction

seems to be interrupted since 2013. Second, the package CMPthesis written and maintained up to now by Vít Zýka, which is provided only internally at http://www-cmp.felk.cvut.cz/proceedings/TeX/texmf-cmp/tex/latex/cmpthesis/cmpthesis.pdf.

Petr Olšák from Department of Mathematics FEE came with the initiative to create a TEX package for qualification theses and offered it to the whole CTU in 2013, see http://petr.olsak.net/ctustyle.html (in Czech). The package is less spread because there are fewer TEX users than LATEX users at CTU.

The ctuthesis IATEX package, described in this document, was inspired by P. Olšák's TEX package. The aim is to preserve very similar graphical look. T. Hejda volunteered to write a IATEX package with similar properties as P. Olšák's ctustyle package. P. Olšák has supported this initiative.

The small team around the ctuthesis package (Tomáš Hejda, Václav Hlaváč, Petr Olšák) has attempted persuading CTU leaders to support this package and help offering it at university-wide scale for the voluntary use. As many students and supervisors use other publishing/typesetting tools, such as Microsoft Word, the mentioned team encourages someone to write a template, maybe with similar outer look to P. Olšák's TEX template ctustyle and T. Hejda's LATEX template ctuthesis.

Chapter 2 User Guide

2.1 Installing the class

The class comprises the files listed in Table 2.1. The class is build over the LATEX3 bundle, which is a project under development and new programming features are added regularly. This means that the class works as is only with TEX Live 2014. If you have an eariler version of LATEX distribution, you have basically two options:

File name	Description
ctuthesis.cls	Class file itself
ctu_logo_blue.pdf	Logo of the university; this file is subject to different license and copyright than the rest of the class files
ctuthesis.ist	Nicely loooking style for makeindex
latex3-tl2014.zip	ZIP file containing the "good" version of \LaTeX
ctuman.pdf	This manual
ctuman-*.tex	Source code to this manual
ctuth-core.tex	Core definitions for the class; users do not need to ever load this file manually
ctuth-pkg.tex	Package loading code for the class; users do not need to ever load this file manually
ctuth-names.tex	Language-dependent part of the class; users should not need to modify this file or load it manually
ctuth-templates.tex	Templates for various parts of the document; users may look inside this file and see how things are done; this is discussed in more detail in Chapter 3

Table 2.1: The files of the class ctuthesis.

1. Install TEX Live 2014 or newer; it is not difficult and it will save you all the troubles. The installing guide is on TUG's website at http://tug.org/texlive/.

2. Install just the new version of LATEX3. This is tested to work on TEX Live from version 2010. The bundle is attached as a ZIP file, it is sufficient to extract all the files in the working directory.

2.2 Minimal example

The minimal example of a Bachelor project at the Nuclear Faculty looks like this:

```
\documentclass{ctuthesis}
\ctusetup{
    xdoctype = B,
    xfaculty = F4,
   mainlanguage = english,
    titlelanguage = english,
    title-english = {Planting Uranium},
    title-czech = {Sázení uranu},
    department-english = {Department of Mathematics},
    author = {Lolek Pilný},
    supervisor = {Prof. Krutoš Spravedlivý, CSc.},
    supervisor-address = {Pěstitelský ústav,\\ Zářivá 232,\\
      12000 Praha 2},
    month = 5,
    year = 2330,
}
\ctuprocess
\begin{abstract-english}
We develop \ldots
\end{abstract-english}
\begin{abstract-czech}
Rozvíjíme \ldots
\end{abstract-czech}
\begin{document}
\maketitle
\chapter{Introduction}
```

```
Foo bar
\chapter{Conclusion}
Lorep ipsum \cite{doe}
\begin{thebibliography}{1}
\bibitem{doe} J. Doe. \emph{Book on foobar.} Publisher X,
2300.
\end{thebibliography}
\end{document}
```

At the first sight, it may look complicated, but the basic structure is pretty simple:

```
\documentclass{ctuthesis}
\ctusetup{
    < key = value settings >
\ctuprocess
< abstracts and other frontmatter text here,
      and standard preamble contents >
\begin{document}
\maketitle
< the whole text here >
\end{document}
```

2.3 **Setting up the class**

This section lists all various settings that can be made to the class. The ones marked '™' are always mandatory. The ones marked '™' are mandatory in almost all cases, with some small exceptions. For most of them, no errors are issued if they are missing, though.

2.3.1 Options to \documentclass

The class ctuthesis itself takes an optional argument draft that sets some documentclass draft options (the ones common in LATEX). It also takes the option oneside

draft oneside

which switches to one-sided mode; however, we strongly advice against using this option.

2.3.2 Parameters to \ctusetup

ctusetup The parameters can be diveded into several groups.

Text fields. Some of the fields — like the theses title — are language-dependent. They are marked key-<lamp> below, and it means that multiple keys exist: key-english, key-czech and key-slovak.

author — author's name, including titles.

 $\verb"supervisor" - supervisor's name, including titles.$

supervisor-address — supervisor's affiliation and address; use \\ to format it with linebreaks.

supervisor supervisor-specialist — supervisor-specialist's name, including titles.

year wear, wmonth, day — numerical values of the date of theses publishing.

month

day ■wtitle-<lame> — title of the thesis.

subtitle-<lang> subtitle-<lang> — subtitle.

title-<lang>

university-<lames> university-<lames> university (is preset for CTU).

university-endl-<lamp> — name of the university broken in 4 lines using \\.

faculty-<lamp> — name of the faculty (set up automatically, see xfaculty below).

a facultynum — standard number of the faculty (set up automatically, see xfaculty below).

department-<lamp> — name of the department.

General fields.

- mainlanguage main language of the thesis; the choices are czech, mainlanguage english and slovak.
- titlelanguage language in which the title pages are typeset (defaults titlelanguage to mainlanguage).
- secondlanguage language of the second abstract (set up automatically secondlanguage so that two abstracts appear: one in English and one in Czech, unless the thesis is in Slovakian, in which case the two abstracts are in English and in Slovakian).
- otherlanguages allows more languages to be loaded by babel pack- otherlanguages age, accepts a comma-separated list.
- **xfaculty** takes values F1, F2, ..., F8 and sets up the faculty name xfaculty and number automatically.
- xdoctype takes values B (bachelor), M (master) or D (dissertation) and xdoctype sets up the document type automatically; for non-thesis-like documents, use doctype-<lamp>.
- Specification-file the path to the specification file (usually something like zadani.pdf, the current directory is searched for the file of course).
- front-specification if set to true, the specification will appear just front-specification after the titlepage (defaults to false).
- front-list-of-figures, front-list-of-tables says whether the list of figures/tables will be set in the frontmatter (default to true) front-list-of-tables
- monochrome switches to optimized monochrome setup, in case the monochrome work will not be printed in colour.
- savetoner disables background and other too dark things to save savetoner toner while printing drafts.

Default package loading. The class attempts to set up some packages nicely if the user wants to use them. So for instance, the package listings can be pre-set to include the blue background of all listings. In order to leave the user the chance to mess with things "his own way", options are offered to enable or disable certain packages. The format of the option name is always pkg-<packagename> and it accepts either true or false

pkg-hyperref (default: true) — sets up all the fields of the PDF pkg-hyperref document.

pkg-listings

ctulst

pkg-listings (default: false) — sets up \ttfamily font for all listings, and adds a background to all display listings. For inline listings, this is a bit more complicated; we rather implemented a new macro \ctulst(color)[settings]!<text>! that behaves exactly like \lstinline!<text>!, but applies the background; the color is an optional argument (in parentheses ()) and defaults to the blue background color seen in this manual. Any printable symbol but one of [({} can be used in place of !. Using none makes the background transparent. The default background for inline listings can be changed by \ctusetup{ ctulstbg = <color> }.

pkg-amsthm

pkg-amsthm (default: true) — sets up nicely the basic styles for theorems, but does not set up the theorem environment themselves. More information is in Section 2.4.7

pkg-biblatex

pkg-biblatex (default: false) — more details in Section ??.

2.3.3 Text environments used in the preamble

There is a small number of environments that should be used in the preamble in order to set up various text fields, mostly used in the front matter.

 ${\sf abstract}{ ext{-}}{\sf <}{\sf lang}{ ext{>}}$

■ ⋈{abstract-<lang>} — abstract; the language has to be always specified.

thanks

■ ► {thanks} — acknowledgements; can be used for both personal and grant ackowledgements.

declaration

■ [declaration] — students are oblidged to declare that the works is their works, and maybe some more things, depending on the faculty's or department's regulations.

2.4 Various parts of the document

2.4.1 Frontmatter

maketitle

Typically, the frontmatter will be only one command: \maketitle. This typesets the titlepage, the acknowledgements, the declaration, the two abstracts, the table of contents, and possibly the lists of figures and tables. Afterwards, it immediately switches to \mainmatter.

frontmatter

mainmatter

Another option, which should be used only in special cases, is to start the frontmatter with \frontmatter, include whatever material should be there and close it by \mainmatter. This is discussed in detail in Chapter ??.

2.4.2 Mainmatter and backmatter. Sectioning

Standard sectioning commands are suported, they are \chapter, \section,

chapter section subsection subsubsection paragraph subparagraph part \subsection, \subsubsection. These ought to follow the hierarchy from top to bottom. There is also \paragraph and \subparagraph which can be used as lowest-level sectioning commands. Long works can be divided into parts using \part; its numbering is independent of the other ones. All these commands take standard optional argument and star; however, we advice against using starred sections.

The appendices are introduced by command \appendix. Then, each appendix is a chapter, so the standard \chapter command ought to be used. In appendix, even chapters started by \chapter* such as the bibliography and the index are numbered. (In a document without appendices, these should be unnumbered. Once appendices are used, all indexes and alike should be standard numbered appendices.) For unnumbered appendices, \chapter** can be used.

If the document is divided into parts, the appendices are introduced by a part-like title "Appendices", both in the document and in the table of contents. This can be suppressed by using \appendix* (keeps the line in the table of contents) or \appendix**.

appendix*

appendix**

If the project specification is to be included as an appendix, it can be done specification as chapter by \ctutemplate{specification as chapter}.

There is no true backmatter behaviour defined in the class. The only thing that would belong to the backmatter is the colophon ('tiráž'). Users are advised to use \cleardoublepage* \thispagestyle{empty} and then typeset the colophon to their liking.

2.4.3 **Bibliography**

There are three ways how to include the bibliography:

- 1. Using Biblatex. In that case, setting up pkg-biblatex = true is recommended. The bibliography is then included using \addbibresource and \printbibliography.
- 2. Using BibTeX. No special setting is needed, and the bibliography is included using \bibliographystyle and \bibliography.
- 3. By direct input. The standard environment {thebibliography} can be used for this.

We kindly ask users to consult the manuals to the specific packages for their usage.

2.4.4 Index

To generate the index, use pkg-makeidx = true, and put \printindex where the index should appear. We provide an in-house style for the index called ctuthesis.ist. The index generation is dependent on calling the external tool makeindex, in a similar way in which the bibliography generation depends on bibtex or biber. The proper way how to call this tool is the following:

makeidx makeindex printindex

```
makeindex -s ctuthesis.ist <filename>
```

ctuthesis.ist where <filename> is the root name of your main project file (without .tex).

2.4.5 List of notation. Nomenclature

We do not preset any special environment for typesetting appendices such as list of notation or nomenclature. One of the possible standard way how to do it is with the help of the packages tabularx, array and booktabs as follows:

tabularx array booktabs

```
\documentclass{ctuthesis}
\ctusetup{ mainlanguage = english }
\ctuprocess
\usepackage{tabularx, array, booktabs}
\begin{document}

\appendix
\chapter*{List of Notation}

\noindent
\begin{tabularx}{\linewidth}
    { 1 >{\raggedright\arraybackslash}X }
\bfseries Symbol & \bfseries Meaning \\Midrule
$\alpha$ & The angle of attack \\
$\mathbb{R}$$ & The real numbers \\
\end{tabularx}
\end{document}
```

Itxtable In the case the notation is longer than one page, the package ltxtable or ltablex can be used.

2.4.6 Floating objects: Figures and tables

figure Floats are input either as {figure} or {table} environment. All floats are table automatically typeset centered, so a typical code for a figure is the following:

```
\begin{figure}
\includegraphics[width=0.8\linewidth]{mygraphicfile.pdf}
\caption{We depict a foo-bar here.}
\label{fig:foobar}
\end{figure}
```

For a table, it is the following:

```
\begin{table}
\begin{ctucolortab}
\begin{tabular}{cc}
```

```
\bfseries Foo & \bfseries Bar \\Midrule
foo1 & bar1 \\
foo2 & bar2
\end{tabular}
\end{ctucolortab}
\caption{Table of foo-bar.}
\label{tab:foobar}
\end{table}
```

Note the usage of the environment {ctucolortab} to make the table get a blue background, and the usage of \Midrule to get a horizontal line in the table (a thinner line can be obtained using \midrule). Also note the deliberate absence of verical rules.

ctucolortab Midrule midrule

2.4.7 Mathematics

All standard concepts for typesetting mathematics are working as in any other LATEX class. We only emphasize how the class behaves in relation to theorem-like environments and proofs. The default behaviour is that the package amsthm is loaded and theorem styles plain, definition and note. Theorems (plain style) are by default slanted rather than italic, should italic theorems be preferred, use plainit. However, no theorem-like environments are predefined, everybody can do this to their liking. The preamble declarations could look like this:

The environment {proof} is provided by default. All theorem handling can be disabled by \ctusetup{ pkg-amsthm = false }.

2.4.8 Colors

The class uses internally many named colors. For the general use, two non-standard colors are provided:

ctublue ctublue;

ctublue

2. User Guide • • • •

ctulightblue

ctulightblue ctulightblue.

The colors are used for the headers, rules in the titles, title texts, backgrounds for listings and tables etc.

2.5 Features not described in this manual. Troubleshooting

I may happen that some of the features of the class are not described in this manual. If the users struggle with anything, they can contact the class authors at tohecz@gmail.com or via the GitHub repository github.com/tohecz/ctuthesis.

Chapter 3

Creating and modifying templates

We apologize, this chapter of the manual is still under construction.