Project: Project Startup and initiation

Project ID: a7053649-7458-4e86-8905-1fef8100cebb

Launch | Implementation

STAGE PROJECT

Click to generate mission and spawn agents

PROJECT DESCRIPTION

This project is about building the folders and a small scription file in each folder with what it is to contain. Each folder should also have place older files created with a descriptor in each file called "Future {purpose of file} place holder.". IN docs folder we should also build an index after this is all done, The first Readme.md and REquirements.txt file should also be created in root.

EDIT

ORCHESTRATOR CREATED MISSION

Mission will appear after staging

Click "Stage Project" to begin orchestrator mission generation

AGENT TEAM 1 AGENT

Orchestrator

Agent ID
`1cad97a1-ed40-4c16-89ad-72ccb4c4508b`

Role/Mission:
No mission assigned

EDIT MISSION

WE ARE MOVING AWAY FROM THIS

SLIDE 1a – Prestaging – Launch Tab

Before Stage project button is pressed and prompt is copied, and before user has pasted in CLI tool to launch orchestrator

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Stage project

Waiting

Launch Jobs

Project Description

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla tincidunt consequat dolor. Praesent sed tempor risus, vitae convallis sapien. Aenean accumsan quis lorem vitae eleifend. Vestibulum sagittis ipsum nec mauris consectetur, commodo posuere libero consectetur.

Donec eget tempor nibh. Fusce vehicula ultrices vehicula. Donec consequat, purus vitae vehicula placerat, erat velit pharetra mauris, eu vestibulum tellus sem at massa. Pellentesque a euismod tortor. Maecenas pretium ultrices rutrum. Cras bibendum, lorem sit amet euismod elementum, quam velit lobortis ex, a commodo sem neque in turpis.

Proin a massa eget sapien sagittis convallis. Suspendisse commodo elit quis arcu dictum porta. Sed consequat ullamcorper eros, id……..

Orchestrator Generated Mission

Default agent

Or Orchestrator

Agent Team

SLIDE 1b – Launch Tab Elements

Tabbed system, can be navigated at any stage, but will show empty implement page layout I user prematurely navigates there, no agents, no activation buttons if they go there

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Stage project

Waiting

Launch Jobs

Project Description

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla tincidunt consequat dolor. Praesent sed tempor risus, vitae convallis sapien. Aenean accumsan quis lorem vitae eleifend. Vestibulum sagittis ipsum nec mauris consectetur, commodo posuere libero consectetur.

Donec eget tempor nibh. Fusce vehicula ultrices vehicula. Donec consequat, purus vitae vehicula placerat, erat velit pharetra mauris, eu vestibulum tellus sem at massa. Pellentesque a euismod tortor. Maecenas pretium ultrices rutrum. Cras bibendum, lorem sit amet euismod elementum, quam velit lobortis ex, a commodo sem neque in turpis.

Proin a massa eget sapien sagittis convallis. Suspendisse commodo elit quis arcu dictum porta. Sed consequat ullamcorper eros, id……..

Orchestrator Generated Mission

Default agent

Or Orchestrator

Agent Team

Project description from ‘active’ project in DB

No mission icon

Sleeping giljo avatar

SLIDE 1c – Implementation Tab. Elements

Navigation is enabled between tabs note faded ‘Launch Tab’

This is the view if navigated before ‘stage project’ is executed

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read

Please Stage Project First

Message Orchestrator | Broadcast

Inactive elements, note inactive color

SLIDE 1d – Pre stage elements

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Stage project

Waiting

Launch Jobs

Project Description

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla tincidunt consequat dolor. Praesent sed tempor risus, vitae convallis sapien. Aenean accumsan quis lorem vitae eleifend. Vestibulum sagittis ipsum nec mauris consectetur, commodo posuere libero consectetur.

Donec eget tempor nibh. Fusce vehicula ultrices vehicula. Donec consequat, purus vitae vehicula placerat, erat velit pharetra mauris, eu vestibulum tellus sem at massa. Pellentesque a euismod tortor. Maecenas pretium ultrices rutrum. Cras bibendum, lorem sit amet euismod elementum, quam velit lobortis ex, a commodo sem neque in turpis.

Proin a massa eget sapien sagittis convallis. Suspendisse commodo elit quis arcu dictum porta. Sed consequat ullamcorper eros, id……..

Orchestrator Generated Mission

Default agent

Or Orchestrator

Agent Team

Stage Job is ready

Orchestrator is default at the ready

Launch jobs is inactive

Info button shows un-editable agent template

Is editable

Scrollable

SLIDE 1e – Launch Tab Elements

Uses Presses ‘stage project’ and gets a prompt to clipboard, user pastes this in agent window on CLI tool

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Stage project

Waiting

Launch Jobs

Project Description

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla tincidunt consequat dolor. Praesent sed tempor risus, vitae convallis sapien. Aenean accumsan quis lorem vitae eleifend. Vestibulum sagittis ipsum nec mauris consectetur, commodo posuere libero consectetur.

Donec eget tempor nibh. Fusce vehicula ultrices vehicula. Donec consequat, purus vitae vehicula placerat, erat velit pharetra mauris, eu vestibulum tellus sem at massa. Pellentesque a euismod tortor. Maecenas pretium ultrices rutrum. Cras bibendum, lorem sit amet euismod elementum, quam velit lobortis ex, a commodo sem neque in turpis.

Proin a massa eget sapien sagittis convallis. Suspendisse commodo elit quis arcu dictum porta. Sed consequat ullamcorper eros, id……..

Orchestrator Generated Mission

Default agent

Or Orchestrator

Agent Team

SLIDE 2a – Orchestrator working elements.

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Stage project

Launch Jobs

Working

Project Description

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla tincidunt consequat dolor. Praesent sed tempor risus, vitae convallis sapien. Aenean accumsan quis lorem vitae eleifend. Vestibulum sagittis ipsum nec mauris consectetur, commodo posuere libero consectetur.

Donec eget tempor nibh. Fusce vehicula ultrices vehicula. Donec consequat, purus vitae vehicula placerat, erat velit pharetra mauris, eu vestibulum tellus sem at massa. Pellentesque a euismod tortor. Maecenas pretium ultrices rutrum. Cras bibendum, lorem sit amet euismod elementum, quam velit lobortis ex, a commodo sem neque in turpis.

Proin a massa eget sapien sagittis convallis. Suspendisse commodo elit quis arcu dictum porta. Sed consequat ullamcorper eros, id……..

Orchestrator Generated Mission

Aliquam vulputate elit vel enim tempus placerat. Cras sollicitudin libero ut ligula aliquam, sit amet molestie lectus consequat. Phasellus pretium est et fermentum faucibus. Donec tempor leo vitae pulvinar fermentum. Nulla facilisi. Duis vitae ligula eget massa varius convallis eget id ante. In fringilla neque vel libero fermentum, et interdum neque lacinia. Vestibulum id laoreet massa, nec dignissim mi. Proin hendrerit nec ex ac feugiat. Integer elementum mauris ut augue cursus pharetra. Vestibulum id laoreet massa, nec dignissim mi. Proin hendrerit nec ex ac feugiat. Integer elementum mauris ut augue cursus pharetra.

Sed id risus ut lorem aucto……

Default agent

Or Orchestrator

Agent Team

Orchestrator Is working, button inactive

Orchestrator fills mission

Launch jobs is inactive

Inactive during working phase

Spinner, until agents populate

SLIDE 2b – Orchestrator finished elements.

Project:
{project_name}
Project ID: {full_UUID}

Launch done, button inactive

Orchestrator has filled mission & assigned agents

Launch jobs is now active

Info button shows un-editable agent template

Status change

Launch | Implement

Stage project

Completed!

Launch Jobs

Project Description

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla tincidunt consequat dolor. Praesent sed tempor risus, vitae convallis sapien. Aenean accumsan quis lorem vitae eleifend. Vestibulum sagittis ipsum nec mauris consectetur, commodo posuere libero consectetur.

Donec eget tempor nibh. Fusce vehicula ultrices vehicula. Donec consequat, purus vitae vehicula placerat, erat velit pharetra mauris, eu vestibulum tellus sem at massa. Pellentesque a euismod tortor. Maecenas pretium ultrices rutrum. Cras bibendum, lorem sit amet euismod elementum, quam velit lobortis ex, a commodo sem neque in turpis.

Proin a massa eget sapien sagittis convallis. Suspendisse commodo elit quis arcu dictum porta. Sed consequat ullamcorper eros, id……..

Orchestrator Generated Mission

Aliquam vulputate elit vel enim tempus placerat. Cras sollicitudin libero ut ligula aliquam, sit amet molestie lectus consequat. Phasellus pretium est et fermentum faucibus. Donec tempor leo vitae pulvinar fermentum. Nulla facilisi. Duis vitae ligula eget massa varius convallis eget id ante. In fringilla neque vel libero fermentum, et interdum neque lacinia. Vestibulum id laoreet massa, nec dignissim mi. Proin hendrerit nec ex ac feugiat. Integer elementum mauris ut augue cursus pharetra. Vestibulum id laoreet massa, nec dignissim mi. Proin hendrerit nec ex ac feugiat. Integer elementum mauris ut augue cursus pharetra.

Sed id risus ut lorem aucto……

Default agent

Or Orchestrator

Agent Team

A Analyzer

Im Implementor

T Tester

Agent template viewable

Is editable

SLIDE 2c – Orchestrator finished elements.

User presses ‘Launch Jobs’ and the tab switches and implement page it filled out see slide 4

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Stage project

Completed!

Launch Jobs

Project Description

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nulla tincidunt consequat dolor. Praesent sed tempor risus, vitae convallis sapien. Aenean accumsan quis lorem vitae eleifend. Vestibulum sagittis ipsum nec mauris consectetur, commodo posuere libero consectetur.

Donec eget tempor nibh. Fusce vehicula ultrices vehicula. Donec consequat, purus vitae vehicula placerat, erat velit pharetra mauris, eu vestibulum tellus sem at massa. Pellentesque a euismod tortor. Maecenas pretium ultrices rutrum. Cras bibendum, lorem sit amet euismod elementum, quam velit lobortis ex, a commodo sem neque in turpis.

Proin a massa eget sapien sagittis convallis. Suspendisse commodo elit quis arcu dictum porta. Sed consequat ullamcorper eros, id……..

Orchestrator Generated Mission

Aliquam vulputate elit vel enim tempus placerat. Cras sollicitudin libero ut ligula aliquam, sit amet molestie lectus consequat. Phasellus pretium est et fermentum faucibus. Donec tempor leo vitae pulvinar fermentum. Nulla facilisi. Duis vitae ligula eget massa varius convallis eget id ante. In fringilla neque vel libero fermentum, et interdum neque lacinia. Vestibulum id laoreet massa, nec dignissim mi. Proin hendrerit nec ex ac feugiat. Integer elementum mauris ut augue cursus pharetra. Vestibulum id laoreet massa, nec dignissim mi. Proin hendrerit nec ex ac feugiat. Integer elementum mauris ut augue cursus pharetra.

Sed id risus ut lorem aucto……

Default agent

Or Orchestrator

Agent Team

A Analyzer

Im Implementor

T Tester

SLIDE 3a – Implementation Tab. Elements

STATUS BOARD Variant MVP

Implement tab is ready and Launch is faded

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Waiting.*			4	1	
An	Analyzer	{Agent UUID full ID}	*Waiting.*				1	
Im	Implementor	{Agent UUID full ID}	*Waiting.*				1	
Te	Tester	{Agent UUID full ID}	*Waiting.*				1	

Message Orchestrator | Broadcast

CLAUDE CODE CLI MODE

SLIDE 3b – Implementation Tab.

STATUS BOARD Variant MVP

Starting state Claude Code CLI toggle on

Only one terminal, so only one trigger prompt for orchestrator

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Waiting.*			4	1	
An	Analyzer	{Agent UUID full ID}	*Waiting.*				1	
Im	Implementor	{Agent UUID full ID}	*Waiting.*				1	
Te	Tester	{Agent UUID full ID}	*Waiting.*				1	

Message Orchestrator | Broadcast

CLAUDE CODE CLI MODE

SLIDE 3c – Implementation Tab.

STATUS BOARD Variant MVP

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Waiting.*			4	1	
An	Analyzer	{Agent UUID full ID}	*Waiting.*				1	
Im	Implementor	{Agent UUID full ID}	*Waiting.*				1	
Te	Tester	{Agent UUID full ID}	*Waiting.*				1	

Message Orchestrator | Broadcast

CLAUDE CODE CLI MODE

Rest of agents are subagents in Claude code CLI buttons inactive

SLIDE 3d – Implementation Tab.

STATUS BOARD Variant MVP

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or Orchestrator	{Agent UUID full ID}	*Waiting.*			4	1	
An Analyzer	{Agent UUID full ID}	*Waiting.*				1	
Im Implementor	{Agent UUID full ID}	*Waiting.*				1	
Te Tester	{Agent UUID full ID}	*Waiting.*				1	

Message Orchestrator | Broadcast | |

CLAUDE CODE CLI MODE

From staging orchestrator has sent missions to the message system for all agents, they are now waiting. (including orchestrator sending one to itself)

SLIDE 3e – Implementation Tab.

STATUS BOARD Variant MVP

User Copies start prompt for orchestrator to clip board for user to paste into terminal to start

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Waiting.*			4	1	
An	Analyzer	{Agent UUID full ID}	*Waiting.*				1	
Im	Implementor	{Agent UUID full ID}	*Waiting.*				1	
Te	Tester	{Agent UUID full ID}	*Waiting.*				1	

Message Orchestrator | Broadcast

CLAUDE CODE CLI MODE

SLIDE 3f – Implementation Tab. Elements

Orchestrator starts working, Note!! Needs new agent reporting status modes, does not exist in code

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Working.*	✓	✓	7		1
An	Analyzer	{Agent UUID full ID}	*Waiting.*				2	
Im	Implementor	{Agent UUID full ID}	*Waiting.*				2	
Te	Tester	{Agent UUID full ID}	*Waiting.*				3	

Message Orchestrator | Broadcast

Orchestrator read its mission message

CLAUDE CODE CLI MODE

SLIDE 3g – Implementation Tab. Elements

Orchestrator may have sent messages, (speculative as an example)

reuse here means prompt has been copied and thus 'used' but can be copied again

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Working.*	✓	✓	7		1
An	Analyzer	{Agent UUID full ID}	*Working.*	✓	✓		1	1
Im	Implementor	{Agent UUID full ID}	*Working.*	✓	✓		1	1
Te	Tester	{Agent UUID full ID}	*Working.*	✓	✓		1	1

Message Orchestrator | Broadcast

All agents have read their mission messages

CLAUDE CODE CLI MODE

SLIDE 3h – Implementation Tab. Elements

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or Orchestrator	{Agent UUID full ID}	*Working.*	✓	✓	7		1
An Analyzer	{Agent UUID full ID}	*Working.*	✓	✓		1	1
Im Implementor	{Agent UUID full ID}	*Working.*	✓	✓		1	1
Te Tester	{Agent UUID full ID}	*Working.*	✓	✓		1	1

Message field

Message Orchestrator | Broadcast | |

Send message

Message to orchestrator or broadcast user option

CLAUDE CODE CLI MODE

SLIDE 3i – Implementation Tab. Elements

This board just shows over time what a message board could look like with the various elements

View this agent's message history, including broadcast messages, sent (direct to another agent or broadcast), received, ack,

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Waiting.*	✓	✓	7		1
An	Analyzer	{Agent UUID full ID}	*Working …*	✓			1	1
Im	Implementor	{Agent UUID full ID}	*Completed.*	✓	✓		1	1
Te	Tester	{Agent UUID full ID}	*Waiting.*				1	1

Message Orchestrator | Broadcast

CLAUDE CODE CLI MODE

SLIDE 4a – Implementation Tab. Elements

STATUS BOARD Variant MVP

Implement tab is ready and Launch is faded

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Waiting.*			4	1	
An	Analyzer	{Agent UUID full ID}	*Waiting.*				1	
Im	Implementor	{Agent UUID full ID}	*Waiting.*				1	
Te	Tester	{Agent UUID full ID}	*Waiting.*				1	

Message Orchestrator | Broadcast

General CLI MODE
(individual terminals for agents

SLIDE 4b – Implementation Tab.

STATUS BOARD Variant MVP

Starting state Claude Code CLI toggle OFF

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Waiting.*			4	1	
An	Analyzer	{Agent UUID full ID}	*Waiting.*				1	
Im	Implementor	{Agent UUID full ID}	*Waiting.*				1	
Te	Tester	{Agent UUID full ID}	*Waiting.*				1	

Message Orchestrator | Broadcast | |

General CLI MODE
(individual terminals for agents

SLIDE 4c – Implementation Tab.

STATUS BOARD Variant MVP

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Waiting.*			4	1	
An	Analyzer	{Agent UUID full ID}	*Waiting.*				1	
Im	Implementor	{Agent UUID full ID}	*Waiting.*				1	
Te	Tester	{Agent UUID full ID}	*Waiting.*				1	

Message Orchestrator | Broadcast | |

General CLI MODE
(individual terminals for agents

From staging orchestrator has sent missions to the message system for all agents, they are now waiting. (including orchestrator sending one to itself)

SLIDE 4d – Implementation Tab.

STATUS BOARD Variant MVP

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Waiting.*			4	1	
An	Analyzer	{Agent UUID full ID}	*Waiting.*				1	
Im	Implementor	{Agent UUID full ID}	*Waiting.*				1	
Te	Tester	{Agent UUID full ID}	*Waiting.*				1	

Message Orchestrator | Broadcast | |

General CLI MODE
(individual terminals for agents

In General CLI Mode each agent needs a prompt for its individual terminal CLI so all buttons have unique prompts to get the agents going

SLIDE 4e – Implementation Tab.

STATUS BOARD Variant MVP

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Waiting.*			4	1	
An	Analyzer	{Agent UUID full ID}	*Waiting.*				1	
Im	Implementor	{Agent UUID full ID}	*Waiting.*				1	
Te	Tester	{Agent UUID full ID}	*Waiting.*				1	

Message Orchestrator | Broadcast | |

General CLI MODE
(individual terminals for agents

User copies and pastes each prompt in each agent's terminal window, some agents may have instructions to wait for another gent to finish, this will require user intervention to retrigger agent

SLIDE 4f – Implementation Tab. Elements

All agents start working, Note!! Needs new agent reporting status modes, does not exist in code

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or Orchestrator	{Agent UUID full ID}	*Working.*	✓	✓	5		1
An Analyzer	{Agent UUID full ID}	*Working.*	✓	✓	1	1	1
Im Implementor	{Agent UUID full ID}	*Working.*	✓	✓		1	1
Te Tester	{Agent UUID full ID}	*Working.*	✓	✓	1	1	1

Message Orchestrator | Broadcast | |

Orchestrator read its mission message

General CLI MODE
(individual terminals for agents

SLIDE 4g – Implementation Tab. Elements

Agentsr may have sent messages, (speculative as an example)

reuse here means prompt has been copied and thus 'used' but can be copied again

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Working.*	✓	✓	5		1
An	Analyzer	{Agent UUID full ID}	*Waiting.*	✓	✓	1	1	1
Im	Implementor	{Agent UUID full ID}	*Waiting.*	✓	✓		1	1
Te	Tester	{Agent UUID full ID}	*Waiting.*	✓	✓	1	1	1

Message Orchestrator | Broadcast | |

General CLI MODE
(individual terminals for agents

SLIDE 4h – Implementation Tab. Elements

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Working.*	✓	✓	5		1
An	Analyzer	{Agent UUID full ID}	*Waiting.*	✓	✓	1	1	1
Im	Implementor	{Agent UUID full ID}	*Waiting.*	✓	✓		1	1
Te	Tester	{Agent UUID full ID}	*Waiting.*	✓	✓	1	1	1

Message field

Message Orchestrator | Broadcast | |

Send message

Message to orchestrator or broadcast user option

General CLI MODE (individual terminals for agents

SLIDE 3e – Implementation Tab. Elements

This board just shows over time what a message board could look like with the various elements

View this agent's message history, including broadcast messages, sent (direct to another agent or broadcast), received, ack,

Project:
{project_name}
Project ID: {full_UUID}

Launch | Implement

Claude Subagents

	Agent Type	Agent ID	Agent Status	Job Read	Job Acknowledged	Messages Sent	Messages waiting	Messages Read
Or	Orchestrator	{Agent UUID full ID}	*Waiting.*	✓	✓	5		1
An	Analyzer	{Agent UUID full ID}	*Working …*	✓	✓	1	1	1
Im	Implementor	{Agent UUID full ID}	*Completed.*	✓	✓		1	1
Te	Tester	{Agent UUID full ID}	*Waiting.*	✓	✓	1	1	1

Message Orchestrator | Broadcast | |

General CLI MODE
(individual terminals for agents

NOT USED AT THIS TIME, FUTURE