

Analyzing and Understanding ABMs

EES 4760/5760

Agent-Based and Individual-Based Computational Modeling

Jonathan Gilligan

Class #24: Thursday, November 18 2021

Schelling Model

Schelling Model of Housing Segregation

- Maybe the first Agent-Based Model.
 - T.C. Schelling, “Dynamic Models of Segregation”, *Journal of Mathematical Sociology* **1**, 143–186 (1971),
 - *Micromotives and Macrobehavior* (WW Norton, 1978).
- No computers. Schelling worked the model on graph paper with pennies and dimes representing the two kinds of agents.
- NetLogo version of Schelling’s segregation model:
 - Download page or
 - https://ees4760.jgilligan.org/models/class_24/class_24_models.zip
 - https://ees4760.jgilligan.org/models/class_24/segregation.nlogo

Model Overview

- Turtles represent households.
 - Two colors of turtles: red and blue
 - Turtles have one state-variable: `happy?` (true or false)
- There is a global variable `%-similar-wanted` and a turtle is `happy?` if at least this fraction of its neighbors have the same color as its own.
- At each tick, unhappy turtles move to a random empty patch.
- When all turtles are `happy?`, the model stops.

Experiments

Experiments

Vary %-similar-wanted and the density of turtles on the patches.

Suggestions:

- Try extreme values of parameters:
 - Set `density` and `%-similar-wanted` to different combinations near maximum, minimum, and in the middle.
 - What do you see?

Extreme Values

- Set `density` to 75% and set `%-similar-wanted` to 95%
- Press `setup` and then press `go`
 - What happens?
- Now, with `go` still pushed, slowly reduce `%-similar-wanted`.
 - Now what happens?

Systematic experiment:

- Using Behaviorspace, create a new experiment to vary `%-similar-wanted`
 - Set `time limit` to 1000
 - Set `density` to 75
 - Measure `percent-similar`
- What do you see?
- Try adjusting both `%-similar-wanted` and `density`

Visualizing Structures

- Add the following to the procedure `to update-turtles`, after `set happy?`

```
ifelse happy? [ set shape "square" ] [ set shape "square-x" ]
```

- Repeat the exercise of:
 - set `density` = 75% and `%-similar-wanted` = 95%,
 - press `setup` and `go`
 - gradually reduce `%-similar-wanted`
- Is it easier to see the emerging patterns now?

Heuristics

Another Heuristic

- When you're at an interesting value for one parameter
 - (e.g., `%-similar-wanted` = 75%),
 - vary other parameters (`density`).
 - Set `density` to 75% and `%-similar-wanted` to 75%.
 - Vary `density`
 - Set `density` to 96% and `%-similar-wanted` to 75%.
 - Vary `%-similar-wanted`
 - Set `%-similar-wanted` to 70%.

Other heuristics:

- Use several *currencies* to evaluate models
 - Statistical analysis of spatial patterns and time-series
 - Analyze agent properties:
 - Are they unimodal or multimodal
 - (e.g., are turtles divided into distinct groups of rich/poor, healthy/sick, etc.,
 - or distributed continuously around one dominant value of state variables?)
 - Stability: Does system return quickly to steady state after it's disturbed?
- Simplify models:
 - Make all patches the same
 - Make all turtles the same
 - Reduce places where you use stochasticity
 - Use fewer turtles and patches
- Explore unrealistic scenarios
- See book for heuristics for statistical analysis of model output...