



Flattening

Jimmy Lee & Peter Stuckey



香港中文大學
The Chinese University of Hong Kong




THE UNIVERSITY OF
MELBOURNE

Overview

► Flattening

- flattening expressions
- unrolling expressions
- arrays
- reification
- predicates
- let expressions

The MiniZinc Tool Chain



3

Flattening

- ⌘ The process of taking a
 - model + data + globals definitions
- ⌘ And creating
 - a FlatZinc model
 - variables (and parameters)
 - primitive constraints
 - solve item
 - output annotations
- ⌘ You can see the result of flattening by
 - in the IDE, use Compile (⌘B)
 - from the command line, use `mzn2fzn` or `mzn-gecode -k` (keep) and see `.fzn`

4

Flattening Expressions

- ▣ Simplifying expressions
- ▣ Evaluating fixed expressions
- ▣ Naming subexpressions (flattening)
 - for newly introduced variables
- ▣ Bounds analysis
- ▣ Common subexpression elimination

5

Flattening Expressions Example

▣ A small model

```
int: i = 3; int: j = 2;  
var int: x; var 0..2: y; var 0..3: z;  
x*y + y*z <= i*j;
```

▣ The resulting flat model is

```
var int: x;  
var 0..2: y;  
var 0..3: z;  
var 0..6: INT01;  
var int: INT02;  
INT01 = y * z;  
INT02 = x * y;  
INT02 + INT01 <= 6;
```

expression evaluation

6

Flattening Expressions Example

■ A small model

```
int: i = 3; int: j = 2;  
var int: x; var 0..2: y; var 0..3: z;  
x*y + y*z <= i*j;
```

■ The resulting FlatZinc is

```
var int: x;  
var 0..2: y;  
var 0..3: z;  
var 0..6: INT01 :: is_defined_var;  
var int: INT02 :: is_defined_var;  
int_times(y,z,INT01) :: defines_var(INT01);  
int_times(x,y,INT02) :: defines_var(INT02);  
int_lin_le([1,1],[INT02,INT01],0);
```

subexpression linking

subexpression linking

7

Flattening Exercise

■ Write down what you think results from

```
int: i = 3; int: j = 3;  
var 0..5: x; var 0..2: y; var 0..3: z;  
(x - i) * (x - j) + y + z + i + j >= 0;
```

■ Did you notice the **common subexpression**

```
var 0..5: x; var 0..2: y; var 0..3: z;  
var -3..2: INT01;  
var -6..9: INT02;  
INT01 = x - 3;  
INT02 = INT01 * INT01;  
INT02 + y + z + 6 >= 0;
```

■ Don't introduce **two names** for same exp

8

Flattening Exercise

- Write down what you think results from

```
int: i = 3; int: j = 3;  
var 0..5: x; var 0..2: y; var 0..3: z;  
(x - i) * (x - j) + y + z + i + j >= 0;
```

- Did you notice the **common subexpression**

```
var 0..5: x; var 0..2: y; var 0..3: z;  
var -3..2: INT01 :: is_defined_var;  
var -6..9: INT02 :: is_defined_var;  
int_lin_eq([1,-1],[x,INT01],3) :: dv(INT01);  
int_times(INT01,INT01,INT02) :: dv(INT02);  
int_lin_le([-1,-1,-1],[z,y,INT02],6);
```

- Don't introduce **two names** for same exp

9

Common Subexpression Elimination (CSE)

- While flattening mzn2fzn checks
 - if the expression has been seen before
 - if so it uses the same name

- CSE is vital for

- small models
- efficient models

- But its not perfect, e.g.

```
(x - y) * (y - x) >= y - x;
```

- Leads to

```
int_lin_eq([1,-1,-1],[x,y,INT01],0);  
int_lin_eq([1,-1,-1],[y,x,INT02],0);  
int_times(INT01,INT02,INT03);  
int_le(INT02,INT03);
```

10

Bounds Analysis

- ⌘ Tight bounds on variables
 - help the solver
 - reduce the size of unrolling (see later)
- ⌘ When introducing a variable
 - `INT01 = exp`
 - determine `l` = minimum possible value of `exp`
 - and `u` = maximum possible values of `exp`.
 - declare `var l..u: INT01;`

11

Bounds Analysis Example

- ⌘ What bounds are determined for

```
var -2..2: x;
var 0..4: y;
constraint x * x + y * y <= 6;
```
- ⌘ Resulting FlatZinc

```
var -2..2: x;
var 0..2: y;
var 0..4: INT01;
var 0..6: INT02;

constraint INT01 = x * x;
constraint INT02 = y * y;
constraint INT01 + INT02 <= 6;
```
- ⌘ Could be improved (presolve is coming)

12

Linear Expressions

- Linear constraints are one of the most important kind of constraint

```
int: k = 4;  
constraint x + 2*(y - x) + z <= k*z;
```

- Naively

```
constraint INT01 = y - x;  
constraint INT02 = 2*INT01;  
constraint INT03 = x + INT02;  
constraint INT04 = INT03 + z;  
constraint INT05 = 4 * z;  
constraint INT04 <= INT05;
```

- Simplified

```
constraint int_lin_le([-1,2,-3],[x,y,z],0);
```

- dfgfd

13

Unrolling

- Models are typically not fixed size
- Iterative constraints are everywhere

```
int: n;    set of int: OBJ = 1..n;  
array[OBJ] of int: size;  
array[OBJ] of int: value;  
int: limit;  
array[OBJ] of var int: x;  
constraint forall(i in OBJ)(x[i] >= 0);  
constraint sum(i in OBJ)(size[i]*x[i])<= limit;  
solve maximize sum(i in OBJ)(value[i]*x[i]);  
n = 4;  
size = [5,8,9,12];  
value = [3,5,7,8];  
limit = 29;
```

14

Unrolling

Iteration in MiniZinc is generator calls

```
sum(i in OBJ)(size[i]*x[i]) <= limit;
```

Which are really comprehensions

```
sum([ size[i]*x[i] | i in OBJ ]) <= limit;
```

Array comprehensions

```
constraint INT01 = 5 * x[1];
constraint INT02 = 8 * x[2];
constraint INT03 = 9 * x[3];
constraint INT04 = 12 * x[4];
array[1..4] of var int: AINT =
    [INT01,INT02,INT03,INT04];
constraint INT05 = sum(AINT);
constraint INT05 <= 29;
```

15

Unrolling conjunction and forall

Top level conjunctions

just split into separate constraints

```
constraint forall(i in OBJ)(x[i] >= 0);
```

Generates

```
array[1..4] of var bool: c =
    [x[1] >= 0, x[2] >= 0, x[3] >= 0, x[4] >= 0];
constraint forall(c);
```

The result is

```
constraint x[1] >= 0;
constraint x[2] >= 0;
constraint x[3] >= 0;
constraint x[4] >= 0;
```

16

Flattening objectives

Objectives in FlatZinc are single variables

```
solve maximize sum(i in OBJ)(value[i]*x[i]);
```

Unrolls to

```
constraint INT06 = 3 * x[1];
constraint INT07 = 5 * x[2];
constraint INT08 = 7 * x[3];
constraint INT09 = 8 * x[4];
array[1..4] of var int: AINT1 =
    [INT06,INT07,INT08,INT09];
constraint INT10 = sum(AINT1);
solve maximize INT10;
```

17

Unrolling

The final version of knapsack

after linear constraint simplification

```
array[1..4] of var int: x;
var int: INT10;
constraint x[1] >= 0;
constraint x[2] >= 0;
constraint x[3] >= 0;
constraint x[4] >= 0;
constraint 5*x[1] + 8*x[2] + 9*x[3] + 12*x[4]
<= 29;
constraint INT10 = 3*x[1] + 5*x[2] + 7*x[3] +
8*x[4];
solve maximize INT10;
```

18

Unrolling

■ The final version of knapsack

• after linear constraint simplification

```
array[1..4] of var int: x;  
var int: INT10;  
constraint int_le(0,x[1]);  
constraint int_le(0,x[2]);  
constraint int_le(0,x[3]);  
constraint int_le(0,x[4]);  
constraint int_lin_le([5,8,9,12],x,29);  
constraint int_lin_eq([-1,3,5,7,8],  
    [INT10,x[1],x[2],x[3],x[4]], 0);  
solve maximize INT10;
```

19

Array Translation

■ Arrays in FlatZinc

- are one dimensional
- start from index 1

■ MiniZinc arrays need to be translated

- modify multi-dimensional lookups to 1D
- shift indices.

■ Translation

```
• array[l1..u1, l2..u2] of int: x;  
• expression x[i,j]  
array[1..(u1-l1+1)*(u2-l2+1)] of int: x;  
    x[(i - l1)*(u2-l2+1) + (j - l2 + 1)]
```

20

Array Translation Example

Example 2D array

```
array[0..2,0..2] of var 0..2: x;  
constraint sum(i in 0..2)(x[i,i]) <= 1;  
constraint x[x[1,1],1] = 2;
```

Flattening

```
array[0..2,0..2] of var 0..2: x;  
constraint x[0,0] + x[1,1] + x[2,2] <= 1;  
var int: INT01 = x[1,1];  
constraint x[INT01,1] = 2;
```

Converting to 1D

```
array[1..9] of var 0..2: x;  
constraint x[1] + x[5] + x[9] <= 1;  
var int: INT01 = x[5];  
var int: INT02 = INT01 * 3 + (1 + 1);  
constraint x[INT02] = 2;
```

21

Element Constraints

- The ability to lookup the entry in array using a variable index is crucial to the modelling power of MiniZinc (and other CP modelling languages)

- element constraint provides this functionality

• `array_int_element(index, array, result)`

• encodes `array[index] = result`

- For example

```
constraint x[INT02] = 2;
```

- Becomes

```
constraint array_int_element(INT02,x,2)
```

22

if-then-else-endif

Flattening `if b then t else e endif`

- evaluate b (assuming it is fixed)
- if true then replace with t
- else replace with e

When b is not fixed

- replace with `[e,t][bool2int(b)+1]` and flatten

```
constraint if b then x else y endif >= 0;
```

- becomes

```
constraint [y,x][bool2int(b)+1] >= 0;
```

- becomes

```
constraint bool2int(b, INT00);  
constraint int_plus(INT00, 1, INT01);  
constraint array_int_element(INT01, [y,x], INT02);  
constraint INT02 >= 0;
```

23

Flattening Boolean Expressions

Recall that solvers only take a conjunction of constraints

- so how do we translate e.g.

```
x > 0 -> bool2int(y > 0 /\ z > 0) + t >= u;
```

We need to be able to “name” constraints

Reification of a constraint c creates

- a constraint $b \leftrightarrow c$
- b is true iff c holds
- b is false iff c does not hold

FlatZinc primitives reified constraints

- e.g. `int_lin_le(constants, variables, lhs)`
- `int_lin_le_reif(constants, variables, lhs, bool)`

24

Reification Example

Consider the expression

```
x > 0 -> bool2int(y > 0 /\ z > 0) + t >= u;
```

Then flattening is analogous to other expressions

```
constraint BOOL01 <-> x > 0;  
constraint BOOL02 <-> y > 0;  
constraint BOOL03 <-> z > 0;  
constraint BOOL04 <-> BOOL02 /\ BOOL03;
```

```
constraint INT01 = bool2int(BOOL04);  
constraint BOOL05 <-> INT01 + t >= u;
```

```
constraint BOOL01 -> BOOL05
```

25

Reification Example

Consider the expression

```
x > 0 -> bool2int(y > 0 /\ z > 0) + t >= u;
```

Then flattening is analogous to other expressions

```
constraint int_le_reif(1,x,BOOL01);  
constraint int_le_reif(1,y,BOOL02);  
constraint int_le_reif(1,z,BOOL03);  
constraint  
array_bool_and([BOOL02,BOOL03],BOOL04);  
constraint bool2int(BOOL04,INT01);  
constraint int_lin_le_reif([-1,-1,1],  
[INT01,t,u],0,BOOL05);  
constraint bool_le(BOOL01,BOOL05);
```

26

Flattening Boolean Expressions

⌘ Avoiding negative contexts

• push negation down to the bottom level

```
x > 0 -> bool2int(y > 0 /\ z > 0) + t >= u;
```

• becomes

```
not x > 0 /\ bool2int(y > 0 /\ z > 0) + t >= u;
```

• becomes

```
x <= 0 /\ bool2int(y > 0 /\ z > 0) + t >= u;
```

• becomes

```
constraint BOOL01 <=> x <= 0;  
constraint BOOL02 <=> y > 0;  
constraint BOOL03 <=> z > 0;  
constraint BOOL04 <=> BOOL02 /\ BOOL03;  
constraint INT01 = bool2int(BOOL04);  
constraint BOOL05 <=> INT01 + t >= u;  
constraint BOOL01 /\ BOOL05
```

27

Flattening Predicates and Functions

⌘ Predicates and functions act like macros

- when we see an expression including them we expand it with the arguments, then flatten

⌘ Given

- $f(x_1, x_2, \dots, x_n) = \text{exp}(x_1, x_2, \dots, x_n)$

⌘ Replace $f(\text{arg1}, \text{arg2}, \dots, \text{argn})$ by

- $\text{exp}(\text{arg1}, \text{arg2}, \dots, \text{argn})$

28

Flattening Predicates and Functions Example

```
predicate far_or_equal(var int:x1, var int:y1,  
                      var int:x2, var int:y2)=  
  man_dist(x1,y1,x2,y2) >= 4 /\  
  (x1 = x2 /\ y1 = y2);  
  
function var int: man_dist(var int:u1,  
  var int:v1, var int:u2, var int:v2) =  
  abs(u1 - u2) + abs(v1 - v2);  
  
constraint far_or_equal(a,b,c,d);
```

29

Flattening Predicates and Functions Example

```
predicate far_or_equal(var int:x1, var int:y1,  
                      var int:x2, var int:y2)=  
  man_dist(x1,y1,x2,y2) >= 4 /\  
  (x1 = x2 /\ y1 = y2);  
  
function var int: man_dist(var int:u1,  
  var int:v1, var int:u2, var int:v2) =  
  abs(u1 - u2) + abs(v1 - v2);  
  
constraint man_dist(a,b,c,d) >= 4 /\  
  (a = c /\ b = d);
```

30

Flattening Predicates and Functions Example

```
predicate far_or_equal(var int:x1, var int:y1,  
                      var int:x2, var int:y2)=  
  man_dist(x1,y1,x2,y2) >= 4 /\  
  (x1 = x2 /\ y1 = y2);  
  
function var int: man_dist(var int:u1,  
  var int:v1, var int:u2, var int:v2) =  
  abs(u1 - u2) + abs(v1 - v2);  
  
constraint abs(a - c) + abs(b - d) >= 4 /\  
  (a = c /\ b = d);
```

31

Flattening Predicates and Functions Example

Then flatten

```
constraint abs(a - c) + abs(b - d) >= 4 /\  
  (a = c /\ b = d);
```

becomes

```
constraint INT01 = a - c;  
constraint INT02 = abs(INT01);  
constraint INT03 = b - d;  
constraint INT04 = abs(INT03);  
constraint BOOL01 <-> INT02 + INT04 >= 4  
constraint BOOL02 <-> a = c;  
constraint BOOL03 <-> b = d;  
constraint BOOL04 <-> BOOL02 /\ BOOL03  
constraint BOOL01 /\ BOOL04;
```

32

Flattening Predicates with no definition

- ⌘ If a global constraint g is native to a solver there is only a definition, not a declaration:

```
predicate
    alldifferent(array[int] of var int: a);
```

- ⌘ How do we translate $g(x_1, \dots, x_n)$
- ⌘ In the root context
 - leave unchanged (send to the solver)
- ⌘ In a reified context?
 - try to use: $g_reif(x_1, \dots, x_n, b)$
- ⌘ This might fail if it does not exist!

33

Flattening predicates with no definition

- ⌘ Example library

```
predicate
    alldifferent(array[int] of var int: a);
predicate alldifferent_reif(
    array[int] of var int: a, var bool: b) =
    b <-> forall(i, j in index_set(a) where i < j)
        (a[i] != a[j]);
```

- ⌘ Example code

```
constraint alldifferent([x,y,z]);
constraint alldifferent([y,z,t]) -> x = 0;
```

- ⌘ Result

```
constraint alldifferent([x,y,z]);
constraint b <-> (y != z /\ y != t /\ z != t);
constraint b -> x = 0;
```

34



Flattening Let Expressions

- ⌘ Let expressions allow us to introduce new variables
- ⌘ FlatZinc consists only of
 - variables declarations
 - primitive constraints
- ⌘ New variables must be “**float**ed” to the top level
- ⌘ **Rename** copies of new variables
- ⌘ Complexities for relational semantics
 - partial functions,
 - local constraints

35

Flattening Let Expressions

- ⌘ Flattening
 - `exp(let { var int: x; constraint c } in exp2(x))`
- ⌘ rename variable to be new
 - `exp(let { var int: y; constraint c } in exp2(y))`
- ⌘ name local constraint by new boolean
 - `exp(let { var int: y; var bool: b = c; constraint b; } in exp2(y))`
- ⌘ float out variable declarations to top, and float constraint to nearest enclosing Boolean context

36

Flattening Let Expressions Example

Consider the code

```
constraint not (8>=sum(i in 1..2)(sqrt(a[i])));  
function var int:sqrt(var int: x) =  
  let { var int: y;  
    constraint y * y = x /\ y >= 0 } in y;
```

Unrolling the sum gives

```
constraint not 8 >=  
  (let { var int: y;  
    constraint y * y = a[1] /\ y >= 0 } in y) +  
  (let { var int: y;  
    constraint y * y = a[2] /\ y >= 0 } in y);
```

37

Flattening Let Expressions Example

Consider the code

```
constraint not 8 >= sum(i in 1..2)(sqrt(a[i]));  
function var int:sqrt(var int: x)  
  :: promise_total =  
  let { var int: y;  
    constraint y * y = x /\ y >= 0 } in y;
```

Renaming the local variables gives

```
constraint not 8 >=  
  (let { var int: y1;  
    constraint y1*y1 = a[1] /\ y1>=0 } in y1) +  
  (let { var int: y2;  
    constraint y2*y2 = a[2] /\ y2>=0 } in y2);
```

38

Flattening Let Expressions Example

Consider the code

```
constraint not 8 >= sum(i in 1..2)(sqrt(a[i]));  
function var int:sqrt(var int: x) =  
  let { var int: y;  
    constraint y * y = x /\ y >= 0 } in y;
```

Naming booleans gives

```
constraint not 8 >=  
(let { var int: y1; constraint b1;  
var bool: b1 = (y1*y1 = a[1]) /\ y1>=0 } in y1)+  
(let { var int: y2; constraint b2;  
var bool: b2 = (y2*y2 = a[2]) /\ y2>=0 } in y2);
```

39

Flattening Let Expressions Example

Consider the code

```
constraint not 8 >= sum(i in 1..2)(sqrt(a[i]));  
function var int:sqrt(var int: x) =  
  let { var int: y;  
    constraint y * y = x /\ y >= 0 } in y;
```

Nearest enclosing Boolean context

```
constraint not 8 >=  
(let { var int: y1; constraint b1;  
var bool: b1 = y1*y1 = a[1] /\ y1>=0 } in y1) +  
(let { var int: y2; constraint b2;  
var bool: b2 = y2*y2 = a[2] /\ y2>=0 } in y2);
```

40

Flattening Let Expressions Example

Consider the code

```
constraint not 8 >= sum(i in 1..2)(sqrt(a[i]));  
function var int:sqrt(var int: x) =  
  let { var int: y;  
    constraint y * y = x /\ y >= 0 } in y;
```

Float out declarations and constraints

```
var int: y1;  
var bool: b1 = (y1*y1 = a[1] /\ y1>=0);  
var int: y2;  
var bool: b2 = (y2*y2 = a[2] /\ y2>=0);  
constraint not (b1 /\ b2 /\ 8 >= y1 + y2);
```

41

Flattening Let Expressions Example

Consider pushing negations

```
constraint 8 < sum(i in 1..2)(sqrt(a[i]));  
function var int:sqrt(var int: x) =  
  let { var int: y;  
    constraint y * y = x /\ y >= 0 } in y;
```

Float out declarations and constraints

```
var int: y1;  
var bool: b1 = (y1*y1 = a[1] /\ y1>=0);  
var int: y2;  
var bool: b2 = (y2*y2 = a[2] /\ y2>=0);  
constraint 8 < y1 + y2;  
constraint b1;  
constraint b2;
```

42

Flattening Let Expressions Example

Consider pushing negations

```
constraint 8 < sum(i in 1..2)(sqrt(a[i]));  
function var int:sqrt(var int: x) =  
  let { var int: y;  
    constraint y * y = x /\ y >= 0 } in y;
```

Simplify true Booleans

```
var int: y1;  
  
var int: y2;  
  
constraint 8 < y1 + y2;  
constraint y1*y1 = a[1] /\ y1>=0;  
constraint y2*y2 = a[2] /\ y2>=0;
```

43

Flattening Let Expressions Example

Consider pushing negations

```
constraint 8 < sum(i in 1..2)(sqrt(a[i]));  
function var int:sqrt(var int: x) =  
  let { var int: y;  
    constraint y * y = x /\ y >= 0 } in y;
```

Flatten top level conjunctions

```
var int: y1;  
var int: y2;  
constraint 8 < y1 + y2;  
constraint y1*y1 = a[1];  
constraint y1>=0;  
constraint y2*y2 = a[2];  
constraint y2>=0;
```

44

Relational Semantics and Partial Functions

- Local variables defined by partial functions

- need careful treatment

- The failure of the partial function must be captured in the right context (nearest)

```
var -3..3: y;  
constraint (let { var int: x = 9 div y }  
            in x * y != 9) -> y != 2;
```

- Translation

```
var {-3,-2,-1,1,2,3}: y1;  
var int: x = 9 div y1;  
var bool: b2 <-> y != 0;  
constraint b2 -> y1 = y;  
constraint (x * y != 9 /\ b2) -> y != 2;
```

45

Overview

- Understanding how MiniZinc works

- helps in debugging models
 - helps in understanding why different modeling approaches are preferable

- Flattening

- converts MiniZinc to a
 - conjunction of primitive constraints
 - which is what a solver can handle

46



EOF

47