

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/266159762>

# The Adaptive Psi Method and the Lapse Rate

Conference Paper in Journal of Vision · May 2012

DOI: 10.1167/12.9.322

CITATIONS

3

READS

201

1 author:



Nicolaas Prins

University of Mississippi

49 PUBLICATIONS 622 CITATIONS

SEE PROFILE

Some of the authors of this publication are also working on these related projects:



Psychophysics: A Practical Introduction, 2nd edition. [View project](#)



# The adaptive psi method and the lapse rate.

Nicolaas Prins, Department of Psychology, University of Mississippi



## Introduction

The adaptive psi-method (Kontsevich & Tyler, 1999): following each trial the psi-method derives a posterior probability distribution across (discrete) values of the threshold and slope parameters based on all previous trials and a user-provided prior distribution. The stimulus intensity to be used on the next trial is then selected such that the expected entropy in the posterior distribution is minimized. The Psi-method uses a fixed assumed value for the lapse rate and this can be expected to lead to bias in threshold and slope estimates when the generating value of the lapse rate does not match the assumed value.

## Methods

PF used:  $\psi(x; \alpha, \beta, \gamma, \lambda) = \gamma + (1 - \gamma - \lambda) \times F_W(x; \alpha, \beta)$   $F_W(x; \alpha, \beta) = 1 - \exp\left(-\left(\frac{x}{\alpha}\right)^\beta\right)$   
 $\alpha = 10$ ,  $\beta = 3$ ,  $\gamma = 0.5$ , and  $\lambda = 0, 0.025$ , or  $0.05$ .

4 priors were used (left). All were uniform within range shown.


Standard Psi method assumed  $\lambda = 0.025$ .

Parameter estimates were derived by Bayesian method (as in K&T, 1999): marginal means across posterior.


Parameter estimates were also derived by Maximum Likelihood (ML) method with free lapse rate.

SEs: square root of average squared deviation of estimate from true, generating value.

Psi method, psi+ method, ML fits performed by the Palamedes Toolbox (Prins & Kingdom, 2009).



## Standard Psi






### Results:

Bayesian fit results in bias when actual lapse rate deviates from that assumed by Psi method.

ML fit with free lapse rate results in bias due to serial dependencies (Prins, 2012; also see Kaernbach, 2001).

## Possible solution I: Include lapse rate in posterior distribution: Psi+



### Results:

Bias is reduced.

Parameter estimates eventually converge on true, generating values, but only after high number of trials.

Sessions contain lengthy consecutive stimulus presentations at very high intensities.

## Possible solution II: 'Asymptotic Performance Lapse Estimation' (APLE; Prins, 2012):

Use standard Psi, but add observations at asymptotic performance intensity (API, here:  $F_W = 0.9999$ ), and fit model which assumes  $F = 1$  at API.


Two versions: jAPLE ('joint-APLE') and iAPLE ('isolated-APLE').

jAPLE:  $\psi(x; \alpha, \beta, \gamma, \lambda) = 1 - \lambda$  when  $x = API$

$\psi(x; \alpha, \beta, \gamma, \lambda) = \gamma + (1 - \gamma - \lambda)F(x; \alpha, \beta)$  otherwise.

iAPLE: two-step procedure: use performance at API to estimate  $\lambda$ , then estimate  $\alpha$  and  $\beta$  from the other, Psi-controlled observations using  $\lambda$  fixed at value estimated at API.

Also included in Figure: ML fit with free lapse rate (e.g., Wichmann & Hill, 2001): nAPLE ('non-APLE').



### Results:

Inclusion of asymptotic level stimuli reduces bias.

Do not impose arbitrary upper limit on lapse rate (see also Prins, 2012).

10-15% of trials should be at API to minimize SE on  $\alpha$  and  $\beta$ .

## Summary

Standard Psi method leads to bias when assumed and generating lapse rate do not match, even when data are fitted post-hoc by ML method with a free lapse rate.

Bias is reduced with proposed Psi+ method with eventual convergence on generating parameter values.

Bias also reduced when very high stimulus intensities are added to standard Psi.

Consider using proposed fitting methods jAPLE and iAPLE.

## References

- Kaernbach, C. (2001). Slope bias of psychometric functions derived from adaptive data. *P&P*, 63, 1389.
- Kontsevich, L.L. & Tyler, C.W. (1999). Bayesian adaptive estimation of psychometric slope and threshold. *VR*, 39, 2729.
- Prins, N. (2012). The psychometric function: The lapse rate revisited, *JoV*. In press. preprint: <http://home.olemiss.edu/~nprins/LapseRateRevisited.html>.
- Prins, N. & Kingdom, F.A.A. (2009). Palamedes: Matlab routines for analyzing psychophysical data. [www.palamedestoolbox.org](http://www.palamedestoolbox.org).
- Wichmann, F.A. & Hill, N.J. (2001). The psychometric function: I. Fitting, sampling and goodness of fit, *P&P*, 63, 1293.

Download this poster: <http://home.olemiss.edu/~nprins/VSS2012.html>.