

BPi-M2M-V1_2 BOM

元件值	规格	封装	位号	数量
10pF	NPO, 5%, 50V, 0402	C0402	C60, C97, C98	3
18pF	NPO, 5%, 50V, 0402	C0402	C35, C36, C40, C41	4
22pF	NPO, 5%, 50V, 0402	C0402	C64, C65	2
33pF	NPO, 5%, 50V, 0402	C0402	C88, C89	2
100pF	NPO, 5%, 50V, 0402	C0402	C86	1
102	X5R, 10%, 25V, 0402	C0402	CP21, C29, C42	3
104	X5R, 10%, 25V, 0402	C0402	C1, C2, CD4, CD5, CD6, C6, CD7, CD8, C8, C9, C12, CP15, C15, C17, C18, C23, C27, C28, C34, C38, C39, C43, C53, C56, C58, C85, C87, C100, C102, C103, C104, C106	33
1uF	X5R, 10%, 25V, 0402	C0402	CD2, CD3, CP4, C4, C5, CP10, C16, C20, C21, C22, C25, C26, CP29, CP30, C31, C32, C47, C52, C55, C57, C83	21
4. 7uF	X5R, 20%, 6. 3V, 0402	C0402	CD1, C3, CP5, C13, CP20, CP24, C24, CP25, CP26, C30, CP31, C37, C49, C54, C63	15
10uF	X5R, 20%, 6. 3V, 0603	C0603	CP1, CP2, CP3, CP6, CP7, CP8, CP9, C10, C11, C11, CP12, CP13, CP14, C14, CP16, C17, CP18, CP19, CP22, CP23, CP32, C46, C61, C66, C68, C84, C94, C105	28
22uF	X5R, 20%, 6. 3V, 0805	C0805	C48, C99, C101	3
0R-1%	1%, 1/16w, 0402	R0402	R4, R25, R108	3
22R	5%, 1/16w, 0402	R0402	R5, R6, R9, R10, R17, R18	6
100R	5%, 1/16w, 0402	R0402	R43	1
240R-1%	1%, 1/16w, 0402	R0402	R1, RD3, RD4	3
1K	5%, 1/16w, 0402	R0402	RP3, RP5, R54, R69, R72, R82, R111	7
1K5	5%, 1/16w, 0402	R0402	R70, R71	2
2K-1%	1%, 1/16w, 0402	R0402	RD1, RD2, R11, R12, R13, R14, R15, R16, R29, R30, R112	11
4K7	5%, 1/16w, 0402	R0402	R78, R79, R80	3

10K	5%, 1/16w, 0402	R0402	RP4, R21, R23, R24, R26, R39, R40, R46, R53, R96, R99, R113	12
51K	5%, 1/16w, 0402	R0402	R33, R34, R35, R36, R37	5
100K-1%	1%, 1/16w, 0402	R0402	R110, R74, R75, R76, R81, R84, R107	7
10M	5%, 1/16w, 0402	R0402	R7	1
133K-1%	1%, 1/16w, 0402	R0402	R22	1
200K-1%	1%, 1/16w, 0402	R0402	R2	1
1M-1%	1%, 1/16w, 0402	R0402	R19	1
OR	1%, 1/10w, 0805	R0805	R109	1
OR01-1%	1%, 1/10w, 0805	R0805	RP1, RP2	2
22R*4	5%, 1/16w, 0402, 排阻	R0402x4	RN1, RN2	2
1. 5uH, 2A DCR<0. 1R	贴片功率电感, 4018	IND4x4	L1, L2, L3, L5	4
2. 2uH, 2A DCR<0. 1R	贴片功率电感, 4018	IND4x4	L6	1
1. 5uH, 1. 5A DCR<0. 1R	贴片功率电感, 3015	IND3x3	L4	1
4. 7uH, 800mA, DCR<0. 1R	贴片功率电感, 3015	IND3x3	L7	1
1N5819W, 1A, SOD123	1N5819W, 1A, SOD123	SOD123	D1, D6	2
LED-R	贴片LED灯, 红色, 0805	LED0805	D3	1
LED-G	贴片LED灯, 绿色, 0805	LED0805	D4	1
LED-B	贴片LED灯, 蓝色, 0805	LED0805	D5	1
ESL100503	USB TVS Protection, 5. 5V, 3pF, 0402	SOD882-ESD	ESD8, ESD9, ESD10, ESD11, ESD12, ESD13, ESD14, ESD15, ESD16, ESD17, ESD18	11
WPM1481-6/TR	P-Channel Power MOSFET, 6A, DFN2x2-6L	DFN2x2-6L	Q1	1
BSN20	N-Channel enhancement mode MOSFET, SOT23	SOT-23	Q2, Q3	2
A03423	P-Channel MOSFET, 20V, 2A, SOT23	SOT-23	Q4	1
MMBT3904	Transistor-NPN, MMBT3904, 40V, 200mA, SOT23	SOT-23	Q5	1
R16/A33	Allwinner R16/A33	BGA282P0 80B14X14H1 30	U1	1
AXP223	Allwinner AXP223	QFN69P0 4B8X8 nh	U2	1
K4B4G1646D-BCK0	DDR3-FBGA96, 256Mx16bit, 1. 5V	FBGA96C80P9X13	DU1	1
KLM8G1GETF-B041	BGA153, eMMC, 8GB	FBGA153-115x130	U8	1
SY7152	1MHz, 2A Step Up Regulator	SOT23-6	U3	1
AP6212	SDIO WIFI 802. 11b/g/n, BT4. 0, 12x12mm	QFN44P 120x120	U5	1
SN2010BIF09E	D类功放, 5V/3W, UTQFN-9	UTQFN-9	U7	1
24MHz-20pF-10PPM	Crystal, 24MHz, 20pF, 10ppm	TSX-3225	X1	1

32.768KHz, 9pF, 20ppm	Crystal,32.768kHz,12.5pF,20ppm	CRYS-SMD-3215	X2	1
E3SB26.0000F16G11	Crystal,26MHz,20pF,10ppm	TSX-3225	X3	1
TF-09P-H1.85	Micro SD卡座,SMT,9Pin外焊,H 1.85mm	microsd-9p-a	CN1	1
DC 0507	DC电源座,Φ4mm,贴片	DC 0507	CN12	1
PH-6AWB-125	PH座子,6PIN,卧贴,1.25mm间距	BAT_SMD6-125	CN13	1
FPC24-05PH-BOT	FPC座,0.5mm Pitch,24PIN,翻盖下接	FPC24-05PH-BOT	CN2,CN3	2
GF-B19	2PIN轻触按键(乌龟按键)	T2Key	K1,K3	2
EM4013S-BC-42	贴片MIC,EM4013S-BC-42	MIC 400CIR180 SMD	MIC1	1
Micro-USB	贴片5PIN MicroUSB,4定位脚,雾锡牛角型	MICRO USB DIP4SMD	USB1	1
USB AF10 0 SMT	USB座子,A型,SMT,两定位脚,卷边	USB AF10 0 SMT	USB2	1
ANT-IPEX1G	USS RF插座,I代,H1.25mm,三焊脚	ANT-MHF-Coaxial	CN4	1
DIP40-254	双排排针,2.54mm间距,2x20PIN,直插	DIP40-254	CON1	1