

CSci 423 Homework 9

Due: 1:00 pm, Wednesday, 11/14

Eric Shih

1. (7 points) Exercise 4.3 on page 183.

A decidable language is closed under the complement. TM $M_{\bar{L}}$ which decides \bar{L} will accept when TM M_L that decides L rejects, and reject when M_L accepts. It has been shown that E_{DFA} is decidable where $E_{DFA} = \{ \langle A \rangle \mid A \text{ is a DFA and } L(A) = \emptyset \}$.

On input $\langle A \rangle$ where A is a DFA:

- (a) Mark the start state of A .
 - (b) Repeat until no new states are marked.
 - (c) Mark states that has a transition coming in from any state that is already marked.
 - (d) If no accept state is marked, accept. Otherwise, reject.
2. (7 points) Exercise 4.6 on page 183.
- Proof by contradiction. Assume that B is countable. Infinite sequences over 0, 1 can be represented by $N = 1, 2, 3, \dots$. A $f(n)$ can be mapped where $n \in N$. $f(n) = (w_{n1}, w_{n2}, w_{n3}, \dots)$ where w_{ni} is the i th bit in the n th sequence. Using diagonalization, it is possible to find a sequence over 0, 1 that is not in $f(n)$, where the i th bit is the opposite of the i th sequence. This means that the sequences are $\notin B$, giving us a contradiction, proving B to be uncountable.

n	$f(n)$
1	$(w_{11}, w_{12}, w_{13}, w_{14}, \dots)$
2	$(w_{21}, w_{22}, w_{23}, w_{24}, \dots)$
3	$(w_{31}, w_{32}, w_{33}, w_{34}, \dots)$
\vdots	\vdots

3. (7 points) Exercise 4.7 on page 183.

reference www.cs.ucdavis.edu/~gusfield/cs120f11/HW6key.pdf

To prove that T is countable we provide a function $f: T \rightarrow \mathbb{N}$. Given a triple (i, j, k) from T f is defined as follows: convert each number i, j , and k to their respective binary representation. We will compute the natural number n in its binary representation. For the a th bit of n , we divide a by 3. This will produce a quotient q and a remainder r . If r is 0 then we extract the q th bit from i , if r is 1 then we extract the q th bit from j , if r is 2 then we extract the q th bit from k . Note that if the q th bit of i, j , or k is not defined then use a 0. Note that f maps every i, j, k tuple to a natural number and every natural number can be converted to an i, j, k tuple (by the reverse process). Hence f is a one-to-one function and onto (aka a bijection). Therefore T is countable.

4. (7 points) Problem 4.19 on page 184.

test.scripts.psu.edu/users/a/y/.../Decidable%20Languages(2).docx

Let $P = \text{ADFA}$. We know this to be decidable.

We also know that regular languages are closed under the reverse operation. So, if there is a DFA D for w , there is a DFA D^R for w^R . We can then construct an NFA N by branching to D and D^R . Since we have an algorithm to convert NFAs to DFAs, we run it on $\langle N \rangle$ to get $\langle M \rangle$. Now we have a

DFA M , and since ADFA is decidable, there is some S such that $S = \{ \langle M \rangle \}$. Since M is a DFA that accepts wR whenever it accepts w , $S = \{ \langle M \rangle \mid M \text{ is a DFA that accepts } w^R \text{ whenever it accepts } w \}$, and S is decidable.

5. (12 points) In class, we learned that A_D is non-TR, A_{TM} and $HALT_{TM}$ are TR but non-TD. What can you say about their complements? Are they non-TR, TR but non-TD, or TD? Justify your answers.

Both \bar{A}_{TM} and \bar{HALT}_{TM} are not TR since A_{TM} and $HALT_{TM}$ are TR. If both sets were TR, then they would also be TD.

\bar{A}_D is not TD, according to the closure property, because A_D is not TD. \bar{A}_D is, on the other hand, TR. In the case $A_D = \{ w_i \mid w_i \notin L(M_i) \}$, its complement $\bar{A}_D = \{ w_i \mid w_i \in L(M_i) \}$. A TM R can be constructed to take w_i as input, then use the string to code TM M_i . Both are then fed into A_{TM} , which will accept if it accepts. This shows that \bar{A}_D is TR.

Reading Summary 4

The Turing machine is far from being bettered by other models. Over 75 years, the Turing Machine is still considered the best machine model available. It can be used to model both modern computing and the natural world. What we have learned over the years in computing is a result of the model.

The Turing machine was so special because it disembodied the machine and broadened the view of computation. It brought the view away from what goes specifically into the machine, but how the machine reacts and works as a whole. There are also challenges to the standard model, which all have an impact on universality; they are labelled into sections called reductionalists, impressionists, remodelers, and incomputability theorists (recursion theorists). The most generally respected challenge to the model, reductionalists, is explained by saying “one can apply it ever more widely to what we observe in nature, and let it mold our expectations of what computing machines can achieve.

The impressionists are a large force in the community of real-world “computation”. Real-world computation is how nature and people in the real world compute. The old definition of computation being steps carried out by a computer is now being challenged by the idea that computation is something can be a non-stop natural process. Some believe that this old idea is a result of a “Mathematical Bias” because the founders of computing were mathematicians.

To capture much of the computational aspects of nature, people have turned to creating models to be analyzed. Hypercomputational packages is one model that is subject to much disagreement. Some think that this idea of computational models that go beyond the Turing Machine are impossible and wrong, while others believe that hypercomputational packages are the way forward.

Finally, the halting set is used by many scholars to explain incomputability. They believe that incomputability is simply the halting set with an existential quantifier added. As it is described, “All the fuss and descriptive variety associated with incomputability in nature and its models merely cloak avatars of halting sets for different machines.”

Even with the amount of discourse between scholars regarding the future of the Turing Machine, there is no doubt that its impact is huge among the subject of computability and will continue to play a factor in the future.