

Image Enhancement in the Spatial Domain 3


using local/global information

Created time : 2024/3/22 09:14

學號 : 109321019 姓名 : 涂价弘

Exercise-1

```
clf('reset');  
img = imread('./images/2/pout.tif');  
hist = gen_hist(img);  
bar(hist)  
axis tight
```




```
imshow(img)
```



Exercise-2

```
clf('reset');  
  
img = imread('./images/flyman/flymanBS.tif');  
imshow(img)
```



```
flyman = img(176:339, 250:444);  
flyman_hist = gen_hist(flyman);  
  
bg = img(1:163, 1:194);  
bg_hist = gen_hist(bg);  
  
subplot(1, 2, 1)  
imshow(flyman)  
title('flyman')  
subplot(1, 2, 2)  
imshow(bg)  
title('background')
```


flyman




background



```
clf('reset');  
  
bar(flyman_hist)  
title('flyman')
```



```
bar(bg_hist)
axis tight
title('test')
title('background')
```





Exercise-3

```
clf('reset')

img1 = imread('./images/3/Fig3.15(a)1top.jpg');
img2 = imread('./images/3/Fig3.15(a)2.jpg');
img3 = imread('./images/3/Fig3.15(a)3.jpg');



[equaized_img1, t1] = histeq(img1);
[equaized_img2, t2] = histeq(img2);
[equaized_img3, t3] = histeq(img3);

subplot(1, 2, 1)
plot(t1)
title('transformation function')
subplot(1, 2, 2)
imshow(equaized_img1)
title('equalized image')
```





```
clf('reset')

subplot(1, 2, 1)
plot(t2)
title('transformation function')
subplot(1, 2, 2)
imshow(equaized_img2)
title('equalized image')
```



```
clf('reset')

subplot(1, 2, 1)
plot(t3)
title('transformation function')
subplot(1, 2, 2)
imshow(equaized_img3)
title('equalized image')
```


Exercise-4

```
clf('reset')  
  
img = imread('./images/3/Fig3.20(a).jpg');  
imshow(img)  
title('original')
```

original



```
[equaized_img, t] = histeq(img);  
  
subplot(1, 2, 1)  
plot(t)  
title('transformation function')  
  
subplot(1, 2, 2)  
imshow(equaized_img)  
title('equalized image')
```




Exercise-5-1

```
clf('reset')


img = imread('./images/3/Fig3.24.jpg');

hist = gen_hist(img);
bar(hist)
title('original histogram')
```




```
imshow(img)  
title('original')
```

original




```
[equaized_img, t] = histeq(img);  
  
plot(t)  
title('transformation function')
```



```
imshow(equaized_img)  
title('equalized image')
```


equalized image



Exercise-5-2


```
A = double(img);  
I1 = nlfilter(img, [3 3], 'mean2');  
I2 = nlfilter(img, [3 3], 'std2');  
  
imshow(I1, [])  
title('local mean')
```

local mean



```
imshow(I2, [])  
title('local standard deviation')
```

local standard deviation



Local enhancement

```
I3 = A;

for x = 1:size(I3, 1)
    for y = 1:size(I3, 2)
        if I1(x, y) <= 40 && I2(x, y) >= 5
            I3(x, y) = I3(x, y) * 3;
        end
    end
end

imshow(I3, [])
title('local enhancement')
```

local enhancement



```
function ret = gen_hist(I)
    % Initial histogram vector
    ret = zeros(256, 1);
    [row, col] = size(I);

    for x = 1:row
        for y = 1:col
            ret(I(x, y) + 1) = ret(I(x, y) + 1) + 1;
        end
    end
end
```