V-65
COMPRESSOR INLET SEPARATOR

Size 3' 5" ID x 12' 0" length
DP 450 PSIG
DT 100 deg F

P-8
COMPRESSOR

50 MSCFH @ 315 deg F disch
and 175 PSID boost pressure

From natural gas source A-3 Dwg. 38422
From natural gas source A-2 Dwg. 38422
From natural gas source A-1 Dwg. 38422
12"x6"
Vent stacks 20' above grade
AND
HS 91
I
M
TIR 88
PIR 89 H L
FSL 75 Set @ 30 MSCFH
FIR 75
FY 75
FT 75
PG 132
PT 74
TE 73 RTD
PG 135
TG 72
To gas cooling Dwg. 10921
12"x8"
PSV 11 Set @ 405 PSIG
PSV 12 Set @ 408 PSIG
PSV 13 Set @ 410 PSIG
PG 131
TT 88
TE 88 RTD
PT 89
12" 4" 1/2" 1" 12"
V-65
Slope 1" ET
1"x1/2" 1"x1/2"
PDT 93
LSHH 231
HHLL = 2' 6" (ESD)
HLL = 1' 11"
NLL = 1' 4"
LLL = 0' 7"
LT 92
LG 93 L
2"
PDSH 93 Set @ 0.9 PSID
PDIR 93 H
LIR 92 H L
LIC 92 H L
FC
LV 92
OWS
Rod out
JAHH 220
JIR 220
JT 220
Anti-surge
XC 76
XA 76
XY 76a I/P IAS
XY 76b 1:1 IAS
PG 134
PDT 77
PG 133
TE 232 RTD
TT 232
TSH 232 Set @ 325 deg F
12" 8"
M
P-8
VZE 221
VXE 222
VYE 223
TE 224 RTD
VXE 225
VYE 226
TE 229 RTD
VXE 227
VYE 228
NDE SV 92 DE vent IAS
To motor controls Dwg. 52331
ESD
HS 230
Vibration monitor
Bently-Nevada 3300 series
(See dwg 58209 for wiring details)

Process Legend

- **Primary Process Piping** — Main gas & liquid inlets / outlets
- **Instrument Signal Lines** — Instrument & control signals
- **Major Equipment** — Vessels, compressor, motor
- **Secondary / Auxiliary Lines** — Bridle, Bypass, Vent