```
anirudh@LAPTOP-H9V5A2PN:~$ cd OSLAB
anirudh@LAPTOP-H9V5A2PN:~/OSLAB$ nano m11.sh
anirudh@LAPTOP-H9V5A2PN:~/OSLAB$ chmod +x m11.sh
anirudh@LAPTOP-H9V5A2PN:~/OSLAB$ ./m11.sh
========================================
     SINGLE QUOTES AND DOUBLE QUOTES
========================================

----- SINGLE QUOTES -----
Hello World
Hello $NAME
The value of $NAME is not expanded.
Stored single-quoted string:
This is a $NAME literal string.
Literal content:
Hello    World    Linux

----- DOUBLE QUOTES -----
Hello World
Hello Shanmukha
The value of NAME is: Shanmukha
Stored double-quoted string:
Hello Shanmukha
String with spaces:
Hello     Linux     World

----- VARIABLE EXPANSION -----
Single quotes: $NAME
Double quotes: Shanmukha

----- NESTED TOKENS -----
Outer quotes with variable: Linux Shell
Command result: Nested Command

----- QUOTED COMMANDS -----
Command stored as:
echo Hello Linux

Executing command:
Hello Linux

----- EDGE CASES -----
Length of single-quoted empty string: 0
Length of double-quoted empty string: 0
Special characters: $ * ? ! # @
Special characters: $ * ? ! # @
```

```
----- VARIABLE EXPANSION -----
Single quotes: $NAME
Double quotes: Shanmukha

----- NESTED TOKENS -----
Outer quotes with variable: Linux Shell
Command result: Nested Command

----- QUOTED COMMANDS -----
Command stored as:
echo Hello Linux

Executing command:
Hello Linux

----- EDGE CASES -----
Length of single-quoted empty string: 0
Length of double-quoted empty string: 0
Special characters: $ * ? ! # @
Special characters: $ * ? ! # @

----- PARSING VALIDATION -----
Single quote parsing result:
Hello $NAME
Double quote parsing result:
Hello Shanmukha

----- COMMAND WITH SPACES -----
Created file:
-rw-r--r-- 1 manchodu manchodu 0 Oct  1 18:10 'test file.txt'

All quote tests completed successfully.
anirudh@LAPTOP-H9V5A2PN:~/OSLAB$
```