Serve: Play more. Manage less.

Meta Global AI Developer Hackathon 2026 · Technical architecture and report · Indie Developer track · Build for Your World

Demo video (2:42): https://github.com/gino6178/serve-meta-hackathon/raw/main/docs/media/Serve_Meta_demo.mp4 · **Live site:** https://play.theminimallab.com · **Code:** https://github.com/gino6178/serve-meta-hackathon

1. Impact

Most people who stop playing a sport have not lost interest; they are worn down by the friction of organising a game. In a 2015 poll by NPR, the Robert Wood Johnson Foundation and the Harvard Chan School, 40% of 18 to 21 year olds played a sport but only 26% of 26 to 49 year olds [1]. Sport New Zealand's Active NZ survey (2023) names what stops adults playing regularly [2]: **times that are hard to fit together around other commitments (64.2%)**, **no way to keep the habit going (21.3%)** and **no regular people to play with (10.2%)**. Serve's three helpers answer these three in turn: Talk fits the time, Match keeps the habit, and the agents find the people. Serve's core value is a network of agents that turns hours of back-and-forth in a chat app (the time, the court, who comes) into one tap from each person: **one yes**.

A first real club. During the hackathon we introduced Serve to a real badminton club: more than 10 people used it, and of the 3 game invites sent through it, 2 became games that were played, within three days. Two players, in their own words (translated from Chinese):


- "*It's actually really handy. You just talk to the agent.*" (Player A)
- "*I think the way it suggests games first can make people more motivated to play.*" (Player B)

A game from one sentence, against a group-chat poll

Step	Group-chat poll	Serve
The time and the court	The organiser picks options and books the court	The agent drafts both from one sentence: the day from the words, the nearest court
Settled when	Everyone has voted and the organiser posts the result	The spots fill: whoever is free taps Join; nobody else is waited for
Someone not in the group	Has to be added to the chat first	Opens the link and joins
Who is in	Read back from the votes and replies	On the card; the agent posts each join in the thread

Serve is a platform where people and agents make games together. Every person on it has an agent: the one Serve gives them, on the web and in Messenger, or their own, which comes in through the same open door (section 2). Behind the agents runs Muse Glimmer and **our own model, a Llama 3.2 1B we distilled from Glimmer**, which makes Glimmer's choice in about 0.9 s instead of about 40 s (2.6). Underneath are four pieces of engineering: a standard A2A protocol with a distributed negotiation engine, active querying by the value of information, a community that evolves the platform with automatic rollback, and 3D reconstruction from a phone video (section 2).

Build for Your World. Each person's world is their own week, their own courts and their own people, and Serve is built around exactly that. Anyone, anywhere, can use it. Courts come from OpenStreetMap, so any town with courts works, for any ball sport (badminton, tennis, pickleball, table tennis, basketball, volleyball, soccer); it runs in a phone's browser and in Messenger. The demo town sits on Taipei, with prices in NT$, but nothing in Serve is tied to one place or one sport.



On the web: a sentence becomes an invite, the players' agents agree the time, one tap books it. In Messenger (right): the same booking, with the agent's real replies from the Messenger end-to-end test

Taking the friction out of a game

- **Match, asking first.** Match learns the player's usual playing times. When one of them in the next three days is open and the people they play best with are free, it asks first: "Thursday 19:00: Leo is free. Want a game?"
- **Talk, agents agreeing on their own.** The person only says they want to play. Each player's agent agrees the time, the people and the court with the others' agents in the background.
- **Body, scheduling around the body.** The player's own body log and health-app export become scheduling limits: doubles instead of singles while a knee is sore, one game fewer in a heavy week. **A body log is not medical advice**: Serve gives no diagnosis, treatment or dose, and a highlight clip is for sharing, never for coaching or scoring.

For groups nobody organises: children's sessions with fair turns and no child accounts, gentle daytime doubles for older adults, and charity round-robins that record pledges but handle no money, each with its rules in code. **Quiet courts:** the group's agent can ask a venue's agent for a quiet-hour price, so venues fill empty hours.


How it was validated in nine days. A long trial with real players is not possible in a nine-day build, so Serve was also checked by agents. Over 25 rounds, a fresh set of independent AI agents used it each round (six a round, five to ten in the first five rounds; 153 in all), each a new model given only a persona and the address, on fresh local copies running the same code as the live site (16,713 logged requests). What they found was fixed between rounds, and the six agents of the last round found no fault in a core flow. Three more agents were given only the address and a request: the best of them was doing useful work by its third request to the API and found its person a Sunday 09:00 tennis game, free, 2.6 km away.

2. Technical depth

Serve keeps one rule throughout: **code computes the facts and keeps the hard rules; the models choose only among the real preferences left.** That keeps a model's mistake from turning into a wrong booking or a clash.

Terms used below. *One yes*: the single tap each person gives before anything is booked. *The student*: our own Llama 3.2 1B, distilled from Muse Glimmer (2.6). *The decider*: Glimmer itself, read from a single token with no reasoning.

The four parts that matter most: a standard A2A protocol with a distributed negotiation engine (2.1), active querying by the value of information (2.2), a community that evolves the platform with automatic rollback (2.3), and 3D reconstruction from a phone video (2.4).



Architecture

2.1 A standard A2A protocol and a distributed negotiation engine

Agents talk over the A2A protocol v1.0 of the Linux Foundation [3], through its official SDK. A person's own agent comes in through an open door: a guide in the site's own HTML, `/llms.txt` with a six-call quick start, an Agent Card, OpenAPI, and a channel where every request carries the agent's own Ed25519 signature.

- **Facts only.** A proposal carries each time as `{id, date, start, venue, court, trip}` and nothing else; an answer carries `{intent, date, start, works}`. Sentences between agents are templates filled by code, so no agent's model ever reads another side's words, and no agent can inject instructions into another.
- **One round, by intersection.** The host's agent lists up to twelve times that fit every calendar and have a court; each player's agent marks the ones that work for its person, and that is binding. Code takes the best time in the intersection, so most talks end in round one: the Contract Net [4] with a one-shot intersection, a simple distributed constraint satisfaction [5]. A player's hard rules (days off, the latest finish, the longest trip) take times off the list before any model sees it.
- **The fairest venue.** For each time, code picks the venue whose longest trip is shortest, from home areas, never addresses; when one player has had the longest trip in two of their last three games, a time that gives them the longest trip again by more than 10 minutes is refused. Over 12 simulated games, no booked game gave anyone a longer longest trip than the best venue possible, at a cost of 2.3 minutes more total travel per game; the fairness score was 0.73, against 0.59 for the shortest total trip and 0.58 for a Nash product.
- **Times ranked by the chance everyone says yes.** A game needs every player, so the times are proposed in order of the product of each player's chance of a yes (from 2.2), and a time where any one player's chance is under 0.15 goes to the back: a least-misery floor, as group recommenders that predict perceived fairness advise [26]. With shared calendars the first time proposed decides whether each agent can say yes by code or must ask a model. Against the old order (the time the most players had free), on 3,000 simulated requests of each kind, the first time kept every player's rules in 89.1% of doubles requests instead of 73.9% (92.4% instead of 89.8% for singles), and the model choices per doubles request fell from 0.261 to 0.109. With private calendars it found no more games.
- **Skill with uncertainty.** Each player has a rating per sport as a mean and an uncertainty, changed only by competitive games that the other side confirms; children's, gentle and charity games never count.
- **Holds, all or nothing.** An agreed time is held by every player's agent for 30 minutes, asked in a fixed order: leases [6] with resource ordering [7]. With two talks at once for one member, 11 of 12 pairs booked the

member twice without holds and 0 of 12 with them.

- **Durable and signed.** A talk is saved before every round, a message is answered once, and booking is idempotent. Agent Cards carry a JWS over their canonical JSON (Ed25519) [8, 9], checked before any talk. The gateway was killed at five points in a booking: all 20 recovery checks passed and no game was booked twice.
- **Across machines.** Two gateways on separate machines, joined only by an SSH tunnel with a pinned host key, with pinned and rotatable Ed25519 keys: the hop added about 185 ms per request, and 22 of 22 checks passed with 12 talks at once.
- **To the standard.** Agent Cards point to their keys with `jku`, the proposal and hold extensions are declared and required, and errors use the protocol's own codes (-32700 for a body that is not JSON, -32005, -32008).

2.2 Active querying by the value of information

When a game's talks have not landed, the agent neither gives up nor asks the player again. For each player and each candidate time it keeps a belief that the player is free then, a Beta(1 + yes, 1 + no) posterior over what it has seen of that player's agent at that weekday and hour (never their calendar), and multiplies it by the chance of a yes. It then asks the **one yes-or-no question whose answer most raises the expected chance of a game**, through a private free-or-busy channel with a disclosure budget, and talks again only on a yes.

Strategy (20,000 simulated requests each; 8 players, 6 times, hidden true availability)	Game found, one question then one talk
No question	40.7%
A random question	44.4%
Ask about the likeliest pair	48.2%
The question worth most (value of information)	**51.9%**

With 20,000 requests each, every rate is good to about 0.7 points either way, so each step in the table is real. A new player starts from what the agent has seen across all players rather than a blank belief.

One answer teaches about the hours like it. At first every weekday and hour had its own belief, so a "no" for Tuesday at 19:00 said nothing about Tuesday at 20:00. Following Pep [24] and VPL [25], which learn a person from a few answers through structure shared across people, an answer now lends part of its count to the hours that go together in the club's own free lists (the same evening an hour or two apart, the same hour on another weeknight, the two weekend days), and the club's prior counts as half an answer instead of two. A window's last hour no longer counts as free when a 90-minute game cannot start then. On 6,000 simulated requests, with members apart from those that make the prior: Brier score 0.223 to 0.200, log loss 0.638 to 0.585, and the chance the first talk lands rose from 68.9% to 73.7%, or from 75.1% to 79.2% with one value-of-information question first. Every free-or-busy question is charged to the same disclosure budget as a proposal, so an agent that keeps asking learns at most 24 of 112 weekly hours in 28 days, and what A tells B never reaches C. No one is asked more than 3 times a week, and an optional micro-randomised trial (off by default) can measure whether an ask at a given moment helps, with its analysis script. A player can also import an `.ics` calendar: only its busy times are read, and they become weekly free windows.

2.3 A community that evolves the platform, with automatic rollback

What members ask for becomes changes to the platform, through a pipeline in which code makes every decision and the models only write short sentences that code checks:

unmet request → one sentence, shared only with a yes → screened → idea and quadratic vote → spec and class → nine gates → canary of members → kept, or rolled back by itself (bigger changes go to a person).

1. **Signals and one yes.** A member's agent counts unmet requests and thumbs, with no words and no player id (an HMAC). Glimmer paraphrases an unmet request as one sentence; code checks it (no names, numbers, links or body terms), and the member taps Share or Don't. Prompt Guard 2, Llama Guard 3 and code screen it again.

2. **Ideas and votes.** DRAMA clusters the sentences. An idea shows once 5 different members have said it, and becomes a proposal only with support on weekdays and weekends. Votes are quadratic [10]: 9 credits a month, n votes cost n^2, so no small group can swamp a vote.
3. **A spec and its class.** Glimmer drafts a spec from a summary alone; code writes the counts, the class, the oracle (a test of the change written from the spec, which the builder never sees) and the privacy line. The class comes from what the change does, never from the draft: C0 a declared setting inside its range, C1 wording, C2 a tool parameter, C3 anything else. A never-list (booking without a yes, data off the server, a diagnosis or dose, editing the tests or the guard) is checked with CodeShield's rules [11].
4. **Nine gates.** Policy, a code scan, unit tests, the crash matrix, the red team, Messenger end to end, the Autopilot test (eight planned weeks, each run three times, every run passing), the spec's oracle and a privacy canary. They stop at the first failure.
5. **Ship, watch, roll back.** A C0 change ships to under 20% of members for 7 days. A booking without a yes, a double booking or the privacy marker leaving turns it off at once. It also rolls itself back when thumbs down on it rise by 10 points or more and the rise is statistically real under an anytime-valid test (an e-process [22], E of 20 or more), so the monitor can look every 5 minutes without false alarms piling up. In 20,000 simulated 7-day canaries of 5 members, looked at every 5 minutes, a harmless change was rolled back 0.6% of the time, against 22% for a z-test checked at every look; the price is caution, as a bad change (thumbs down from 25% to 60%) was caught in 61% of canaries.
6. **A person for anything bigger.** A C1 to C3 change waits for a maintainer; then the builder agent, Glimmer in a tool loop, writes it on a branch in its own git worktree, never reading community text, with the tests read-only and no network, and a person merges it.

It draws on the Darwin Gödel Machine [12], which hacked its own evaluation (so the tests are read-only here), AlphaEvolve [13] (keep a change only when evaluators pass it), Clio [14] (minimum cluster sizes for privacy) and CaMeL [15] (the model that reads untrusted text is not the code that acts).

2.4 3D reconstruction and automatic highlights from a phone video

For a highlight, Serve can stop time and move the camera round the player, from one ordinary phone video:

- **Reconstruction.** MapAnything [16] reads metric depth and the camera from the moment's frame; SAM 2.1 [17] cuts the player out, and the court behind them is filled in from neighbouring frames. The scene is then re-rendered from a camera swung around the player.
- **Knowing how far to go.** Arcs of about ±6 to 12° look like a real camera move; wider ones bend posts and double the net. Seen from a new angle, part of the frame was never filmed, and the renderer has to make those pixels up. One learned threshold on that share of invented pixels (6.26% of the frame) picks the widest arc that still looks right, or falls back to a zoom: on 84 labelled frames it reached precision 1.00 and recall 0.79, against 0.45 and 0.64 for our first rule (a budget on invented patches at low resolution). From 14 moments of one clip it chose 4 orbits, 6 zooms and 4 holds.
- **A second opinion that says why.** The threshold decides; Muse Wonder explains. On the same 84 frames it agreed with the labels 87% of the time, and it names what it rejects ("doubled ghost net outline above the net"), which a pixel count cannot.
- **Never an empty shot.** A frame-by-frame check that the player and the racket hand are there (SAM 2.1 as a video tracker, RT-DETR [18] and Sapiens2) caught every frame where they were missing. A moment takes 19.9 s on the RTX 3090 once the models are loaded.
- **Automatic highlights.** A clip to share is cut from the player's own video with no editing by the player: RT-DETR finds the people (about 4 boxes a frame against DETR's 15 to 20, about 2× faster, and the right player on all three test clips), Sapiens2 finds the moment worth sharing (a racket's fastest swing, the top of a jump, a kick), SAM 2.1 cuts the player out, and the clip replays that moment in slow motion with a caption Glimmer writes and code checks. The presence check above keeps the zoom on the player. With ball tracking on, the clip can start and end with the rally itself, cut where the shuttle comes into play and where it goes out.



An automatic highlight as the pipeline cut it: the rally, the jump smash zoomed in slow motion, back to the rally (clip: Badminton klub Ljubljana, CC BY 3.0)


2.5 A tiered decision engine, and a booking step by step

Following FrugalGPT [19], decisions pass through layers, each taking only what the one before could not settle:

- **Layer 0, code (milliseconds):** free times, calendar clashes, trips and every hard rule. The game's card comes from this layer: on a local copy it appeared 7 ms after the request at the median (97 ms at most, 9 runs).
- **Layer 1, our own distilled model (about 0.9 s):** the Llama 3.2 1B we trained from Muse Glimmer (2.6) answers when it is at least 0.5 sure, which is nearly every choice: 99.0% of ordinary ones and 96.9% of the hardest.
- **Two cheap reads that agree.** When the student is unsure, the decider (0.53 s) reads Glimmer's choice in one token. It keeps its pick alone when the chance that it differs from Glimmer's full answer is under 5%; and when the student (at least 0.3 sure) and the decider (at least 0.5) pick the same time, that time stands. On the decider's 196 hardest cases, split in halves 500 times, with the student at the earlier 0.6, this rule raised the choices settled without Glimmer's full answer from 72.1% to 79.0%, matching Glimmer 68.9% of the time instead of 69.6% (Glimmer matches itself 73.5%). Now that the student answers from 0.5, it applies only to the few choices left.
- **Layer 2, Muse Glimmer (about 20 to 40 s), stopped early when it is sure.** Only the few choices still open reach it, streamed to the screen step by step (NDJSON). Following DEER [23], once its reasoning is 1,000 characters long the options are read at each break in it, and the first read that is 0.98 sure ends the answer. On the RTX 3090, one answer at a time on 30 cases, Glimmer wrote 30% fewer tokens (596 to 420 an answer) and answered no later (22.3 s to 21.3 s), though each read takes in the reasoning again (prompt tokens 1,074 to 4,885); read after the fact on 119 cases, 1.7% of answers differ from the full one. Every wait the person starts shows a moving bar and a status line within 250 ms.
- **Text, by length.** Free text (wording an invite, a summary, a reply) goes by how long the call is: see section 3.

Before any of them, Match works ahead of time: it asks about the player's usual times before the player does, so the agents have often agreed a game before anyone waits at all.

A booking, step by step, with its measured times



A booking, step by step

2.6 Our own model: a Llama 3.2 1B distilled from Muse Glimmer

We trained our own model. A member's agent spends most of its time on one judgment: which of several workable times its person would like best. We had Muse Glimmer make that choice 4,868 times through the real agent call, then distilled its choices into **Llama 3.2 1B Instruct** with LoRA and quantized it to int4, so it runs on the server's CPU and takes no GPU memory from Glimmer. It works the way TypeSafe's Jev decision models do [20]: the options are declared in advance and scored together in a single read, instead of an answer generated token by token. So it returns a probability for each option and never writes text that could break a rule, and every option it sees already keeps the person's hard rules.

	Muse Glimmer, full answer	Our 1B student
Agreement with Glimmer on all 500 held-out cases (every case answered; always taking the first listed time: 82.7%)	88.8% (with itself)	**89.5%** (88.5% after int4)
Time per choice	about 40 s, on the RTX 3090	**about 0.9 s, on the CPU**
Cases it answers at 0.5 sure (the served threshold)	all	99.0% of 500; 96.9% of the 196 hardest (the asked time breaks a rule, calendars shared)
Agreement with Glimmer at 0.5 sure, with Glimmer on the rest	88.3% on the 500; 73.5% on the hardest (Glimmer again)	89.6% on the 500; 61.2% on the hardest

The threshold was 0.6 until the last day: there it answered 96.0% of the 500 and 73.0% of the hardest, with agreement 89.9% and 68.4%. Most choices are not hard, so we lowered it to 0.5 to keep Glimmer's GPU free: on the hardest it now leaves 3.1% of the choices to the layers after it instead of 27.0%, at a cost of 7.2 points of agreement there (0.3 on the 500). This is a trade, not a free gain; `A2A_STUDENT_SURE=0.6` restores the earlier point. A pick whose reading of which times work differs from code's still goes to Glimmer. At 0.6, in talks with the simulated club, it cut Glimmer's member answers by 67% (ordinary talks) and 54% (with private calendars on), with no rule broken. When it is unsure, busy for 8 s or silent for 20 s, Glimmer answers instead. With 500 cases each agreement rate is good to about 3 points either way, so the student matches Glimmer as closely as Glimmer matches itself, about 44 times faster than its full answer.

Its confidence can be trusted: over the 500 held-out cases its expected calibration error is 0.052, and at 0.8 sure it answers 89% of them and differs from Glimmer on only 7%.

Why distil, when the one-pass decider takes 0.53 s? The decider is still Glimmer, so it needs the GPU that every agent's reasoning and the video models share, and it keeps a pick only when it is that sure (about 8% of choices). The student runs on the CPU, answers 99.0% of the 500 test cases on its own, and leaves the GPU free for the work only Glimmer can do.

What surprised us. Four findings from running Meta's models in a product, each measured:

- **Muse Glimmer reasons even when told not to.** Over 2,755 calls, 84% of the tokens it wrote were reasoning and 9% of calls came back empty, nearly all from a quick pick whose budget ran out mid-thought; with thinking switched off it reasoned in a hidden channel and returned nothing. Every call now asks for `think: "low"` with 900 tokens of room.
- **A 1B student agrees with Glimmer as often as Glimmer agrees with itself.** Distilled from 4,868 of Glimmer's choices, Llama 3.2 1B agrees with Glimmer on 89.5% of 500 held-out cases, against Glimmer's 88.8% with itself, in about 0.9 s instead of about 40 s.
- **Glimmer can decide in one token.** Read with no chat template, Glimmer's next token gives a probability for each option, so the one-pass decider gets its choice in 0.53 s with no reasoning at all.
- **Llama Guard 3 reads sports injuries as medical advice.** Its S6 category flagged 6 to 8 of 15 ordinary injury-care answers. S6 now blocks a text only when code also finds a dose, a medicine to take, or a condition the player is said to have.

2.7 Security, and a failure the agents found

- **Attacks and crashes.** 93 attack cases, named by OWASP LLM Top 10 risk, were all stopped; the crash and recovery checks are in 2.1. Prompt Guard 2 now reads every post and comment first, before Llama Guard 3 and code.
- **A signed record of every yes.** Each consent is appended to a log in which every entry is signed and carries the hash of the one before, so a yes cannot be changed or removed afterwards without it showing.
- **No-shows, with no money.** A player's show-up record fades with a 60-day half-life and is shown as a range in words, never a score; a game short of its minimum players is called off 3 hours before; a freed spot is offered to the waitlist with 12 hours to confirm.
- **A failure, and the fix.** During the agent rounds, a tester working as a host found it could work out how many people nearby were open to being asked, first from a count and then from the talk. Now nearby people appear only once they can actually play, and everyone else sees only published badge words; later rounds re-checked it and found nothing.

3. Meta models and tools

Serve runs its open-weights models on our own GPU server (two RTX 3090s and their CPU), so players' data stays there, and calls the Meta Model API for live voice, a fallback, very long calls, images and checks.

Which model answers, by length. Each text call is routed by its estimated length. A short call (up to about 700 tokens) at a site where our 1B was checked goes to the 1B, run as a chat model on Glimmer's Ollama with no reasoning; anything longer, or anywhere else, goes to Muse Glimmer; a very long call (12,000 tokens or more, near Glimmer's 16,384-token context) goes to Muse Spark on the Meta Model API; with the fallback, these are the only text calls that leave our server. A 1B reply that is empty or does not fit its schema is asked again of Glimmer, and tool loops and images never go to the 1B. We first sent every short call to the 1B, and it did not hold up: it filed training on the wrong day, logged games wrongly and could not phrase a wish (9 end-to-end checks failed), let 2 of 6 hostile comments through the post standard, and obeyed 4 of 10 court reviews that told it what to say. It was distilled to choose among options, not to read and write freely. So the 1B takes short text only at five checked sites (wording a game ask, a court's name in English, a memory's beliefs, a paper's summary, a question about the

feed), and new sites go to Glimmer by default. With that list, the end-to-end test, the feed red team (13 of 13) and the red team (93 of 93) pass as with Glimmer alone; in the end-to-end test the 1B served 4 of about 37 model calls.

The hackathon's models: the Muse family and SAM 3.1

Kind	Model	Runs on	Its job in Serve
Reasoning	Muse Glimmer (30B)	RTX 3090 (GPU 1)	Every agent: the Autopilot's tool loop, each member's decision, the community specs, reading what a person wants. A JSON Schema on every call, and code checks every text
Live voice	Muse Voice Transcribe	Meta Model API	24 kHz PCM full duplex, with Kokoro speaking the reply on the server; the player can talk over the agent
Long calls and fallback	Muse Spark 1.3	Meta Model API	Calls of 12,000 tokens or more; a fallback when the GPU server can't take a call; an alternative model for the builder (which uses Glimmer by default)
Images	Muse Image	Meta Model API	Faces for the club's agents and the art of rematch posters
Cross-check	SAM 3.1	Meta Model API	Cross-checks SAM 2.1's player outline: 0.974 IoU on a smash frame
Vision judge	Muse Wonder	Meta Model API	Judges orbit frames for defects: agreed with the labels on 87% of 84 frames

Meta's other open models, including our own distilled Llama

Kind	Model	Runs on	Its job in Serve
Our model	Llama 3.2 1B Instruct, distilled by us	Server CPU (int4), and Glimmer's Ollama for short text	Trained from 4,868 of Glimmer's decisions; picks among times as Glimmer would, about 44 times faster (2.6); short text at five checked sites
Safety	Llama Guard 3 1B	Server CPU	Both ways in Messenger and on community wishes; code checks its S6 flag so sports injuries are not read as medical advice
Safety	Prompt Guard 2 (86M)	Server CPU	Untrusted text (Google reviews of courts, community wishes, every post and comment) before a model reads it
Meaning	DRAMA (drama-base)	Server CPU	Memory by meaning (768 dimensions) and a softmax head that catches game requests the regular expressions miss
Speech	Omnilingual ASR (CTC 1B)	Server CPU	Voice notes in Messenger, for players who can't type
Detection	DETR (ResNet-50)	RTX 3090 (GPU 0)	The fallback person detector; RT-DETR (not Meta's) is now the default, as it follows the right player (2.4)
Body pose	Sapiens2 (0.4B)	RTX 3090 (GPU 0)	The moment worth sharing, and whether the player is in view
Video segmentation	SAM 2.1 (Hiera-L)	RTX 3090 (GPU 0)	Tracks and cuts out the player for highlight clips
3D	MapAnything	RTX 3090 (GPU 0)	Metric depth and the camera for orbit replays

Meta's safety and platform pieces

- **The Agents Rule of Two** [21]: no agent or loop stage holds untrusted input, private data and the power to act at once.
- **LlamaFirewall's CodeShield rules** [11] screen community specs and generated code.
- **Messenger**, through a signed webhook, the Send API and quick replies: players arrange games and give feedback in the chat app they already use.

4. What is not done yet

- **Most validation is simulated.** Beyond one real club and two games, the evidence comes from AI agents, simulated members and local copies; timings such as the 7 ms card were measured on a local copy, not the live site.
- **The slow path still exists.** When the small models are unsure, Glimmer takes about 20 to 40 s. The person sees the steps stream in and a moving status line, but it is still a wait.
- **Venues are samples.** No venue has joined yet, so quiet-hour prices are sample prices.
- **The community loop has not run on real members.** An idea shows only once 5 different members ask for it, so with one small real club it has so far run on a simulated club.
- **Orbit replays are short.** Only arcs of about ±6 to 12° look right; otherwise Serve falls back to a zoom.

5. Sources and notes

- **Where the numbers come from.** Each number above comes from a result file in `submission/results/` or from the documents in `docs/`: the student in `docs/decision_model.md`, the decider in `docs/decider.md`, A2A and holds in `contention_eval.json`, the value of information in `voi_sim.json` and `pref_share.json`, the time order in

`rank_calls.json`, the agreement rule in `agree_cascade.json`, the early exit in `early_exit_ab.json` and `early_exit.json`, the loop in `loop_eval.json`, orbits in `submission/results/orbit/`, and the agent testing in `submission/agent_testing.md`.

- **Built during the hackathon.** Building started on October 27, the hackathon's first day. We designed Serve and decided what it does and how; an AI coding agent (Claude Code) wrote code to our instructions, credited in the repository's commits, and every change went through the tests. The one earlier piece is TrackNetV5, our published shuttle tracker, fetched at run time and off unless `BALL_TRACKING=1`.
- **Real and simulated.** The badminton club above is real people. Separately, the built-in demo club that a new visitor sees, the clubs used for evaluations and the members the agent testers met are simulated and labelled as such; the testers were AI models, not people.
- **Code:** https://github.com/gino6178/serve-meta-hackathon, with the full evaluation in `README.md` and `docs/`.

References

1. NPR, Robert Wood Johnson Foundation and Harvard T.H. Chan School of Public Health. Sports and Health in America, a poll of 2,506 adults, 2015 (news.harvard.edu/gazette/story/2015/07/keeping-adults-in-the-game).
2. Sport New Zealand. Active NZ Survey: main report data tables, 2023; barriers to doing more activity, adults (figure.nz/chart/6HXITdQ2MBBAjZxH).
3. Agent2Agent (A2A) Protocol, v1.0. Linux Foundation.
4. Smith. The Contract Net Protocol. IEEE Transactions on Computers, 1980.
5. Yokoo et al. The Distributed Constraint Satisfaction Problem: Formalization and Algorithms. IEEE TKDE, 1998.
6. Gray and Cheriton. Leases: An Efficient Fault-Tolerant Mechanism for Distributed File Cache Consistency. SOSP 1989.
7. Havender. Avoiding Deadlock in Multitasking Systems. IBM Systems Journal, 1968.
8. RFC 7515, JSON Web Signature.
9. RFC 8785, JSON Canonicalization Scheme.
10. Lalley and Weyl. Quadratic Voting: How Mechanism Design Can Radicalize Democracy. AEA Papers and Proceedings, 2018.
11. LlamaFirewall: An Open Source Guardrail System for Building Secure AI Agents. arXiv 2505.03574, 2025.

12. Darwin Gödel Machine: Open-Ended Evolution of Self-Improving Agents. arXiv 2505.22954, 2025.
13. AlphaEvolve: A Coding Agent for Scientific and Algorithmic Discovery. arXiv 2506.13131, 2025.
14. Clio: Privacy-Preserving Insights into Real-World AI Use. arXiv 2412.13678, 2024.
15. CaMeL: Defeating Prompt Injections by Design. arXiv 2503.18813, 2025.
16. MapAnything: Universal Feed-Forward Metric 3D Reconstruction. arXiv 2509.13414, 3DV 2026.
17. Ravi et al. SAM 2: Segment Anything in Images and Videos. 2024.
18. Zhao et al. DETRs Beat YOLOs on Real-time Object Detection (RT-DETR). CVPR 2024.
19. Chen, Zaharia and Zou. FrugalGPT: How to Use Large Language Models While Reducing Cost and Improving Performance. arXiv 2305.05176, 2023.
20. TypeSafe. Jev: decision models that score declared options in one pass. 2026.
21. Meta. Agents Rule of Two. October 2025.
22. Ramdas, Grünwald, Vovk and Shafer. Game-Theoretic Statistics and Safe Anytime-Valid Inference. Statistical Science, 2023.
23. Yang et al. Dynamic Early Exit in Reasoning Models (DEER). arXiv 2504.15895, 2025.
24. Bose et al. Pep: Cold-Start Personalization via Training-Free Priors from Structured World Models. arXiv 2602.15012, 2026.
25. Poddar et al. Personalizing Reinforcement Learning from Human Feedback with Variational Preference Learning. arXiv 2408.10075, NeurIPS 2024.
26. Waterschoot, Tintarev and Barile. Consensus vs. Dissent: Dynamic LLM Modeling of Subjective Preferences in Group Recommenders. arXiv 2607.10235, RecSys 2026.

The decider's thresholds use conformal risk control (Angelopoulos et al., 2022); more in `docs/methods.md`.