

JAVADOC

Farisano Gino

Esposito Vincenzo

Scovotto Vanessa

Valitutto Giuseppe

Indice

1.Client Pc	3
2.Dispositivo Android	16

1.Client Pc



Documentazione Gestione Appuntamento

Documentazione Gestione Utente

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP
PREV CLASS NEXT CLASS FRAMES NO FRAMES ALL CLASSES
SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

guiSegretaria
Class FormCalendario.RegistraAppuntamento

java.lang.Object
 guiSegretaria.FormCalendario.RegistraAppuntamento

All Implemented Interfaces:
java.awt.event.MouseListener, java.util.EventListener

Enclosing class:
FormCalendario

```
public class FormCalendario.RegistraAppuntamento
extends java.lang.Object
implements java.awt.event.MouseListener

Classe che gestisce quale interfaccia mostrare.
```

Constructor Summary

Constructors

Constructor and Description

RegistraAppuntamento ()

Method Summary

All Methods **Instance Methods** **Concrete Methods**

Modifier and Type	Method and Description
void	mouseClicked(java.awt.event.MouseEvent arg0)
void	mouseEntered(java.awt.event.MouseEvent arg0)
void	mouseExited(java.awt.event.MouseEvent arg0)
void	mousePressed(java.awt.event.MouseEvent arg0)
void	mouseReleased(java.awt.event.MouseEvent arg0)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

RegistraAppuntamento

public RegistraAppuntamento()

Method Detail

mouseClicked

```
public void mouseClicked(java.awt.event.MouseEvent arg0)
```

Specified by:

mouseClicked in interface java.awt.event.MouseListener

mouseEntered

```
public void mouseEntered(java.awt.event.MouseEvent arg0)
```

Specified by:

mouseEntered in interface java.awt.event.MouseListener

mouseExited

```
public void mouseExited(java.awt.event.MouseEvent arg0)
```

Specified by:

mouseExited in interface java.awt.event.MouseListener

mousePressed

```
public void mousePressed(java.awt.event.MouseEvent arg0)
```

Specified by:

mousePressed in interface java.awt.event.MouseListener

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES ALL CLASSES
SUMMARY NESTED FIELD CONSTR METHOD DETAIL FIELD CONSTR METHOD

guiSegretaria

Class FormCalendario.RicercaAppuntamento

java.lang.Object
guiSegretaria.FormCalendario.RicercaAppuntamento

All Implemented Interfaces:

java.awt.event.ActionListener, java.util.EventListener

Enclosing class:

FormCalendario

```
public class FormCalendario.RicercaAppuntamento  
extends java.lang.Object  
implements java.awt.event.ActionListener
```

Classe che elenca gli appuntamenti odierni.

Constructor Summary

Constructors

Constructor and Description

RicercaAppuntamento()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type Method and Description

void actionPerformed(java.awt.event.ActionEvent arg0)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

RicercaAppuntamento

```
public RicercaAppuntamento()
```

Method Detail

actionPerformed

```
public void actionPerformed(java.awt.event.ActionEvent arg0)
```

Specified by:

actionPerformed in interface java.awt.event.ActionListener

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES ALL CLASSES
SUMMARY NESTED FIELD CONSTR METHOD DETAIL FIELD CONSTR METHOD

guiSegretaria

Class FormCalendario.eliminaAppuntamento

java.lang.Object
guiSegretaria.FormCalendario.eliminaAppuntamento

All Implemented Interfaces:

java.awt.event.ActionListener, java.util.EventListener

Enclosing class:

FormCalendario

```
public class FormCalendario.eliminaAppuntamento
extends java.lang.Object
implements java.awt.event.ActionListener
```

Classe che gestisce l'eliminazione di un appuntamento.

Constructor Summary

Constructors

Constructor and Description

eliminaAppuntamento()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	actionPerformed(java.awt.event.ActionEvent arg0)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

eliminaAppuntamento

public eliminaAppuntamento()

Method Detail

actionPerformed

public void actionPerformed(java.awt.event.ActionEvent arg0)

Specified by:

actionPerformed in interface java.awt.event.ActionListener

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES ALL CLASSES

SUMMARY NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

guiSegretaria

Class RegistraPaziente.inserisciPaziente

java.lang.Object
 guiSegretaria.RegistraPaziente.inserisciPaziente

All Implemented Interfaces:

java.awt.event.ActionListener, java.util.EventListener

Enclosing class:

RegistraPaziente

```
public class RegistraPaziente.inserisciPaziente
extends java.lang.Object
implements java.awt.event.ActionListener
```

Classe che inserisce un paziente nel sistema.

Constructor Summary

Constructors

Constructor and Description

`inserisciPaziente()`

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	<code>actionPerformed(java.awt.event.ActionEvent arg0)</code>

Methods inherited from class `java.lang.Object`

`equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Constructor Detail

`inserisciPaziente`

`public inserisciPaziente()`

Method Detail

`actionPerformed`

`public void actionPerformed(java.awt.event.ActionEvent arg0)`

Specified by:

`actionPerformed` in interface `java.awt.event.ActionListener`

PACKAGE **CLASS** USE TREE DEPRECATED INDEX HELP
PREV CLASS NEXT CLASS FRAMES NO FRAMES ALL CLASSES
SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

guiSegretaria

Class ModificaPaziente

java.lang Object
guiSegretaria.ModificaPaziente

All Implemented Interfaces:

java.awt.event.MouseListener, java.util.EventListener

```
public class ModificaPaziente
extends java.lang.Object
implements java.awt.event.MouseListener
```

Nested Class Summary

Nested Classes

Modifier and Type	Class and Description
class	<code>ModificaPaziente.effettuaModifiche</code> Classe che effettua le modifiche su un paziente.
class	<code>ModificaPaziente.esce</code> Classe che esce dalla schermata di modifica.

```
class ModificaPaziente.resetta
Classe che resetta l'inserimento dei dati.
```

Constructor Summary

Constructors

Constructor and Description

`ModificaPaziente(GuiModificaPaziente p)`

Classe che modifica un paziente.

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	<code>mouseClicked(java.awt.event.MouseEvent arg0)</code> Metodo che disegna l'interfaccia per la modifica di un cliente.
void	<code>mouseEntered(java.awt.event.MouseEvent arg0)</code>
void	<code>mouseExited(java.awt.event.MouseEvent arg0)</code>
void	<code>mousePressed(java.awt.event.MouseEvent arg0)</code>
void	<code>mouseReleased(java.awt.event.MouseEvent arg0)</code>

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Constructor Detail**ModificaPaziente**

```
public ModificaPaziente(GuiModificaPaziente p)
```

Classe che modifica un paziente.

Parameters:

p - the p

Method Detail**mouseClicked**

```
public void mouseClicked(java.awt.event.MouseEvent arg0)
```

Metodo che disegna l'interfaccia per la modifica di un cliente.

Specified by:

mouseClicked in interface java.awt.event.MouseListener

mouseEntered

```
public void mouseEntered(java.awt.event.MouseEvent arg0)
```

Specified by:

mouseEntered in interface java.awt.event.MouseListener

mouseExited

```
public void mouseExited(java.awt.event.MouseEvent arg0)
```

Specified by:

mouseExited in interface java.awt.event.MouseListener

mousePressed

```
public void mousePressed(java.awt.event.MouseEvent arg0)
```

Specified by:

mousePressed in interface java.awt.event.MouseListener

mouseReleased

```
public void mouseReleased(java.awt.event.MouseEvent arg0)
```

Specified by:

mouseReleased in interface java.awt.event.MouseListener

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXI CLASS FRAMES NO FRAMES ALL CLASSES
SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

guiSegretaria

Class ModificaPaziente.effettuaModifiche

java.lang.Object
guiSegretaria.ModificaPaziente.effettuaModifiche
All Implemented Interfaces:
java.awt.event.ActionListener, java.util.EventListener
Enclosing class:
ModificaPaziente

```
public class ModificaPaziente.effettuaModifiche
extends java.lang.Object
implements java.awt.event.ActionListener
```

Classe che effettua le modifiche su un paziente.

Constructor Summary

Constructors

Constructor and Description

effettuaModifiche()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	actionPerformed(java.awt.event.ActionEvent arg0)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

effettuaModifiche

public effettuaModifiche()

Method Detail

actionPerformed

public void actionPerformed(java.awt.event.ActionEvent arg0)

Specified by:

actionPerformed in interface java.awt.event.ActionListener

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES ALL CLASSES
SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

guiSegretaria

Class ModificaPaziente.esci

java.lang.Object
guiSegretaria.ModificaPaziente.esci

All Implemented Interfaces:

java.awt.event.ActionListener, java.util.EventListener

Enclosing class:

ModificaPaziente

```
public class ModificaPaziente.esci
extends java.lang.Object
implements java.awt.event.ActionListener
```

Classe che esce dalla schermata di modifica.

Constructor Summary

Constructors

Constructor and Description

esci()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type Method and Description

void	actionPerformed(java.awt.event.ActionEvent e)
------	---

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

esci

public esci()

Method Detail

actionPerformed

public void actionPerformed(java.awt.event.ActionEvent e)

Specified by:

actionPerformed in interface java.awt.event.ActionListener

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES ALL CLASSES
SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

guiSegretaria

Class ModificaPaziente.resetta

java.lang.Object
 guiSegretaria.ModificaPaziente.resetta

All Implemented Interfaces:

java.awt.event.ActionListener, java.util.EventListener

Enclosing class:

ModificaPaziente

```
public class ModificaPaziente.resetta
extends java.lang.Object
implements java.awt.event.ActionListener
```

Classe che resetta l'inserimento dei dati.

Constructor Summary

Constructors

Constructor and Description

resetta()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type Method and Description

void	actionPerformed(java.awt.event.ActionEvent e)
------	---

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

resetta

public resetta()

Method Detail

actionPerformed

public void actionPerformed(java.awt.event.ActionEvent e)

Specified by:

actionPerformed in interface java.awt.event.ActionListener

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES ALL CLASSES
SUMMARY NESTED | FIELD | CONSTR | METHOD DETAIL FIELD | CONSTR | METHOD

guiSegretaria

Class VisualizzaStorico

java.lang.Object
guiSegretaria.VisualizzaStorico

All Implemented Interfaces:

java.awt.event.MouseListener, java.util.EventListener

```
public class VisualizzaStorico
extends java.lang.Object
implements java.awt.eventMouseListener
```

Classe che mostra la lista dello storico delle operazioni.

Author:

V.Esposito

Nested Class Summary

Nested Classes

Modifier and Type	Class and Description
class	VisualizzaStorico.Esci Classe che esce dalla schermata di storico.

class	VisualizzaStorico.Esci Classe che esce dalla schermata di storico.
-------	---

Constructor Summary

Constructors

Constructor and Description
VisualizzaStorico(GuiModificaPaziente p)

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	getStorico() Metodo che ritorna lo storico di un paziente.
void	modificaPagatoStorico(java.lang.String codice, boolean stato) Classe che modifica il pagamento nello storico.
void	mouseClicked(java.awt.event.MouseEvent arg0) Metodo che mostra l'interfaccia di visualizzazione storico.
void	mouseEntered(java.awt.event.MouseEvent arg0)
void	mouseExited(java.awt.event.MouseEvent arg0)

```
void mousePressed(java.awt.event.MouseEvent arg0)
void mouseReleased(java.awt.event.MouseEvent arg0)
javax.swing.JPanel pannelloRicerca()
Metodo che crea il frame con la lista dello storico.
```

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Constructor Detail

VisualizzaStorico

```
public VisualizzaStorico(GuiModificaPaziente p)
```

Method Detail

mouseClicked

```
public void mouseClicked(java.awt.event.MouseEvent arg0)
```

Metodo che mostra l'interfaccia di visualizzazione storico.

Specified by:

mouseClicked in interface java.awt.event.MouseListener

pannelloRicerca

```
public javax.swing.JPanel pannelloRicerca()
```

Metodo che crea il frame con la lista dello storico.

modificaPagatoStorico

```
public void modificaPagatoStorico(java.lang.String codice,
                                    boolean stato)
```

Classe che modifica il pagamento nello storico.

Parameters:

codice - the codice

stato - the stato

getStorico

```
public void getStorico()
```

Metodo che ritorna lo storico di un paziente.

mouseEntered

```
public void mouseEntered(java.awt.event.MouseEvent arg0)
```

Specified by:

mouseEntered in interface java.awt.event.MouseListener

Specified by:
mouseEntered in interface java.awt.event.MouseListener

mouseExited

public void mouseExited(java.awt.event.MouseEvent arg0)

Specified by:
mouseExited in interface java.awt.event.MouseListener

mousePressed

public void mousePressed(java.awt.event.MouseEvent arg0)

Specified by:
mousePressed in interface java.awt.event.MouseListener

mouseReleased

public void mouseReleased(java.awt.event.MouseEvent arg0)

Specified by:
mouseReleased in interface java.awt.event.MouseListener

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES ALL CLASSES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

guiSegretaria

Class GuiListaPazienti.RicercaPaziente

java.lang.Object
 guiSegretaria.GuiListaPazienti.RicercaPaziente

All Implemented Interfaces:

java.awt.event.ActionListener, java.util.EventListener

Enclosing class:

GuiListaPazienti

```
public class GuiListaPazienti.RicercaPaziente
extends java.lang.Object
implements java.awt.event.ActionListener
```

Classe che ricerca un paziente.

Constructor Summary

Constructors

Constructor and Description

RicercaPaziente()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	actionPerformed(java.awt.event.ActionEvent arg0)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

RicercaPaziente

public RicercaPaziente()

Method Detail

actionPerformed

```
public void actionPerformed(java.awt.event.ActionEvent arg0)  
Specified by:  
actionPerformed in interface java.awt.event.ActionListener
```

2. Dispositivo Android



Documentazione Gestione Appuntamento
Documentazione Gestione Utente

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.manager

Class Summary

Class	Description
AppuntamentiDottoriMenager	Menager utilizzato per interrogare il web service su informazioni che riguardano i dottori (dati di quest'ultimi e appuntamenti in una determinata data).

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.manager

Class AppuntamentiDottoriMenager

java.lang.Object
com.project.fulldentclientandroid.manager.AppuntamentiDottoriMenager

```
public class AppuntamentiDottoriMenager  
extends java.lang.Object
```

Menager utilizzato per interrogare il web service su informazioni che riguardano i dottori (dati di quest'ultimi e appuntamenti in una determinata data).

Author:

ginofarisano

See Also:

dottori

Constructor Summary

Constructors

Constructor and Description

AppuntamentiDottoriMenager()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type

Method and Description

```
java.util.ArrayList<com.project.fulldentclientandroid.bean.Dottore> getLisDottori(java.lang.String string,  
java.lang.String date)
```

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Constructor Detail

AppuntamentiDottoriMenager

```
public AppuntamentiDottoriMenager()
```

Method Detail

getLisDottori

```
public java.util.ArrayList<com.project.fulldentclientandroid.bean.Dottore> getLisDottori(java.lang.String string,  
java.lang.String date)
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.manager

Class Summary

Class	Description
AppuntamentiMenager	Gestisce gli appuntamenti dell'utente

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.manager

Class AppuntamentiMenager

java.lang.Object
com.project.fulldentclientandroid.manager.AppuntamentiMenager

```
public class AppuntamentiMenager  
extends java.lang.Object
```

Gestisce gli appuntamenti dell'utente

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description

```
AppuntamentiMenager()
```

Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type	Method and Description	
boolean	checkIfisValid(java.lang.String ora, java.lang.String durata, java.util.ArrayList<com.project.fulldentclientandroid.bean.Appuntamento> appuntamenti)	
	Controlla se la visita che vuole prenotare l'utente Ã“ compatibile con quelle giÃ presenti nel database	
boolean	deleteAppuntamento(java.lang.String url)	
	Elimina l'ultimo appuntamento a cui deve presentarsi l'utente	
com.project.fulldentclientandroid.bean.Visita	prossimoAppuntamento(java.lang.String url)	
	Restituisce il prossimo appuntamento a cui dovrÃ presentarsi l'utente.	
boolean	sendNewAppuntamento(java.lang.String string, com.project.fulldentclientandroid.bean.Prenotazione prenotazione)	
	Invia un nuovo appuntamento al web service	

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Detail

deleteAppuntamento

public boolean deleteAppuntamento(java.lang.String url)

Elimina l'ultimo appuntamento a cui deve presentarsi l'utente

Parameters:

url -

Returns:

prossimoAppuntamento

public com.project.fulldentclientandroid.bean.Visita prossimoAppuntamento(java.lang.String url)

Restituisce il prossimo appuntamento a cui dovrÃ presentarsi l'utente. La gestione della data corrente Ã“ delegata al server

Parameters:

url -

Returns:

Visita

checkIfisValid

```
public boolean checkIfisValid(java.lang.String ora,
                             java.lang.String durata,
                             java.util.ArrayList<com.project.fulldentclientandroid.bean.Appuntamento> appuntamenti)
```

Controlla se la visita che vuole prenotare l'utente Ã  compatibile con quelle giÃ presenti nel database

Parameters:

ora -

durata -

appuntamenti -

Returns:

boolean

sendNewAppuntamento

```
public boolean sendNewAppuntamento(java.lang.String string,
                                    com.project.fulldentclientandroid.bean.Prenotazione prenotazione)
```

Invia un nuovo appuntamento al web service

Parameters:

string -

prenotazione -

Returns:

boolean

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.bean

Class Summary

Class	Description
Appuntamento	Bean appuntamento utilizzato per visualizzare gli orari non disponibili al momento della prenotazione

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.bean

Class Appuntamento

java.lang.Object
com.project.fulldentclientandroid.bean.Appuntamento

```
public class Appuntamento
extends java.lang.Object
```

Bean appuntamento utilizzato per visualizzare gli orari non disponibili al momento della prenotazione

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description

Appuntamento()

Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type	Method and Description	
java.lang.String	getDurata()	
java.lang.String	getOra()	
void	setDurata(java.lang.String durata)	
void	setOra(java.lang.String ora)	
Methods inherited from class java.lang.Object		
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait		

Constructor Detail

Appuntamento
public Appuntamento()

Method Detail

getOra
public java.lang.String getOra()
setOra
public void setOra(java.lang.String ora)
getDurata
public java.lang.String getDurata()
setDurata
public void setDurata(java.lang.String durata)

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

Package com.project.fulldentclientandroid.activity

Class Summary
Class
CalendarioActivity

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.activity

Class CalendarioActivity

java.lang.Object
Activity
com.project.fulldentclientandroid.activity.CalendarioActivity

```
public class CalendarioActivity  
extends Activity
```

Permette di selezionare una data per fissare un appuntamento

Author:

ginofarisano

See Also:

MainActivityPrenotazione

Constructor Summary

Constructors

Constructor and Description

CalendarioActivity()

Method Summary

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

CalendarioActivity

```
public CalendarioActivity()
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.util

Class Summary

Class	Description
Costanti	Costanti utilizzate per parole ricorrenti da usare nell'applicazione

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

com.project.fulldentclientandroid.util

Class Costanti

```
java.lang.Object
  com.project.fulldentclientandroid.util.Costanti
```

```
public class Costanti
extends java.lang.Object
```

Costanti utilizzate per parole ricorrenti da usare nell'applicazione

Author:

ginofarisano

Field Summary**Fields**

Modifier and Type	Field and Description
static int	CAMPARI_ERRATTI
static int	CAMPARI_VUOTI_NOCHIOCCIOLA
static java.lang.String	CONFERMA Messaggi vari utilizzati all'interno di toast o dialogs
static java.lang.String	CONFERMA_ELIMINAZIONE
static java.lang.String	CONFERMAPRENOTAZIONE
static java.lang.String	CREDENZIALI Extras salvabili nelle preferenze
static int	DATE
static java.lang.String	ERROR
static java.lang.String	ERRORDATE
static java.lang.String	ERRORDATEAFTERTODAY
static java.lang.String	ERRORPRENOTAZIONE
static java.lang.String	EXTRA_COD_FISC
static java.lang.String	EXTRA_IND
static java.lang.String	EXTRA_MAIL
static java.lang.String	EXTRA_NAME
static java.lang.String	EXTRA_PASS
static java.lang.String	EXTRA_SURNAME
static java.lang.String	EXTRA_TEL
static java.lang.String	MSG
static int	NO_INTERNET Costanti numeriche utilizzate per gestire le chiamate delle varie dialogs
static int	NOTHING

static int	NOTHING
static java.lang.String	RICHIESTADATI1 Tutte le chiamate al web service.
static java.lang.String	RICHIESTADATI10
static java.lang.String	RICHIESTADATI11
static java.lang.String	RICHIESTADATI2
static java.lang.String	RICHIESTADATI3
static java.lang.String	RICHIESTADATI4
static java.lang.String	RICHIESTADATI5
static java.lang.String	RICHIESTADATI6
static java.lang.String	RICHIESTADATI7
static java.lang.String	RICHIESTADATI8
static java.lang.String	RICHIESTADATI9
static java.lang.String	SECTION1 Sezione utilizzate nella sezione gestione utente
static java.lang.String	SECTION2
static java.lang.String	SECTION3
static int	SELEZIONA_SERVIZIO
static int	VERIFICA_CREDENZIALI

Constructor Summary

Constructors

Constructor and Description

Costanti()

Method Summary

Methods inherited from class `java.lang.Object`

`equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Field Detail

NO_INTERNET

`public static final int NO_INTERNET`

Costanti numeriche utilizzate per gestire le chiamate delle varie dialogs

See Also:

[Constant Field Values](#)

CAMPI_VUOTI_NOCHIOCCIOLA

```
public static final int CAMPI_VUOTI_NOCHIOCCIOLA
```

See Also:

Constant Field Values

CAMPI_ERRATI

```
public static final int CAMPI_ERRATI
```

See Also:

Constant Field Values

VERIFICA_CREDENZIALI

```
public static final int VERIFICA_CREDENZIALI
```

See Also:

Constant Field Values

NOTHING

```
public static final int NOTHING
```

See Also:

DATE

```
public static final int DATE
```

See Also:

Constant Field Values

SELEZIONA_SERVIZIO

```
public static final int SELEZIONA_SERVIZIO
```

See Also:

Constant Field Values

CREDENZIALI

```
public static final java.lang.String CREDENZIALI
```

Extras salvabili nelle preferenze

See Also:

Constant Field Values

EXTRA_NAME

```
public static final java.lang.String EXTRA_NAME
```

See Also:

[Constant Field Values](#)

EXTRA_MAIL

```
public static final java.lang.String EXTRA_MAIL
```

See Also:

[Constant Field Values](#)

EXTRA_PASS

```
public static final java.lang.String EXTRA_PASS
```

See Also:

[Constant Field Values](#)

EXTRA_COD_FISC

```
public static final java.lang.String EXTRA_COD_FISC
```

EXTRA_TEL

```
public static final java.lang.String EXTRA_TEL
```

See Also:

[Constant Field Values](#)

EXTRA_IND

```
public static final java.lang.String EXTRA_IND
```

See Also:

[Constant Field Values](#)

EXTRA_SURNAME

```
public static final java.lang.String EXTRA_SURNAME
```

See Also:

[Constant Field Values](#)

CONFERMA

```
public static final java.lang.String CONFERMA
```

Messaggi vari utilizzati all'interno di toast o dialogs

See Also:

[Constant Field Values](#)

CONFERMA_ELIMINAZIONE

```
public static final java.lang.String CONFERMA_ELIMINAZIONE
```

See Also:

Constant Field Values

ERRORDATE

```
public static final java.lang.String ERRORDATE
```

See Also:

Constant Field Values

ERRORDATEAFTERTODAY

```
public static final java.lang.String ERRORDATEAFTERTODAY
```

See Also:

Constant Field Values

MSG

```
public static final java.lang.String MSG
```

See Also:

Constant Field Values

ERROR

```
public static final java.lang.String ERROR
```

See Also:

Constant Field Values

ERRORPRENOTAZIONE

```
public static final java.lang.String ERRORPRENOTAZIONE
```

See Also:

Constant Field Values

CONFERMAPRENOTAZIONE

```
public static final java.lang.String CONFERMAPRENOTAZIONE
```

See Also:

Constant Field Values

SECTION1

```
public static final java.lang.String SECTION1
```

Sezione utilizzate nella sezione gestione utente

See Also:

[Constant Field Values](#)

SECTION2

```
public static final java.lang.String SECTION2
```

See Also:

[Constant Field Values](#)

SECTION3

```
public static final java.lang.String SECTION3
```

See Also:

[Constant Field Values](#)

RICHIESTADATI1

```
public static final java.lang.String RICHIESTADATI1
```

Tutte le chiamate al web service. Costruire la chiamata concatenando RICHIESTADATI₁ (varia a seconda dell'host su cui si lancia il web service) RICHIESTADATI₂ e RICHIESTADATI_i (i da 3 a 11) a seconda del servizio che si vuole chiamare

See Also:

[Constant Field Values](#)

RICHIESTADATI2

```
public static final java.lang.String RICHIESTADATI2
```

See Also:

[Constant Field Values](#)

RICHIESTADATI3

```
public static final java.lang.String RICHIESTADATI3
```

See Also:

[Constant Field Values](#)

RICHIESTADATI4

```
public static final java.lang.String RICHIESTADATI4
```

See Also:

[Constant Field Values](#)

RICHIESTADATI5

```
public static final java.lang.String RICHIESTADATI5
```

See Also:

[Constant Field Values](#)

RICHIESTADATI6

```
public static final java.lang.String RICHIESTADATI6
```

See Also:

[Constant Field Values](#)

RICHIESTADATI7

```
public static final java.lang.String RICHIESTADATI7
```

See Also:

Constant Field Values

RICHIESTADATI8

```
public static final java.lang.String RICHIESTADATI8
```

See Also:

Constant Field Values

RICHIESTADATI9

```
public static final java.lang.String RICHIESTADATI9
```

See Also:

Constant Field Values

RICHIESTADATI10

```
public static final java.lang.String RICHIESTADATI10
```

See Also:

Constant Field Values

RICHIESTADATI11

```
public static final java.lang.String RICHIESTADATI11
```

See Also:

Constant Field Values

Constructor Detail

Costanti

```
public Costanti()
```

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

Package com.project.fulldentclientandroid.util

Class Summary

Class	Description
DateValidator	Funzioni di utilitÃ utilizzate per manipolare le date

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

com.project.fulldentclientandroid.util

Class DateValidator

```
java.lang.Object
  com.project.fulldentclientandroid.util.DateValidator
```

```
public class DateValidator
extends java.lang.Object
```

Funzioni di utilità utilizzate per manipolare le date

Author:

ginefarisano

Constructor Summary**Constructors****Constructor and Description**

DateValidator()

Method Summary**All Methods Instance Methods Concrete Methods**

Modifier and Type	Method and Description
boolean	beforeToday(java.lang.String date) Verifica se la data selezionata è antecedente a quella odierna
java.lang.String	currentTime(java.lang.String format) Restituisce la data corrente
boolean	isThisDateValid(java.lang.String dateToValidate, java.lang.String dateFromat) Controlla validità della data inserita
java.lang.String	modifyFormat(int dayOrMonth) Modifica il mese o il giorno da intero a Stringa (antecedendo lo zero se necessario)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail**DateValidator**

public DateValidator()

Method Detail**isThisDateValid**

public boolean isThisDateValid(java.lang.String dateToValidate, java.lang.String dateFromat)

Controlla validità della data inserita

Parameters:

dateToValidate -

dateFromat -

Returns:

modifyFormat

```
public java.lang.String modifyFormat(int dayOrMonth)

Modifica il mese o il giorno da intero a Stringa (antecedente lo zero se necessario)

Parameters:
dayOrMonth - in formato int

Returns:
dayOrMonth in formato String
```

beforeToday

```
public boolean beforeToday(java.lang.String date)

Verifica se la data selezionata Ã  antecedente a quella odierna

Parameters:
date -

Returns:
boolean
```

currentTime

```
public java.lang.String currentTime(java.lang.String format)

Restituisce la data corrente

Returns:
data in formato string
```

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

Package com.project.fulldentclientandroid.bean

Class Summary

Class	Description
Dottore	Bean dottore contenente informazioni su ciascun dottore compresi gli appuntamenti per il giorno in cui l'utente intende prenotare una vistia

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

com.project.fulldentclientandroid.bean

Class Dottore

java.lang.Object
com.project.fulldentclientandroid.bean.Dottore

```
public class Dottore  
extends java.lang.Object
```

Bean dottore contenente informazioni su ciascun dottore compresi gli appuntamenti per il giorno in cui l'utente intende prenotare una vistia

Author:

gincfarisano

See Also:

Appuntamento

Constructor Summary

Constructors

Constructor and Description

Dottore()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
java.util.ArrayList<com.project.fulldentclientandroid.bean.Appuntamento>	getAppuntamenti()
java.lang.String	getCognome()
java.lang.String	getIdDottore()
java.lang.String	getNome()
void	setAppuntamento(com.project.fulldentclientandroid.bean.
void	setCognome(java.lang.String cognome)
void	setIdDottore(java.lang.String idDottore)
void	setNome(java.lang.String nome)
java.lang.String	toString()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

Dottore

```
public Dottore()
```

Method Detail

getNome

```
public java.lang.String getNome()
```

setNome

```
public void setNome(java.lang.String nome)
```

getCognome

```
public java.lang.String getCognome()
```

setCognome

```
public void setCognome(java.lang.String cognome)
```

getIdDottore

```
public java.lang.String getIdDottore()
```

setIdDottore

```
public void setIdDottore(java.lang.String idDottore)
```

getAppuntamenti

```
public java.util.ArrayList<com.project.fulldentclientandroid.bean.Appuntamento> getAppuntamenti()
```

setAppuntamento

```
public void setAppuntamento(com.project.fulldentclientandroid.bean.Appuntamento appuntamento)
```

toString

```
public java.lang.String toString()
```

Overrides:

`toString` in class `java.lang.Object`

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.engine

Class Summary

Class	Description
Engine	Classe con variabili statiche utilizzata per: -settare e restituire il context dell'applicazione lÃ¬ dove quest'ultimo non Ã" accessibile attraverso l'activity -controllare la presenza della connessione ad internet -salvare le preferenze

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.engine

Class Engine

java.lang.Object
com.project.fulldentclientandroid.engine.Engine

```
public class Engine  
extends java.lang.Object
```

Classe con variabili statiche utilizzata per: -settare e restituire il context dell'applicazione lÃ¬ dove quest'ultimo non Ã" accessibile attraverso l'activity -controllare la presenza della connessione ad internet -salvare le preferenze

Author:

ginofarisano

See Also:

Context, InternetMenager, Preferenze

Constructor Summary

Constructors

Constructor and Description

Engine()

Method Summary

All Methods Static Methods Concrete Methods

Modifier and Type	Method and Description
static Context	getContext()
static com.project.fulldentclientandroid.manager.InternetManager	getInternetManager()
static com.project.fulldentclientandroid.manager.Preferenze	getSharedPreferences()
static void	startApplication(Context c)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

Engine

```
public Engine()
```

Method Detail

startApplication

```
public static void startApplication(Context c)
```

getContext

```
public static Context getContext()
```

getInternetManager

```
public static com.project.fulldentclientandroid.manager.InternetManager getInternetManager()
```

getSharedPreferences

```
public static com.project.fulldentclientandroid.manager.Preferenze getSharedPreferences()
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.activity

Class Summary

Class	Description
FirstActivity	Activity che visualizza un messaggio di benvenuto all'utente loggatosi.

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.activity

Class FirstActivity

java.lang.Object
Activity
com.project.fulldentclientandroid.activity.FirstActivity

```
public class FirstActivity  
extends Activity
```

Activity che visualizza un messaggio di benvenuto all'utente loggatosi. Permette di effettuare due scelte a seconda se l'utente vuole prenotare una nuova visita oppure consultare i suoi dati (storico, prossimo appuntamento)

Author:

gincfarisano

See Also:

MainActivityPrenotazione, GestioneUtenteActivity

Constructor Summary

Constructors

Constructor and Description

FirstActivity()

Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type		Method and Description
void	gestioneUtente(View view)	Lancia l'attività GestioneUtenteActivity
void	logout(View view)	Effettua il logout dell'utente reindirizzando quest'ultimo all'activity LoginActivity
void	prenota(View view)	Lancia l'attività CalendarioActivity
Methods inherited from class java.lang.Object		
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait		

Constructor Detail

FirstActivity

```
public FirstActivity()
```

Method Detail

gestioneUtente

```
public void gestioneUtente(View view)
```

Lancia l'attività GestioneUtenteActivity

Parameters:

View -

See Also:

GestioneUtenteActivity

prenota

```
public void prenota(View view)
```

Lancia l'attività CalendarioActivity

Parameters:

View -

See Also:

CalendarioActivity

logout

```
public void logout(View view)
```

Effettua il logout dell'utente reindirizzando quest'ultimo all'activity LoginActivity

See Also:

Preferenze, LoginActivity

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.app

Class Summary

Class	Description
FullDentApplication	Inizializza oggetti utilizzati dall'applicazione

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.app

Class FullDentApplication

java.lang.Object
Application
com.project.fulldentclientandroid.app.FullDentApplication

```
public class FullDentApplication  
extends Application
```

Inizializza oggetti utilizzati dall'applicazione

Author:

ginofarisano

See Also:

Engine

Constructor Summary

Constructors

Constructor and Description

FullDentApplication()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type Method and Description

void onCreate()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

FullDentApplication

public FullDentApplication()

Method Detail

onCreate

public void onCreate()

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.manager

Class Summary

Class Description

GestioneUtenteMenager Utilizzato per gestire e manipolare i dati dell'utente

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.manager

Class GestioneUtenteMenager

java.lang.Object
com.project.fulldentclientandroid.manager.GestioneUtenteMenager

public class GestioneUtenteMenager
extends java.lang.Object

Utilizzato per gestire e manipolare i dati dell'utente

Author:

ginefarisano

Constructor Summary

Constructors

Constructor and Description

GestioneUtenteMenager()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
boolean	modifyData(java.lang.String url, com.project.fulldentclientandroid.bean.Utente utente)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

GestioneUtenteMenager

public GestioneUtenteMenager()

Method Detail

modifyData

public boolean modifyData(java.lang.String url,
com.project.fulldentclientandroid.bean.Utente utente)

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.manager

Class Summary

Class Description

InternetManager Classe utilizzata per verificare la presenza della connessione ad internet

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.manager

Class InternetManager

java.lang.Object
com.project.fulldentclientandroid.manager.InternetManager

public class InternetManager
extends java.lang.Object

Classe utilizzata per verificare la presenza della connessione ad internet

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description

InternetManager(Context c)

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
boolean	checkConnection()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

InternetManager

```
public InternetManager(Context c)
```

Method Detail

checkConnection

```
public boolean checkConnection()
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.util

Class Summary

Class Description

JsonReader	Varie funzioni di utilitÃ per la lettura di dati in formato json
------------	--

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.util

Class JsonReader

java.lang.Object
com.project.fulldentclientandroid.util.JsonReader

```
public class JsonReader  
extends java.lang.Object
```

Varie funzioni di utilitÃ per la lettura di dati in formato json

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description

JsonReader()

Method Summary

All Methods	Static Methods	Concrete Methods
Modifier and Type	Method and Description	
static JSONArray	readJsonArrayFromUrl(java.lang.String url) Restituisce un array json	
static JSONObject	readJsonFromUrl(java.lang.String url) Restituisce un oggetto json	
Methods inherited from class java.lang.Object		
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait		

Constructor Detail

JsonReader

public JsonReader()

Method Detail

readJsonFromUrl
public static JSONObject readJsonFromUrl(java.lang.String url) throws java.io.IOException, JSONException
Restituisce un oggetto json
Parameters:
url -
Returns:
object in formato json
Throws:
java.io.IOException
JSONException

readJsonArrayFromUrl
public static JSONArray readJsonArrayFromUrl(java.lang.String url) throws java.io.IOException, JSONException
Restituisce un array json
Parameters:
url -
Returns:
array in formato json
Throws:
java.io.IOException
JSONException

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.manager

Class Summary

Class	Description
Login	classe per gestire l'autenticazione

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.manager

Class Login

java.lang.Object
com.project.fulldentclientandroid.manager.Login

public class Login
extends java.lang.Object

classe per gestire l'autenticazione

Author:

ginofarisano

See Also:

Utente

Constructor Summary

Constructors

Constructor and Description

Login(java.lang.String mail, java.lang.String password)

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.manager

Class Login

java.lang.Object
com.project.fulldentclientandroid.manager.Login

public class Login
extends java.lang.Object

classe per gestire l'autenticazione

Author:

ginofarisano

See Also:

Utente

Constructor Summary

Constructors

Constructor and Description

Login(java.lang.String mail, java.lang.String password)

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
boolean	campivuoti()
java.lang.String	getMail()
java.lang.String	getPassword()
boolean	noChiocciola()
	controllo blando sulla mail se non Ã" presente la chiocciola nel campo mail non puÃ² essere una mail
void	setMail(java.lang.String mail)
void	setPassword(java.lang.String password)
com.project.fulldentclientandroid.bean.Utente	verifica() Verifica se l'utente Ã" presente nel database e in caso affermativo restituisce il bean contenente tutte le sue informazioni.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Detail

getMail

```
public java.lang.String getMail()
```

setMail

```
public void setMail(java.lang.String mail)
```

getPassword

```
public java.lang.String getPassword()
```

setPassword

```
public void setPassword(java.lang.String password)
```

verifica

```
public com.project.fulldentclientandroid.bean.Utente verifica()
```

Verifica se l'utente Ã" presente nel database e in caso affermativo restituisce il bean contenente tutte le sue informazioni. Se tutti i campi del bean sono vuoti significa che l'utente non Ã" presente nel database quindi restituisce null

Returns:

Utente

See Also:

Utente

campivuoti

```
public boolean campivuoti()
```

noChiocciola

```
public boolean noChiocciola()
```

controllo blando sulla mail se non Ã" presente la chiocciola nel campo mail non puÃ² essere una mail

Returns:

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.activity

Class Summary

Class	Description
LoginActivity	Utilizzata per effettuare il login

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.activity

Class LoginActivity

java.lang.Object
Activity
com.project.fulldentclientandroid.activity.LoginActivity

```
public class LoginActivity  
extends Activity
```

Utilizzata per effettuare il login

Author:
ginofarisano

Constructor Summary

Constructors

Constructor and Description

LoginActivity()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	info (View view) Utilizzato per visualizzare informazioni sull'app

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

LoginActivity

```
public LoginActivity()
```

Constructor Detail

LoginActivity

```
public LoginActivity()
```

Method Detail

info

```
public void info(View view)
```

Utilizzato per visualizzare informazioni sull'app

Parameters:

View -

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

Package com.project.fulldentclientandroid.activity

Class Summary

Class	Description
MainActivityPrenotazione	Activity per la prenotazione di un nuovo appuntamento.
MainActivityPrenotazione.PlaceholderFragment	Un placeholder fragment che crea dinamicamente tante view quanti sono i dottori che operano nel centro.

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#)

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.activity

Class MainActivityPrenotazione

```
java.lang.Object
    com.project.fulldentclientandroid.activity.MainActivityPrenotazione
```

```
public class MainActivityPrenotazione
extends java.lang.Object
```

Activity per la prenotazione di un nuovo appuntamento. Permette di scegliere un orario e un dottore con il quale effettuare la visita

Author:

ginofarisano

Nested Class Summary

Nested Classes

Modifier and Type	Class and Description
static class	MainActivityPrenotazione.PlaceholderFragment Un placeholder fragment che crea dinamicamente tante view quanti sono i dottori che operano nel centro.
class	MainActivityPrenotazione.SectionsPagerAdapter A FragmentPagerAdapter that returns a fragment corresponding to one of the sections/tabs/pages.

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	onTabReselected(android.support.v7.app.ActionBar.Tab tab, android.support.v4.app.FragmentTransaction fragmentTransaction)
void	onTabSelected(android.support.v7.app.ActionBar.Tab tab, android.support.v4.app.FragmentTransaction fragmentTransaction)
void	onTabUnselected(android.support.v7.app.ActionBar.Tab tab, android.support.v4.app.FragmentTransaction fragmentTransaction)
void	prenota(View view)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Detail

prenota

```
public void prenota(View view)
```

onTabSelected

```
public void onTabSelected(android.support.v7.app.ActionBar.Tab tab,  
                           android.support.v4.app.FragmentTransaction fragmentTransaction)
```

onTabUnselected

```
public void onTabUnselected(android.support.v7.app.ActionBar.Tab tab,  
                           android.support.v4.app.FragmentTransaction fragmentTransaction)
```

onTabReselected

```
public void onTabReselected(android.support.v7.app.ActionBar.Tab tab,  
                           android.support.v4.app.FragmentTransaction fragmentTransaction)
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fullidentclientandroid.activity

Class MainActivityPrenotazione.PlaceholderFragment

java.lang.Object
 com.project.fullidentclientandroid.activity.MainActivityPrenotazione.PlaceholderFragment

Enclosing class:

MainActivityPrenotazione

```
public static class MainActivityPrenotazione.PlaceholderFragment  
extends java.lang.Object
```

Un placeholder fragment che crea dinamicamente tante view quante sono i dottori che operano nel centro. Le textview contenute al suo interno vengono colorate di rosso se l'orario di prenotazione non Ã disponibile

Constructor Summary

Constructors

Constructor and Description

PlaceholderFragment()

Method Summary

All Methods Static Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
	<code>static MainActivityPrenotazione.PlaceholderFragment newInstance(int sectionNumber, Context context)</code> Returns a new instance of this fragment for the given section number.
View	<code>onCreateView(LayoutInflater inflater, ViewGroup container, Bundle savedInstanceState)</code>
Methods inherited from class java.lang.Object	
<code>equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait</code>	

Constructor Detail

PlaceholderFragment

```
public PlaceholderFragment()
```

Method Detail

newInstance

```
public static MainActivityPrenotazione.PlaceholderFragment newInstance(int sectionNumber,
Context context)
```

Returns a new instance of this fragment for the given section number.

Parameters:

context -

onCreateView

```
public View onCreateView(LayoutInflater inflater,
ViewGroup container,
Bundle savedInstanceState)
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.activity

Interface Summary

Interface Description

`NavigationDrawerFragment.NavigationDrawerCallbacks` Callbacks interface that all activities using this fragment must implement.

Class Summary

Class Description

`NavigationDrawerFragment` Fragment used for managing interactions for and presentation of a navigation drawer.

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

com.project.fulldentclientandroid.activity

Class NavigationDrawerFragment

```
java.lang.Object
  com.project.fulldentclientandroid.activity.NavigationDrawerFragment
```

```
public class NavigationDrawerFragment
extends java.lang.Object
```

Fragment used for managing interactions for and presentation of a navigation drawer. See the design guidelines for a complete explanation of the behaviors implemented here.

Nested Class Summary**Nested Classes**

Modifier and Type	Class and Description
static interface	NavigationDrawerFragment.NavigationDrawerCallbacks Callbacks interface that all activities using this fragment must implement.

Constructor Summary**Constructors****Constructor and Description**

```
NavigationDrawerFragment()
```

Method Summary**All Methods** **Instance Methods** **Concrete Methods**

Modifier and Type	Method and Description
boolean	isDrawerOpen()
void	onActivityCreated(Bundle savedInstanceState)
void	onAttach(Activity activity)
void	onConfigurationChanged(Configuration newConfig)
void	onCreate(Bundle savedInstanceState)
void	onCreateOptionsMenu(Menu menu, MenuInflater inflater)
View	onCreateView(LayoutInflater inflater, ViewGroup container, Bundle savedInstanceState)
void	onDetach()
boolean	onOptionsItemSelected(MenuItem item)
void	onSaveInstanceState(Bundle outState)
void	setUp(int fragmentId, android.support.v4.widget.DrawerLayout drawerLayout) Users of this fragment must call this method to set up the navigation drawer interactions.

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Constructor Detail

NavigationDrawerFragment

```
public NavigationDrawerFragment()
```

Method Detail

onCreate

```
public void onCreate(Bundle savedInstanceState)
```

onActivityCreated

```
public void onActivityCreated(Bundle savedInstanceState)
```

onCreateView

```
public View onCreateView(LayoutInflater inflater,
                        ViewGroup container,
                        Bundle savedInstanceState)
```

isDrawerOpen

```
public boolean isDrawerOpen()
```

setUp

```
public void setUp(int fragmentId,
                  android.support.v4.widget.DrawerLayout drawerLayout)
```

Users of this fragment must call this method to set up the navigation drawer interactions.

Parameters:

fragmentId - The android:id of this fragment in its activity's layout.

drawerLayout - The DrawerLayout containing this fragment's UI.

onAttach

```
public void onAttach(Activity activity)
```

```
onDetach  
  
public void onDetach()  
  
onSaveInstanceState  
  
public void onSaveInstanceState(Bundle outState)  
  
onConfigurationChanged  
  
public void onConfigurationChanged(Configuration newConfig)  
  
onCreateOptionsMenu  
  
public void onCreateOptionsMenu(Menu menu,  
                               MenuInflater inflater)
```

```
onOptionsItemSelected  
  
public boolean onOptionsItemSelected(MenuItem item)
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.activity

Interface NavigationDrawerFragment.NavigationCallbacks

Enclosing class:

NavigationDrawerFragment

```
public static interface NavigationDrawerFragment.NavigationCallbacks
```

Callbacks interface that all activities using this fragment must implement.

Method Summary

All Methods Instance Methods Abstract Methods

Modifier and Type	Method and Description
void	onNavigationDrawerItemSelected(int position) Called when an item in the navigation drawer is selected.

Method Detail

onNavigationDrawerItemSelected

```
void onNavigationDrawerItemSelected(int position)
```

Called when an item in the navigation drawer is selected.

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.manager

Class Summary

Class	Description
Preferenze	Classe utilizzata per gestire le preferenze.

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.manager

Class Preferenze

java.lang.Object
com.project.fulldentclientandroid.manager.Preferenze

```
public class Preferenze  
extends java.lang.Object
```

Classe utilizzata per gestire le preferenze. In particolar modo utilizzata per memorizzare mail e password così da non reinserire quest'ultimi ad ogni accesso

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description

Preferenze(Context context)

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
java.lang.String	getString(java.lang.String extra) Restituisce il valore di un parametro precedentemente salvato
void	savePreferences(java.lang.String what, java.lang.String value) Salva le preferenze

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

Preferenze

```
public Preferenze(Context context)
```

Method Detail

savePreferences

```
public void savePreferences(java.lang.String what,  
                           java.lang.String value)
```

Salva le preferenze

Parameters:

what - cosa si vuole memorizzare (utilizzare la classe Costanti)

value - valore del parametro memorizzato

See Also:

Costanti

getString

```
public java.lang.String getString(java.lang.String extra)
```

Restituisce il valore di un parametro precedentemente salvato

Parameters:

extra - nome del parametro salvato

Returns:

value parametro salvato

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

Package com.project.fulldentclientandroid.bean

Class Summary

Class	Description
Prenotazione	Bean Prenotazione utilizzato per inviare al web service informazioni riguardanti la visita prenotata

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#)

SUMMARY: NESTED | FIELD | CONSTR | METHOD | DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.bean

Class Prenotazione

java.lang.Object
com.project.fulldentclientandroid.bean.Prenotazione

```
public class Prenotazione  
extends java.lang.Object
```

Bean Prenotazione utilizzato per inviare al web service informazioni riguardanti la visita prenotata

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description

Prenotazione()

Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type	Method and Description	
java.lang.String	getCodiceFiscale()	
java.lang.String	getData()	
java.lang.String	getIdPersonale()	
java.lang.String	getIdPrestazione()	
java.lang.String	getOra()	
void	setCodiceFiscale(java.lang.String codiceFiscale)	
void	setData(java.lang.String data)	
void	setIdPersonale(java.lang.String idPersonale)	
void	setIdPrestazionee(java.lang.String idPrestazione)	
void	setOra(java.lang.String ora)	
java.lang.String	toString()	

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

Prenotazione

```
public Prenotazione()
```

Method Detail

getCodiceFiscale

```
public java.lang.String getCodiceFiscale()
```

setCodiceFiscale

```
public void setCodiceFiscale(java.lang.String codiceFiscale)
```

getIdPrestazione

```
public java.lang.String getIdPrestazione()
```

setIdPrestazionee

```
public void setIdPrestazionee(java.lang.String idPrestazione)
```

getIdPersonale

```
public java.lang.String getIdPersonale()
```

setIdPersonale

```
public void setIdPersonale(java.lang.String idPersonale)
```

getData

```
public java.lang.String getData()
```

```
setData  
  
public void setData(java.lang.String data)
```

```
getOra  
  
public java.lang.String getOra()
```

```
setOra  
  
public void setOra(java.lang.String ora)
```

```
toString  
  
public java.lang.String toString()  
  
Overrides:  
toString in class java.lang.Object
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.activity

Class Summary

Class	Description
ProssimoAppuntamentoActivity	Visualizza informazioni sull'ultimo appuntamento al quale l'utente deve presentarsi

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.activity

Class ProssimoAppuntamentoActivity

java.lang.Object
Activity
com.project.fulldentclientandroid.activity.ProssimoAppuntamentoActivity

```
public class ProssimoAppuntamentoActivity  
extends Activity
```

Visualizza informazioni sull'ultimo appuntamento al quale l'utente deve presentarsi

Author:

ginofarisan0

Constructor Summary

Constructors

Constructor and Description

ProssimoAppuntamentoActivity()

Method Summary

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

ProssimoAppuntamentoActivity

public ProssimoAppuntamentoActivity()

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentandroid.adapter

Class Summary

Class

Description

ServiziAdapter

Adapeter utilizzato per popolare la listview contenente i servizi offerti dal centro

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentandroid.adapter

Class ServiziAdapter

java.lang.Object
<any>

com.project.fulldentandroid.adapter.ServiziAdapter

public class ServiziAdapter
extends <any>

Adapeter utilizzato per popolare la listview contenente i servizi offerti dal centro

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description

ServiziAdapter(Context context, int textViewResourceId,
java.util.List<com.project.fulldentclientandroid.bean.Servizio> objects)

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
View	getView(int position, View convertView, ViewGroup parent)
View	getViewOptimize(int position, View convertView, ViewGroup parent)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

ServiziAdapter

```
public ServiziAdapter(Context context,
                      int textViewResourceId,
                      java.util.List<com.project.fulldentclientandroid.bean.Servizio> objects)
```

Method Detail

getView

```
public View getView(int position,
                   View convertView,
                   ViewGroup parent)
```

getViewOptimize

```
public View getViewOptimize(int position,
                           View convertView,
                           ViewGroup parent)
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.manager

Class Summary

Class Description

ServiziMenager	Restituisce informazioni sui servizi fruibili nel centro dentistico
----------------	---

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.manager

Class ServiziMenager

java.lang.Object
com.project.fulldentclientandroid.manager.ServiziMenager

```
public class ServiziMenager  
extends java.lang.Object
```

Restituisce informazioni sui servizi fruibili nel centro dentistico

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description

ServiziMenager()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type

Method and Description

```
java.util.ArrayList<com.project.fulldentclientandroid.bean.Servizio> getSerVizi(java.lang.String url)  
Restituisce una lista di servizi
```

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

ServiziMenager

```
public ServiziMenager()
```

Method Detail

getSerVizi

```
public java.util.ArrayList<com.project.fulldentclientandroid.bean.Servizio> getSerVizi(java.lang.String url)
```

Restituisce una lista di servizi

Parameters:

url - del servizio richiesto

Returns:

arraylist dei servizi

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.bean

Class Summary

Class	Description
Servizio	Bean servizio utilizzato per visualizzare i servizi friubili nel centro dentistico

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES
SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.bean

Class Servizio

java.lang.Object
com.project.fulldentclientandroid.bean.Servizio

```
public class Servizio  
extends java.lang.Object
```

Bean servizio utilizzato per visualizzare i servizi friubili nel centro dentistico

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description

Servizio()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
java.lang.String	getCosto()
java.lang.String	getDurata()
java.lang.String	getIdPrestazione()
java.lang.String	getNome()
void	setCosto(java.lang.String costo)
void	setDurata(java.lang.String durata)
void	setIdPrestazione(java.lang.String idPrestazione)
void	setNome(java.lang.String nome)
java.lang.String	toString()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

Servizio

```
public Servizio()
```

Method Detail

getNome

```
public java.lang.String getNome()
```

setNome

```
public void setNome(java.lang.String nome)
```

getCosto

```
public java.lang.String getCosto()
```

setCosto

```
public void setCosto(java.lang.String costo)
```

getDurata

```
public java.lang.String getDurata()
```

setDurata

```
public void setDurata(java.lang.String durata)
```

getIdPrestazione

```
public java.lang.String getIdPrestazione()
```

setIdPrestazione

```
public void setIdPrestazione(java.lang.String idPrestazione)
```

toString

```
public java.lang.String toString()
```

Overrides:

toString in class java.lang.Object

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.activity

Class Summary

Class	Description
SplashActivity	Prima activity mostrata al lancio del programma.

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.activity

Class SplashActivity

java.lang.Object
Activity
com.project.fulldentclientandroid.activity.SplashActivity

```
public class SplashActivity  
extends Activity
```

Prima activity mostrata al lancio del programma. Controlla se l'utente Ã" presente nelle preferenze e in caso affermativo effettua automaticamente il login

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description
SplashActivity()

Method Summary

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

SplashActivity

```
public SplashActivity()
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.manager

Class Summary

Class	Description
StoricoMenager	Classe utilizzata per gestire lo storico delle visite effettuate dall'utente

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.manager

Class StoricoMenager

java.lang.Object
com.project.fulldentclientandroid.manager.StoricoMenager

public class StoricoMenager
extends java.lang.Object

Classe utilizzata per gestire lo storico delle visite effettuate dall'utente

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description

StoricoMenager()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
java.util.List	getStorico(java.lang.String url)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

StoricoMenager

public StoricoMenager()

Method Detail

getStorico

public java.util.List getStorico(java.lang.String url)

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.bean

Class Summary

Class	Description
Utente	

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.bean

Class Utente

java.lang.Object
com.project.fulldentclientandroid.bean.Utente

public class Utente
extends java.lang.Object

Author:

ginofarisano bean contenente informazioni sull'utente. Il metodo `toString()` è stato riscritto per creare automaticamente un file json da mandare al server

Constructor Summary

Constructors

Constructor and Description

Utente()

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
java.lang.String	getCodiceFiscale()
java.lang.String	getCognome()
java.lang.String	getEmail()
java.lang.String	getIndirizzo()
java.lang.String	getNome()
java.lang.String	getPassword()
java.lang.String	getTelefono()
void	setCodiceFiscale(java.lang.String codiceFiscale)
void	setCognome(java.lang.String cognome)
void	setEmail(java.lang.String email)
void	setIndirizzo(java.lang.String indirizzo)
void	setNome(java.lang.String nome)
void	setPassword(java.lang.String password)
void	setTelefono(java.lang.String telefono)
java.lang.String	toString()

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, wait, wait, wait
```

Constructor Detail**Utente**

```
public Utente()
```

Method Detail**getCodiceFiscale**

```
public java.lang.String getCodiceFiscale()
```

setCodiceFiscale

```
public void setCodiceFiscale(java.lang.String codiceFiscale)
```

getNome

```
public java.lang.String getNome()
```

setNome

```
public void setNome(java.lang.String nome)
```

getCognome

```
public java.lang.String getCognome()
```

setCognome

```
public void setCognome(java.lang.String cognome)
```

getTelefono

```
public java.lang.String getTelefono()
```

setTelefono

```
public void setTelefono(java.lang.String telefono)
```

getEmail

```
public java.lang.String getEmail()
```

setEmail

```
public void setEmail(java.lang.String email)
```

getPassword

```
public java.lang.String getPassword()
```

```
setPassword  
public void setPassword(java.lang.String password)
```

```
getIndirizzo  
public java.lang.String getIndirizzo()
```

```
setIndirizzo  
public void setIndirizzo(java.lang.String indirizzo)
```

```
toString  
public java.lang.String toString()
```

Overrides:

```
java.lang.Object.toString()
```

```
setPassword  
public void setPassword(java.lang.String password)
```

```
getIndirizzo  
public java.lang.String getIndirizzo()
```

```
setIndirizzo  
public void setIndirizzo(java.lang.String indirizzo)
```

```
toString  
public java.lang.String toString()
```

Overrides:

```
toString in class java.lang.Object
```

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

Package com.project.fulldentclientandroid.bean

Class Summary

Class	Description
Visita	Bean Visita utilizzato per visualizzare lo storico delle visite effettuate dall'utente

[PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV PACKAGE](#) [NEXT PACKAGE](#) [FRAMES](#) [NO FRAMES](#)

com.project.fulldentclientandroid.bean

Class Visita

```
java.lang.Object  
    com.project.fulldentclientandroid.bean.Visita
```

```
public class Visita  
extends java.lang.Object
```

Bean Visita utilizzato per visualizzare lo storico delle visite effettuate dall'utente

Author:

ginofarisano

Constructor Summary

Constructors

Constructor and Description

Visita()

Method Summary

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
java.lang.String	getCognomePersonale()
java.lang.String	getData()
java.lang.String	getNomePersonale()
java.lang.String	getNomePrestazione()
java.lang.String	getNote()
java.lang.String	getOra()
java.lang.String	getPagato()
void	setCognomePersonale(java.lang.String cognomePersonale)
void	setData(java.lang.String data)
void	setNomePersonale(java.lang.String nomePersonale)
void	setNomePrestazione(java.lang.String nomePrestazione)
void	setNote(java.lang.String note)
void	setOra(java.lang.String ora)
void	setPagato(java.lang.String pagato)

```
java.lang.String           toString()
```

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, wait, wait, wait
```

Constructor Detail

Visita

```
public Visita()
```

Method Detail

getData

```
public java.lang.String getData()
```

setData

```
public void setData(java.lang.String data)
```

getPagato

```
public java.lang.String getPagato()
```

setPagato

```
public void setPagato(java.lang.String pagato)
```

getNote

```
public java.lang.String getNote()
```

setNote

```
public void setNote(java.lang.String note)
```

setNomePrestazione

```
public void setNomePrestazione(java.lang.String nomePrestazione)
```

getNomePrestazione

```
public java.lang.String getNomePrestazione()
```

```
setOra  
  
public void setOra(java.lang.String ora)  
  
getOra  
  
public java.lang.String getOra()  
  
setNomePersonale  
  
public void setNomePersonale(java.lang.String nomePersonale)  
  
getNomePersonale  
  
public java.lang.String getNomePersonale()  
  
setCognomePersonale  
  
public void setCognomePersonale(java.lang.String cognomePersonale)  
  
getCognomePersonale  
  
public java.lang.String getCognomePersonale()  
  
toString  
  
public java.lang.String toString()  
  
Overrides:  
toString in class java.lang.Object
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentclientandroid.activity

Class Summary

Class	Description
VisitaUtenteActivity	

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

com.project.fulldentclientandroid.activity

Class VisitaUtenteActivity

java.lang.Object
Activity
com.project.fulldentclientandroid.activity.VisitaUtenteActivity

```
public class VisitaUtenteActivity  
extends Activity
```

Constructor Summary

Constructors

Constructor and Description

VisitaUtenteActivity()

Method Summary

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

VisitaUtenteActivity

```
public VisitaUtenteActivity()
```

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

Package com.project.fulldentandroid.adapter

Class Summary

Class	Description
VisiteAdapter	Adapeter utilizzato per popolare la listview contenente lo storico dell'utente

PACKAGE CLASS USE TREE DEPRECATED INDEX HELP

PREV PACKAGE NEXT PACKAGE FRAMES NO FRAMES

com.project.fulldentandroid.adapter

Class VisiteAdapter

```
java.lang.Object
  <any>
    com.project.fulldentandroid.adapter.VisiteAdapter
```

```
public class VisiteAdapter
extends <any>
```

Adapeter utilizzato per popolare la listview contenente lo storico dell'utente

Author:

ginofarisano

Constructor Summary**Constructors****Constructor and Description**

```
VisiteAdapter(Context context, int textViewResourceId,
  java.util.List<com.project.fulldentclientandroid.bean.Visita> objects)
```

Method Summary

All Methods	Instance Methods	Concrete Methods
-------------	------------------	------------------

Modifier and Type	Method and Description
-------------------	------------------------

View	getView(int position, View convertView, ViewGroup parent)
------	---

View	getViewOptimize(int position, View convertView, ViewGroup parent)
------	---

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Constructor Detail**VisiteAdapter**

```
public VisiteAdapter(Context context,
  int textViewResourceId,
  java.util.List<com.project.fulldentclientandroid.bean.Visita> objects)
```

Method Detail**getView**

```
public View getView(int position,
  View convertView,
  ViewGroup parent)
```

getViewOptimize

```
public View getViewOptimize(int position,
  View convertView,
  ViewGroup parent)
```