

Extended Data for

Copying explains the collective behavior of AI agents in the wild


Giordano De Marzo, Nicola Alboré and David Garcia




Extended Data Fig. 1: Copying in six models. Fig. 2 with four further open-weight models added to the record (black), gpt-oss-20b (vermilion) and GPT-6.1 Sol (amber): Gemma 4 31B and Gemma 4 26B-A4B (blues), Qwen3.8 27B (purple) and Ministral 3 14B (green), each run on the same 820 stimuli, with the share of each option assigned at random (Supplementary Information S7). (a) Where to write: the probability that a page is chosen against its share of the last 100 lines of the feed. (b) How to sign: the probability that a name carries one of the 16 name features against its share among the task-mates in the feed (record) or among the handles of the feed (laboratory), with feature intercepts. (c) How to write: the probability that a use takes a form against its share on the page (record: first uses of the 16 conventions; laboratory: the uses of the 8 conventions whose share was assigned). Model points are drawn at the bin positions of the record, interpolating between the bins of each model, and offset slightly; bars are 95% confidence intervals; the dashed line is proportionality. Every model chooses pages in proportion to their share of the feed (slopes 0.73 to 0.98) and, except GPT-6.1 Sol, copies the forms of writing close to proportion (0.68 to 0.84); the models differ most in how much they copy names (0.26 to 0.65), that is in the strength of their prior for this choice.




Extended Data Fig. 2: Exposure against shared task conditions. (a) First uses whose page and the other pages of the same task disagree: the share of A among at least three earlier uses on the page and among the last 30 uses of the convention by other handles on the other pages of the same task family lie on opposite sides of one half (shares of exactly one half excluded). Probability that the use follows the page, for the three classes of conventions and pooled, and for name features when the share among the earlier same-task authors of the newcomer's first page and among same-task handles of the previous six hours that wrote on other pages disagree; n in the bars, 95% Wilson intervals. The dotted line at one half is a descriptive reference: the conflicts are a selected subset of uses, and a base rate for a form would move the expected share away from one half. (b) Differences between exposure coefficients, with 95% intervals from the full covariance of the coefficients clustered by handle (Wald contrasts). Filled: the specifications of Table 1, with feature or convention intercepts and task by three-hour intercepts (names 9,728 newcomer–feature records; forms 1,052 first uses). Open: stricter intercepts, feature by task added for names, and one intercept per convention, task and three-hour block for forms, which identifies the coefficients only from first uses with others of the same convention, task and block. Page minus the task's other pages: a joint least-squares fit of the outcome on the shares on the page, on the task's other pages and in the feed (forms, 1,798 first uses with all three shares; names, 6,352 records). The samples and the identifying variation differ between rows, and the rows are not repetitions of one test. (c) Names: feed minus out of view and page minus out of view in the specification of Table 1, with the task-mates born in the previous 1.5, 3, 6 or 12 h (7,136, 8,640, 9,840 and 11,088 records); 95% intervals as in b.



Extended Data Fig. 3: Each convention against the model run at its own fitted priors. For each of the 16 conventions the copy model of Fig. 3 is run 50 times with the prior probabilities μ_A and μ_B fitted on the individual uses of that convention, and nothing else is fitted. Median over the runs (points) against the observed value, with the 10th to 90th percentile of the runs (bars), which is the spread of single realizations of the model, not an uncertainty on the median. (a) Consistency within a page: the probability that two uses on the same page both take the minority form, divided by the same probability for two uses on different pages (16 conventions). (b) Volatility over time: the standard deviation of the share of form A over consecutive blocks of 50 first uses, divided by the binomial standard deviation at the overall share, on each handle's first use in the record and each agent's first use in the model (15 conventions with at least 150 first uses). (c) The final share of form A over all uses (16 conventions). The observed value falls inside the 10th to 90th percentile of its runs for 11 of 16, 13 of 15 and 15 of 16 conventions, with correlations between observed values and model medians of 0.59 (of the logarithms), 0.86 and 0.64. Conventions outside the band are labelled in a and b. Colours give the class of the convention; the dashed line is equality.



Extended Data Fig. 4: Checking in six models. The experiments of Fig. 4a and b for the six laboratory models, on pages made of notes of the record. (a–c) Pages of 0, 1, 3, 7, 11, 19 or 32 notes all giving the wrong value: the probability that the agent opens the source (a), answers right (b), and answers wrong although it opened the source (c), 100 agents per point; the record after the first correction is drawn in a and b (black, dashed, open circles; in a the note cites a source, as in Fig. 4a, and in b it gives the right value). (d–f) Pages of 20 notes of the record, a fraction of which were turned right by writing the right value in place of the wrong one, 100 agents per point. Bars are 95% Wilson intervals. Five of the six models answer right less often as more notes agree on the wrong value. They fail in two ways: gpt-oss-20b and GPT-6.1 Sol stop opening the source, while Gemma 4 31B, Qwen3.8 27B and, less, Ministral 3 14B keep opening it and then give the wrong value of the page (c). A few right notes among the wrong ones restore right answers in these models (e, f). Gemma 4 26B-A4B is unaffected. With synthetic template notes instead of the notes of the record, only gpt-oss-20b is misled (Supplementary Information S7).



Extended Data Fig. 5: Checking before the correction, in the record and in the laboratory. Checking relative to an empty page against the number of notes agreeing on the wrong value: the record before the first correction, when every use gave the padded value (black; the note cites a source; 12 of 55 notes on an empty page, pages with 1–3 and 4 or more agreeing uses, 45 and 60 uses), and the two laboratory models of Fig. 4a (the agent fetches the workbook; 1.00 for both on an empty page). The two measures differ: the laboratory observes the fetch, the record only what the note says. Bars are 95% bootstrap intervals of the ratio (2,000 resamples).