

# [AIMLBD] MACHINE LEARNING, BIG DATA, ARTIFICIAL INTELLIGENCE per medicina e chirurgia high tech

L01: Machine Learning Overview

Dott. Giorgio De Magistris

*demagistris@diag.uniroma1.it*

CORSO DI LAUREA IN MEDICINA E CHIRURGIA HIGH TECH



SAPIENZA  
UNIVERSITÀ DI ROMA

I3S

FACOLTÀ DI INGEGNERIA DELL'INFORMAZIONE, INFORMATICA E STATISTICA

DIAG

DIPARTIMENTO DI INGEGNERIA INFORMATICA, AUTOMATICA E GESTIONALE

TUTTI I DIRITTI RELATIVI AL PRESENTE MATERIALE DIDATTICO ED AL SUO CONTENUTO SONO RISERVATI A SAPIENZA E AI SUOI AUTORI (O DOCENTI CHE LO HANNO PRODOTTO). È CONSENTITO L'USO PERSONALE DELLO STESSO DA PARTE DELLO STUDENTE A FINI DI STUDIO. NE È VIETATA NEL MODO PIÙ ASSOLUTO LA DIFFUSIONE, DUPLICAZIONE, CESSIONE, TRASMISSIONE, DISTRIBUZIONE A TERZI O AL PUBBLICO PENA LE SANZIONI APPLICABILI PER LEGGE


# What is Machine Learning?

A computer program is said to learn from experience  $E$  with respect to some class of tasks  $T$  and performance measure  $P$ , if its performance at tasks in  $T$ , as measured by  $P$ , improves with experience  $E$ .

*Mitchell (1997)*

# Experience

We can partition the ML algorithms into 3 macro categories according to which kind of experience is allowed during training.



## **Supervised Learning Tasks:**



- Classification
- Regression
- ...

## **Unsupervised Learning Tasks:**

- Dimensionality Reduction
- Clustering
- Density Estimation
- ...


# Performance

The performance measure depends on the task, and it is necessary to quantify the ability of the ML algorithm to solve the specific task. It could be a measure of the error to minimize or a score to maximize.





# Data generation process

- Assume data is sampled from an (unknown) probability distribution  $p_{\text{data}}$
- We usually make the “*independent and identically distributed*” (**I.I.D.**) assumption, meaning that each data sample comes from the same distribution  $p_{\text{data}}$  and that samples are independent
- Assume we have a dataset  $D = \{x_1, \dots, x_n\}$ . The independence assumption allows us to factorize the probability of observing the dataset as:
  - $P(D) = P(X_1=x_1, \dots, X_n=x_n) = \prod_{i=1}^n P(X_i=x_i)$
- We also assume that **trainingset**, **validationset** and **testset** are sampled from the same distribution  $p_{\text{data}}$



# Hypotheses Space and Inductive Bias

- The Hypotheses space is the set of all the functions that the ML algorithm is allowed to learn
- The prioritization of some hypotheses (restriction of hypothesis space) is an inductive bias.



# Generalization

- We optimize the ML model on the trainingset in order to minimize the **training error**
- However we are interested in the error on new data, that is not encountered during training
- The error on the testset is called **generalization error** and it quantifies the ability of the model to generalize on unseen data




Image credit: [The Inductive Bias of ML Models, and Why You Should Care About It](#)



# Overfitting and Underfitting

- When training a ML model two things can happen:
  - The model struggles to minimize the training error, this phenomenon is called **Underfitting**
  - The model reaches a small training error, but the gap between training error and generalization error is large, this phenomenon is called **Overfitting**




Image credit: [Deep Learning Book](#)

# Capacity

- I can balance the overfitting and underfitting acting on the model capacity
- The model capacity is the complexity of the model:
  - A model with high capacity can fit a wide range of functions
  - A model with limited capacity can fit a small range of functions
- Usually I have the best generalization error when:
  - the capacity of the model is well proportionate to the task
  - I have a lot of training examples





Image credit: [The Inductive Bias of ML Models, and Why You Should Care About It](#)


# Feature and Feature Vector

- Each data sample is described as a set of features
- A feature is an individual characteristic of the observed object
- Usually it is represented as a real value (even if different types of feature exist, like categorical features or graph features)
- In the case of real valued features, a sample is represented as a vector which components are the values of the features called feature vector




# Features and Task

- I can use many different sets of feature to describe the same object
- Which is the best representation?
- It depends on the task !



# Feature Space

- Once I've chosen a representation, the set of all feature vectors form a Feature Space
- I can represent an object as a vector in the feature space, which coordinates are the values of the features
- Usually a feature space with  $n$  features is represented as the vector space  $\mathbb{R}^n$



# Learning

- In this context, learning means to find a function that maps the input feature space to the desired output
- The feature space must exhibit a sort of structure, otherwise no learning is possible

$$f ( \nearrow ) = \textit{Anemic}$$

# The Curse of Dimensionality

- Assume we represent our objects using  $n$  features, and each feature has  $m$  admissible values
- The feature space has  $m^n$  elements, which is exponential in  $n$
- In general to learn a function over a feature space we need at least a number of samples that is proportional to the size of the feature space
- Hence the number of samples grows exponentially with respect to the dimensionality of the feature space ( $n$ )




Image credit: [Deep Learning Book](#)

# Intrinsic Dimensionality

- How can we learn when the dimensionality of the input is higher than the number of samples?
- Often the input data that comes in an high dimensional space (images, audio, text etc.) but can be represented in a lower dimensional feature space in which learning is feasible
- The intrinsic dimensionality is the minimum number of meaningful dimensions needed to capture the essential characteristics or structure of the data without introducing unnecessary noise or redundancy
- The intrinsic dimensionality of a dataset can be influenced by various factors, such as the type of data (e.g., images, text, time series) and the nature of the problem (e.g., classification, regression)



---

## **Slides distribuite con Licenza Creative Commons (CC BY-NC-ND 4.0) Attribuzione - Non commerciale - Non opere derivate 4.0 Internazionale**

### **PUOI CONDIVIDERLE ALLE SEGUENTI CONDIZIONI**

(riprodurre, distribuire, comunicare o esporre in pubblico, rappresentare, eseguire e recitare questo materiale con qualsiasi mezzo e formato)

#### **Attribuzione\***

Devi riconoscere una menzione di paternità adeguata, fornire un link alla licenza e indicare se sono state effettuate delle modifiche. Puoi fare ciò in qualsiasi maniera ragionevole possibile, ma non con modalità tali da suggerire che il licenziante avalli te o il tuo utilizzo del materiale.

#### **Non Commerciale**

Non puoi utilizzare il materiale per scopi commerciali.

#### **Non opere derivate**

Se remixi, trasformi il materiale o ti basi su di esso, non puoi distribuire il materiale così modificato.

#### **Divieto di restrizioni aggiuntive**

Non puoi applicare termini legali o misure tecnologiche che impongano ad altri soggetti dei vincoli giuridici a questa licenza