secrets-service. API

Brief description

API Host

Host address:	• staging • production NL • production US
Swagger:	http://nl-internal-nginx1.jooble.com/secrets-service/prod/swagger/index.html

Endpoints

GET /api/v1/Info

To check the current status of the service.

Request:	*GET {host_address}/api/v1/Info*
Body parameters:	–
Response parameters:	Information about the current state of the service
Example (request):	**Request**: GET http://nl-internal-nginx1.jooble.com/secrets-service/prod/api/v1/Info

Success response:	**200 OK**
	
	``json
	{
	  "upTime": "8.16:52:54.5800909",
	  "swaggerPath": "/secrets-service/prod/swagger",
	  "viewConfiguartion": "/secrets-service/prod/api/configuration",
	  "reloadConfiguartion": "/secrets-service/prod/api/configuration/reload",
	  "baseDirectory": "/publish/",
	  "currentEnvironment": "Production",
	  "machineName": "secrets-service-blue-jooble-service-chart-598d755b4c-s7f9s",
	  "computerName": "nl-k8s-secrets-service-blue",
	  "releaseInfo": {
	    "branch": "master",
	    "buildNumber": 579
	  },
	  "clientIp": "10.244.0.0",
	  "options": {
	``

```
        "postgres": {
          "host": "",
          "database": "",
          "credentials": null,

      "enableSensitiveDataLogging":
      false,
          "commandTimeout": "00:00:
      30"
        },
        "email": {
          "host": "****.jooble.
      com",
          "port": ******,
          "enableSsl": false,
          "userName":
      "*******@jooble.com",
          "password": "*******"
        },
        "encryption": {
          "supportedDataTypes": [
            "phone",
            "email"
          ],
          "encryptedColumnPrefix":
      "encrypted_"
        },
        "date": {
          "now": null
        }
      }
    }
```

| Error response: | **ERROR CODE** - standard list of API errors |