

Instructions for Authors of SBC Conferences

Papers and Abstracts

Giovani Ferreira¹, Gustavo Coimbra¹, Eduardo San¹

¹CEUB - Centro Universitário de Brasília
Caixa Postal 4488 – 70.904-970 – Brasília – DF – Brazil

Abstract.

Resumo.

1. Introduction

Nowadays, most business operations are supported by IT systems. Therefore, their availability is critical to keep business running smoothly and continuously. In order to provide high quality IT services, a well-managed data center is required to house computer servers, storage systems, network devices, and their associated components. Downtime of the data center can be costly resulting in production and business losses so that the high availability requirement of the data center is needed. Data center always requires a non-stopped service or 24x7 availability. The availability of data center mainly requires the protection of computer equipment and personnel. There are some potential hazards which may occur and impact the availability of data center. Fire is the most potential hazard which can create severe effects on data center. Fire can occur in a data center by mechanical failure, intentional arson, or natural causes. Data Center Physical Security Ontology for Automated Evaluation (Abstract).

Data Center is a facility used for housing a large amount of computer and communications equipment maintained by an organization for the purpose of handling the data necessary for its operations. Glossary of MMC Terminology. Available: [http://msdn.microsoft.com/en-us/library/bb246417\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/bb246417(VS.85).aspx).

2. Related Concepts

2.1. Time

It's important to understand what is time and it's related concepts. For this purpose, the definitions provided by [Kopetz 2011] will be considered:

1. The flow of time is a directed time line that extends from the past into the future.
2. A cut of the time line is called an instant.
3. Any ideal occurrence that happens at an instant is called an event.
4. The present point in time, now, is a very special event that separates the past from the future.
5. An interval on the time line, called a duration, is defined by two events, the start event and the terminating event of the interval.
6. The instant when a result must be produced is called a deadline.

In the context of deadlines, [Kopetz 2011] also provides a good definition, classifying them in three different ways:

1. Soft deadline: If a result has utility even after the deadline has passed,
2. Firm deadline: If a result does not matter after the deadline.
3. Hard deadline: If severe consequences could result if a firm deadline is missed.

2.2. Real-time systems

For [Kopetz 2011], a real-time computer system is a computer system where the correctness of the system behavior depends not only on the logical results of the computations, but also on the physical time when these results are produced. [Lichtenstein et al. 1985] states that a real-time system is a reactive system, that is, it must react to stimuli from its environment within time intervals dictated by its environment. According to [Stankovic and Ramamritham 1990], a real-time computer system can be classified in 2 different ways:

1. Static real-time system: where all deadlines can be guaranteed a priori.
2. Dynamic real-time system: large, complex, distributed, adaptive, contain many types of timing constraints, need to operate in a highly nondeterministic environment, and evolves over a long system lifetime.

The type of the deadline affects the real-time system. If the system must meet at least one hard deadline, it's called a hard real-time computer system. If no hard deadline exists, then the system is called a soft real-time computer system. The design of a hard real-time system is fundamentally different from the design of a soft real-time system. While the first must sustain a guaranteed temporal behavior under all specified load and fault conditions, it is permissible for the second to miss a deadline occasionally [Kopetz 2011]. [Stankovic 1996] also points that hard real-time systems usually cause several consequences, even death, when missed an important deadline.

2.3. Tasks

For [Stankovic 1996] tasks can be classified as:

1. Periodic task: activated every T units. The deadline for each activated instance may be less than, equal to, or greater than the period T .
2. Aperiodic task: activated at unpredictable times.
3. Sporadic task: an aperiodic task with the additional constraint that there is a minimum interarrival time between task activations.

Real-time scheduling is the process of creating start and finish times for sets of tasks such that all timing, precedence, and resource constraints are met.

3. The RTDMS

The RTDMS, that stands for Real Time Datacenter Monitor System, is a real time system aiming to provide a reliable and solid way to measure and monitor the conditions of a datacenter. Using sensors for temperature, humidity and flood, the RTDMS is able to quickly discover adverse conditions in a datacenter and reduce the warning time, so the support team have more time to take the appropriate interventions and avoid worse situations.

3.1. Tasks Model

The RTDMS have the following tasks model:

[Tabela com as tasks]

Comentarios sobre cada task especifica.

3.1.1. Time Restrictions

The RTDMS time restriction is the warning time. In the moment that RTDMS detects an adverse condition, the alarm task must be execute instantly. The failure of this task, not warning or warning with delay, can cause big problems to the owners of the datacenter, including the loss of all data and equipments.

3.1.2. Scalability

The problem of schedule periodic tasks with hard deadlines equal to the task periods is not trivial, being studied in literature since [Liu and Layland 1973], that appoints the rate monotonic, that assigns a higher priority to a task with shorter period, as an optimal fixed priority algorithm.

To calculate if a set of tasks is scalable in Rate Monotonic, it's used the following equation:

[Equacao do Rate Monotonic]

The set of tasks for RTDMS was mathematically proved as scalable:

[Contas de escalonabilidade das tasks do RTDMS]

This set of tasks were submitted to simulation in XXXX(nome da ferramenta) and was proved as scalable:

[Imagem da ferramenta mostrando que eh escalonavel]

4. Experiments and Evaluation

5. Conclusion

Referências

- Kopetz, H. (2011). *Real-time systems: design principles for distributed embedded applications*. Springer Science & Business Media.
- Lichtenstein, O., Pnueli, A., and Zuck, L. (1985). *The glory of the past*. Springer.
- Liu, C. L. and Layland, J. W. (1973). Scheduling algorithms for multiprogramming in a hard-real-time environment. *Journal of the ACM (JACM)*, 20(1):46–61.
- Stankovic, J. A. (1996). Real-time and embedded systems. *ACM Computing Surveys (CSUR)*, 28(1):205–208.
- Stankovic, J. A. and Ramamritham, K. (1990). What is predictability for real-time systems? *Real-Time Systems*, 2(4):247–254.