


Sampling in inverse problems

Giovanni S. Alberti


MaLGa – Machine Learning Genoa Center
Department of Mathematics
University of Genoa

Harmonic Analysis E-Seminars
13 November 2024

Joint work with



Alessandro Felisi
(UniGe)



Matteo Santacesaria
(UniGe)



S. Ivan Trapasso
(PoliTo)

Compressed sensing for inverse problems and the sample complexity of the sparse Radon transform, J. Eur. Math. Soc., to appear

Outline

Sampling and inverse problems

Compressed sensing

Compressed sensing for inverse problems

Outline

Sampling and inverse problems

Compressed sensing

Compressed sensing for inverse problems

Sampling

- ▶ Function $f \in L^2(\mathcal{D})$
- ▶ Sampling points $t_l \in \mathcal{D}, l = 1, \dots, m$
- ▶ **Sampling problem:**

$$(f(t_l))_{l=1}^m \rightsquigarrow f$$

Sampling

- ▶ Function $f \in L^2(\mathcal{D})$
- ▶ Sampling points $t_l \in \mathcal{D}, l = 1, \dots, m$
- ▶ **Sampling problem:**

$$(f(t_l))_{l=1}^m \leadsto f$$

- ▶ Need assumptions on f
- ▶ Classically, f is ω -bandlimited (**linear** condition):

$$m \gtrsim \omega$$

Inverse problems

- ▶ \mathcal{H} (e.g. $\mathcal{H} = L^2(\Omega)$): Hilbert space of inputs
- ▶ $F: \mathcal{H} \rightarrow L^2(\mathcal{D}; \mathcal{H}')$ linear **forward map** (compact)

Inverse problems

- ▶ \mathcal{H} (e.g. $\mathcal{H} = L^2(\Omega)$): Hilbert space of inputs
- ▶ $F: \mathcal{H} \rightarrow L^2(\mathcal{D}; \mathcal{H}')$ linear **forward map** (compact)
- ▶ Inverse problem:

$$F(u) \leadsto u$$

Inverse problems

- ▶ \mathcal{H} (e.g. $\mathcal{H} = L^2(\Omega)$): Hilbert space of inputs
- ▶ $F: \mathcal{H} \rightarrow L^2(\mathcal{D}; \mathcal{H}')$ linear **forward map** (compact)
- ▶ Inverse problem:

$$F(u) \leadsto u$$

Examples

1. **Deconvolution** (with Bessel operator):

$$F = (I - \Delta)^{-b/2}: L^2(\mathbb{R}^2) \rightarrow L^2(\mathbb{R}^2), \quad F(u) = \kappa_b * u$$

where $b > 2$ and $\kappa_b := \mathcal{F}^{-1}((1 + |\cdot|^2)^{-b/2})$

Inverse problems

- ▶ \mathcal{H} (e.g. $\mathcal{H} = L^2(\Omega)$): Hilbert space of inputs
- ▶ $F: \mathcal{H} \rightarrow L^2(\mathcal{D}; \mathcal{H}')$ linear **forward map** (compact)
- ▶ Inverse problem:

$$F(u) \leadsto u$$

Examples

1. **Deconvolution** (with Bessel operator):

$$F = (I - \Delta)^{-b/2}: L^2(\mathbb{R}^2) \rightarrow L^2(\mathbb{R}^2), \quad F(u) = \kappa_b * u$$

where $b > 2$ and $\kappa_b := \mathcal{F}^{-1}((1 + |\cdot|^2)^{-b/2})$

2. **Radon transform**¹:

$$\mathcal{R}: L^2(\mathcal{B}_1) \rightarrow L^2(\mathbb{S}^1; L^2(-1, 1)), \quad (\mathcal{R}u)(\theta) = \int_{\theta^\perp} u(y + \cdot \theta) dy \in L^2(-1, 1)$$

Sampling in inverse problems

- ▶ $F: \mathcal{H} \rightarrow L^2(\mathcal{D}; \mathcal{H}')$ linear forward map
- ▶ Sampling points $t_l \in \mathcal{D}, l = 1, \dots, m$
- ▶ Inverse problems with sampling:

$$(F_{t_l} u := (Fu)(t_l))_{l=1}^m \rightsquigarrow u$$

Sampling in inverse problems

- ▶ $F: \mathcal{H} \rightarrow L^2(\mathcal{D}; \mathcal{H}')$ linear forward map
- ▶ Sampling points $t_l \in \mathcal{D}, l = 1, \dots, m$
- ▶ Inverse problems with sampling:

$$(F_{t_l} u := (Fu)(t_l))_{l=1}^m \rightsquigarrow u$$

Examples

1. Deconvolution: $F: L^2(\mathbb{R}^2) \rightarrow L^2(\mathbb{R}^2)$

$$((\kappa_b * u)(t_l))_{l=1}^m \rightsquigarrow u$$

Sampling in inverse problems

- ▶ $F: \mathcal{H} \rightarrow L^2(\mathcal{D}; \mathcal{H}')$ linear forward map
- ▶ Sampling points $t_l \in \mathcal{D}, l = 1, \dots, m$
- ▶ Inverse problems with sampling:

$$(F_{t_l} u := (Fu)(t_l))_{l=1}^m \rightsquigarrow u$$

Examples

1. Deconvolution: $F: L^2(\mathbb{R}^2) \rightarrow L^2(\mathbb{R}^2)$


$$((\kappa_b * u)(t_l))_{l=1}^m \rightsquigarrow u$$

2. Radon transform: $\mathcal{R}: L^2(\mathcal{B}_1) \rightarrow L^2(\mathbb{S}^1; L^2(-1, 1))$

$$(\mathcal{R}_{\theta_l} u)_{l=1}^m \rightsquigarrow u$$


The sparse Radon transform

$$\mathcal{R}_{\theta}u(s) = \int_{\theta^{\perp}} u(y + s\theta)dy, \quad \theta = \theta_1$$




The sparse Radon transform

$$\mathcal{R}_{\theta}u(s) = \int_{\theta^{\perp}} u(y + s\theta)dy, \quad \theta = \theta_2$$




The sparse Radon transform

$$\mathcal{R}_\theta u(s) = \int_{\theta^\perp} u(y + s\theta) dy, \quad \theta = \theta_3$$




The sparse Radon transform

$$\mathcal{R}_\theta u(s) = \int_{\theta^\perp} u(y + s\theta) dy, \quad \theta = \theta_4$$



The sparse Radon transform

$$(\mathcal{R}u(\theta_1, \cdot), \dots, \mathcal{R}u(\theta_m, \cdot)), \quad \theta_1, \dots, \theta_m \in \mathbb{S}^1$$



Sampling in inverse problems

- ▶ $F: \mathcal{H} \rightarrow L^2(\mathcal{D}; \mathcal{H}')$ linear forward map
- ▶ Sampling points $t_l \in \mathcal{D}, l = 1, \dots, m$
- ▶ Inverse problems with sampling:

$$(F_{t_l} u)_{l=1}^m \rightsquigarrow u$$

Sampling in inverse problems

- ▶ $F: \mathcal{H} \rightarrow L^2(\mathcal{D}; \mathcal{H}')$ linear forward map
- ▶ Sampling points $t_l \in \mathcal{D}, l = 1, \dots, m$
- ▶ Inverse problems with sampling:

$$(F_{t_l} u)_{l=1}^m \rightsquigarrow u$$

Need **prior assumptions**:

- ▶ **Linear**: u bandlimited (or, more generally, smooth) is not realistic in most cases

Sampling in inverse problems

- ▶ $F: \mathcal{H} \rightarrow L^2(\mathcal{D}; \mathcal{H}')$ linear forward map
- ▶ Sampling points $t_l \in \mathcal{D}, l = 1, \dots, m$
- ▶ Inverse problems with sampling:

$$(F_{t_l} u)_{l=1}^m \rightsquigarrow u$$

Need **prior assumptions**:

- ▶ **Linear**: u bandlimited (or, more generally, smooth) is not realistic in most cases
- ▶ **Nonlinear**²: u sparse...

Sparsity

- $\{\phi_n\}_n$ **orthonormal/Riesz basis** of \mathcal{H}

Sparsity

- ▶ $\{\phi_n\}_n$ **orthonormal/Riesz basis** of \mathcal{H}
- ▶ $u \in \mathcal{H}$ is **s-sparse** if

$$\#\{n : \langle u, \phi_n \rangle \neq 0\} \leq s$$

Sparsity

► $\{\phi_n\}_n$ **orthonormal/Riesz basis** of \mathcal{H}

► $u \in \mathcal{H}$ is **s-sparse** if

$$\#\{n : \langle u, \phi_n \rangle \neq 0\} \leq s$$

► compare with a **linear** condition:

$$\{n : \langle u, \phi_n \rangle \neq 0\} \subseteq \{1, \dots, s\}$$

Sparsity

- ▶ $\{\phi_n\}_n$ **orthonormal/Riesz basis** of \mathcal{H}
- ▶ $u \in \mathcal{H}$ is **s-sparse** if

$$\#\{n : \langle u, \phi_n \rangle \neq 0\} \leq s$$

- ▶ compare with a **linear** condition:

$$\{n : \langle u, \phi_n \rangle \neq 0\} \subseteq \{1, \dots, s\}$$



Figure: **Important** Genoese




Figure: **Wavelet** coefficients

Main goal

Problem:

$$(\mathbb{F}_{t_l} u)_{l=1}^m \rightsquigarrow u$$

Main goal

Problem:

$$(F_{t_l} u)_{l=1}^m \rightsquigarrow u$$

The **main goal** is to understand

- how to choose the samples $t_1, \dots, t_m \in \mathcal{D}$

Main goal

Problem:

$$(F_{t_l} u)_{l=1}^m \rightsquigarrow u$$

The **main goal** is to understand

- ▶ how to choose the samples $t_1, \dots, t_m \in \mathcal{D}$
- ▶ and how many are needed ($m = ?$)

Outline

Sampling and inverse problems

Compressed sensing

Compressed sensing for inverse problems

An example: Magnetic Resonance Imaging



Measurements: F = Fourier transform

Compressed sensing³

Setup:

³E. J. Candès, J. K. Romberg, T. Tao. Stable signal recovery from incomplete and inaccurate measurements. *Comm. Pure Appl. Math.* 59(8) (2006), 1207-1223
D. L. Donoho. Compressed sensing. *IEEE Trans. Inf. Theory*, 52(4) (2006), 1289–1306

Compressed sensing³

Setup:

- ▶ **Unknown:** $u^\dagger \in \mathbb{C}^M$ is s -sparse
- ▶ $\{\psi_t\}_t$ orthonormal basis (MRI: Fourier)
- ▶ Random subsampling: $t_l \in \{1, \dots, M\}$ chosen uniformly at random

³E. J. Candès, J. K. Romberg, T. Tao. Stable signal recovery from incomplete and inaccurate measurements. *Comm. Pure Appl. Math.* 59(8) (2006), 1207-1223
D. L. Donoho. Compressed sensing. *IEEE Trans. Inf. Theory*, 52(4) (2006), 1289–1306

Compressed sensing³

Setup:

- ▶ **Unknown:** $u^\dagger \in \mathbb{C}^M$ is s -sparse
- ▶ $\{\psi_t\}_t$ orthonormal basis (MRI: Fourier)
- ▶ Random subsampling: $t_l \in \{1, \dots, M\}$ chosen uniformly at random

Problem:

$$(\langle u, \psi_{t_l} \rangle)_{l=1}^m \rightsquigarrow u^\dagger$$

³E. J. Candès, J. K. Romberg, T. Tao. Stable signal recovery from incomplete and inaccurate measurements. *Comm. Pure Appl. Math.* 59(8) (2006), 1207-1223
D. L. Donoho. Compressed sensing. *IEEE Trans. Inf. Theory*, 52(4) (2006), 1289–1306

Compressed sensing³

Setup:

- ▶ **Unknown:** $u^\dagger \in \mathbb{C}^M$ is s -sparse
- ▶ $\{\psi_t\}_t$ orthonormal basis (MRI: Fourier)
- ▶ Random subsampling: $t_l \in \{1, \dots, M\}$ chosen uniformly at random

Problem:

$$(\langle u, \psi_{t_l} \rangle)_{l=1}^m \rightsquigarrow u^\dagger$$

with

$$m \gtrsim s$$

³E. J. Candès, J. K. Romberg, T. Tao. Stable signal recovery from incomplete and inaccurate measurements. Comm. Pure Appl. Math. 59(8) (2006), 1207-1223
D. L. Donoho. Compressed sensing. IEEE Trans. Inf. Theory, 52(4) (2006), 1289–1306


Coherence

In general, sparsity alone is **not enough**

Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider a sensing system $\psi_l = \delta_l$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider a sensing system $\psi_l = \delta_l$; we count $m = 1$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider a sensing system $\psi_l = \delta_l$; we count $m = 2$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider a sensing system $\psi_l = \delta_l$; we count $m = 3$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider a sensing system $\psi_l = \delta_l$; we count $m = 4$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider a sensing system $\psi_l = \delta_l$; we count $m = 5$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider a sensing system $\psi_l = \delta_l$; we count $m = 6$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider a sensing system $\psi_t = \delta_t$; we count $m = 7$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider a sensing system $\psi_t = \delta_t$; we count $m = 8$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider a sensing system $\psi_t = \delta_t$; we count $m = M$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider another sensing system $(\psi_t)_t$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider another sensing system $(\psi_t)_t$; we count $m = 1$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider another sensing system $(\psi_t)_t$; we count $m = 2$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider another sensing system $(\psi_t)_t$; we count $m = 3$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider another sensing system $(\psi_t)_t$; we count $m = 4$




Coherence

In general, sparsity alone is **not enough**

Suppose we have a 1-sparse vector $u^\dagger \in \mathbb{R}^M$ ($M = 8$) w.r.t. $\phi_n = \delta_n$

Consider another sensing system $(\psi_t)_t$; we count $m = 1 + \log_2 M$



Coherence

This feature is measured by the **coherence** between the **sparsifying dictionary** and the **sensing system**

Coherence

This feature is measured by the **coherence** between the **sparsifying dictionary** and the **sensing system**

$$B = \sqrt{M} \cdot \max_{n,t} |\langle \phi_n, \psi_t \rangle|$$

Coherence

$$B = \sqrt{M} \cdot \max |\langle \phi_n, \psi_t \rangle|$$



Figure: **First example:** $B = \sqrt{M}$

Coherence

$$B = \sqrt{M} \cdot \max |\langle \phi_n, \psi_t \rangle|$$



Figure: **Second example:** $B = 1$

Recovery estimate⁴

- ▶ $u^\dagger \in \mathbb{C}^M$ **unknown**
- ▶ u^\dagger is **s-sparse** w.r.t. $\{\phi_n\}_{n=1}^M$
- ▶ **minimization problem**

$$\hat{u} \in \arg \min_{u \in \mathbb{C}^M} \|(\langle u, \phi_n \rangle)_n\|_1 : \langle u, \psi_{t_l} \rangle = \langle u, \psi_{t_l} \rangle, \quad l = 1, \dots, m$$

Recovery estimate⁴

- ▶ $u^\dagger \in \mathbb{C}^M$ **unknown**
- ▶ u^\dagger is **s-sparse** w.r.t. $\{\phi_n\}_{n=1}^M$
- ▶ **minimization problem**

$$\hat{u} \in \arg \min_{u \in \mathbb{C}^M} \|(\langle u, \phi_n \rangle)_n\|_1 : \langle u, \psi_{t_l} \rangle = \langle u^\dagger, \psi_{t_l} \rangle, \quad l = 1, \dots, m$$

Theorem

If

$$m \gtrsim B^2 s \cdot \log \text{ factors}$$

then

$$\hat{u} = u^\dagger$$

with overwhelming probability.

Outline

Sampling and inverse problems

Compressed sensing

Compressed sensing for inverse problems

Setting⁵

- ▶ $\mathcal{H} = L^2(\Omega)$ with $\Omega \subset \mathbb{R}^2$ bounded
- ▶ $(\phi_{j,n})_{j,n}$: sufficiently nice **wavelet basis**
- ▶ u^\dagger is **s-sparse** w.r.t. the wavelet basis

⁵B. Adcock, A. C. Hansen, C. Poon, B. Roman, Breaking the coherence barrier: A new theory for compressed sensing, Forum Math. Sigma, 2017.

E. Herrholz, G. Teschke, Compressive sensing principles and iterative sparse recovery for inverse and ill-posed problems, Inverse Probl., 2010

Setting⁵

- ▶ $\mathcal{H} = L^2(\Omega)$ with $\Omega \subset \mathbb{R}^2$ bounded
- ▶ $(\phi_{j,n})_{j,n}$: sufficiently nice **wavelet basis**
- ▶ u^\dagger is **s-sparse** w.r.t. the wavelet basis

Forward map

$$u \longmapsto (F_{t_l} u)_{l=1}^m$$

not a subsampled isometry, but a **subsampled compact** operator

⁵B. Adcock, A. C. Hansen, C. Poon, B. Roman, Breaking the coherence barrier: A new theory for compressed sensing, Forum Math. Sigma, 2017.

E. Herrholz, G. Teschke, Compressive sensing principles and iterative sparse recovery for inverse and ill-posed problems, Inverse Probl., 2010

Difficulties with the Radon transform

Difficulties with the Radon transform

- ▶ From Jørgensen, Coban, Lionheart, McDonald and Withers, 2017:
Compressive sensing connects the critical number of projections to the image sparsity, but does not cover CT. Empirical results suggest a similar connection.
- ▶ From Hansen, 2017:
We used simulations studies to provide a foundation for the use of sparsity in CT where, unlike compressed sensing, it is not possible to give rigorous proofs.

Difficulties with the Radon transform

- ▶ From Jørgensen, Coban, Lionheart, McDonald and Withers, 2017:
Compressive sensing connects the critical number of projections to the image sparsity, but does not cover CT. Empirical results suggest a similar connection.
- ▶ From Hansen, 2017:
We used simulations studies to provide a foundation for the use of sparsity in CT where, unlike compressed sensing, it is not possible to give rigorous proofs.

Key tools:

1. Quasi-diagonalization of F
2. Relative coherence

Quasi-diagonalization

► u^\dagger is **s-sparse**

Quasi-diagonalization

- u^\dagger is **s-sparse** – what about Fu^\dagger ?

Quasi-diagonalization

- ▶ u^\dagger is **s-sparse** – what about Fu^\dagger ?
- ▶ **smoothing operators** F :

$$\|Fu\|_{L^2} \asymp \|u\|_{H^{-b}}$$

Quasi-diagonalization

- ▶ u^\dagger is **s-sparse** – what about Fu^\dagger ?
- ▶ **smoothing operators** F :

$$\|Fu\|_{L^2} \asymp \|u\|_{H^{-b}}$$

- ▶ **Littlewood-Paley properties of wavelets**⁶:

$$\|u\|_{H^{-b}}^2 \asymp \sum_{j,n} 2^{-2bj} |\langle u, \phi_{j,n} \rangle|^2$$

Quasi-diagonalization

- ▶ u^\dagger is **s-sparse** – what about Fu^\dagger ?
- ▶ **smoothing operators** F :

$$\|Fu\|_{L^2} \asymp \|u\|_{H^{-b}}$$

- ▶ **Littlewood-Paley properties of wavelets**⁶:

$$\|u\|_{H^{-b}}^2 \asymp \sum_{j,n} 2^{-2bj} |\langle u, \phi_{j,n} \rangle|^2$$

- ▶ **quasi-diagonalization** property:

$$\|Fu\|_{L^2}^2 \asymp \sum_{j,n} 2^{-2bj} |\langle u, \phi_{j,n} \rangle|^2$$

Quasi-diagonalization

- ▶ u^\dagger is **s-sparse** – what about Fu^\dagger ?
- ▶ **smoothing operators** F :

$$\|Fu\|_{L^2} \asymp \|u\|_{H^{-b}}$$

- ▶ **Littlewood-Paley properties of wavelets**⁶:

$$\|u\|_{H^{-b}}^2 \asymp \sum_{j,n} 2^{-2bj} |\langle u, \phi_{j,n} \rangle|^2$$

- ▶ **quasi-diagonalization** property:

$$\|Fu\|_{L^2}^2 \asymp \sum_{j,n} 2^{-2bj} |\langle u, \phi_{j,n} \rangle|^2$$

- ▶ **pseudo-sparsity property** on Fu^\dagger : use compressed sensing methods

Relative coherence

What is the analogous concept of **coherence** in this case?

Relative coherence

What is the analogous concept of **coherence** in this case?

Classically defined as

$$B = \sqrt{M} \sup_{n,t} |F_t(\phi_n)|$$

when we sampled with respect to the **uniform probability** on $[M]$

Relative coherence

$$B = \sqrt{M} \sup_{n,t} |F_t(\phi_n)|$$

$g(t) \equiv 1/M$ is the **probability density** w.r.t. the counting measure on $\mathcal{D} = \{1, \dots, M\}$

Relative coherence

$$B = \sup_{n,t} \sqrt{\frac{1}{g(t)}} \cdot |F_t(\phi_n)|$$

$g(t) \equiv 1/M$ is the **probability density** w.r.t. the counting measure on $\mathcal{D} = \{1, \dots, M\}$

Relative coherence

$$B = \sup_{n,t} \sqrt{\frac{1}{g(t)}} \cdot |F_t(\phi_n)|$$

$g(t) \equiv 1/M$ is the **probability density** w.r.t. the counting measure on $\mathcal{D} = \{1, \dots, M\}$

Sampling rule in general \mathcal{D} (e.g. $\mathcal{D} \subseteq \mathbb{R}^d$):

$$g(t) dt$$

Relative coherence

$$B = \sup_{n,t} \sqrt{\frac{1}{g(t)}} \cdot |F_t(\phi_n)|$$

Relative coherence

$$B = \sup_{n,t} \sqrt{\frac{1}{g(t)}} \cdot |F_t(\phi_n)|$$

Compact operator: need to normalize

$$B_{\text{rel}} = \sup_{n,t} \sqrt{\frac{1}{g(t)}} \cdot \frac{F_t \phi_n}{\|F \phi_n\|_{L^2}}$$

Relative coherence

$$B = \sup_{n,t} \sqrt{\frac{1}{g(t)}} \cdot |F_t(\phi_n)|$$

Compact operator: need to normalize

$$B_{\text{rel}} = \sup_{n,t} \sqrt{\frac{1}{g(t)}} \cdot \frac{F_t \phi_n}{\|F \phi_n\|_{L^2}}$$

We call this quantity **relative coherence**

Optimizing the probability density $g(t)$

The **optimal choice** for $g(t)$ (minimizing B_{rel}) depends on the decay in t of $|F_t \phi_{j,n}|$

Optimizing the probability density $g(t)$

The **optimal choice** for $g(t)$ (minimizing B_{rel}) depends on the decay in t of $|F_t \phi_{j,n}|$

Examples

Optimizing the probability density $g(t)$

The **optimal choice** for $g(t)$ (minimizing B_{rel}) depends on the decay in t of $|F_t \phi_{j,n}|$

Examples

1. **Deconvolution** for $b > 2$:

$$|((I - \Delta)^{-b/2} \phi_{j,n})(t)| \lesssim \frac{e^{-C_b |d(t, \Omega)|}}{2^{(b-1)j}} \quad \Rightarrow \quad g(t) \propto e^{-C_b |d(t, \Omega)|}$$

Optimizing the probability density $g(t)$

The **optimal choice** for $g(t)$ (minimizing B_{rel}) depends on the decay in t of $|F_t \phi_{j,n}|$

Examples

1. **Deconvolution** for $b > 2$:

$$|((I - \Delta)^{-b/2} \phi_{j,n})(t)| \lesssim \frac{e^{-C_b |d(t, \Omega)|}}{2^{(b-1)j}} \quad \Rightarrow \quad g(t) \propto e^{-C_b |d(t, \Omega)|}$$

2. **The Radon transform:**

$$|\mathcal{R}_\theta \phi_{j,n}| \lesssim 1 \quad \Rightarrow \quad g(\theta) = \frac{1}{2\pi}$$

Main abstract result⁷

Theorem

Main abstract result⁷

Theorem

► **Unknown:** $u^\dagger \in L^2(\Omega)$

Main abstract result⁷

Theorem

- ▶ **Unknown:** $u^\dagger \in L^2(\Omega)$
- ▶ **Sparsity:** u^\dagger is s -sparse w.r.t. the wavelet basis $(\phi_{j,n})_{j,n}$

Main abstract result⁷

Theorem

- ▶ **Unknown:** $u^\dagger \in L^2(\Omega)$
- ▶ **Sparsity:** u^\dagger is s -sparse w.r.t. the wavelet basis $(\phi_{j,n})_{j,n}$
- ▶ **Measurements:** $t_1, \dots, t_m \in \mathcal{D}$ chosen i.i.d. w.r.t. $g(t) dt$ with

$$m \gtrsim B_{\text{rel}}^2 s \cdot \log \text{ factors}$$

Main abstract result⁷

Theorem

- **Unknown:** $u^\dagger \in L^2(\Omega)$
- **Sparsity:** u^\dagger is s -sparse w.r.t. the wavelet basis $(\phi_{j,n})_{j,n}$
- **Measurements:** $t_1, \dots, t_m \in \mathcal{D}$ chosen i.i.d. w.r.t. $g(t) dt$ with

$$m \gtrsim B_{\text{rel}}^2 s \cdot \log \text{ factors}$$

- **Minimization problem:**

$$\hat{u} \in \arg \min_{u \in \mathcal{H}} \|(\langle u, \phi_{j,n} \rangle)_{j,n}\|_{1,w} : F_{t_l} u = F_{t_l} u^\dagger, l = 1, \dots, m$$

Main abstract result⁷

Theorem

- **Unknown:** $u^\dagger \in L^2(\Omega)$
- **Sparsity:** u^\dagger is s -sparse w.r.t. the wavelet basis $(\phi_{j,n})_{j,n}$
- **Measurements:** $t_1, \dots, t_m \in \mathcal{D}$ chosen i.i.d. w.r.t. $g(t) dt$ with

$$m \gtrsim B_{\text{rel}}^2 s \cdot \log \text{ factors}$$

- **Minimization problem:**

$$\hat{u} \in \arg \min_{u \in \mathcal{H}} \|(\langle u, \phi_{j,n} \rangle)_{j,n}\|_{1,w} : F_{t_l} u = F_{t_l} u^\dagger, l = 1, \dots, m$$

Then

$$\hat{u} = u^\dagger$$

with overwhelming probability.

A corollary for the Radon transform⁸

$$(\mathcal{R}u^\dagger(\theta_1, \cdot), \dots, \mathcal{R}u^\dagger(\theta_m, \cdot)) \in L^2(-1, 1)^m \quad \longrightarrow \quad u^\dagger \in L^2(\mathcal{B}_1)$$

A corollary for the Radon transform⁸

$$(\mathcal{R}u^\dagger(\theta_1, \cdot), \dots, \mathcal{R}u^\dagger(\theta_m, \cdot)) \in L^2(-1, 1)^m \quad \longrightarrow \quad u^\dagger \in L^2(\mathcal{B}_1)$$

Theorem

- Sparsity: unknown $u^\dagger \in L^2(\mathcal{B}_1)$ is s -sparse wrt an ONB of wavelets $(\phi_{j,n})_{j,n}$

A corollary for the Radon transform⁸

$$(\mathcal{R}u^\dagger(\theta_1, \cdot), \dots, \mathcal{R}u^\dagger(\theta_m, \cdot)) \in L^2(-1, 1)^m \quad \longrightarrow \quad u^\dagger \in L^2(\mathcal{B}_1)$$

Theorem

- ▶ Sparsity: unknown $u^\dagger \in L^2(\mathcal{B}_1)$ is s -sparse wrt an ONB of wavelets $(\phi_{j,n})_{j,n}$
- ▶ Measurements: $\theta_1, \dots, \theta_m \in [0, \pi]$ chosen uniformly at random with

$$m \gtrsim s \cdot \log \text{ factors}$$

A corollary for the Radon transform⁸

$$(\mathcal{R}u^\dagger(\theta_1, \cdot), \dots, \mathcal{R}u^\dagger(\theta_m, \cdot)) \in L^2(-1, 1)^m \quad \longrightarrow \quad u^\dagger \in L^2(\mathcal{B}_1)$$

Theorem

- Sparsity: unknown $u^\dagger \in L^2(\mathcal{B}_1)$ is s -sparse wrt an ONB of wavelets $(\phi_{j,n})_{j,n}$
- Measurements: $\theta_1, \dots, \theta_m \in [0, \pi]$ chosen uniformly at random with

$$m \gtrsim s \cdot \log \text{ factors}$$

- Minimization problem:

$$u_* \in \arg \min_u \|\Phi u\|_{1,w} \quad \text{subject to} \quad \mathcal{R}_{\theta_l} u = \mathcal{R}_{\theta_l} u^\dagger, \quad l = 1, \dots, m$$

A corollary for the Radon transform⁸

$$(\mathcal{R}u^\dagger(\theta_1, \cdot), \dots, \mathcal{R}u^\dagger(\theta_m, \cdot)) \in L^2(-1, 1)^m \quad \longrightarrow \quad u^\dagger \in L^2(\mathcal{B}_1)$$

Theorem

- Sparsity: unknown $u^\dagger \in L^2(\mathcal{B}_1)$ is s -sparse wrt an ONB of wavelets $(\phi_{j,n})_{j,n}$
- Measurements: $\theta_1, \dots, \theta_m \in [0, \pi]$ chosen uniformly at random with

$$m \gtrsim s \cdot \log \text{ factors}$$

- Minimization problem:

$$u_* \in \arg \min_u \|\Phi u\|_{1,w} \quad \text{subject to} \quad \mathcal{R}_{\theta_l} u = \mathcal{R}_{\theta_l} u^\dagger, \quad l = 1, \dots, m$$

Then, with high probability,

$$u_* = u^\dagger$$

Conclusions

Past

- ▶ Theory of CS for random matrices and subsampled isometries (e.g. MRI)
- ▶ Empirical evidence for compressed sensing Radon transform

Present

- ▶ Abstract theory of sample complexity
- ▶ Rigorous theory of compressed sensing for the sparse Radon transform

Future

- ▶ Wavelets \rightarrow shearlets, curvelets, etc.
- ▶ Generalisation to other ill-posed problems, possibly nonlinear



Paper



Slides

UniGe

MaL**Ga**