

Implement a new Graph

The BRAPH 2 Developers

July 26, 2023

This is the developer tutorial for implementing a new graph. In this Tutorial, we will explain how to create the generator file *.gen.m for a new graph which can be compiled by braph2genesis, using the graphs GraphBD, MultilayerWU, Multiplex??, OrdMl?? as examples. and OrdMx?? as examples.

Contents

<i>Implementation of Unilayer Graph</i>	<i>2</i>
<i>Unilayer Graph Binary Directed (GraphBD)</i>	<i>2</i>
<i>Implementation of Multilayer Graph</i>	<i>8</i>
<i>Multilayer Weighed Directed Graph (MultilayerWD)</i>	<i>8</i>
<i>Multiplex Graph ()</i>	<i>12</i>
<i>Ordinal Multilayer Graph ()</i>	<i>13</i>
<i>Ordinal Multiplex ... Graph ()</i>	<i>14</i>

Implementation of Unilayer Graph

Unilayer Graph Binary Directed (GraphBD)

We will start by implementing in detail the graph GraphBD which is a direct extension of the element Graph.

Code 1: GraphBD element header. The header section of generator code for `_GraphBD.gen.m` provides the general information about the GraphBD element.

```

1 %% iheader!
2 GraphBD < Graph (m, binary directed graph) is a binary directed graph. ①
3
4 %%% idescription!
5 In a binary directed (BD) graph, the edges are directed and they can be
6 either 0 (absence of connection) or 1 (existence of connection).
```

① The element GraphBD is defined as a subclass of Graph. The moniker will be m.

Code 2: GraphBD element layout. The layout section of generator code for `_GraphBD.gen.m` creates the general variables needed for the GraphBD element.

```

1 %% ilayout!
2 %%% iprop!
3 %%% iid!
4 GraphBD.ID
5 %%% ititle!
6 Graph ID
7
8 %%% iprop!
9 %%% iid!
10 GraphBD.LABEL
11 %%% ititle!
12 Graph NAME
13
14 %%% iprop!
15 %%% iid!
16 GraphBD.NODELABELS
17 %%% ititle!
18 NODES labels
19
20 %%% iprop!
21 %%% iid!
22 GraphBD.B
23 %%% ititle!
24 Input ADJACENCY MATRIX
25
26 %%% iprop!
27 %%% iid!
28 GraphBD.SEMIPOSITIVIZE_RULE
29 %%% ititle!
30 NEGATIVE WEIGHTS RULE
31
32 %%% iprop!
33 %%% iid!
34 GraphBD.A
35 %%% ititle!
36 Binary Directed ADJACENCY MATRIX
```

```

37
38 %% iprop!
39 %%% iid!
40 GraphBD.PFGA
41 %%% ititle!
42 Adjacency Matrix Plot
43
44 %% iprop!
45 %%% iid!
46 GraphBD.PFGH
47 %%% ititle!
48 Graph Histogram
49
50 %% iprop!
51 %%% iid!
52 GraphBD.M_DICT
53 %%% ititle!
54 Graph MEASURES
55
56 %% iprop!
57 %%% iid!
58 GraphBD.NOTES
59 %%% ititle!
60 Graph NOTES

```

Code 3: **GraphBD element prop update.** The `props_update` section of generator code for `GraphBD.gen.m` updates the properties of the Graph element. This defines the core properties of the graph.

```

1 %% iprops_update!
2 %%% iprop!
3 NAME (constant, string) is the name of the binary directed graph.
4 %%%  idefault!
5 'GraphBD'
6
7 %% iprop!
8 DESCRIPTION (constant, string) is the description of the  binary directed
9   graph.
10 %%%  idefault!
11 'In a binary directed (BD) graph, the edges are directed and they can be
12   either 0 (absence of connection) or 1 (existence of connection).'
13
14 %% iprop!
15 TEMPLATE (parameter, item) is the template of the  binary directed graph.
16
17 %% iprop!
18 ID (data, string) is a few-letter code of the  binary directed graph.
19 %%%  idefault!
20 'GraphBD ID'
21
22 %% iprop!
23 LABEL (metadata, string) is an extended label of the binary directed graph.
24 %%%  idefault!
25 'GraphBD label'
26
27 %% iprop!
28 NOTES (metadata, string) are some specific notes about the binary directed
29   graph.
30 %%%  idefault!
31 'GraphBD notes'

```

```

29
30 %% iprop! ①
31 GRAPH_TYPE (constant, scalar) returns the graph type __Graph.GRAPH__.
32 %%% idefault!
33 Graph.GRAPH
34
35 %% iprop! ②
36 CONNECTIVITY_TYPE (query, smatrix) returns the connectivity type __Graph.
    BINARY__.
37 %%% idefault!
38 value = Graph.BINARY;
39
40 %% iprop! ③
41 DIRECTIONALITY_TYPE (query, smatrix) returns the directionality type
    __Graph.DIRECTED__.
42 %%% idefault!
43 value = Graph.DIRECTED;
44
45 %% iprop! ④
46 SELFCONNECTIVITY_TYPE (query, smatrix) returns the self-connectivity type
    __Graph.NONSELFCONNECTED__.
47 %%% idefault!
48 value = Graph.NONSELFCONNECTED;
49
50 %% iprop! ⑤
51 NEGATIVITY_TYPE (query, smatrix) returns the negativity type __Graph.
    NONNEGATIVE__.
52 %%% idefault!
53 value = Graph.NONNEGATIVE;
54
55 %% iprop! ⑥
56 A (result, cell) is the binary adjacency matrix of the binary directed graph
    .
57 %%% icalculate!
58 B = g.get('B'); ⑦
59
60 B = dedagonalize(B); ⑧
61 B = semipositivize(B, 'SemipositivizeRule', g.get('SEMIPOSITIVIZE_RULE'));
62 B = binarize(B);
63
64 A = {B}; ⑨
65 value = A; ⑩
66
67 %%% igui! ⑪
68 pr = PanelPropCell('EL', g, 'PROP', GraphBD.A, ... ⑫
69 'TABLE_HEIGHT', s(40), ...
70 'XSLIDERSHOW', false, ...
71 'YSLIDERSHOW', false, ...
72 'ROWNAME', g.getCallback('ANODELABELS'), ...
73 'COLUMNNAME', g.getCallback('ANODELABELS'), ...
74 );
75
76
77
78
79
80

```

① We need to define the type of graph: `Graph.GRAPH` (consists of a single layer), `Graph.MULTIGRAPH` (multiple unconnected layers of graphs), `Graph.MULTILAYER` (multiple layers with categorical connections between any nodes), `Graph.ORDERED_MULTILAYER` (multiple layers with ordinal connections between any nodes), `Graph.MULTIPLEX` (multilayer graph where only interlayer edges are allowed between homologous nodes) and `Graph.ORDERED_MULTIPLEX` (multiplex graph that consists of a sequence of layers with ordinal edges between corresponding nodes in subsequent layers).

② Graphs have a `CONNECTIVITY_TYPE`: `Graph.BINARY` (Graph with binary, 0 or 1, connections) or `Graph.WEIGHTED` (Graph with weighted connections).

③ Graphs have a `DIRECTIONALITY_TYPE`: `Graph.DIRECTED` (graph with directed edges) or `Graph.UNDIRECTED` (graph with undirected edges).

④ Graphs have a `SELFCONNECTIVITY_TYPE`: `Graph.NONSELFCONNECTED` (Graph without self-connections) or `Graph.SELFCONNECTED` (Graph with self-connections).

⑤ Graphs have a `NEGATIVITY_TYPE`: `Graph.NONNEGATIVE` (Graph without negative edges) or `Graph.NEGATIVE` (Graph allowing negative edges).

⑥ The property A contains the code to be executed to calculate the graph.

⑦ retrieves the cell with the adjacency matrix of the graph

⑧ Apply corresponding functions to define the properties of the graph: `dediagonalize` (removes the off-diagonal), `dediagonalize` (removes the diagonal), `binarize` (binarizes with threshold=0), `semipositivize` (removes negative weights), `standardize` (normalizes between 0 and 1) or `symmetrize` (symmetrizes the matrix)

⑨ preallocates the adjacency matrix that contains the result of the defined graph.

⑩ returns the calculated graph A assigning it to the output variable `value`.

⑪ Each graph has a panel figure of the cell containing the graph adjacency matrix.

⑫ `PanelPropCell` plots the panel for a CELL property with a table and two sliders. It can be personalized with props, e.g., `TABLE_HEIGHT` (height in pixels), `XSLIDERSHOW` (whether to show the x-slider), or `COLUMNNAME` (string list with column names)

```

81
82
83 %% iprop! (13)
84 COMPATIBLE_MEASURES (constant, classlist) is the list of compatible measures
85 .
86 %%% idefault!
87 getCompatibleMeasures('GraphBD')
88
89 %% iprop! (14)
90 %% igui!
91 pr = PanelPropMatrix('EL', g, 'PROP', GraphBD.B, ... (15)
92 'TABLE_HEIGHT' , s(40), ...
93 'ROWNAME' , g.getCallback('ANODELABELS'), ...
94 'COLUMNNAME', g.getCallback('ANODELABELS'), ...
95 varargin{:});
96
97 %% iprop! (16)
98 SEMIPOSITIVIZE_RULE (parameter, option) determines how to remove the
99 negative edges.
100 %%% isettings!
101 {'zero', 'absolute'}

```

(13) Each graph has a list of compatible measures.

(14) Each graph has a panel figure of the graph adjacency matrix.

(15) PanelPropMatrix plots the panel of a property matrix-like with a table. It can be personalized with props as in (12).

(16) Each graph have different rules that need to be defined:
 SYMMETRIZE_RULE: symmetrizes the matrix A by the symmetrize rule specified by RULE and the admissible RULE options are: 'max' (default, maximum between inconnection and outconnection), 'sum' (convert negative values to absolute value), 'average' (average of inconnection and outconnection) or 'min' (minimum between inconnection and outconnection)
 SEMIPOSITIVIZE_RULE: determines how to remove the negative edges and the admissible RULE options are: 'zero' (default, convert negative values to zeros) or 'absolute' (convert negative values to absolute value)
 STANDARDIZE_RULE : determines how to normalize the weights between 0 and 1 and the admissible RULE options are: 'threshold' (default, normalizes the matrix A by converting negative values to zero and values larger than 1 to 1) or 'range' (normalizes the matrix A in order to have values scaled between 0 and 1 by using a linear function).

Code 4: **GraphBD element tests.** The tests section from the element generator `_GraphBD.gen.m`. A general test should be prepared to test the properties of the graph when it is empty and full. Furthermore, additional tests should be prepared for the rules defined (one test per rule).

```

1
2
3 %% itests!
4
5 %%% iexcluded_props! ①
6 [GraphBD.PFGA GraphBD.PFGH]
7
8 %%% itest!
9 %%% iname!
10 Constructor - Empty ②
11 %%% iprobability! ③
12 .01
13 %%% icode!
14 B = []; ④
15 g = GraphBD('B', B); ⑤
16
17 g.get('A-CHECK'); ⑥
18
19 A = {binarize(semipositivize(dediagonalize(B)))}; ⑦
20 assert(isequal(g.get('A'), A), ... ⑧
21 [BRAPH2.STR ':GraphBD:' BRAPH2.FAIL_TEST], ...
22 'GraphBD is not constructing well.')
23
24 %%% itest!
25 %%% iname!
26 Constructor - Full ⑨
27 %%% iprobability! ③
28 .01 ③
29 %%% icode!
30 B = randn(randi(10)); ⑩
31 g = GraphBD('B', B); ⑤
32
33 g.get('A-CHECK') ⑥
34
35 A = {binarize(semipositivize(dediagonalize(B)))}; ⑦
36 assert(isequal(g.get('A'), A), ... ⑧
37 [BRAPH2.STR ':GraphBD:' BRAPH2.FAIL_TEST], ...
38 'GraphBD is not constructing well.')
39
40 %%% itest!
41 %%% iname!
42 Semipositivize Rules ⑩
43 %%% iprobability!
44 .01 ③
45 %%% icode!
46 B = [
47 -2 -1 0 1 2
48 -1 0 1 2 -2
49 0 1 2 -2 -1

```

① List of properties that are excluded from testing.

② Checks that an empty GraphBD graph is constructing well

③ Assigns a low test execution probability

④ Initializes an empty GraphBD graph

⑤ Constructs the GraphBD graph from the initialized B

⑥ Performs the corresponding checks for the format of the adjacency matrix A: GRAPH_TYPE, CONNECTIVITY_TYPE, DIRECTIONALITY_TYPE, SELFCONNECTIVITY_TYPE and NEGATIVITY_TYPE.

⑦ Calculates the value of the graph by apply the corresponding properties function

⑧ tests that the value of generated graph calculated by applying the properties functions coincides with the expected value

⑨ Checks that a full GraphBD graph is constructing well

④ Generates a random graph

⑩ Checks the SEMIPOSITIVIZE_RULE on the GraphBD graph.

```

50 1 2 -2 -1 0
51 2 -2 -1 0 1
52 ]; (11)
53
54 g0 = GraphBD('B', B); (12)
55 A0 = {[
56 0 0 0 1 1
57 0 0 1 1 0
58 0 1 0 0 0
59 1 1 0 0 0
60 1 0 0 0 0
61 ]}; (13)
62 assert(isequal(g0.get('A'), A0), ... (8)
63 [BRAPH2.STR ':GraphBD:' BRAPH2.FAIL_TEST], ...
64 'GraphBD is not constructing well.')
65
66 g_zero = GraphBD('B', B, 'SEMIPOSITIVIZE_RULE', 'zero'); (14)
67 A_zero = {[
68 0 0 0 1 1
69 0 0 1 1 0
70 0 1 0 0 0
71 1 1 0 0 0
72 1 0 0 0 0
73 ]}; (13)
74 assert(isequal(g_zero.get('A'), A_zero), ... (8)
75 [BRAPH2.STR ':GraphBD:' BRAPH2.FAIL_TEST], ...
76 'GraphBD is not constructing well.')
77
78 g_absolute = GraphBD('B', B, 'SEMIPOSITIVIZE_RULE', 'absolute'); (15)
79 A_absolute = {[
80 0 1 0 1 1
81 1 0 1 1 1
82 0 1 0 1 1
83 1 1 1 0 0
84 1 1 1 0 0
85 ]}; (13)
86 assert(isequal(g_absolute.get('A'), A_absolute), ... (8)
87 [BRAPH2.STR ':GraphBD:' BRAPH2.FAIL_TEST], ...
88 'GraphBD is not constructing well.')
89
90 ...

```

(11) Generates an example graph with negative weights

(12) Constructs the GraphBD graph from the initialized B with default RULE for SEMIPOSITIVIZE_RULE.

(13) Expected value of the graph calculated by external means

(14) Constructs the GraphBD graph from the initialized B with RULE = 'zero' for SEMIPOSITIVIZE_RULE.

(15) Constructs the GraphBD graph from the initialized B with RULE = 'absolute' for SEMIPOSITIVIZE_RULE

Implementation of Multilayer Graph

Multilayer Weighted Directed Graph (MultilayerWD)

We can now use GraphBD as the basis to implement the global measure MultilayerWD. The parts of the code that are modified are highlighted.

Code 5: MultilayerWD element header. The header section of generator code for `_MultilayerWD.gen.m` provides the general information about the MultilayerWD element. ← [Code 1](#)

```

1 %% iheader!
2 MultilayerWD < Graph (g, multilayer weighted directed graph) is a multilayer
  weighted directed graph.
3
4 %%% idescription!
5 In a multilayer weighted directed (WD) graph, layers could have different
  number
6 of nodes with within-layer weighted directed edges, associated with a real
7 number between 0 and 1 and indicating the strength of the connection.
8 The connectivity matrices are symmetric (within layer).
9 All node connections are allowed between layers.
```

Code 6: MultilayerWD element prop update. The `props_update` section of generator code for `_MultilayerWD.gen.m` updates the properties of MultilayerWD.

```

1 %% iprops_update!
2
3 %%% iprop!
4 NAME (constant, string) is the name of the multilayer weighted directed
  graph.
5 %%% idefault!
6 'MultilayerWD'
7
8 %%% iprop!
9 DESCRIPTION (constant, string) is the description of the multilayer weighted
  directed graph.
10 %%% idefault!
11 'In a multilayer weighted directed (WD) graph, layers could have different
  number
12 of nodes with within-layer weighted directed edges, associated with a real
13 number between 0 and 1 and indicating the strength of the connection.
14 The connectivity matrices are symmetric (within layer).
15 All node connections are allowed between layers.'
```

```

16
17 %%% iprop!
18 TEMPLATE (parameter, item) is the template of the multilayer weighted
  directed graph.
19
20 %%% iprop!
21 ID (data, string) is a few-letter code of the multilayer weighted directed
  graph.
22 %%% idefault!
23 'MultilayerWD ID'
24
25 %%% iprop!
```



```

26 LABEL (metadata, string) is an extended label of the multilayer weighted
    directed graph.
27 %%%% idefault!
28 'MultilayerWD label'
29
30 %%% iprop!
31 NOTES (metadata, string) are some specific notes about the multilayer
    weighted directed graph.
32 %%%% idefault!
33 'MultilayerWD notes'
34
35 %%% iprop!
36 GRAPH_TYPE (constant, scalar) returns the graph type __Graph.MULTILAYER__.
37 %%%% idefault!
38 Graph.MULTILAYER
39
40 %%% iprop!
41 CONNECTIVITY_TYPE (query, smatrix) returns the connectivity type __Graph.
    WEIGHTED__ * ones(layernumber).
42 %%%% icalculate!
43 if isempty(varargin)
44     layernumber = 1;
45 else
46     layernumber = varargin{1};
47 end
48 value = Graph.WEIGHTED * ones(layernumber);
49
50 %%% iprop!
51 DIRECTIONALITY_TYPE (query, smatrix) returns the directionality type __Graph.
    .DIRECTED__ * ones(layernumber).
52 %%%% icalculate!
53 if isempty(varargin)
54     layernumber = 1;
55 else
56     layernumber = varargin{1};
57 end
58 value = Graph.DIRECTED * ones(layernumber);
59
60 %%% iprop!
61 SELFCONNECTIVITY_TYPE (query, smatrix) returns the self-connectivity type
    __Graph.NONSELFCONNECTED__ on the diagonal and __Graph.SELFCONNECTED__
    off diagonal.
62 %%%% icalculate!
63 if isempty(varargin)
64     layernumber = 1;
65 else
66     layernumber = varargin{1};
67 end
68 value = Graph.SELFCONNECTED * ones(layernumber);
69 value(1:layernumber+1:end) = Graph.NONSELFCONNECTED;
70
71 %%% iprop!
72 NEGATIVITY_TYPE (query, smatrix) returns the negativity type __Graph.
    NONNEGATIVE__ * ones(layernumber).
73 %%%% icalculate!
74 if isempty(varargin)
75     layernumber = 1;
76 else
77     layernumber = varargin{1};
78 end
79 value = Graph.NONNEGATIVE * ones(layernumber);

```

```

80
81 %%% iprop!
82 A (result, cell) is the cell containing the within-layer weighted adjacency
    matrices of the multilayer weighted directed graph and the connections
    between layers.
83
84 %%% icalculate!
85 B = g.get('B');
86 L = length(B);
87 A = cell(L, L);
88 for i = 1:L (1)
89     M = dedagonalize(B{i,i});
90     M = semipositivize(M, 'SemipositivizeRule', g.get('SEMIPOSITIVIZE_RULE'));
91     M = standardize(M, 'StandardizeRule', g.get('STANDARDIZE_RULE'));
92     A(i, i) = {M};
93     if ~isempty(A{i, i})
94         for j = i+1:L
95             M = semipositivize(B{i,j}, 'SemipositivizeRule', g.get('
                SEMIPOSITIVIZE_RULE'));
96             M = standardize(M, 'StandardizeRule', g.get('STANDARDIZE_RULE'));
97             A(i, j) = {M};
98             M = semipositivize(B{j,i}, 'SemipositivizeRule', g.get('
                SEMIPOSITIVIZE_RULE'));
99             M = standardize(M, 'StandardizeRule', g.get('STANDARDIZE_RULE'));
100            A(j, i) = {M};
101        end
102    end
103 end
104 value = A;

```

(1) For each layer in MultilayerWD graph the corresponding functions are applied as in Code 3 (8)

Code 7: **MultilayerWD element tests.** The tests section from the element generator `_MultilayerWD.gen.m`.

```

1 %%% itests!
2
3 %%% iexcluded_props!
4 [MultilayerWD.PFGA MultilayerWD.PFGH]
5
6 %%% itest!
7 %%% iname!
8 Constructor - Full
9 %%% iprobability!
10 .01
11 %%% icode!
12 B1 = rand(randi(10));
13 B2 = rand(randi(10));
14 B3 = rand(randi(10));
15 B12 = rand(size(B1, 1), size(B2, 2));
16 B13 = rand(size(B1, 1), size(B3, 2));
17 B23 = rand(size(B2, 1), size(B3, 2));
18 B21 = rand(size(B2, 1), size(B1, 2));
19 B31 = rand(size(B3, 1), size(B1, 2));
20 B32 = rand(size(B3, 1), size(B2, 2));
21 B = {
22     B1                B12                B13
23     B21                B2                 B23
24     B31                B32                B3
25 };
26 g = MultilayerWD('B', B);
27 g.get('A_CHECK')

```

```

28 A1 = standardize(semipositivize(dediagonalize(B1)));
29 A2 = standardize(semipositivize(dediagonalize(B2)));
30 A3 = standardize(semipositivize(dediagonalize(B3)));
31 A12 = standardize(semipositivize(B12));
32 A13 = standardize(semipositivize(B13));
33 A23 = standardize(semipositivize(B23));
34 A21 = standardize(semipositivize(B21));
35 A31 = standardize(semipositivize(B31));
36 A32 = standardize(semipositivize(B32));
37 B{1,1} = A1;
38 B{2,2} = A2;
39 B{3,3} = A3;
40 B{1,2} = A12;
41 B{1,3} = A13;
42 B{2,3} = A23;
43 B{2,1} = A21;
44 B{3,1} = A31;
45 B{3,2} = A32;
46 A = B;
47 assert(isequal(g.get('A'), A), ...
48 [BRAPH2.STR ': MultilayerWD: ' BRAPH2.FAIL_TEST], ...
49 'MultilayerWD is not constructing well.')

```

Multiplex Graph ()

Ordinal Multilayer Graph ()

Ordinal Multiplex ... Graph ()