## **BMP File Format**

Um ficheiro BMP é constituído por 4 blocos principais de informação:

- Um cabeçalho do ficheiro BitmapFileHeader
- Um cabeçalho da imagem (DIB) BitmapInfoHeader
- Opcional: Uma palete de cores dependendo do BitmapInfoHeader
- Um bloco com a imagem pixel data

De seguida passamos a descrever cada um desses blocos:

```
Class Bitmap{
   BitmapFileHeader bitmapFileHeader;
   BitmapInfoHeader bitmapInfoHeader;
   byte[] rqbQuad;
   byte[] data;
                  // pixel data
}
Class BitmapFileHeader {
   // specifies the size of the file in bytes
   short reserved1; // must always be set to zero
   short reserved2; // must always be set to zero
   int offBits;  // specifies the offset from the
                    // beginning of the file to the bitmap data
}
Class BitmapInfoHeader{
   int size;
                     // the size of this header (40 bytes)
   int xPelsPerMeter; // the horizontal resolution of the image (pixel per meter)
   int yPelsPerMeter; // the vertical resolution of the image (pixel per meter)
   int clrUsed; // the number of colors in the color palette,
                     // or 0 to default to 2n
   int clrImportant; // the number of important colors used,
                     // or 0 when every color is important
}
```

## RGBQUAD structure (ColorPallete):

Start	Size	Name	Purpose
1	1	rgbBlue	Specifies the blue part of the color.

2	1	rgbGreen	Specifies the green part of the color.
3	1	rgbRed	Specifies the red part of the color.
4	1	rgbReserved	must always be set to zero.

## **Some Important Notes:**

- 1. Pixels are stored "upside-down" (Last row first).
- 2. RGB color (24-bit) pixel values are stored with bytes as BGR (blue, green, red).
- 3. Padding bytes are inserted in order to keep the line of data in multiples of four.
- 4. The color palette is not used when the bitmap is 16-bit or higher. There is no palette byte array in those BMP files.
- 5. BitmapInfoHeader compression method field:

Value	Identified by	Compression method	Comments
0	BI_RGB	none	Most common
1	BI_RLE8	RLE 8-bit/pixel	Can be used only with 8-bit/pixel bitmaps
2	BI_RLE4	RLE 4-bit/pixel	Can be used only with 4-bit/pixel bitmaps
3	BI_BITFIELDS	Bit field	Can be used only with 16 and 32-bit/pixel bitmaps.
4	BI_JPEG	JPEG	The bitmap contains a JPEG image
5	BI_PNG	PNG	The bitmap contains a PNG image

## Example of a 2×2 Pixel Bitmap, with 24 bits/pixel encoding

Offset	Size	Hex Value	Value	Description
0h	2	42 4D	"BM"	Magic Number (unsigned integer 66, 77)
2h	4	46 00 00 00	70 Bytes	Size of the BMP file
6h	2	00 00	Unused	Application Specific
8h	2	00 00	Unused	Application Specific
Ah	4	36 00 00 00	54 bytes	The offset where the bitmap data (pixels) can be found.
Eh	4	28 00 00 00	40 bytes	The number of bytes in the header (from this point).
12h	4	02 00 00 00	2 pixels	The width of the bitmap in pixels
16h	4	02 00 00 00	2 pixels	The height of the bitmap in pixels
1Ah	2	01 00	1 plane	Number of color planes being used.
1Ch	2	18 00	24 bits	The number of bits/pixel.
1Eh	4	00 00 00 00	0	BI_RGB, No compression used
22h	4	10 00 00 00	16 bytes	The size of the raw BMP data (after this header)

26h	4	13 OB 00 00	2,835 pixels/meter	The horizontal resolution of the image	
2Ah	4	13 0B 00 00	2,835 pixels/meter	The vertical resolution of the image	
2Eh	4	00 00 00 00	0 colors	Number of colors in the palette	
32h	4	00 00 00 00	0 important colors	Means all colors are important	
	Start of Bitmap Data				
36h	3	00 00 FF	0 0 255	Red, Pixel (0,1)	
39h	3	FF FF FF	255 255 255	White, Pixel (1,1)	
3Ch	2	00 00	0 0	Padding for 4 byte alignment (Could be a value other than zero)	
3Eh	3	FF 00 00	255 0 0	Blue, Pixel (0,0)	
41h	3	00 FF 00	0 255 0	Green, Pixel (1,0)	
44h	2	00 00	0 0	Padding for 4 byte alignment (Could be a value other than zero)	