

SMS API Documentation

Developer Integration Guide

1. Overview

This document describes the SMS API used to send transactional, Unicode, and scheduled SMS messages. It includes the request endpoint, parameter details, sample requests, response format, and common error codes.

2. API Endpoint

GET

```
https://smsfortius.org/V2/apikey.php?apikey=XXXXXXXXXXXXXXXXXXXX&senderid=XXXXXX&templateid=XXXXXXXXXXXX&number=XXXXXXXXXX,XXXXXXXXXX&message=Hello%20There
```

The API accepts query string parameters. The message value must be URL encoded.

3. Authentication

The API supports usage with or without an API key, depending on the route and account configuration. When API-key authentication is used, pass the apikey parameter generated from the SMS account. For normal API flow, the apikey parameter is not required.

4. Request Parameters

Name	Parameter	Description	Expected Values	Required
API Key	apikey	API key generated from your SMS account.	Key generated from your account	Conditional
Sender ID	senderid	Sender ID assigned to your account.	6 characters only	Yes
Mobile Number	number	Destination number(s) for SMS delivery. Multiple numbers can be comma-separated. The number may be provided with or without 91.	91XXXXXXXXXX or 98908XXXXX or 91XXXXXXXXXX,98908XXXXX	Yes
Message	message	Message to be sent. Must be URL encoded.	Text message, max 1000 characters for normal SMS and 500 for Unicode	Yes
Unicode Flag	unicode	Specifies that the message is Unicode.	2	Optional
Schedule Time	time	Date and time for scheduling the SMS.	YYYY-MM-DD HH:MM:SS or YYYY-MM-DD HH:MM AM/PM, for example 2016-12-06 04:45pm	Optional
DLT Template ID	templateid	Registered DLT template ID for the message.	Share DLT Registered Template-ID	Optional

Response Format	format	Output response format.	PHP or JSON. Default response is JSON	Optional
-----------------	--------	-------------------------	---------------------------------------	----------

Note: If templateid is not sent, the system checks the sender ID and message details, then forwards the best match to the vendor for SMS termination.

5. Request Examples

5.1 Normal SMS

```
https://smsfortius.org/V2/apikey.php?apikey=XXXXXXXXXXXXXXXXXXXX&senderid=XXXXXX&templateid=XXXXXXXXXXXX&number=XXXXXXXXXX,XXXXXXXXXX&message=Hello%20There
```

5.2 Unicode SMS

```
https://smsfortius.org/V2/apikey.php?apikey=XXXXXXXXXXXXXXXXXXXX&senderid=XXXXXX&templateid=XXXXXXXXXXXX&number=XXXXXXXXXX&message=%E0%A4%A8%E0%A4%AE%E0%A4%B8%E0%A5%8D%E0%A4%A4%E0%A5%87&unicode=2
```

5.3 Scheduled SMS

```
https://smsfortius.org/V2/apikey.php?apikey=XXXXXXXXXXXXXXXXXXXX&senderid=XXXXXX&templateid=XXXXXXXXXXXX&number=XXXXXXXXXX&message=Hello%20There&time=2016-12-06%2004:45pm
```

5.4 Unicode Scheduled SMS

```
https://smsfortius.org/V2/apikey.php?apikey=XXXXXXXXXXXXXXXXXXXX&senderid=XXXXXX&templateid=XXXXXXXXXXXX&number=XXXXXXXXXX&message=%E0%A4%A8%E0%A4%AE%E0%A4%B8%E0%A5%8D%E0%A4%A4%E0%A5%87&unicode=2&time=2016-12-06%2004:45pm
```

6. Success Response

On successful submission, the API returns a JSON response in the following structure:

```
{
  "status": true,
  "code": "011",
  "data": {
    "messageid": "message campaign id",
    "totnumber": "total numbers of sms",
    "totalcredit": "total sms credit"
  }
}
```

Field meaning: status indicates success or failure, code contains the response code, and data contains the campaign details.

7. API Error Codes

Error Code	Status	Description
001	false	Kindly provide apikey
002	false	Invalid route-Id
004	false	No Message Found!
005	false	Schedule Date/time can't less than current time!
006	false	Invalid Date Time Format!

007	false	No numbers found!
008	false	You have insufficient credit!
009	false	Parent has Less Balance!
010	false	Message campaign failed!
011	Success	Message submitted successfully

8. Implementation Notes

- Always URL encode the message text before sending the request.
- Use the correct sender ID registered to your account.
- For multiple recipients, separate numbers with commas.
- Use unicode=2 only when the message contains Unicode characters.
- For scheduled SMS, ensure the time is in a valid future date/time format.
- Register and use the correct DLT template ID where required.
- Handle both success and error responses in the client application.

Prepared for developer integration and client-side implementation.