


Self-Supervised depth estimation

Aleksei Karpov
Moscow Institute of Physics and Technology


Introduction

- Training:
 - Model for depth prediction using only geometrical constraints during training
 - Data for training: stereo pairs or image sequences
 - Target: estimate nearby frame
 - Loss function: photometric reprojection error
 - Model predict depth and egomotion between two frames (for image sequences)
- Comparison with supervised
 - Easier data collection (not require LiDAR data)
 - Better generalization
 - Worse performance



Current architectures



- Fully convolutional networks for both networks
- U-Net based architectures for depth model:
 - Encoder: ResNet (Usually ResNet18 pretrained on ImageNet)
 - Decoder: Convolutional architecture
- ResNet for pose model
- Papers: [monodepth2](#), [ManyDepth](#)
- CNN limitations:
 - Small receptive field
 - Poorly process global features



Novel architectures


Vision Transformers (ViT)

- Split image into patches
 - Embed patches
 - Add position encoding
 - Feed vectors to Transformer
-
- Advantages:
 - Global receptive field
 - Achieved promising results for classification and segmentation
 - Disadvantages:
 - High complexity
 - Position encoding is fixed-dimension vectors
-
- [Original ViT paper](#)
 - [ViT for supervised depth prediction](#)



ViT improvements


- Progressive shrinking to reduce complexity
- Overlapped patches
- Conditional position encoding
- Spatially sparable self-attention
- Papers: [PVTv1](#), [PVTv2](#), [Swin](#), [Twins](#)
- Main improvements:
 - Less complexity(comparable with ResNet18)
 - Better performance
 - More suitable for dense prediction tasks



ViT for self-supervised depth estimation


ViT Encoder

- Encoder based on PVT models
- Decoder contains CNN blocks
- Encoder weights pretrained on ImageNet
- Stable training process




Pure ViT model

- Encoder based on PVT model
- Encoder contains ViT blocks
- Encoder weights pretrained on ImageNet
- Unstable training process



ViT Middle

- Encoder is ResNet18
- Middle based on ViT
- Decoder contains CNN blocks
- Encoder weights pretrained on ImageNet
- Stable training process



Conclusion

- **Current results:**

- Overview current self-supervised depth estimation architectures
- Analyze Vision Transformer architectures
- Propose Transformer architecture for self-supervised depth estimation
- Novel architecture better process global features

- **Future work:**

- Train models with different ViT encoder architectures*
- Train models with various CNN and ViT combinations*
- Compare models performance
- Implement cost volume based depth estimator like [ManyDepth](#)

* - partially done

Thank you for attention