PageRank Simple NNs

Vladislav Goncharenko

Senior researcher

girafe ai

MIPT,
spring 2025

Lecture plan

- SLIM
- Factorization machines
- Content-based recommendations
- Neural network recommendations.

PageRank

girafe ai

01

Markov chains



- Popular tale on Markov chains https://www.youtube.com/watch?v=KZeIEiBrT_w
- PageRank video https://www.youtube.com/watch?v=JGQe4kiPnrU


Internet model

Web pages are nodes, hyperlinks are directed edges.

We want to generate features for pages. They could be importances of pages.

On important page people spend more time. We can model people behaviour with a discrete random process of moving from one page to another.


Then stationary state of a Markov chain corresponds to time on page and we need to calculate it.



Transition matrix

represents connections in a directed graph. Each column corresponds to a vertex (all outgoing connections).

Then stationary state is when given distribution of users is the same after some step. In matrix form it corresponds to a [characteristic equation](#) for that matrix.



$$P \cdot V_K = V_{K+1}$$


$$PV = V \qquad (P - \lambda I)V = 0$$

eigen val/vect

Eigenvectors of a matrix

Could be determined by

1. Symbolic derivation
   a. takes n^3 time, not practical
2. Power iteration
   a. better, but not for 100m pages
3. Monte Carlo method
   a. scales, provides approximate solution.



Monte Carlo regularization

Users get bored sometimes, so in our model they go to a random page with a small probability (5-10%).

$$(P + p_r F) \cdot r_k = r_{k+1}$$

$$\begin{bmatrix} p_r \\ p_r \\ p_r \\ p_r \end{bmatrix} = p_r \cdot \begin{bmatrix} 1 & 1 & \cdots \\ 1 & 1 & \\ 1 & 1 & \\ 1 & 1 & \end{bmatrix} = p_r F$$

$$p_r = \frac{\alpha}{N^2}$$

Content models usage


girafe ai

02

Main takeouts

Content models

- are most valuable for cold items
- could be trained on collaborative target (e.g. inner products matrix)
- serve as one more candidate source (especially for cold items)




Two Tower Neural Networks

girafe ai


03

SVD is a kind of neural network

Let's go back to the matrix decomposition and think about how we can take into account additional features in it.




We teach using
Matrix Factorization



Early binding and later binding

$$R(Q,D) = \text{cosine}(y_Q, y_D) = \frac{{y_Q}^T y_D}{\|y_Q\|\|y_D\|}$$




Advantages of later binding:

- add users, items without retrain of all model
- ability to pre-calculate (usually item) vectors
  - ability to use kNN indexes

Deep Structured Semantic Models

$$R(Q,D) = \text{cosine}(y_Q, y_D) = \frac{{y_Q}^T y_D}{\|y_Q\| \|y_D\|}$$



DSSM is a classic search and ranking model

- ***Q*** – text query, ***D*** – document
- x_Q and x_D are their representations, for example, in the form of bag of words (~100k)
- The request and the document are translated by neural networks into embeddings of a small size (~300)
- Between them we consider the proximity function, cosine, scalar product, etc
- We rank documents by the proximity value

Deep Structured Semantic Models: how to train?

We will consider the conditional probability of a click on the document ***D*** under the condition of the query ***Q***.

$$P(D|Q) = \frac{\exp(\gamma R(Q,D))}{\sum_{D} \exp(\gamma R(Q,D))}$$

$$R(Q,D) = \text{cosine}(y_Q, y_D) = \frac{{y_Q}^T y_D}{\|y_Q\| \|y_D\|}$$

Here
γ – k-t smoothing, established empirically
D – the set of all documents

Calculating the gradient of such a functional for each example is expensive. What can be done?

Deep Structured Semantic Models: how to train?

We will consider the conditional probability of a click on the document ***D*** under the condition of the query ***Q***.

$$P(D|Q) = \frac{\exp(\gamma R(Q,D))}{\sum_{D} \exp(\gamma R(Q,D))}$$

$$R(Q,D) = \text{cosine}(y_Q, y_D) = \frac{y_Q{}^T y_D}{\|y_Q\| \|y_D\|}$$

Here
γ – k-t smoothing, established empirically
D – the set of all documents

Negative sampling options:

1. It is equally likely to select a subset of documents from non-selected ones
2. It is more likely to choose those unlisted documents whose popularity is higher
3. At each epoch of training, choose non-called documents with the maximum score (the score is taken from the previous epoch)

Deep Structured Semantic Models: how to train?

Taking into account negative sampling , the probability of a click in the document is described by the formula


$$P(D|Q) = \frac{\exp(\gamma R(Q,D))}{\exp(\gamma R(Q,D)) + \sum_{d \in \mathbf{D}^-} \exp(\gamma R(Q,d))}$$

During the training process, we will maximize the likelihood of the sample, or, what is the same thing, minimize the loss:

$$L(\Lambda) = -\log \prod_{(Q,d \in \mathbf{D}^+)} P(d|Q)$$

where Λ are the parameters of the layers
***D*⁺** – a lot of clicked documents
***D*⁻** – lots of negative sampling documents

A quantum leap from search to recommendations




The search for relevant items can be presented as a ranking task, where the user, his history and features are used as a query.

Document features

As signs, you can use:

- standard document statistics: number of likes, clicks, subscriptions
- author's signs: number of subscribers, genre
- unstructured data: document text (you can use BOW format, or you can use it before trained embeddings), videos and pictures (also pre-submit them as embedding)




User features

As features, you can use:

- information about the user: age, gender, language, how long the service
- has been using information about the context of the request: from which device was made, at what time
- information about the user's friends/subscribers and their interactions

It makes sense to use the user's history as an average embedding of those articles that he read. Or train RNN or Transformer on history and concatenate the result to the rest of the features.



Learning strategies

girafe ai

04

Two-tower neural network: types of losses

- Regression - MSE
- Classification - Cross Entropy Loss (CE)
- Ranking - Pairwise loss, LambdaRank
- Representation learning aka Metric learning
    - Full Product Softmax loss (aka: Infancy, InfoMAX, SINCLAR)

Cross entropy loss

The probability that user u will click on item i can be represented as:

$$\widehat{p}_{ui} = \sigma(R(u,i)) = \sigma(\mathrm{dot}(y_u, y_i))$$

Were:

y_i – embedding of aitema

y_u – embedding the user

$\sigma(x) = \frac{1}{1+e^{-x}}$

Then the loss has the form ($r_{u,i} \in \{0,1\}$ – rating):

$$L = -\sum_{u,i}(r_{ui}\log\widehat{p}_{u,i} + (1-r_{u,i})\log(1-\widehat{p}_{u,i}))$$

Pairwise losses

Consider a pair of items in which i_1 – positive, i_2 – negative, there are several options for pairwise loss:

$$L(R(u, i_1), R(u, i_2)) = \text{CrossEntropy}(1.0,\ \sigma(R(u, i_1) - R(u, i_2)))$$


the network learns to rank positive examples above negative ones

$$L(R(u, i_1), R(u, i_2)) = \max(0, \alpha - R(u, i_1) + R(u, i_2))$$


the network makes sure that the positive and negative examples differ as much as possible (known as triplet loss, which is used to train Siamese networks)

https://www.v7labs.com/blog/contrastive-learning-guide
https://medium.com/@maksym.bekuzarov/losses-explained-contrastive-loss-f8f57fe32246


Pairwise losses




Pairwise losses



Pairwise losses




Pairwise losses




Full Product Softmax loss

Consider a batch of interactions of size m, consisting of
- User embedding matrices $U \in \mathbb{R}^{m \times d}$
- Embedding matrices of aitems $I \in \mathbb{R}^{m \times d}$
- Target vectors $r \in \mathbb{R}^m$

Consider a matrix $\text{Softmax}(\alpha \cdot UI^T + \beta),\ UI^T \in \mathbb{R}^{m \times m}$ where softmax is taken by rows.




CLIP pre-training



https://openai.com/index/clip/

CLIP usage


plane
car
dog
bird
a photo of a {object}.
Text Encoder
...
3. Use for zero-shot prediction
T_1 T_2 T_3 ... T_N
Image Encoder
I_1
$I_1 \cdot T_1$ $I_1 \cdot T_2$ $I_1 \cdot T_3$ ... $I_1 \cdot T_N$
a photo of a dog.

Full Product Softmax loss

Consider a loss of the form


$$L = -(r > 0)^T \cdot \log(\text{diag}(\text{softmax}(\alpha \cdot UI^T + \beta)))$$


The loss makes the diagonal elements of the matrix larger than the rest of the elements: so in a dataset with unique users and documents on the diagonal of the optimal matrix will be $r > 0$

Data augmentation for IR

As well as in other fields of ML we may use augmentation to generate data for contrastive learning


What else have we tried?






1. Users and items have learnable embedding
2. Embedding is concatenated and passed through MLP
3. The neural network provides a prediction of the rating

What else have we tried?







Method	Movielens		Pinterest		Result
	HR@10	NDCG@10	HR@10	NDCG@10	from
Popularity	0.4535	0.2543	0.2740	0.1409	[8]
SLIM [25, 30]	<u>0.7162</u>	<u>0.4468</u>	0.8679	<u>0.5601</u>	[8]
iALS [20]	0.7111	0.4383	0.8762	0.5590	[8]
NeuMF (MLP+GMF) [17]	0.7093	0.4349	<u>0.8777</u>	0.5576	[8]
Matrix Factorization	**0.7294**	**0.4523**	**0.8895**	**0.5794**	Fig. 2

Conclusions

1. The fundamental difference between neural network models and factorization machines is that we do not limit ourselves only to linear transformations and add non-linearity
2. Two-tower architecture (in particular DSSM) has a number of advantages:
   A. A large space for creativity in the design of features ☝
   B. Fast inference, since embedding and items can be pre-calculated offline
   C. The ability to build an offline (and even online) selection of candidates for trained embedding

3. Teaching an alternative dot-y measure of proximity using MLP is a flexible idea

Self-attention

girafe ai


07

Self-attention

The layer receives the embedding $x_1, \ldots, x_t$ of sequence elements as input and converts them into embeddings $z_1, \ldots, z_t$ that take into account information about the elements in all other positions.


Let's look at the illustration for the texts:

- In each position we look at all the words in the text
- We determine which words need to be looked at more strongly, and which ones are weaker
- Based on this information, we are building a new embedding position



Self-attention


The first step is to build three vectors Key, Query and Value for each word in the sentence



Self-attention

The first step is to build three vectors Key, Query and Value for each word in the sentence

Further, the scalar product of the vectors q_i and k_i lo shows how much attention should be paid to the word j in position i.




Self-attention

The first step is to build three vectors Key, Query and Value for each word in the sentence

Further, the scalar product of the vectors q_i and k_i lo shows how much attention should be paid to the word ***j*** in position ***i***.

Then we normalize the scores by the root of the dimensions of the key and query vectors and calculate the softmax of the scores for each position.
We get the weights with which we look at each word in the sentence.




Self-attention

The first step is to build three vectors Key, Query and Value for each word in the sentence


Further, the scalar product of the vectors q_i and k_i lo shows how much attention should be paid to the word ***j*** in position ***i***.

Then we normalize the scores by the root of the dimensions of the key and query vectors and calculate the softmax of the scores for each position.
We get the weights with which we look at each word in the sentence.

With these weights, we average the value vectors and get a new embedding of a word in a sentence that takes into account all other words



Self-attention in matrix form




$$\text{softmax}\left(\frac{Q \times K^T}{\sqrt{d_k}}\right) V = Z$$

Multi-head Self-attention

We will use several parallel heads of self-attention.

For each head we have our own projection matrices




Multi-head Self-attention

We will use several parallel heads of self-attention.


For each head we have our own projection matrices

At the end we concatenate the embedding and from all the heads and linearly project it into the embedding of the correct size



Multi-head Self-attention

The main idea: different heads pay attention to the different dependencies between the elements of the sequence



Positional Encoding

girafe ai

08

Positional Encoding

Problem: in this formula there is no dependence on the position in the sentence, we work with its elements as with a set

Positional Encoding

Problem: in this formula there is no dependence on the position in the sentence, we work with its elements as with a set


Solution: to embedding positional embedding and, instead of xi, consider xi + pi, where positional embedding pi depends only on position i.

Positional Encoding

Problem: in this formula there is no dependence on the position in the sentence, we work with its elements as with a set

Solution: to embedding positional embedding and, instead of ***xi***, consider ***xi*** + ***pi***, where positional embedding ***pi*** depends only on position ***i***.

Option 1: positional embedding is deterministically calculated by cosine formulas




Positional Encoding

Problem: in this formula there is no dependence on the position in the sentence, we work with its elements as with a set

Solution: to embedding positional embedding and, instead of ***xi***, consider ***xi*** + ***pi***, where positional embedding ***pi*** depends only on position ***i***.

Option 1: positional embedding is deterministically calculated by cosine formulas

Option 2: Positional embedding is trained together with the entire model



Bert4Rec

girafe ai

09

Bert4Rec

- The self-attention approach shows itself well in tasks related to texts, audio and images
- The Bert4Rec model is an attempt to apply this approach to the task of recommendations
- The model is applied to a sequence of items from the user's history and predicts the next item

Multi-head Self-attention

The layer receives the embedding $h_1, \ldots, h_t$ of sequence elements as input and converts them into embeddings $h'_1, \ldots, h'_t$ hat take into account information about all other positions.

Let's define the basic Attention operation, which takes the input of the matrix Q, K, V and returns

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{m}}\right)V, \quad Q, K, V \in \mathbb{R}^{t \times m}$$

- $\text{Attention}(Q, K, V)_i = \text{softmax}\left(\frac{Q_i K^T}{\sqrt{m}}\right)V$

This is a linear combination of strings from V with weights $\text{softmax}\left(\frac{Q_i K_1}{\sqrt{m}}\right), \ldots, \text{softmax}\left(\frac{Q_i K_t}{\sqrt{m}}\right)$

- Accordingly, ***Qi*** and ***K*** express how much contribution information about all other elements should have to the element of position ***i***.
- The matrix ***V*** carries the information that each position should transmit.

Multi-Head Self-Attention

Let the input embedding form a matrix $H \in \mathbb{R}^{t \times d}$


Define

$$MH(H) = [\text{head}_1, \ldots, \text{head}_h]W^O, \quad W^O \in \mathbb{R}^{d \times d}$$

$$\text{head}_i = Attention(HW_i^Q, HW_i^K, HW_i^V), \quad W_i^Q, W_i^K, W_i^V \in \mathbb{R}^{d \times d/h}$$

W^O, W_i^Q, W_i^K, W_i^V – trainable parameters

Transformers layer



(a) Transformer Layer.


Consists of:

- Multi-Head Self-Attention Layer
- Position-wise Feed-Forward, applied to outputs piecemeal

$$FFN(x) = GELU(xW^{(1)} + b^{(1)})W^{(2)} + b^{(2)}$$

- Dropout, skip connection and LayerNorm after both previous ones

Bert4Rec Architecture




(b) BERT4Rec model architecture.

The model consists of

- Layers of embeddings of aitems
- ***L*** Transformer layers
- A projecting head that performs predictions

Bert4Rec Architecture



(b) BERT4Rec model architecture.

The model consists of


- Layers of embeddings of aitems
- ***L*** Transformer layers
- A projecting head that performs predictions

Itemes of positive user interactions are submitted to the input in order of time.

A special [mask] item is added to the end of the story.

To the output embedding corresponding to this special item, we apply a projection head that predicts the relevant next item.

Bert4Rec Architecture



(b) BERT4Rec model architecture.

The model consists of

- Layers of embeddings of aitems
- ***L*** Transformer layers
- A projecting head that performs predictions

Itemes of positive user interactions are submitted to the input in order of time.

A special [mask] item is added to the end of the story.

To the output embedding corresponding to this special item, we apply a projection head that predicts the relevant next item.

The projection layer is arranged as


$$P(v) = \text{softmax}\left(GELU(h_i^L W^P + b^P)E^T + b^O\right),$$

where $E \in \mathbb{R}^{|V| \times d}$ the trainable matrix of aitems

Bert4Rec, Fei Sun, Jun Liu, Jian Wu et al.

Bert4Rec Training

- We will randomly mask the share of the items **ρ** from the user's history, that is, we will replace it with a special item [mask]



- Let S_u^m be the set of masked positions of the user ***u***,

  S'_u – a sequence of aitems with replaced by [mask] aitems,

  v_m^* – predictions of aitems in disguised positions

  Then we optimize the likelihood, that is:

$$\mathcal{L} = -\frac{1}{|S_u^m|} \sum_{m \in S_u^m} \log P(v_m^* = v_m | S'_u)$$

- In other words, learning is similar to Masked Language Model learning in text tasks

Thanks for attention!

Questions?



girafe
ai

