

Feedback — Final Exam

[Help](#)

You submitted this exam on **Wed 14 May 2014 5:17 PM PDT**. You got a score of **13.00** out of **13.00**.

Question 1

Let (E, D) be an authenticated encryption system built by combining a CPA-secure symmetric cipher and a MAC. The system is combined with an error-correction code to correct random transmission errors. In what order should encryption and error correction be applied?

Your Answer	Score	Explanation
<input type="radio"/> Apply the error correction code and then encrypt the result.		
<input type="radio"/> The order does not matter -- neither one can correct errors.		
<input type="radio"/> The order does not matter -- either one is fine.		
<input checked="" type="radio"/> Encrypt and then apply the error correction code.	✓ 1.00	That is correct. The error correction code will do its best to correct random errors after which the MAC in the ciphertext will be checked to ensure no other errors remains.
Total	1.00 / 1.00	

Question 2

Let X be a uniform random variable over the set $\{0, 1\}^n$. Let Y be an arbitrary random variable over the set $\{0, 1\}^n$ (not necessarily uniform) that is independent of X . Define the random variable $Z = X \oplus Y$. What is the probability that Z equals 0^n ?

Your Answer

Score Explanation

☐ $2/2^n$

☒ $1/2^n$



1.00

The probability is $1/2^n$. To see why, observe that whatever Y is, the probability that $Z = X \oplus Y = 0^n$ is the same as the probability that $X = Y$ which is exactly $1/2^n$ because X is uniform.

☐ $1/n^2$

☐

$1 - (1/2^n)$

Total

1.00 /

1.00

Question 3

Suppose (E_1, D_1) is a symmetric cipher that uses 128 bit keys to encrypt 1024 bit messages. Suppose (E_2, D_2) is a symmetric cipher that uses 128 bit keys to encrypt 128 bit messages. The encryption algorithms E_1 and E_2 are deterministic and do not use nonces. Which of the following statements is true?

Your Answer

Score Explanation

☒ (E_1, D_1) can be one-time semantically secure.



0.25

Yes, for example (E_1, D_1) can be a secure stream cipher.

☒ (E_2, D_2) can be one-time semantically secure and perfectly secure.



0.25

Yes, for example (E_2, D_2) can be the one time pad.

☐ (E_1, D_1) can be perfectly secure.



0.25

The statement is incorrect: for (E_1, D_1) the keys are too short to provide perfect

secrecy.

<input type="checkbox"/> (E_1, D_1) can be semantically secure under a chosen plaintext attack.	✓ 0.25	The statement is incorrect: (E_1, D_1) is deterministic and uses no nonces
---	--------	--

Total	1.00 /
	1.00

Question 4

Which of the following statements regarding CBC and counter mode is correct?

Your Answer	Score	Explanation
<input checked="" type="radio"/> CBC mode encryption requires a block cipher (PRP), but counter mode encryption only needs a PRF.	✓ 1.00	Yes, CBC needs to invert the PRP for decryption, while counter mode only needs to evaluate the PRF in the forward direction for both encryption and decryption. Therefore, a PRF is sufficient for counter mode.
<input type="radio"/> Both counter mode and CBC mode can operate just using a PRF.		
<input type="radio"/> counter mode encryption requires a block cipher (PRP), but CBC mode encryption only needs a PRF.		
<input type="radio"/> Both counter mode and CBC mode require a block cipher (PRP).		
Total	1.00 /	
	1.00	

Question 5

Let $G : X \rightarrow X^2$ be a secure PRG where $X = \{0, 1\}^{256}$. We let $G(k)[0]$ denote the left half of the output and $G(k)[1]$ denote the right half. Which of the following statements is true?

Your Answer	Score	Explanation
<input type="radio"/> $F(k, m) = m \oplus k$ is a secure PRF with key space and message space X .		
<input type="radio"/> $F(k, m) = G(m)[0] \oplus k$ is a secure PRF with key space and message space X .		
<input type="radio"/> $F(k, m) = G(k)[0] \oplus m$ is a secure PRF with key space and message space X .		
<input checked="" type="radio"/> $F(k, m) = G(k)[m]$ is a secure PRF with key space X and message space $m \in \{0, 1\}$.	1.00	Yes, since the output of $G(k)$ is indistinguishable from random, the left and right halves are indistinguishable from random independent values.
Total	1.00 / 1.00	

Question 6

Let (E, D) be a nonce-based symmetric encryption system (i.e. algorithm E takes as input a key, a message, and a nonce, and similarly the decryption algorithm takes a nonce as one of its inputs). The system provides chosen plaintext security (CPA-security) as long as the nonce never repeats. Suppose a single encryption key is used to encrypt 2^{32} messages and the nonces are generated independently at random for each encryption, how long should the nonce be to ensure that it never repeats with high probability?

Your Answer	Score	Explanation
<input type="radio"/> 16 bits		
<input checked="" type="radio"/> 128 bits	✓ 1.00	Yes, the probability of repetition after 2^{32} samples is negligible.
<input type="radio"/> 32 bits		
<input type="radio"/> 48 bits		
Total	1.00 / 1.00	

Question 7

Same as question 6 except that now the nonce is generated using a counter. The counter resets to 0 when a new key is chosen and is incremented by 1 after every encryption. What is the shortest nonce possible to ensure that the nonce does not repeat when encrypting 2^{32} messages using a single key?

Your Answer	Score	Explanation
<input type="radio"/> 128 bits		
<input checked="" type="radio"/> 32 bits	✓ 1.00	Yes, with 32 bits there are 2^{32} nonces and each message will use a different nonce.
<input type="radio"/> 16 bits		
<input type="radio"/> the nonce must be chosen at random, otherwise the system cannot be CPA secure.		
Total	1.00 / 1.00	

Question 8

Let (S, V) be a deterministic MAC system with message space M and key space K . Which of the following properties is implied by the standard MAC security definition?

Your Answer	Score	Explanation
<input type="radio"/> The function $S(k, m)$ is a secure PRF.		
<input type="radio"/> Given a key k in K it is difficult to find distinct messages m_0 and m_1 such that $S(k, m_0) = S(k, m_1)$		
<input checked="" type="radio"/> Given m and $S(k, m)$ it is difficult to compute k .	✓ 1.00	yes, otherwise the attacker can easily mount an existential forgery.
<input type="radio"/> $S(k, m)$ preserves semantic security of m . That is, the adversary learns nothing about m given $S(k, m)$.		
Total	1.00 / 1.00	

Question 9

Let $H : M \rightarrow T$ be a collision resistant hash function where $|T|$ is smaller than $|M|$. Which of the following properties is implied by collision resistance?

Your Answer	Score	Explanation
<input type="radio"/> For all m in M , $H(m)$ must be shorter than m .		
<input type="radio"/> it is difficult to find m_0 and m_1 such that $H(m_0) = H(m_1) + 1$ (here we treat the outputs of H as integers)		
<input checked="" type="radio"/> Given a tag $t \in T$ it is difficult to construct $m \in M$ such that $H(m) = t$	✓ 1.00	yes, if these were easy then the attacker could easily find collisions.
<input type="radio"/> $H(m)$ preserves semantic security of		

m (that is, given $H(m)$ the attacker learns nothing about m).

Total	1.00 /
	1.00

Question 10

Recall that when encrypting data you should typically use a symmetric encryption system that provides authenticated encryption. Let (E, D) be a symmetric encryption system providing authenticated encryption. Which of the following statements is implied by authenticated encryption?

Your Answer	Score	Explanation
<input checked="" type="checkbox"/> (E, D) provides chosen-ciphertext security.	<input checked="" type="checkbox"/> 0.25	yes, we showed this in class.
<input checked="" type="checkbox"/> Given m and $E(k, m)$ the attacker cannot create a valid encryption of $m + 1$ (here we treat plaintexts as integers)	<input checked="" type="checkbox"/> 0.25	yes, otherwise the system would not have ciphertext integrity.
<input type="checkbox"/> Given $c = E(k, m)$ for some secret k, m , the attacker cannot find k', m' such that $c = E(k', m')$	<input checked="" type="checkbox"/> 0.25	The statement is incorrect: there are no guarantees about the hardness of finding keys k' with special properties. For example, it is possible to build a GCM-like system where finding k' and m' is easy, despite the system providing authenticated encryption.
<input type="checkbox"/> Given k, m and $E(k, m)$ the attacker cannot create a valid encryption of	<input checked="" type="checkbox"/> 0.25	The statement is incorrect: once the attacker is given k the system has no security.

$m + 1$ under key k . (here we treat plaintexts as integers)

Total	1.00 /
	1.00

Question 11

Which of the following statements is true about the basic Diffie-Hellman key-exchange protocol.

Your Answer	Score	Explanation
<input type="checkbox"/> The protocol is based on the concept of a trapdoor function.	✓ 0.25	The statement is incorrect: Diffie-Hellman does not use trapdoor functions. It is based on the exponentiation function $f(x) = g^x$ and the fact that $(g^a)^b = (g^b)^a$. The exponentiation function in \mathbb{Z}_p^* does not have a trapdoor (as far as we know).
<input type="checkbox"/> As with RSA, the protocol only provides eavesdropping security in the group \mathbb{Z}_N^* where N is an RSA modulus.	✓ 0.25	The statement is incorrect: Diffie-Hellman works in any group where the Hash Diffie-Hellman problem holds.
<input checked="" type="checkbox"/> The protocol can be converted to a public-key encryption system called the ElGamal public-key system.	✓ 0.25	yes, that is correct.
<input checked="" type="checkbox"/> The protocol provides security against eavesdropping in any finite group in which the Hash	✓ 0.25	yes, in any such group the hash of the Diffie-Hellman secret g^{ab} can be used as a shared secret.

Diffie-Hellman
(HDH) assumption
holds.

Total	1.00 / 1.00
-------	----------------

Question 12

Suppose $n + 1$ parties, call them B, A_1, \dots, A_n , wish to setup a shared group key. They want a protocol so that at the end of the protocol they all have a common secret key k , but an eavesdropper who sees the entire conversation cannot determine k . The parties agree on the following protocol that runs in a group G of prime order q with generator g :

- for $i = 1, \dots, n$ party A_i chooses a random a_i in $\{1, \dots, q\}$ and sends to Party B the quantity $X_i \leftarrow g^{a_i}$.
- Party B generates a random b in $\{1, \dots, q\}$ and for $i = 1, \dots, n$ responds to Party A_i with the messages $Y_i \leftarrow X_i^b$.

The final group key should be g^b . Clearly Party B can compute this group key. How would each Party A_i compute this group key?

Your Answer	Score	Explanation
<input type="radio"/> Party A_i computes g^b as $Y_i^{a_i}$		
<input checked="" type="radio"/> Party A_i computes g^b as Y_i^{1/a_i}	✓ 1.00	Yes, $Y_i^{1/a_i} = g^{(ba_i)/a_i} = g^b$.
<input type="radio"/> Party A_i computes g^b as Y_i^{-1/a_i}		
<input type="radio"/> Party A_i computes g^b as $Y_i^{-a_i}$		
Total	1.00 / 1.00	

Question 13

Recall that the RSA trapdoor permutation is defined in the group \mathbb{Z}_N^* where N is a product of two large primes. The public key is (N, e) and the private key is (N, d) where d is the inverse of

$e \in \mathbb{Z}_{\varphi(N)}^*$.

Suppose RSA was defined modulo a prime p instead of an RSA composite N . Show that in that case anyone can compute the private key (N, d) from the public key (N, e) by computing:

Your Answer	Score	Explanation
<input checked="" type="radio"/> $d \leftarrow e^{-1} \pmod{p-1}$	✓ 1.00	yes, that is correct.
<input type="radio"/> $d \leftarrow e^{-1} \pmod{p}$		
<input type="radio"/> $d \leftarrow e^2 \pmod{p}$		
<input type="radio"/> $d \leftarrow e^{-1} \pmod{p^2}$		
Total	1.00 / 1.00	