

CRACK A HACK

Road Maintenance

Course: ALGORITHMIC PROBLEM SOLVING

Course code: 17ECSE309

by:

Pooja S Galer

USN: 01FE15BCS130

1. Introduction

Byteland has N cities (numbered from 1 to N) and $N-1$ bidirectional roads. A *path* is comprised of 1 or more connected roads. It is guaranteed that there is a path from any city to any other city.

Steven is a road maintenance worker in Byteland. He is required to maintain *exactly* M paths on any given workday. He *cannot* work on the same road twice in one day (so no 2 paths can contain the same 2 roads). Steven can start his workday in any city and, once he has finished maintaining a path, teleport to his next starting city.

The problem is related to Depth First Search (DFS) for given M level from every node to $M-1$ nodes in all directions. Here, we travel in same direction until M levels are met, then the starting node changed.

2. Example




Figure 2.1: DFS Algorithm example

3. Algorithm

```
DFS(G)
1  for each vertex  $u \in G.V$ 
2       $u.color = \text{WHITE}$ 
3       $u.\pi = \text{NIL}$ 
4   $time = 0$ 
5  for each vertex  $u \in G.V$ 
6      if  $u.color == \text{WHITE}$ 
7          DFS-VISIT( $G, u$ )

DFS-VISIT( $G, u$ )
1   $time = time + 1$                 // white vertex  $u$  has just been discovered
2   $u.d = time$ 
3   $u.color = \text{GRAY}$ 
4  for each  $v \in G.Adj[u]$         // explore edge  $(u, v)$ 
5      if  $v.color == \text{WHITE}$ 
6           $v.\pi = u$ 
7          DFS-VISIT( $G, v$ )
8   $u.color = \text{BLACK}$             // blacken  $u$ ; it is finished
9   $time = time + 1$ 
10  $u.f = time$ 
```

Figure 3.1: DFS Algorithm Pseudocode

4. Code (in C)

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
typedef struct way{
    int x;
    int w;
    struct way *next;
} path;
#define MOD 1000000007
#define MAX 100000
int m;
int tp[MAX]={0};
long long dp[6][6][MAX]={0};
```

```

path *table[MAX]={0};
void dfs(int x){
int i,j,k,l;
long long t[6][6];
path *p;
tp[x]=1;
dp[0][0][x]=1;
for(p=table[x];p;p=p->next)
if(!tp[p->x]){
dfs(p->x);
memset(t,0,sizeof(t));
for(i=0;i<=m;i++)
for(j=0;j<=m+1;j++)
for(k=0;k<=i;k++)
for(l=0;l<=j;l++){
if(i+j<=m){
t[k][i+j]=(t[k][i+j]+dp[k][i][x]*dp[l][j][p->x])%MOD;
if(k)
t[k-1][i+j]=(t[k-1][i+j]+dp[k][i][x]*dp[l][j][p->x]%MOD*k)%MOD;
if(k+1<=i+j)
t[k+1][i+j]=(t[k+1][i+j]+dp[k][i][x]*dp[l][j][p->x]%MOD*l)%MOD;
}
if(i+j && k)
t[k-1][i+j-1]=(t[k-1][i+j-1]+dp[k][i][x]*dp[l][j][p->x]%MOD*k*l)%MOD;
if(i+j+1<=m)
t[k+1][i+j+1]=(t[k+1][i+j+1]+dp[k][i][x]*dp[l][j][p->x])%MOD;
}
for(i=0;i<=m;i++)
for(j=0;j<=m;j++)
dp[i][j][x]=t[i][j]%MOD;
}
return;
}

```

```

void addto(int x,int y,int w){
path *t=(struct way*)malloc(sizeof(path));
t->x=y;
t->w=w;
t->next=table[x];
table[x]=t;
return;
}

```

```

int main(){
int N,x,y,i;
long long order;
scanf("%d%d",&N,&m);
for(i=0;i<N-1;i++){
scanf("%d%d",&x,&y);
addto(x-1,y-1,1);
}
}

```

```

dfs(0);
for(i=ans=0;i<=m;i++)
    order=(order+dp[i][m][0])%MOD;
printf("%lld",order);
return 0;
}

```

5. Time Complexity

The time complexity of the above code is $O(|N-1|+|N|)$, Where 'N-1' is the number of edges(roads) and 'N' is the number of cities.

6. Applications

- Finding Connectivity in graphs.
- Topological ordering of jobs based on dependencies
- Planarity Testing

7. References

- 1) <https://www.geeksforgeeks.org/depth-first-search-or-dfs-for-a-graph/>
- 2) <https://www.programiz.com/dsa/graph-dfs>