Main	24952.54	24952.54 Comme			ercial		
North-South Road Name	Project No. Sheet No.	Project No. Sheet No. Intersection No. East-Wes		t Road Name See https://www.oregon.gov/odot/Engineering/Docum RoadwayEng/ADA ExhibitA.pdf for more corner s			
	Calibration Date	10/8/2024 (mm/dd/yy)				County corner numbering system	
PL	RAMP RUN 1	Pass	Fail	4		15	
Ramp Style The passing value for Gutter Flow Slope (GFS)	Running Slope 1	3.3 ≤ 2.0%	> 2.0% ■	Corner	_ ,	Corner Positions	
	Cross Slope 1	6.1 ≤ 2.0%	> 2.0%	Position	3	5 2A	
depends on the Intersection Control Type. At a	Detectable Warning	N Y	N 🔳		1		
Midblock (MB), GFS must be ≤ Slope of the Road, at Signalized or Uncontrolled (SU), GFS	Lip Height	0 ≤ 1/4" ■	> 1/4"		3A -	^	
must be ≤ 5.0%, and at Stop	Gutter Flow Slope	3 ≤*	>*		2	North	
or Yield (SY), GFS must be ≤ 2.0%.	Curb Running Slope(avg)	4.96 ≤ 8.3%	> 8.3%>			11	
^{f 1} If Back of Ramp Obstruction is Yes, turn space length Y must be minimum 5.0 ft.	Counter Slope (+/-)*2		> 5.0%	1	4	Ramp 1	
*2 Clear Space area is the width of Ramp Run 1 and extends 4.0 ft into the roadway.	Det. warning full width of ram	p N Y	N 🔳	Ramp Position		5	
	RAMP RUN 2 Pass Fail			PE Stamp (red			
	Running Slope 2	≤ 8.3%	> 8.3%			private developme	
See also <u>Standard Drawings</u> to assess provisions not shown: (inlets, alignment, etc.)	Length 2	7.25					
	Cross Slope 2	6.8 ≤ 2.0%	> 2.0%				
Counter slope Conter Now slope	RAMP RUN 3	RAMP RUN 3 Pass Fai]			
	Running Slope 3	9.9 ≤ 8.3%	> 8.3%				
	Length 3	7.25					
	Cross Slope 3	≤ 2.0%	> 2.0%				
	TURN SPACE	TURN SPACE Pass Fai					
	Width X	5.1 ≥ 4.0'	< 4.0'	No Td. All ramp features asphalt			
PARALLEL RAMP (PL)	Length Y	5.0 ≥ 4.0'*1 ■	< 4.0'*1				
PARALLEL RAMP (PL)	Back of Ramp Obstruction (Y/N)	Y ≥ 5.0'*1	< 5.0'*1				
Pedestrian Access Route (to measure Clear Width)	Slope X (Cross Slope 1)	6.1 ≤ 2.0%	> 2.0%				
Detectable Warning Surface	l		2 00/				

Cross Slope (2.0% max.)

Running Slope (8.3% max.) Counter Slope (5.0% max.)

Gutter Flow Slope (as directed)

Turning Space (X & Y) (2.0% max. / 4' x 4' min.)*
* If constrained at back of walk, min. Y length is 5'.

Slope Y (Running Slope 1)

MISCELLANEOUS

Clear Width (feet)

Horizontal Gaps

Intersection Control Type

3.3

5.0

SY

≤ 2.0%

≥ 4.0'

> 2.0%

< 4.0'

Pass

≤ 1/2" ■ > 1/2"

Slope of Rd. 2.1

Fail Inspector's Signature

Darrell Wyant

Print name clearly

Company/Agency

3J Consulting

Date (mm/dd/yy)

Certification No.

52638



ADA Curb Ramp Images

Attached photos must be in .pdf format in order to be placed





