

ADA Curb Ramp New Construction Inspection Form (Perpendicular)

Contract.							
Nw287	24952.54				Nw m	ays	
North-South Road Name	Project No. Shee	et No.	ntersection N	о.	East-W	est Ro	pad Name
	Calibration Date	3/20/2024	(mm/dd/	/yy)			k - ') ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
Ramp Style PR	RAMP RUN 1 Running Slope 1	\equiv	≤ 8.3%	Pass	>8.3%	Fail	Corner
The passing value for Gutter Flow Slope (GFS) depends on the Intersection Control Type. At a	Length 1	11.15	į				Positions Positions 2A
idblock (MB), GFS must be ≤ Slope of the Road, at	Cross Slope 1		≤ 2.0%		>2.0%		1
ignalized or Uncontrolled (SU), GFS must be ≤ .0%, and at Stop or Yield (SY), GFS must be ≤ 2.0%.	Detectable Warning (Y,N)		Y		N	Ш	3A North
If Back of Ramp Obstruction is Yes, turn space	Lip Height	\vdash	1/4"		>1/4"	Н	2
ength Y must be minimum 5.0 ft.	Gutter Flow Slope		≤ *		>*	Н	4 Ramp 1
Clear Space area is the width of Ramp Run 1 and xtends 4.0 ft into the roadway.	Curb Running Slope (avg) Counter Slope (+/-) *2	3.6	≤ 8.3% ≤ 5.0%		>8.3% > 5.0%		Ramp Position Positions
See also <u>Standard Drawings</u> to assess provisions not shown: (inlets, alignment, etc.)	Longest distance from corner to back of curb (see dwg on BT form)	2.1	< 5.0'		≥ 5.0'		PE Stamp (requi private develop
The state of the s	Detectable warning extends full width of ramp throat opening] Y		N		
/ * * * * / * / * * / * * / * * / * * / * * / * * / * / * / * * /	TURN SPACE LANDING	G NON	NE	Pass		Fail	
Counter slope Guiter Flow slope Counter slope	Width X	3.1	≥ 4.0'		< 4.0'		
	Length Y	5.8	≥ 4.0'*1		< 4.0'*1		Comments:
	Back of Ramp Obstruction (Y/N)		≥ 5.0'*1		< 5.0'*1		ICRR, DIFFERENTIAL SETTLEMEN RR1/TS Crack
PERPENDICULAR RAMP (PR)	Slope X		≤2.0%		>2.0%		
Pedestrian Access Route (to measure Clear Width)	Slope Y		≤2.0%		>2.0%		
Detectable Warning Surface	MISCELLANEOUS Traversa	 able		Pass		Fail	
← Cross Slope (2.0% max.) ← Running Slope (8.3% max.)	Flare Slope 1		≤ 10%	T USS	< 10%		Inspector's Signature Date (
Counter Slope (5.0% max.)	Flare Slope 2		≤ 10%		<10%	H	
Turning Space (X & Y) (2.0% max. / 4' x 4' min.)* * If constrained at back of walk, min. Y length is 5'.	Clear Width (feet)	3.1	≥ 4.0'		< 4.0'		Darrell Wyant 5263 Print name clearly Certific
Gutter Flow Slope (as directed)	Intersection Control Type		Slope of	Road	1.4		3J Consulting
							III OU COUSUIIIIO



ADA Curb Ramp Images

Attached photos must be in .pdf format in order to be placed





