Main	24952.54		Hillcrest			
North-South Road Name	Project No. Sheet No.	Intersection No.	East-West F	Road Name		egon.gov/odot/Engineering/Document
	Calibration Date	10/8/2024 (mm/dd/yy)				NDA_ExhibitA.pdf for more corner style on County corner numbering system.
PL	RAMP RUN 1	Pass	Fail	4		
*The passing value for Gutter Flow Slope (GFS) depends on the Intersection Control Type. At a	Running Slope 1	≤ 2.0%	2.0%	Corner		Corner Positions
	Cross Slope 1	6.6 ≤ 2.0%	2.0%	Position	3	Positions 2A
	Detectable Warning	Y Y	N		1	2
Aidblock (MB), GFS must be ≤ Slope of the	Lip Height	0 ≤ 1/4" ■ >	1/4"		1	<b>↑</b>
load, at Signalized or Uncontrolled (SU), GFS nust be ≤ 5.0%, and at Stop	' '	31/4 🖃 /			3A 2	North
or Yield (SY), GFS must be $\leq$ 2.0%.	Gutter Flow Slope		>*		1	2
<sup>1</sup> If Back of Ramp Obstruction is Yes, turn	Curb Running Slope(avg)	9.26 ≤ 8.3%   >	8.3%>		4	Ramp 1
space length Y must be minimum 5.0 ft.	Counter Slope (+/-)*2	12.2 ≤ 5.0%  >	5.0%	1	2	Positions
*2 Clear Space area is the width of Ramp Run 1 and extends 4.0 ft into the roadway.	Det. warning full width of ram	p Y Y	N	Ramp Position		5
	RAMP RUN 2	Pass	Fail			PE Stamp (required for
	Running Slope 2	≤ 8.3%	8.3%			private development)
See also <u>Standard Drawings</u> to assess provisions not shown: (inlets, alignment, etc.)	Length 2					
	Cross Slope 2	≤ 2.0%	2.0%			
Counter slope  Counter slope  Counter slope	RAMP RUN 3	Pass	Fail			
	Running Slope 3	9.4 ≤ 8.3%	> 8.3% ■			
	Length 3	7.25				
	Cross Slope 3	≤ 2.0%	> 2.0%			
	TURN SPACE	TURN SPACE Pass Fail		Comments:		
	Width X	4.8 ≥ 4.0'	< 4.0'	IITD gt2	2. R2 gravel p	parking lot.
PARALLEL RAMP (PL)	Length Y	6.15 ≥ 4.0'*1 <b>■</b> <	4.0'*1			
PARALLEL RAMP (PL)	Back of Ramp Obstruction (Y/N)	N ≥ 5.0'*1 <	5.0'*1			
Pedestrian Access Route (to measure Clear Width)	Slope X (Cross Slope 1)		≥ 2.0%			
Detectable Warning Surface			2.0%			
	Slope Y (Running Slope 1)	■ ■	> / U%	1		

Cross Slope (2.0% max.)

Running Slope (8.3% max.) Counter Slope (5.0% max.)

Gutter Flow Slope (as directed)

Turning Space (X & Y) (2.0% max. / 4' x 4' min.)\*
\* If constrained at back of walk, min. Y length is 5'.

Slope Y (Running Slope 1)

**MISCELLANEOUS** 

Clear Width (feet)

**Horizontal Gaps** 

Intersection Control Type

SY

Pass

≤ 1/2" ■ > 1/2"

Slope of Rd. 3.1

< 4.0'

≥ 4.0'

Date (mm/dd/yy)

Certification No.

52638

Fail Inspector's Signature

**Darrell Wyant** 

Print name clearly

Company/Agency

3J Consulting



## **ADA Curb Ramp Images**

Attached photos must be in .pdf format in order to be placed





