Main	24952.54		Wascoe			
North-South Road Name	Project No. Sheet No.	. Intersection No.	East-West	Road Name		egon.gov/odot/Engineering/Docur
	Calibration Date	10/8/2024 (mm/dd/yy)				DA_ExhibitA.pdf for more corner on County corner numbering systems.
PL	RAMP RUN 1	Pass	Fail	1		- 15
Ramp Style	Running Slope 1	≤ 2.0%	2.0%	Corner		Corner Positions
The passing value for Gutter Flow Slope (GFS)	Cross Slope 1	3.4 ≤ 2.0%	2.0%	Position	3   10	5 2A
epends on the Intersection Control Type. At a	Detectable Warning	Y Y	N		1	2
idblock (MB), GFS must be ≤ Slope of the		0 < 1/4"  >	4 /411		1	^
oad, at Signalized or Uncontrolled (SU), GFS	Lip Height	0 ≤ 1/4" ■ >	1/4"		( 3A )	North
nust be ≤ 5.0%, and at Stop r Yield (SY), GFS must be ≤ 2.0%.	Gutter Flow Slope	1.2 ≤ *	> *		2	2
	Curb Running Slope(avg)	1.22 ≤ 8.3% ■ >	8.3%>			(1)
<sup>1</sup> If Back of Ramp Obstruction is Yes, turn pace length Y must be minimum 5.0 ft.	Counter Slope (+/-)*2	8.2 ≤ 5.0%  >	5.0%	2	4	Ramp 1
* <sup>2</sup> Clear Space area is the width of Ramp Run 1 and extends 4.0 ft into the roadway.	Det. warning full width of ram	p Y Y	N	Ramp Position		5
	RAMP RUN 2 Pass Fail		TOSICION		PE Stamp (required	
	Running Slope 2	8.5 ≤ 8.3%	8.3%			private developme
See also <u>Standard Drawings</u> to assess provisions not shown: (inlets, alignment, etc.)	Length 2	7.65				
	Cross Slope 2	≤ 2.0% ■ >	2.0%			
Counter slope  Run 3  Run 2  Gutter Flow slope	RAMP RUN 3	Pass	Fail	1		
	Running Slope 3	≤ 8.3%	> 8.3%			
	Length 3					
	Cross Slope 3	≤ 2.0%	> 2.0%			
	TURN SPACE	TURN SPACE Pass Fail		Comments:		
	Width X	5.0 ≥ 4.0'	< 4.0'	Rr3 gravel. No end of walk barricade IITD gt2. Crack in rr2. No end		
PARALLEL RAMP (PL)	Length Y	6.25 ≥ 4.0'*1 ■ <	4.0'*1	giz	CIACK III IIZ	L. INO GIIU
PARALLEL RAMP (PL)	Back of Ramp Obstruction (Y/N)	N ≥ 5.0'*1 <	< 5.0'*1			
Pedestrian Access Route (to measure Clear Width)	Slope X (Cross Slope 1)	3.4 ≤ 2.0%	> 2.0% ■			
Detectable Warning Surface			2 22/			

Cross Slope (2.0% max.)

Running Slope (8.3% max.) Counter Slope (5.0% max.)

Gutter Flow Slope (as directed)

Turning Space (X & Y) (2.0% max. / 4' x 4' min.)\*
\* If constrained at back of walk, min. Y length is 5'.

Slope Y (Running Slope 1)

**MISCELLANEOUS** 

Clear Width (feet)

**Horizontal Gaps** 

Intersection Control Type

≤ 2.0%

≥ 4.0'

Slope of Rd.

> 2.0%

< 4.0'

Pass

≤ 1/2" ■ > 1/2"

Fail Inspector's Signature

Darrell Wyant

Print name clearly

Company/Agency

3J Consulting

Date (mm/dd/yy)

Certification No.

52638.0



## **ADA Curb Ramp Images**

Attached photos must be in .pdf format in order to be placed





