

ADA Curb Ramp New Construction Inspection Form (Blended Transition)

NV	W MAIN ST	24953	N	IW NORTH AVE		
No	rth-South Road Name	Project No. Sheet No. Calibration Date	. Intersection No. Ea 10/24/2024 (mm/dd/y	ast-West Road Name	_RoadwayEng/ADA_Exhi	/odot/Engineering/Documents bitA. for more corner styles. r corner numbering system.
depends Midblock Signalized 5.0%, and * ¹ Clear S extends 4	BT Ramp Style sing value for Gutter Flow Slope (GFS) on the Intersection Condition Type. At a (MB), GFS must be ≤ Slope of the Road, at d or Uncontrolled (SU), GFS must be ≤ d at Stop or Yield (SY), GFS must be ≤ 2.0%. Space area is the width of Ramp Run 1 and d.0 ft into the roadway. Indiana Drawings to assess provisions not shown: Inment, etc.) BLENDED TRANSITION (BT) Pedestrian access route (To measure clear width)	grade 5.0 ft f One o of the grade greate	Pass 0.9	>2.0% N	Comments:	PE Stamp (required for private development)
	Detectable warning surface	MISCELLANEOUS Traversab	ole Pa	ss Fail		
4=	Cross slope (2.0% finish grade max.)	Flare Slope 1	≤ 10%			
***	Running slope (<5.0% finish grade max.) (If running slope ≥5.0%, this is a curb ramp, not a blended transition.)	Flare Slope 2	≤ 10%	>10%	Inspector's Signature	Date (mm/dd/yy
4	Counter slope (5.0% finish grade max.)	Clear Width (feet)	≥ 4.0'	< 4.0'	Darrell Wyant	52638.0
-	Gutter flow slope (as required)	Horizontal Gaps	≤ 1/2" ■	>1/2"	Print name clearly	Certification No
-	Edge of Gutter Pan	Intersection Control Type	SY Slope o	of Road 1.0	3J Consulting Company/Agency	



ADA Curb Ramp Images

Blended Transitions are locations where the pedestrian walkway (which has one direction of travel) and the street crossing intersect at the same plane without the need of a ramp. If the Running Slope is 5.0% or more, the ramp is not a Blended Transition and should be inspected using a different inspection form.

Attached photos must be in .pdf format in order to be placed





