

ZED-F9K module




High precision dead reckoning with integrated IMU sensors

Reliable lane identification for ADAS applications up to 105 °C

- Fully integrated dead reckoning RTK solution up to 50 Hz with very low latency
- Multi-band operation for flexibility and security
- Multiple outputs to serve all possible architecture
- Dependable protection level output
- Advanced security by top-notch spoofing & jamming algorithms
- Native support of global PointPerfect augmentation



17.0 × 22.0 × 2.4 mm



Product description

The ZED-F9K-01A module features the u-blox F9 GNSS platform, which provides continuous decimeter-level positioning accuracy for the most challenging automotive use cases. It supports both L1/L2/E5B and L1/L5 bands for maximum flexibility, satellite availability, and security. The sophisticated built-in algorithms cleverly fuse the IMU data, GNSS measurements, wheel ticks, and vehicle dynamics model to identify driving lanes where GNSS alone would fail.

The module natively supports the u-blox PointPerfect GNSS augmentation service. It delivers multiple GNSS and IMU outputs in parallel to support all possible architectures, including a 50 Hz sensor-fused solution with very low latency. It also enables advanced real-time applications like augmented reality, while the optimized multi-band and multi-constellation capability maximizes the number of visible satellites even in urban conditions.

The device is a self-contained solution, which provides the best possible system performance to address issues such as latency constraints, RF front-end design issues, or RTK algorithm integration. This eliminates the technical risk and effort of selecting and integrating RF components and third-party libraries, like positioning engines, which helps customers optimize time to market. The u-blox approach also dramatically reduces supply chain complexity during production.

The u-blox position engine incorporates a dependable protection level output and advanced security features including anti-spoofing and anti-jamming. Operation up to 105 °C makes it possible to integrate the product anywhere in the car without design constraints.

u-blox manufacturing partners use ISO/TS 16949 certified sites and adhere to the latest standards in the automotive industry. Qualification tests are performed as stipulated in the AEC-Q104 standard: "Failure mechanism based stress test qualification for multichip modules (MCM) in automotive applications".

ZED-F9K

Grade	
Automotive	•
Professional	
Standard	
GNSS	
GPS / QZSS	•
GLONASS	•
Galileo	•
BeiDou	•
NavIC	•
Multi-band	•
Interfaces	
UART	2
USB	1
SPI	1
DDC (I2C compliant)	1
Features	
Programmable (Flash)	•
Additional SAW	•
RTC crystal	•
Oscillator	T
OSR correction support	•
PointPerfect support	•
Timepulse	1
Power supply	
2.7 V – 3.6 V	•

T = TCXO

ZED-F9K module



Features

Receiver type	184-channel u-blox F9 engine Option A: GPS L1/L2C, Galileo E1/E5b, GLONASS L1/L2, BeiDou B1/B2I, QZSS L1/L2C, SBAS L1 Option B: GPS L1/L5, Galileo E1/E5a, GLONASS L1, BeiDou B1/B2a, QZSS L1/L5, NavIC L5, SBAS L1	
Nav. update rate	up to 50 Hz	
Position accuracy	RTK	< 0.2 m + 1 ppm CEP
ADR position error	< 1% of distance travelled without GNSS	
Convergence time	RTK	< 10 s
Acquisition	Cold starts	24 s
	Aided starts	4 s
	Reacquisition	2 s
Sensitivity	Tracking & nav. ¹	-160 dBm
	Cold starts	-147 dBm
	Hot starts	-158 dBm
Built-in	TCXO, RTC, flash memory, 3D accelerometer, 3D gyroscope, diplexer, SAW filters	
Supported antennas	Active	

1 Limited by firmware for best DR performance

Software features

Anti-jamming	Advanced anti-jamming algorithms
Anti-spoofing	Advanced anti-spoofing algorithms Sensor based spoofing detection
Raw data	Code and Doppler measurements and IMU data
Protocols	NMEA, UBX binary, RTCM version 3.3

Interfaces

Serial interfaces	2 UART 1 USB 1 SPI (optional) 1 DDC
Digital I/O	Configurable timepulse
Timepulse	Configurable: 0.25 Hz to 10 MHz

Package

54-pin LGA (Land Grid Array) 17 x 22 x 2.4 mm
--

Environmental data, quality & reliability

Operating temp.	-40 °C to +105 °C
Storage temp.	-40 °C to +105 °C
RoHS compliant (lead-free, 2015/863/EU)	
Green (halogen-free)	
EU Radio Equipment Directive compliant 2014/53/EU	
Module qualification according to AEC-Q104	
Manufactured and fully tested in ISO/TS 16949 certified production sites	
Uses u-blox F9 chips qualified according to AEC-Q100	

Electrical data

Supply voltage	2.7 V to 3.6 V
Power consumption	85 mA @ 3.0 V (continuous)
Backup supply	1.65 V to 3.6 V

Compatible u-blox products and services

Products	NEO-D9S correction receiver
Location services	AssistNow A-GNSS service PointPerfect GNSS augmentation service

Support products

EVK-F9DR	Easy to use evaluation board with various communication interfaces for correction services
----------	--

Product variants

ZED-F9K-01A	u-blox F9 multi-band high precision dead reckoning, automotive grade. L1/L2/E5b or L1/L5 bands, up to 105 °C LAP 1.30 firmware
ZED-F9K-02A	u-blox F9 multi-band high precision dead reckoning, automotive grade. L1/L2/E5b or L1/L5 bands, up to 105 °C LAP 1.50 firmware

Further information

For contact information, see www.u-blox.com/contact-u-blox.
For more product details and ordering information, see the product data sheet.

Legal Notice:

u-blox or third parties may hold intellectual property rights in the products, names, logos and designs included in this document. Copying, reproduction, or modification of this document or any part thereof is only permitted with the express written permission of u-blox. Disclosure to third parties is permitted for clearly public documents only.
The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose, or content of this document. This document may be revised by u-blox at any time. For most recent documents and product statuses, please visit www.u-blox.com.