

ARLAS

The ARLAS API makes the ARLAS catalog available for exploration and browsing. The catalog contains collections of geo-referenced products. Every product has a geometry, a centroid, a timestamp and a set of fields specific to the collection.

URL Schema

The table below lists the URL endpoints and their optional "parts". A part is composed of optional parameters. The parameters are separated with the character &.

PATH Template	Description
<code>/arlas/_describe</code>	List the collections configured in ARLAS
<code>/arlas/{collection}/_describe?form</code>	Describe the structure and the content of the given collection
<code>/arlas/{collections}/_count?filter & form</code>	Count the number of products found in the collection(s), given the filters
<code>/arlas/{collections}/_search?filter & form & format & projection & size & sort</code>	Search and return the products found in the collection(s), given the filters
<code>/arlas/{collections}/_aggregate?aggregation & filter & form & format & size & sort</code>	Aggregate the products in the collection(s), given the filters and the aggregation parameters
<code>/arlas/{collections}/_suggest?filter & form & size & suggest</code>	Suggest the the n (n=size) most relevant terms given the filters

When multiple collections are permitted ({collections}), the comma is used for separating the collection names.

Examples

`https://api.gisaia.com/demo/arlas/_describe`

`https://api.gisaia.com/demo/arlas/city,state,country/_describe`

`https://api.gisaia.com/demo/arlas/city,state,country/_count?q=bord*&f=country:France&pretty=true&human=true`

`https://api.gisaia.com/demo/arlas/election/_search?f=country:France&after=1490613808&format=geojson&pretty=true&human=true&size=1000&include=id,name`

`https://api.gisaia.com/demo/arlas/election/_aggregate?f=country:France&after=1490613808&format=geojson&`

pretty=true&human=true&size=1000&include=id,name&agg=geohash&agg_interval=4

URL Parts

Part: aggregation

The [aggregation] url part allows the following parameters to be specified:

Parameter	Default value	Values	Description	Multiple
agg	None	datehistogram,geohash,histogram	Type of aggregation	false
agg_field	None	{field}	Aggregates on the {field}.	true
agg_interval	None	interval	Size of the intervals.	true
agg_format	None	Date format (https://www.elastic.co/guide/en/elasticsearch/reference/current/search-aggregations-bucket-daterange-aggregation.html#date-format-pattern) for key aggregation	Size of the intervals.	true

Each aggregation has its own type of interval. The table below lists the semantic of the interval.

Aggregation	Interval	Description
datehistogram	{size} (year,quarter,month,week,day,hour,minute,second) unit)	Size of a time interval with the given unit (no space between number and unit)
geohash	{length}	The geohash length: lower the length, greater is the surface of aggregation. See table below.
numeric	{size}	The interval size of the numeric aggregation

The table below shows the metric dimensions for cells covered by various string lengths of geohash. Cell dimensions vary with latitude and so the table is for the worst-case scenario at the equator.

GeoHash length **Area width x height**

1	5,009.4km x 4,992.6km
2	1,252.3km x 624.1km
3	156.5km x 156km
4	39.1km x 19.5km
5	4.9km x 4.9km
6	1.2km x 609.4m
7	152.9m x 152.4m
8	38.2m x 19m
9	4.8m x 4.8m
10	1.2m x 59.5cm
11	14.9cm x 14.9cm
12	3.7cm x 1.9cm

Example: agg=datehistogram&agg_field=date&agg_interval=10d&agg_format=yyyyMMdd

Part: filter

The filter url part allows the following parameters to be specified:

Parameter	Default value	Values	Description	Multiple
f	None	{fieldName} {operator} {value}	A triplet for filtering the result. Multiple filter can be provided. The order does not matter. A triplet is composed of a field name, a comparison operator and a value. The AND operator is applied between filters having different fieldNames. The OR operator is applied on filters having the same fieldName. If the fieldName starts with - then a must not filter is used	true
q	None	text	A full text search	false
before	None	timestamp	Any element having its point in time reference before the given timestamp	false
after	None	timestamp	Any element having its point in time reference after the given timestamp	false
pwithin	None	geometry	Any element having its centroid contained within the given geometry	false

gwithin	None	geometry	Any element having its geometry contained within the given geometry	false
gintersect	None	geometry	Any element having its geometry intersecting the given geometry (WKT)	false

Operator	Description	Value type
:	{fieldName} equals {value}	numeric or strings
:>=	{fieldName} is greater than or equal to {value}	numeric
:>	{fieldName} is greater than {value}	numeric
:<=	{fieldName} is less than or equal to {value}	numeric
:<	{fieldName} is less than {value}	numeric

Example: f=city:Toulouse&f=city:Bordeaux&after=1490613808&

Part: form

The form url part allows the following parameters to be specified:

Parameter	Default value	Values	Description	Multiple
pretty	false	true, false	Pretty print	false
human	false	true, false	Human readable print	false

Example: pretty=true&human=true

Part: format

The format url part allows the following parameters to be specified:

Parameter	Default value	Values	Description	Multiple
format	false	json, geojson	JSON or GeoJSON format	false

Example: format=geojson

Part: projection

The projection url part allows the following parameters to be specified:

Parameter	Default value	Values	Description	Multiple
include	*	{fieldNamePattern}	List the name patterns of the field to be included in the result. Seperate patterns with a comma.	true
exclude	*	{fieldNamePattern}	List the name patterns of the field to be excluded in the result. Seperate patterns with a comma.	true

Example: include=*&exclude=city,state

Part: suggest

The suggest url part allows the following parameters to be specified:

Parameter	Default value	Values	Description	Multiple
field	_all	{fieldName}	Name of the field to be used for retrieving the most relevant terms	false

Example: field=recommended

Part: size

The size url part allows the following parameters to be specified:

Parameter	Default value	Values	Description	Multiple
size	10	>0	The maximum number of entries or sub-entries to be returned.	true

Example: size=1000

Part: sort

The sort url part allows the following parameters to be specified:

Parameter	Default value	Values	Description	Multiple
sort	None	{fieldName}: Sort the result on a given field, ascending or descending. The parameter can be provided several times. (ASC,DESC)	The order matters. For aggregation, provide the agg keyword as the {fieldName}.	true

Example: sort=country:ASC&sort=city:ASC