

# Contents

1 Basic	1	7.24 Theorem	20
1.1 createFile	1	8 Stringology	21
1.2 run	1	8.1 Aho–Corasick AM [1f3003]	21
1.3 tem	1	8.2 Double String [1cdcb3b]	22
1.4 debug [ca7eb5]	1	8.3 Lyndon Factorization [822807]	22
1.5 run.bat	1	8.4 Manacher [ad2217]	22
1.6 random	2	8.5 SA–IS [72a941, a9701f]	22
1.7 Hash	2	8.6 Suffix Array [5455bf]	23
2 Misc	2	8.7 SuffixAutomaton [c59c1d]	23
2.1 FastIO	2	8.8 Z–value [a39b66]	23
2.2 stress.sh	2	1 Basic	
2.3 stress.bat	2	1.1 createFile	
2.4 Timer	2	// Linux	
2.5 MinPlusConvolution [a3e78d]	2	for i in {A..Z}; do cp tem.cpp \$i.cpp; done	
2.6 FractionSearch [be56a1]	3	// Windows	
2.7 Montgomery [525d1f]	3	'A'..'Z'   % { cp tem.cpp "\$_.cpp" }	
2.8 PyTrick	3	1.2 run	
3 Data Structure	3	g++ -std=c++20 -DPEPPA -Wall -Wextra -Wshadow -O2 -fsanitize=	
3.1 Fenwick Tree [6837cb]	3	address,undefined -g \$1.cpp -o \$1 && ./ \$1	
3.2 Li Chao [d18bf0]	3	1.3 tem	
3.3 PBDS [e96d11]	4	#include <bits/stdc++.h>	
3.4 ODT [0ed806]	4	#pragma GCC optimize("Ofast,unroll-loops,no-stack-protector")	
3.5 Sparse Table [9db772]	4	#pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")	
3.6 Splay [650110]	5	using namespace std;	
3.7 Treap [b6b227]	5	using i64 = long long;	
4 Matching and Flow	5	#define int i64	
4.1 Dinic [f4f3bb]	5	#define all(a) begin(a), end(a)	
4.2 General Matching [c4df3f]	6	#define rep(a, b, c) for (int a = b; a < c; a++)	
4.3 KM [8aa560]	6	void solve() {	
4.4 HopcroftKarp [a760ee]	6	//	
4.5 MCMF [ffa875]	6	}	
4.6 Model	7	int32_t main() {	
5 Geometry	7	std::ios::sync_with_stdio(false);	
5.1 Point [aa26d8]	7	std::cin.tie(nullptr);	
5.2 Line [45ec8b]	8	int t = 1;	
5.3 Circle [55cf19]	8	std::cin >> t;	
5.4 Point to Segment Distance [0c07fc]	8	while (t--) {	
5.5 Point In Polygon [ae764a]	8	solve();	
5.6 Intersection of Line [31415c]	8	}	
5.7 Intersection of Circles [3c00f3]	8	return 0;	
5.8 Intersection of Circle and Line [a53f3c]	8	}	
5.9 Area of Circle Polygon [6783c6]	8	1.4 debug [ca7eb5]	
5.10 Convex Hull [d56d39]	8	#ifdef PEPPA	
5.11 Convex Trick [92ac89]	8	template <typename R>	
5.12 Half Plane Intersection [b913b6]	9	concept I = ranges::range<R> && !std::same_as<ranges::	
5.13 Minimal Enclosing Circle [a05bc4]	9	range_value_t<R>, char>;	
5.14 Minkowski [e90206]	9	template <typename A, typename B>	
5.15 Point In Circumcircle [f499c7]	9	std::ostream& operator<<(std::ostream& o, const std::pair<A, B	
5.16 Tangent Lines of Circle from Point [bebedd]	9	>& p) {	
5.17 Tangent Lines of Circles [fd34e8]	9	return o << "(" << p.first << ", " << p.second << ");	
5.18 Triangle Center [085b8e]	10	}	
5.19 Union of Circles [f29049]	10	template <I T>	
6 Graph	10	std::ostream& operator<<(std::ostream& o, const T& v) {	
6.1 Block Cut Tree [c8aef1]	10	o << "{";	
6.2 Count Cycles [a0754a]	10	int f = 0;	
6.3 Dominator Tree [4b8835]	11	for (auto &i : v) o << (f++ ? " " : "") << i;	
6.4 Enumerate Planar Face [ac7b47]	11	return o << "}";	
6.5 Manhattan MST [98280c]	11	}	
6.6 Matroid Intersection [c3d412]	12	void debug__(int c, auto&&... a) {	
6.7 Maximum Clique [3ca044]	12	std::cerr << "\e[1;" << c << "m";	
6.8 Tree Hash [af0b82]	12	(..., (std::cerr << a << " "));	
6.9 Two–SAT [80853f]	12	std::cerr << "\e[0m" << std::endl;	
6.10 Virtual Tree [83c4da]	13	}	
6.11 Functional Graph [a9b3cd]	13	#define debug_(c, x...) debug__(c, __LINE__, "[" + std::string	
7 Math	14	(#x) + "]", x)	
7.1 Combinatoric	14	#define debug(x...) debug_(93, x)	
7.2 Discrete Log [442909]	14	#else	
7.3 Div Floor Ceil	14	#define debug(x...) void(0)	
7.4 exCRT [fccd2c]	14	#endif	
7.5 Factorization [cd95b9]	14	1.5 run.bat	
7.6 Floor Sum [92460c]	15	@echo off	
7.7 FWT [a0135a]	15	g++ -std=c++23 -DPEPPA -Wall -Wextra -Wshadow -O2 %1.cpp -o %1.	
7.8 Gauss Elimination [e45cbd]	15	exe	
7.9 Lagrange Interpolation [b70847]	15	if "%2" == "" ("%1.exe") else ("%1.exe" < "%2")	
7.10 Linear Sieve [e7d01a]	15		
7.11 Lucas [5facf0]	16		
7.12 Mod Int [5a3b5b]	16		
7.13 Primitive Root [bebd30]	16		
7.14 Simplex [2e718d]	16		
7.15 Sqrt Mod [4e4b23]	17		
7.16 LinearSolve [1c7d11]	17		
7.17 PiCount [b9ce98]	17		
7.18 Triangular	17		
7.19 ModMin [79217f]	18		
7.20 FFT [474566]	18		
7.21 NTT [ff4101]	18		
7.22 NTT prime	18		
7.23 Polynomial	18		

## 1.6 random

```
std::mt19937_64 rng(std::chrono::steady_clock::now().
    time_since_epoch().count());
inline i64 rand(i64 l, i64 r) { return std::
    uniform_int_distribution<i64>(l, r)(rng); }
```

## 1.7 Hash

```
def get_hash(path):
    from subprocess import run, PIPE
    from hashlib import md5

    p = run(
        ["cpp", "-dD", "-P", "-fpreprocessed", path],
        stdout = PIPE,
        stderr = PIPE,
        text = True
    )

    if p.returncode != 0:
        raise RuntimeError(p.stderr)

    s = ''.join(p.stdout.split())
    return md5(s.encode()).hexdigest()[:6]

print(get_hash("file.cpp"))
```

# 2 Misc

## 2.1 FastIO

```
#include <unistd.h>
int OP;
char OB[65536];
inline char RC() {
    static char buf[65536], *p = buf, *q = buf;
    return p == q && (q = (p = buf) + read(0, buf, 65536)) == buf
        ? -1 : *p++;
}
inline int R() {
    static char c;
    while ((c = RC()) < '0');
    int a = c ^ '0';
    while ((c = RC()) >= '0') a *= 10, a += c ^ '0';
    return a;
}
inline void W(int n) {
    static char buf[12], p;
    if (n == 0) OB[OP++] = '0';
    p = 0;
    while (n) buf[p++] = '0' + (n % 10), n /= 10;
    for (--p; p >= 0; --p) OB[OP++] = buf[p];
    if (OP > 65520) write(1, OB, OP), OP = 0;
}
// {b95f3b}

// another FastIO
char buf[1 << 21], *p1 = buf, *p2 = buf;
inline char getc() {
    return p1 == p2 && (p2 = (p1 = buf) + fread(buf, 1, 1 << 21,
        stdin), p1 == p2) ? 0 : *p1++;
}
template<typename T> void Cin(T &a) {
    T res = 0; int f = 1;
    char c = getc();
    for (; c < '0' || c > '9'; c = getc()) {
        if (c == '-') f = -1;
    }
    for (; c >= '0' && c <= '9'; c = getc()) {
        res = res * 10 + c - '0';
    }
    a = f * res;
}
template<typename T, typename... Args> void Cin(T &a, Args &...
    args) {
    Cin(a), Cin(args...);
}
template<typename T> void Cout(T x) { // there's no '\n' in
    output
    if (x < 0) putchar('-'), x = -x;
    if (x > 9) Cout(x / 10);
    putchar(x % 10 + '0');
}
// {795778}
```

## 2.2 stress.sh

```
#!/usr/bin/env bash
g++ $1.cpp -o $1
g++ $2.cpp -o $2
g++ $3.cpp -o $3
for i in {1..100} ; do
    ./$3 > input.txt
    # st=$(date +%s%N)
    ./$1 < input.txt > output1.txt
    # echo "$((((date +%s%N) - $st)/1000000))ms"
    ./$2 < input.txt > output2.txt
    if cmp --silent -- "output1.txt" "output2.txt" ; then
        continue
    fi
    echo Input:
    cat input.txt
    echo Your Output:
    cat output1.txt
    echo Correct Output:
    cat output2.txt
    exit 1
done
echo OK!
./stress.sh main good gen
```

## 2.3 stress.bat

```
@echo off
setlocal EnableExtensions

g++ -std=c++20 -O3 "%1.cpp" -o "%1.exe"
g++ -std=c++20 -O3 "%2.cpp" -o "%2.exe"
g++ -std=c++20 -O3 "%3.cpp" -o "%3.exe"

for /l %i in (1,1,100) do (
    "%3.exe" > input.txt
    "%1.exe" < input.txt > output1.txt
    "%2.exe" < input.txt > output2.txt

    fc /b output1.txt output2.txt >nul
    if errorlevel 1 (
        echo Input:
        type input.txt
        echo Your Output:
        type output1.txt
        echo Correct Output:
        type output2.txt
        exit /b 1
    )
)

@REM ./stress main good gen
```

## 2.4 Timer

```
struct Timer {
    int t;
    bool enable = false;

    void start() {
        enable = true;
        t = std::clock();
    }
    int msec() {
        assert(enable);
        return (std::clock() - t) * 1000 / CLOCKS_PER_SEC;
    }
};
```

## 2.5 MinPlusConvolution [a3e78d]

```
// a is convex a[i+1]-a[i] <= a[i+2]-a[i+1]
vector<int> min_plus_convolution(vector<int> &a, vector<int> &b
    ) {
    int n = ssize(a), m = ssize(b);
    vector<int> c(n + m - 1, INF);
    auto dc = [&](auto Y, int l, int r, int jl, int jr) {
        if (l > r) return;
        int mid = (l + r) / 2, from = -1, &best = c[mid];
        for (int j = jl; j <= jr; ++j)
            if (int i = mid - j; i >= 0 && i < n)
                if (best > a[i] + b[j])
                    best = a[i] + b[j], from = j;
        Y(Y, l, mid - 1, jl, from), Y(Y, mid + 1, r, from, jr);
    };
    return dc(dc, 0, n - 1 + m - 1, 0, m - 1), c;
}
```

## 2.6 FractionSearch [be56a1]

```
// Binary search on Stern-Brocot Tree
// Parameters: n, pred
// n: Q_n is the set of all rational numbers whose denominator
// does not exceed n
// pred: pair<i64, i64> -> bool, pred({0, 1}) must be true
// Return value: {{a, b}, {x, y}}
// a/b is bigger value in Q_n that satisfy pred()
// x/y is smaller value in Q_n that not satisfy pred()
// Complexity: O(log^2 n)
using Pt = pair<i64, i64>;
Pt operator+(Pt a, Pt b) { return {a.ff + b.ff, a.ss + b.ss}; }
Pt operator*(i64 a, Pt b) { return {a * b.ff, a * b.ss}; }
pair<pair<i64, i64>, pair<i64, i64>> FractionSearch(i64 n,
    const auto &pred) {
    pair<i64, i64> low{0, 1}, hei{1, 0};
    while (low.ss + hei.ss <= n) {
        bool cur = pred(low + hei);
        auto &fr{cur ? low : hei}, &to{cur ? hei : low};
        u64 L = 1, R = 2;
        while ((fr + R * to).ss <= n and pred(fr + R * to) == cur)
            {
                L *= 2;
                R *= 2;
            }
        while (L + 1 < R) {
            u64 M = (L + R) / 2;
            ((fr + M * to).ss <= n and pred(fr + M * to) == cur ? L :
                R) = M;
        }
        fr = fr + L * to;
    }
    return {low, hei};
}
```

## 2.7 Montgomery [525d1f]

```
struct Montgomery {
    u32 mod, modr;
    Montgomery(u32 m) : mod(m), modr(1) {
        for (int i = 0; i < 5; ++i) modr *= 2 - mod * modr;
    }
    u32 reduce(u64 x) const {
        u32 q = u32(x) * modr;
        u32 m = (u64(q) * mod) >> 32;
        u32 v = (x >> 32) + mod - m;
        return (v >= mod ? v - mod : v);
    }
    u32 mul(u32 x, u32 y) const { return reduce(u64(x) * y); }
    u32 add(u32 x, u32 y) const { return (x + y >= mod ? x + y -
        mod : x + y); }
    u32 sub(u32 x, u32 y) const { return (x < y ? x + mod - y : x
        - y); }
    u32 transform(u32 x) const { return (u64(x) << 32) % mod; }
};
// int p;
// Montgomery space(p);
// u32 a[n][n], b[n][n], c[n][n]; // 裡面元素皆已 v =
// space.transform(v); 過
// for (int i = 0; i < n; ++i) {
//     for (int k = 0; k < n; ++k) {
//         for (int j = 0; j < n; ++j) {
//             c[i][j] = space.add(c[i][j], space.mul(a[i][k], b[k][j]
// ));
//         }
//     }
// }
// cout << space.reduce(c[0][0]) << "\n"; // 輸出 (a * b)
// [0][0] mod
```

## 2.8 PyTrick

```
import sys
input = sys.stdin.readline

from itertools import permutations
op = ['+', '-', '*', '']
a, b, c, d = input().split()
ans = set()
for (x, y, z, w) in permutations([a, b, c, d]):
    for op1 in op:
        for op2 in op:
            for op3 in op:
                val = eval(f"{x}{op1}{y}{op2}{z}{op3}{w}")
                if (op1 == '' and op2 == '' and op3 == '') or val < 0:
```

```
        continue
    ans.add(val)
print(len(ans))

map(int, input().split())
arr2d = [ [ list(map(int, input().split())) ] for i in range(N)
    ] # N*M

from decimal import *
from fractions import *
s = input()
n = int(input())
f = Fraction(s)
g = Fraction(s).limit_denominator(n)
h = f * 2 - g
if h.numerator <= n and h.denominator <= n and h < g:
    g = h
print(g.numerator, g.denominator)

from fractions import Fraction
x = Fraction(1, 2), y = Fraction(1)
print(x.as_integer_ratio()) # print 1/2
print(x.is_integer())
print(x.__round__())
print(float(x))

r = Fraction(input())
N = int(input())
r2 = r - 1 / Fraction(N) ** 2
ans = r.limit_denominator(N)
ans2 = r2.limit_denominator(N)
if ans2 < ans and 0 <= ans2 <= 1 and abs(ans - r) >= abs(ans2 -
    r):
    ans = ans2
print(ans.numerator, ans.denominator)
```

## 3 Data Structure

### 3.1 Fenwick Tree [6837cb]

```
template<class T>
struct Fenwick {
    int n;
    vector<T> a;
    Fenwick(int _n) : n(_n), a(_n) {}
    void add(int p, T x) {
        for (int i = p; i < n; i = i | (i + 1)) {
            a[i] = a[i] + x;
        }
    }
    T qry(int p) { // sum [0, p]
        T s{};
        for (int i = p; i >= 0; i = (i & (i + 1)) - 1) {
            s = s + a[i];
        }
        return s;
    }
    T qry(int l, int r) { // sum [l, r]
        return qry(r - 1) - qry(l - 1);
    }
};
pair<int, T> select(T k) { // [first position >= k, sum [0, p]
    )
    T s{};
    int p = 0;
    for (int i = 1 << __lg(n); i; i >= 1) {
        if (p + i <= n and s + a[p + i - 1] < k) {
            p += i;
            s = s + a[p - 1];
        }
    }
    return {p, s};
}
```

### 3.2 Li Chao [d18bf0]

```
struct Line {
    // y = ax + b
    i64 a{0}, b{-inf<i64>};
    i64 operator()(i64 x) {
        return a * x + b;
    }
};
// max LiChao
struct Seg {
    int l, r;
```

```

Seg *ls{}, *rs{};
Line f{};
Seg(int l, int r) : l(l), r(r) {}
void add(Line g) {
    int m = (l + r) / 2;
    if (g(m) > f(m)) {
        swap(g, f);
    }
    if (g.b == -inf<i64> or r - l == 1) {
        return;
    }
    if (g.a < f.a) {
        if (!ls) {
            ls = new Seg(l, m);
        }
        ls->add(g);
    } else {
        if (!rs) {
            rs = new Seg(m, r);
        }
        rs->add(g);
    }
}
i64 qry(i64 x) {
    if (f.b == -inf<i64>) {
        return -inf<i64>;
    }
    int m = (l + r) / 2;
    i64 y = f(x);
    if (x < m and ls) {
        chmax(y, ls->qry(x));
    } else if (x >= m and rs) {
        chmax(y, rs->qry(x));
    }
    return y;
}
};

```

### 3.3 PBDS [e96d11]

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
template<typename T> using RBT = tree<T, null_type, less<T>,
    rb_tree_tag, tree_order_statistics_node_update>;
/*
.find_by_order(k) 回傳第 k 小的值 (based-0)
.order_of_key(k) 回傳有多少元素比 k 小
*/
struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }

    size_t operator()(uint64_t x) const {
        static const uint64_t FIXED_RANDOM = chrono::steady_clock::
            now().time_since_epoch().count();
        return splitmix64(x + FIXED_RANDOM);
    }
};
// gp_hash_table<int, int, custom_hash> ss;

```

### 3.4 ODT [0ed806]

```

map<int, int> odt;
// initialize edges odt[1] and odt[n + 1]
auto split = [&](const int &x) -> void {
    const auto it = prev(odt.upper_bound(x));
    odt[x] = it->second;
};
auto merge = [&](const int &l, const int &r) -> void {
    auto itl = odt.lower_bound(l), itr = odt.lower_bound(r + 1);
    for (; itl != itr; itl = odt.erase(itl)) {
        // do something
    }
    // assign value to odt[l]
};

```

### 3.5 Sparse Table [9db772]

```

template<class T>
struct SparseTable{
    function<T(T, T)> F;

```

```

    vector<vector<T>> sp;
    SparseTable(vector<T> &a, const auto &f) {
        F = f;
        int n = a.size();
        sp.resize(n, vector<T>(__lg(n) + 1));
        for (int i = n - 1; i >= 0; i--) {
            sp[i][0] = a[i];
            for (int j = 1; i + (1 << j) <= n; j++) {
                sp[i][j] = F(sp[i][j - 1], sp[i + (1 << j - 1)][j - 1]);
            }
        }
    }
    T query(int l, int r) { // [l, r)
        int k = __lg(r - l);
        return F(sp[l][k], sp[r - (1 << k)][k]);
    }
};

```

### 3.6 Splay [650110]

```

struct Node {
    Node *ch[2]{}; *p{};
    Info info{}; sum{};
    Tag tag{};
    int size{};
    bool rev{};
} pool[1E5 + 10], *top = pool;
Node *newNode(Info a) {
    Node *t = top++;
    t->info = t->sum = a;
    t->size = 1;
    return t;
}
int size(const Node *x) { return x ? x->size : 0; }
Info get(const Node *x) { return x ? x->sum : Info{}; }
int dir(const Node *x) { return x->p->ch[1] == x; }
bool nroot(const Node *x) { return x->p and x->p->ch[dir(x)] == x; }
void reverse(Node *x) { if (x) x->rev = !x->rev; }
void update(Node *x, const Tag &f) {
    if (!x) return;
    f(x->tag);
    f(x->info);
    f(x->sum);
}
void push(Node *x) {
    if (x->rev) {
        swap(x->ch[0], x->ch[1]);
        reverse(x->ch[0]);
        reverse(x->ch[1]);
        x->rev = false;
    }
    update(x->ch[0], x->tag);
    update(x->ch[1], x->tag);
    x->tag = Tag{};
}
void pull(Node *x) {
    x->size = size(x->ch[0]) + 1 + size(x->ch[1]);
    x->sum = get(x->ch[0]) + x->info + get(x->ch[1]);
}
void rotate(Node *x) {
    Node *y = x->p, *z = y->p;
    push(y);
    int d = dir(x);
    push(x);
    Node *w = x->ch[d ^ 1];
    if (nroot(y)) {
        z->ch[dir(y)] = x;
    }
    if (w) {
        w->p = y;
    }
    (x->ch[d ^ 1] = y->ch[d] = w;
    (y->p = x->p = z;
    pull(y);
    pull(x);
}
void splay(Node *x) {
    while (nroot(x)) {
        Node *y = x->p;
        if (nroot(y)) {
            rotate(dir(x) == dir(y) ? y : x);
        }
    }
}

```

```

    rotate(x);
}
}
Node *nth(Node *x, int k) {
    assert(size(x) > k);
    while (true) {
        push(x);
        int left = size(x->ch[0]);
        if (left > k) {
            x = x->ch[0];
        } else if (left < k) {
            k -= left + 1;
            x = x->ch[1];
        } else {
            break;
        }
    }
    splay(x);
    return x;
}
Node *split(Node *x) {
    assert(x);
    push(x);
    Node *l = x->ch[0];
    if (!l) l->p = x->ch[0] = nullptr;
    pull(x);
    return l;
}
Node *join(Node *x, Node *y) {
    if (!x || !y) return x ? x : y;
    y = nth(y, 0);
    push(y);
    y->ch[0] = x;
    if (x) x->p = y;
    pull(y);
    return y;
}
Node *find_first(Node *x, auto &pred) {
    Info pre{};
    while (true) {
        push(x);
        if (pred(pre + get(x->ch[0]))) {
            x = x->ch[0];
        } else if (pred(pre + get(x->ch[0]) + x->info) || !x->ch[1]) {
            break;
        } else {
            pre = pre + get(x->ch[0]) + x->info;
            x = x->ch[1];
        }
    }
    splay(x);
    return x;
}
}

```

### 3.7 Treap [b6b227]

```

struct Treap {
    Treap *l, *r;
    int key, size;
    Treap(int k) : l(nullptr), r(nullptr), key(k), size(1) {}
    void pull();
    void push() {}
};
inline int SZ(Treap *p) {
    return p == nullptr ? 0 : p->size;
}
void Treap::pull() {
    size = 1 + SZ(l) + SZ(r);
    // fa = nullptr
}
Treap *merge(Treap *a, Treap *b) {
    if (!a || !b) return a ? a : b;
    if (rand() % (SZ(a) + SZ(b)) < SZ(a)) {
        return a->push(), a->r = merge(a->r, b), a->pull(), a;
    }
    return b->push(), b->l = merge(a, b->l), b->pull(), b;
} // [98da40]
// <= k, > k
void split(Treap *p, Treap *a, Treap *b, int k) { // by key
    if (!p) return a = b = nullptr, void();
    p->push();
    if (p->key <= k) {
        a = p, split(p->r, a->r, b, k), a->pull();
    } else {

```

```

        b = p, split(p->l, a, b->l, k), b->pull();
    }
} // [6bb6f4]
// k, n - k
void split2(Treap *p, Treap *a, Treap *b, int k) { // by size
    if (!p) return a = b = nullptr, void();
    p->push();
    if (SZ(p->l) + 1 <= k) {
        a = p, split2(p->r, a->r, b, k - SZ(p->l) - 1);
    } else {
        b = p, split2(p->l, a, b->l, k);
    }
    p->pull();
} // [758990]
void insert(Treap *p, int k) {
    Treap *l, *r;
    p->push(), split(p, l, r, k);
    p = merge(merge(l, new Treap(k)), r);
    p->pull();
}
bool erase(Treap *p, int k) {
    if (!p) return false;
    if (p->key == k) {
        Treap *t = p;
        p->push(), p = merge(p->l, p->r);
        delete t;
        return true;
    }
    Treap *t = k < p->key ? p->l : p->r;
    return erase(t, k) ? p->pull(), true : false;
} // [300206]
int Rank(Treap *p, int k) { // # of key < k
    if (!p) return 0;
    if (p->key < k) return SZ(p->l) + 1 + Rank(p->r, k);
    return Rank(p->l, k);
}
Treap *kth(Treap *p, int k) { // 1-base
    if (k <= SZ(p->l)) return kth(p->l, k);
    if (k == SZ(p->l) + 1) return p;
    return kth(p->r, k - SZ(p->l) - 1);
} // [d1db1c]
// pref: kth(Rank(x)), succ: kth(Rank(x)+1)
tuple<Treap*, Treap*, Treap*> interval(Treap *o, int l, int r)
    { // 1-based
    Treap *a, *b, *c; // b: [l, r]
    split2(o, a, b, l - 1), split2(b, b, c, r - l + 1);
    return make_tuple(a, b, c);
} // {f2fff2}
// need record fa
int get_pos(Treap *p) {
    if (!p) return 0;
    int sz = SZ(p->l) + 1;
    while (p->fa) {
        if (p->fa->r == p) {
            sz += SZ(p->fa->l) + 1;
        }
        p = p->fa;
    }
    return sz;
} // {db3d15}

```

## 4 Matching and Flow

### 4.1 Dinic [f4f3bb]

```

template <typename T>
struct Dinic {
    const T INF = numeric_limits<T>::max() / 2;
    struct edge {
        int v, r; T rc;
    };
    vector<vector<edge>> adj;
    vector<T> dis, it;
    Dinic(int n) : adj(n), dis(n), it(n) {}
    void add_edge(int u, int v, T c) {
        adj[u].push_back({v, adj[v].size(), c});
        adj[v].push_back({u, adj[u].size() - 1, 0});
    }
    bool bfs(int s, int t) {
        fill(all(dis), INF);
        queue<int> q;
        q.push(s);
        dis[s] = 0;
        while (!q.empty()) {

```

```

    int u = q.front();
    q.pop();
    for (const auto& [v, r, rc] : adj[u]) {
        if (dis[v] < INF || rc == 0) continue;
        dis[v] = dis[u] + 1;
        q.push(v);
    }
}
return dis[t] < INF;
}

T dfs(int u, int t, T cap) {
    if (u == t || cap == 0) return cap;
    for (int &i = it[u]; i < (int)adj[u].size(); ++i) {
        auto &[v, r, rc] = adj[u][i];
        if (dis[v] != dis[u] + 1) continue;
        T tmp = dfs(v, t, min(cap, rc));
        if (tmp > 0) {
            rc -= tmp;
            adj[v][r].rc += tmp;
            return tmp;
        }
    }
    return 0;
}

T flow(int s, int t) {
    T ans = 0, tmp;
    while (bfs(s, t)) {
        fill(all(it), 0);
        while ((tmp = dfs(s, t, INF)) > 0) {
            ans += tmp;
        }
    }
    return ans;
}

bool inScut(int u) { return dis[u] < INF; }
};

```

## 4.2 General Matching [c4df3f]

```

struct GeneralMatching { // n <= 500
    const int BLOCK = 10;
    int n;
    vector<vector<int>> > g;
    vector<int> hit, mat;
    priority_queue<pair<int, int>, vector<pair<int, int>>,
        greater<pair<int, int>>> unmat;
    GeneralMatching(int _n) : n(_n), g(_n), mat(n, -1), hit(n) {}
    void add_edge(int a, int b) { // 0 <= a != b < n
        g[a].push_back(b);
        g[b].push_back(a);
    }
    int get_match() {
        for (int i = 0; i < n; i++) if (!g[i].empty()) {
            unmat.emplace(0, i);
        }
        // If WA, increase this
        // there are some cases that need >= 1.3*n^2 steps for BLOCK
        // =1
        // no idea what the actual bound needed here is.
        const int MAX_STEPS = 10 + 2 * n + n * n / BLOCK / 2;
        mt19937 rng(random_device{}());
        for (int i = 0; i < MAX_STEPS; ++i) {
            if (unmat.empty()) break;
            int u = unmat.top().second;
            unmat.pop();
            if (mat[u] != -1) continue;
            for (int j = 0; j < BLOCK; j++) {
                ++hit[u];
                auto &e = g[u];
                const int v = e[rng() % e.size()];
                mat[u] = v;
                swap(u, mat[v]);
                if (u == -1) break;
            }
            if (u != -1) {
                mat[u] = -1;
                unmat.emplace(hit[u] * 100ULL / (g[u].size() + 1), u);
            }
        }
        int siz = 0;
        for (auto e : mat) siz += (e != -1);
        return siz / 2;
    }
};

```

```

}
};

4.3 KM [8aa560]
template<class T>
T KM(const vector<vector<T>> &w) {
    const T INF = numeric_limits<T>::max() / 2;
    const int n = w.size();
    vector<T> lx(n), ly(n);
    vector<int> mx(n, -1), my(n, -1), pa(n);
    auto augment = [&](int y) {
        for (int x, z; y != -1; y = z) {
            x = pa[y];
            z = mx[x];
            my[y] = x;
            mx[x] = y;
        }
    };
    auto bfs = [&](int s) {
        vector<T> sy(n, INF);
        vector<bool> vx(n), vy(n);
        queue<int> q;
        q.push(s);
        while (true) {
            while (q.size()) {
                int x = q.front();
                q.pop();
                vx[x] = 1;
                for (int y = 0; y < n; y++) {
                    if (vy[y]) continue;
                    T d = lx[x] + ly[y] - w[x][y];
                    if (d == 0) {
                        pa[y] = x;
                        if (my[y] == -1) {
                            augment(y);
                            return;
                        }
                        vy[y] = 1;
                        q.push(my[y]);
                    } else if (chmin(sy[y], d)) {
                        pa[y] = x;
                    }
                }
            }
            T cut = INF;
            for (int y = 0; y < n; y++)
                if (!vy[y])
                    chmin(cut, sy[y]);
            for (int j = 0; j < n; j++) {
                if (vx[j]) lx[j] -= cut;
                if (vy[j]) ly[j] += cut;
                else sy[j] -= cut;
            }
            for (int y = 0; y < n; y++)
                if (!vy[y] and sy[y] == 0) {
                    if (my[y] == -1) {
                        augment(y);
                        return;
                    }
                    vy[y] = 1;
                    q.push(my[y]);
                }
        }
    };
    for (int x = 0; x < n; x++)
        lx[x] = ranges::max(w[x]);
    for (int x = 0; x < n; x++)
        bfs(x);
    T ans = 0;
    for (int x = 0; x < n; x++)
        ans += w[x][mx[x]];
    return ans;
}

```

## 4.4 HopcroftKarp [a760ee]

```

// Complexity: O(m sqrt(n))
// edge (u \in A) -> (v \in B) : G[u].push_back(v);
struct HK {
    const int n, m;
    vector<int> l, r, a, p;
    int ans;
    HK(int n, int m) : n(n), m(m), l(n, -1), r(m, -1), ans{} {}
    void work(const auto &G) {

```



```

for (bool match = true; match; ) {
    match = false;
    queue<int> q;
    a.assign(n, -1), p.assign(n, -1);
    for (int i = 0; i < n; i++)
        if (l[i] == -1) q.push(a[i] = p[i] = i);
    while (!q.empty()) {
        int z, x = q.front(); q.pop();
        if (l[a[x]] != -1) continue;
        for (int y : G[x]) {
            if (r[y] == -1) {
                for (z = y; z != -1; ) {
                    r[z] = x;
                    swap(l[x], z);
                    x = p[x];
                }
                match = true;
                ans++;
                break;
            } else if (p[r[y]] == -1) {
                q.push(z = r[y]);
                p[z] = x;
                a[z] = a[x];
            }
        }
    }
}
};

```

## 4.5 MCMF [ffa875]

```

template<class T>
struct MCMF {
    const T INF = numeric_limits<T>::max() / 2;
    struct edge { int v, r; T f, w; };
    vector<vector<edge>> adj;
    const int n;
    MCMF(int n) : n(n), adj(n) {}
    void addEdge(int u, int v, T f, T c) {
        adj[u].push_back({v, ssize(adj[v]), f, c});
        adj[v].push_back({u, ssize(adj[u]) - 1, 0, -c});
    }
    vector<T> dis;
    vector<bool> vis;
    bool spfa(int s, int t) {
        queue<int> que;
        dis.assign(n, INF);
        vis.assign(n, false);
        que.push(s);
        vis[s] = 1;
        dis[s] = 0;
        while (!que.empty()) {
            int u = que.front(); que.pop();
            vis[u] = 0;
            for (auto [v, _, f, w] : adj[u])
                if (f && chmin(dis[v], dis[u] + w))
                    if (!vis[v]) {
                        que.push(v);
                        vis[v] = 1;
                    }
            }
        }
        return dis[t] != INF;
    }
    T dfs(int u, T in, int t) {
        if (u == t) return in;
        vis[u] = 1;
        T out = 0;
        for (auto [v, rev, f, w] : adj[u])
            if (f && !vis[v] && dis[v] == dis[u] + w) {
                T x = dfs(v, min(in, f), t);
                in -= x;
                out += x;
                f -= x;
                adj[v][rev].f += x;
                if (!in) break;
            }
        if (in) dis[u] = INF;
        vis[u] = 0;
        return out;
    }
    pair<T, T> flow(int s, int t) { // {flow, cost}
        T a = 0, b = 0;
        while (spfa(s, t)) {
            T x = dfs(s, INF, t);

```

```

        a += x;
        b += x * dis[t];
    }
    return {a, b};
}
};

```

## 4.6 Model

- Maximum/Minimum flow with lower bound / Circulation problem
  - Construct super source  $S$  and sink  $T$ .
  - For each edge  $(x, y, l, u)$ , connect  $x \rightarrow y$  with capacity  $u - l$ .
  - For each vertex  $v$ , denote by  $in(v)$  the difference between the sum of incoming lower bounds and the sum of outgoing lower bounds.
  - If  $in(v) > 0$ , connect  $S \rightarrow v$  with capacity  $in(v)$ , otherwise, connect  $v \rightarrow T$  with capacity  $-in(v)$ .
    - To maximize, connect  $t \rightarrow s$  with capacity  $\infty$  (skip this in circulation problem), and let  $f$  be the maximum flow from  $S$  to  $T$ . If  $f \neq \sum_{v \in V, in(v) > 0} in(v)$ , there's no solution. Otherwise, the maximum flow from  $s$  to  $t$  is the answer.
    - To minimize, let  $f$  be the maximum flow from  $S$  to  $T$ . Connect  $t \rightarrow s$  with capacity  $\infty$  and let the flow from  $S$  to  $T$  be  $f'$ . If  $f + f' \neq \sum_{v \in V, in(v) > 0} in(v)$ , there's no solution. Otherwise,  $f'$  is the answer.
  - The solution of each edge  $e$  is  $l_e + f_e$ , where  $f_e$  corresponds to the flow of edge  $e$  on the graph.
- Construct minimum vertex cover from maximum matching  $M$  on bipartite graph  $(X, Y)$ 
  - Redirect every edge:  $y \rightarrow x$  if  $(x, y) \in M$ ,  $x \rightarrow y$  otherwise.
  - DFS from unmatched vertices in  $X$ .
  - $x \in X$  is chosen iff  $x$  is unvisited.
  - $y \in Y$  is chosen iff  $y$  is visited.
- Minimum cost cyclic flow
  - Construct super source  $S$  and sink  $T$
  - For each edge  $(x, y, c)$ , connect  $x \rightarrow y$  with  $(cost, cap) = (c, 1)$  if  $c > 0$ , otherwise connect  $y \rightarrow x$  with  $(cost, cap) = (-c, 1)$
  - For each edge with  $c < 0$ , sum these cost as  $K$ , then increase  $d(y)$  by 1, decrease  $d(x)$  by 1
  - For each vertex  $v$  with  $d(v) > 0$ , connect  $S \rightarrow v$  with  $(cost, cap) = (0, d(v))$
  - For each vertex  $v$  with  $d(v) < 0$ , connect  $v \rightarrow T$  with  $(cost, cap) = (0, -d(v))$
  - Flow from  $S$  to  $T$ , the answer is the cost of the flow  $C + K$
- Maximum density induced subgraph
  - Binary search on answer, suppose we're checking answer  $T$
  - Construct a max flow model, let  $K$  be the sum of all weights
  - Connect source  $s \rightarrow v$ ,  $v \in G$  with capacity  $K$
  - For each edge  $(u, v, w)$  in  $G$ , connect  $u \rightarrow v$  and  $v \rightarrow u$  with capacity  $w$
  - For  $v \in G$ , connect it with sink  $v \rightarrow t$  with capacity  $K + 2T - (\sum_{e \in E(v)} w(e)) - 2w(v)$
  - $T$  is a valid answer if the maximum flow  $f < K|V|$
- Minimum weight edge cover
  - Change the weight of each edge to  $\mu(u) + \mu(v) - w(u, v)$ , where  $\mu(v)$  is the cost of the cheapest edge incident to  $v$ .
  - Let the maximum weight matching of the graph be  $x$ , the answer will be  $\sum \mu(v) - x$ .

## 5 Geometry

### 5.1 Point [aa26d8]

```

using numbers::pi;
template<class T> inline constexpr T eps = numeric_limits<T>::
    epsilon() * 1E6;
using Real = long double;
struct Pt {
    Real x{}, y{};
    Pt operator+(Pt a) const { return {x + a.x, y + a.y}; }
    Pt operator-(Pt a) const { return {x - a.x, y - a.y}; }
    Pt operator*(Real k) const { return {x * k, y * k}; }
    Pt operator/(Real k) const { return {x / k, y / k}; }
    Real operator*(Pt a) const { return x * a.x + y * a.y; }
    Real operator^(Pt a) const { return x * a.y - y * a.x; }
    auto operator<=>(const Pt&) const = default;
    bool operator==(const Pt&) const = default;
};
int sgn(Real x) { return (x > -eps<Real>) - (x < eps<Real>); }
Real ori(Pt a, Pt b, Pt c) { return (b - a) ^ (c - a); }
bool argcmp(const Pt &a, const Pt &b) { // arg(a) < arg(b)
    int f = (Pt{a.y, -a.x} > Pt{b.y, -b.x}) ? 1 : -1;
    int g = (Pt{b.y, -b.x} > Pt{a.y, -a.x}) ? 1 : -1;
    return f == g ? (a ^ b) > 0 : f < g;
}
Pt rotate(Pt u) { return {-u.y, u.x}; }
Real abs2(Pt a) { return a * a; }
// floating point only

```

```
Pt rotate(Pt u, Real a) {
    Pt v{sinl(a), cosl(a)};
    return {u ^ v, u * v};
}
Real abs(Pt a) { return sqrtl(a * a); }
Real arg(Pt x) { return atan2l(x.y, x.x); }
Pt unit(Pt x) { return x / abs(x); }
```

## 5.2 Line [45ec8b]

```
struct Line {
    Pt a, b;
    Pt dir() const { return b - a; }
};
int PtSide(Pt p, Line l) {
    return sgn(ori(l.a, l.b, p)); // for int
    return sgn(ori(l.a, l.b, p) / abs(l.a - l.b));
}
bool PtOnSeg(Pt p, Line l) {
    return PtSide(p, l) == 0 and sgn((p - l.a) * (p - l.b)) <= 0;
}
Pt proj(Pt p, Line l) {
    Pt dir = unit(l.b - l.a);
    return l.a + dir * (dir * (p - l.a));
}
```

## 5.3 Circle [55cf19]

```
struct Cir {
    Pt o;
    double r;
    bool inside(Pt p) {
        return sgn(r - abs(p - o)) >= 0;
    }
};
bool disjunct(const Cir &a, const Cir &b) {
    return sgn(abs(a.o - b.o) - a.r - b.r) >= 0;
}
bool contain(const Cir &a, const Cir &b) {
    return sgn(a.r - b.r - abs(a.o - b.o)) >= 0;
}
```

## 5.4 Point to Segment Distance [0c07fc]

```
double PtSegDist(Pt p, Line l) {
    double ans = min(abs(p - l.a), abs(p - l.b));
    if (sgn(abs(l.a - l.b)) == 0) return ans;
    if (sgn((l.a - l.b) * (p - l.b)) < 0) return ans;
    if (sgn((l.b - l.a) * (p - l.a)) < 0) return ans;
    return min(ans, abs(ori(p, l.a, l.b)) / abs(l.a - l.b));
}
double SegDist(Line l, Line m) {
    return PtSegDist({0, 0}, {l.a - m.a, l.b - m.b});
}
```

## 5.5 Point In Polygon [ae764a]

```
int inPoly(Pt p, const vector<Pt> &P) {
    const int n = P.size();
    int cnt = 0;
    for (int i = 0; i < n; i++) {
        Pt a = P[i], b = P[(i + 1) % n];
        if (PtOnSeg(p, {a, b})) return 1; // on edge
        if ((sgn(a.y - p.y) == 1) ^ (sgn(b.y - p.y) == 1))
            cnt += sgn(ori(a, b, p));
    }
    return cnt == 0 ? 0 : 2; // out, in
}
```

## 5.6 Intersection of Line [31415c]

```
bool isInter(Line l, Line m) {
    if (PtOnSeg(m.a, l) or PtOnSeg(m.b, l) or
        PtOnSeg(l.a, m) or PtOnSeg(l.b, m))
        return true;
    return PtSide(m.a, l) * PtSide(m.b, l) < 0 and
        PtSide(l.a, m) * PtSide(l.b, m) < 0;
} // [19282c]
Pt LineInter(Line l, Line m) {
    double s = ori(m.a, m.b, l.a), t = ori(m.a, m.b, l.b);
    return (l.b * s - l.a * t) / (s - t);
} // [0f777a]
bool strictInter(Line l, Line m) {
    int la = PtSide(m.a, l);
    int lb = PtSide(m.b, l);
    int ma = PtSide(l.a, m);
    int mb = PtSide(l.b, m);
```

```
if (la == 0 and lb == 0) return false;
return la * lb < 0 and ma * mb < 0;
}
```

## 5.7 Intersection of Circles [3c00f3]

```
vector<Pt> CircleInter(Cir a, Cir b) {
    double d2 = abs2(a.o - b.o), d = sqrt(d2);
    if (d < max(a.r, b.r) - min(a.r, b.r) || d > a.r + b.r)
        return {};
    Pt u = (a.o + b.o) / 2 + (a.o - b.o) * ((b.r * b.r - a.r * a.r) / (2 * d2));
    double A = sqrt((a.r + b.r + d) * (a.r - b.r + d) * (a.r + b.r - d) * (-a.r + b.r + d));
    Pt v = rotate(b.o - a.o) * A / (2 * d2);
    if (sgn(v.x) == 0 and sgn(v.y) == 0) return {u};
    return {u - v, u + v}; // counter clockwise of a
}
```

## 5.8 Intersection of Circle and Line [a53f3c]

```
vector<Pt> CircleLineInter(Cir c, Line l) {
    Pt H = proj(c.o, l);
    Pt dir = unit(l.b - l.a);
    double h = abs(H - c.o);
    if (sgn(h - c.r) > 0) return {};
    double d = sqrt(max((double)0., c.r * c.r - h * h));
    if (sgn(d) == 0) return {H};
    return {H - dir * d, H + dir * d};
    // Counterclockwise
}
```

## 5.9 Area of Circle Polygon [6783c6]

```
double CirclePoly(Cir C, const vector<Pt> &P) {
    auto arg = [&](Pt p, Pt q) { return atan2(p ^ q, p * q); };
    double r2 = C.r * C.r / 2;
    auto tri = [&](Pt p, Pt q) {
        Pt d = q - p;
        auto a = (d * p) / abs2(d), b = (abs2(p) - C.r * C.r) / abs2(d);
        auto det = a * a - b;
        if (det <= 0) return arg(p, q) * r2;
        auto s = max(0., -a - sqrt(det)), t = min(1., -a + sqrt(det));
        if (t < 0 or 1 <= s) return arg(p, q) * r2;
        Pt u = p + d * s, v = p + d * t;
        return arg(p, u) * r2 + (u ^ v) / 2 + arg(v, q) * r2;
    };
    double sum = 0.0;
    for (int i = 0; i < P.size(); i++)
        sum += tri(P[i] - C.o, P[(i + 1) % P.size()] - C.o);
    return sum;
}
```

## 5.10 Convex Hull [d56d39]

```
vector<Pt> BuildHull(vector<Pt> pt) {
    sort(all(pt));
    pt.erase(unique(all(pt)), pt.end());
    if (pt.size() <= 2) return pt;
    vector<Pt> hull;
    int sz = 1;
    rep (t, 0, 2) {
        rep (i, t, ssize(pt)) {
            while (ssize(hull) > sz && ori(hull.end()[-2], pt[i], hull.back()) >= 0)
                hull.pop_back();
            hull.push_back(pt[i]);
        }
        sz = ssize(hull);
        reverse(all(pt));
    }
    hull.pop_back();
    return hull;
}
```

## 5.11 Convex Trick [92ac89]

```
struct Convex {
    int n;
    vector<Pt> A, V, L, U;
    Convex(const vector<Pt> &A) : A(A), n(A.size()) { // n >= 3
        auto it = max_element(all(A));
        L.assign(A.begin(), it + 1);
        U.assign(it, A.end()), U.push_back(A[0]);
        rep (i, 0, n) {
```



```

    V.push_back(A[(i + 1) % n] - A[i]);
}
}
int inside(Pt p, const vector<Pt> &h, auto f) {
    auto it = lower_bound(all(h), p, f);
    if (it == h.end()) return 0;
    if (it == h.begin()) return p == *it;
    return 1 - sgn(ori(*prev(it), p, *it));
}
// 0: out, 1: on, 2: in
int inside(Pt p) {
    return min(inside(p, L, less{}), inside(p, U, greater{}));
}
static bool cmp(Pt a, Pt b) { return sgn(a ^ b) > 0; }
// [d74fcb]
// A[i] is a far/closer tangent point
int tangent(Pt v, bool close = true) {
    assert(v != Pt{});
    auto l = V.begin(), r = V.end() - 1;
    if (v < Pt{}) l = r, r = V.end();
    if (close) return (lower_bound(l, r, v, cmp) - V.begin()) % n;
    return (upper_bound(l, r, v, cmp) - V.begin()) % n;
} // [6d8bda]
// closer tangent point
array<int, 2> tangent2(Pt p) {
    array<int, 2> t{-1, -1};
    if (inside(p) == 2) return t;
    if (auto it = lower_bound(all(L), p); it != L.end() and p == *it) {
        int s = it - L.begin();
        return {(s + 1) % n, (s - 1 + n) % n};
    }
    if (auto it = lower_bound(all(U), p, greater{}); it != U.end() and p == *it) {
        int s = it - U.begin();
        return {(s + 1) % n, (s - 1 + n) % n};
    }
    for (int i = 0; i != t[0]; i = tangent((A[t[0] = i] - p), 0));
    for (int i = 0; i != t[1]; i = tangent((p - A[t[1] = i]), 1));
    return t;
} // [583fa1]
int find(int l, int r, Line L) {
    if (r < l) r += n;
    int s = PtSide(A[l % n], L);
    return *ranges::partition_point(views::iota(l, r), [&](int m) {
        return PtSide(A[m % n], L) == s;
    }) - 1;
};
// Line A_x A_{x+1} intersect with L
vector<int> intersect(Line L) {
    int l = tangent(L.a - L.b, r = tangent(L.b - L.a);
    if (PtSide(A[l], L) * PtSide(A[r], L) >= 0) return {};
    return {find(l, r, L) % n, find(r, l, L) % n};
} // [6e9761]
};

```

## 5.12 Half Plane Intersection [b913b6]

```

bool cover(Line L, Line P, Line Q) {
    // for double, i128 => Real
    i128 u = (Q.a - P.a) ^ Q.dir();
    i128 v = P.dir() ^ Q.dir();
    i128 x = P.dir().x * u + (P.a - L.a).x * v;
    i128 y = P.dir().y * u + (P.a - L.a).y * v;
    return sgn(x * L.dir().y - y * L.dir().x) * sgn(v) >= 0;
}
vector<Line> HPI(vector<Line> P) {
    sort(all(P), [&](Line l, Line m) {
        if (argcmp(l.dir(), m.dir()) return true;
        if (argcmp(m.dir(), l.dir()) return false;
        return ori(m.a, m.b, l.a) > 0;
    });
    int n = P.size(), l = 0, r = -1;
    for (int i = 0; i < n; i++) {
        if (i and !argcmp(P[i - 1].dir(), P[i].dir())) continue;
        while (l < r and cover(P[i], P[r - 1], P[r])) r--;
        while (l < r and cover(P[i], P[l], P[l + 1])) l++;
        P[++r] = P[i];
    }
}

```

```

while (l < r and cover(P[l], P[r - 1], P[r])) r--;
while (l < r and cover(P[r], P[l], P[l + 1])) l++;
if (r - l <= 1 or !argcmp(P[l].dir(), P[r].dir()))
    return {}; // empty
if (cover(P[l + 1], P[l], P[r]))
    return {}; // infinity
return vector(P.begin() + l, P.begin() + r + 1);
}

```

## 5.13 Minimal Enclosing Circle [a05bc4]

```

Pt Center(Pt a, Pt b, Pt c) {
    Pt x = (a + b) / 2;
    Pt y = (b + c) / 2;
    return LineInter({x, x + rotate(b - a)}, {y, y + rotate(c - b)});
}
Cir MEC(vector<Pt> P) {
    mt19937 rng(time(0));
    shuffle(all(P), rng);
    Cir C{};
    for (int i = 0; i < P.size(); i++) {
        if (C.inside(P[i])) continue;
        C = {P[i], 0};
        for (int j = 0; j < i; j++) {
            if (C.inside(P[j])) continue;
            C = {(P[i] + P[j]) / 2, abs(P[i] - P[j]) / 2};
            for (int k = 0; k < j; k++) {
                if (C.inside(P[k])) continue;
                C.o = Center(P[i], P[j], P[k]);
                C.r = abs(C.o - P[i]);
            }
        }
    }
    return C;
}

```

## 5.14 Minkowski [e90206]

```

// P, Q, R(return) are counterclockwise order convex polygon
vector<Pt> Minkowski(vector<Pt> P, vector<Pt> Q) {
    assert(P.size() >= 2 && Q.size() >= 2);
    auto cmp = [&](Pt a, Pt b) {
        return Pt{a.y, a.x} < Pt{b.y, b.x};
    };
    auto reorder = [&](auto &R) {
        rotate(R.begin(), min_element(all(R), cmp), R.end());
        R.push_back(R[0]), R.push_back(R[1]);
    };
    const int n = P.size(), m = Q.size();
    reorder(P), reorder(Q);
    vector<Pt> R;
    for (int i = 0, j = 0, s; i < n || j < m; ) {
        R.push_back(P[i] + Q[j]);
        s = sgn((P[i + 1] - P[i]) ^ (Q[j + 1] - Q[j]));
        if (s >= 0) i++;
        if (s <= 0) j++;
    }
    return R; // May not be a strict convexhull
}

```

## 5.15 Point In Circumcircle [f499c7]

```

// p[0], p[1], p[2] should be counterclockwise order
int inCC(const array<Pt, 3> &p, Pt a) {
    i128 det = 0;
    for (int i = 0; i < 3; i++)
        det += i128(abs2(p[i]) - abs2(a)) * ori(a, p[(i + 1) % 3], p[(i + 2) % 3]);
    return (det > 0) - (det < 0); // in:1, on:0, out:-1
}

```

## 5.16 Tangent Lines of Circle from Point [bebedd]

```

vector<Line> CircleTangent(Cir c, Pt p) {
    vector<Line> z;
    double d = abs(p - c.o);
    if (sgn(d - c.r) == 0) {
        Pt i = rotate(p - c.o);
        z.push_back({p, p + i});
    } else if (d > c.r) {
        double o = acos(c.r / d);
        Pt i = unit(p - c.o);
        Pt j = rotate(i, o) * c.r;
    }
}

```

```

    Pt k = rotate(i, -o) * c.r;
    z.push_back({c.o + j, p});
    z.push_back({c.o + k, p});
}
return z;
}

```

## 5.17 Tangent Lines of Circles [fd34e8]

```

vector<Line> CircleTangent(Cir c1, Cir c2, int sign1) {
    // sign1 = 1 for outer tang, -1 for inter tang
    vector<Line> ret;
    double d_sq = abs2(c1.o - c2.o);
    if (sgn(d_sq) == 0) return ret;
    double d = sqrt(d_sq);
    Pt v = (c2.o - c1.o) / d;
    double c = (c1.r - sign1 * c2.r) / d;
    if (c * c > 1) return ret;
    double h = sqrt(max(0.0, 1.0 - c * c));
    for (int sign2 = 1; sign2 >= -1; sign2 -= 2) {
        Pt n = Pt(v.x * c - sign2 * h * v.y, v.y * c + sign2 * h *
            v.x);
        Pt p1 = c1.o + n * c1.r;
        Pt p2 = c2.o + n * (c2.r * sign1);
        if (sgn(p1.x - p2.x) == 0 && sgn(p1.y - p2.y) == 0)
            p2 = p1 + rotate(c2.o - c1.o);
        ret.push_back({p1, p2});
    }
    return ret;
}

```

## 5.18 Triangle Center [085b8e]

```

Pt TriangleCircumCenter(Pt a, Pt b, Pt c) {
    Pt res;
    double a1 = atan2(b.y - a.y, b.x - a.x) + pi / 2;
    double a2 = atan2(c.y - b.y, c.x - b.x) + pi / 2;
    double ax = (a.x + b.x) / 2;
    double ay = (a.y + b.y) / 2;
    double bx = (c.x + b.x) / 2;
    double by = (c.y + b.y) / 2;
    double r1 = (sin(a2) * (ax - bx) + cos(a2) * (by - ay)) / (sin
        (a1) * cos(a2) - sin(a2) * cos(a1));
    return Pt(ax + r1 * cos(a1), ay + r1 * sin(a1));
} // {a62645}
Pt TriangleMassCenter(Pt a, Pt b, Pt c) {
    return (a + b + c) / 3.0;
}
Pt TriangleOrthoCenter(Pt a, Pt b, Pt c) {
    return TriangleMassCenter(a, b, c) * 3.0 -
        TriangleCircumCenter(a, b, c) * 2.0;
} // [af83d3]
Pt TriangleInnerCenter(Pt a, Pt b, Pt c) {
    Pt res;
    double la = abs(b - c);
    double lb = abs(a - c);
    double lc = abs(a - b);
    res.x = (la * a.x + lb * b.x + lc * c.x) / (la + lb + lc);
    res.y = (la * a.y + lb * b.y + lc * c.y) / (la + lb + lc);
    return res;
} // {bea9ac}

```

## 5.19 Union of Circles [f29049]

```

// Area[i] : area covered by at least i circle
vector<double> CircleUnion(const vector<Cir> &C) {
    const int n = C.size();
    vector<double> Area(n + 1);
    auto check = [&](int i, int j) {
        if (!contain(C[i], C[j]))
            return false;
        return sgn(C[i].r - C[j].r) > 0 or (sgn(C[i].r - C[j].r) ==
            0 and i < j);
    };
    struct Teve {
        double ang; int add; Pt p;
        bool operator<(const Teve &b) { return ang < b.ang; }
    };
    auto ang = [&](Pt p) { return atan2(p.y, p.x); };
    for (int i = 0; i < n; i++) {
        int cov = 1;
        vector<Teve> event;
        for (int j = 0; j < n; j++) if (i != j) {
            if (check(j, i)) cov++;
            else if (!check(i, j) and !disjunct(C[i], C[j])) {
                auto I = CircleInter(C[i], C[j]);

```

```

                assert(I.size() == 2);
                double a1 = ang(I[0] - C[i].o), a2 = ang(I[1] - C[i].o)
                    ;
                event.push_back({a1, 1, I[0]});
                event.push_back({a2, -1, I[1]});
                if (a1 > a2) cov++;
            }
        }
        if (event.empty()) {
            Area[cov] += pi * C[i].r * C[i].r;
            continue;
        }
        sort(all(event));
        event.push_back(event[0]);
        for (int j = 0; j + 1 < event.size(); j++) {
            cov += event[j].add;
            Area[cov] += (event[j].p ^ event[j + 1].p) / 2.;
            double theta = event[j + 1].ang - event[j].ang;
            if (theta < 0) theta += 2 * pi;
            Area[cov] += (theta - sin(theta)) * C[i].r * C[i].r / 2.;
        }
    }
    return Area;
}

```

## 6 Graph

### 6.1 Block Cut Tree [c8aef1]

```

struct BlockCutTree {
    int n;
    vector<vector<int>> adj;
    BlockCutTree(int _n) : n(_n), adj(_n) {}
    void addEdge(int u, int v) {
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    pair<int, vector<pair<int, int>>> work() {
        vector<int> dfn(n, -1), low(n), stk;
        vector<pair<int, int>> edg;
        int cnt = 0, cur = 0;
        function<void(int)> dfs = [&](int x) {
            stk.push_back(x);
            dfn[x] = low[x] = cur++;
            for (auto y : adj[x]) {
                if (dfn[y] == -1) {
                    dfs(y);
                    low[x] = min(low[x], low[y]);
                    if (low[y] == dfn[x]) {
                        int v;
                        do {
                            v = stk.back();
                            stk.pop_back();
                            edg.emplace_back(n + cnt, v);
                        } while (v != y);
                        edg.emplace_back(x, n + cnt);
                        cnt++;
                    }
                } else {
                    low[x] = min(low[x], dfn[y]);
                }
            }
        };
        for (int i = 0; i < n; i++) {
            if (dfn[i] == -1) {
                stk.clear();
                dfs(i);
            }
        }
        return {cnt, edg};
    }
};

```

### 6.2 Count Cycles [a0754a]

```

// ord = sort by deg decreasing, rk[ord[i]] = i
// D: undirected to directed edge from rk small to rk big
vector<int> vis(n, 0);
int c3 = 0, c4 = 0;
for (int x : ord) { // c3
    for (int y : D[x]) vis[y] = 1;
    for (int y : D[x]) for (int z : D[y]) c3 += vis[z];
    for (int y : D[x]) vis[y] = 0;
}

```

```

for (int x : ord) { // c4
    for (int y : D[x]) for (int z : adj[y])
        if (rk[z] > rk[x]) c4 += vis[z]++;
    for (int y : D[x]) for (int z : adj[y])
        if (rk[z] > rk[x]) --vis[z];
}

```

### 6.3 Dominator Tree [4b8835]

```

vector<int> BuildDomTree(vector<vector<int>> adj, int rt) {
    int n = adj.size();

    // buckets: list of vertices y with sdom(y) = x
    vector<vector<int>> buckets(n), radj(n);

    // rev[dfn[x]] = x
    vector<int> dfn(n, -1), rev(n, -1), pa(n, -1);
    vector<int> sdom(n, -1), dom(n, -1);
    vector<int> fa(n, -1), val(n, -1);

    int stamp = 0;

    // re-number in DFS order
    auto dfs = [&](auto self, int u) -> void {
        rev[dfn[u] = stamp] = u;
        fa[stamp] = sdom[stamp] = val[stamp] = stamp;
        stamp++;
        for (int v : adj[u]) {
            if (dfn[v] == -1) {
                self(self, v);
                pa[dfn[v]] = dfn[u];
            }
            radj[dfn[v]].pb(dfn[u]);
        }
    };

    function<int(int, bool)> Eval = [&](int x, bool fir) {
        if (x == fa[x]) return fir ? x : -1;
        int p = Eval(fa[x], false);
        // x is one step away from the root
        if (p == -1) return x;
        if (sdom[val[x]] > sdom[val[fa[x]]]) val[x] = val[fa[x]];
        fa[x] = p;
        return fir ? val[x] : p;
    };

    auto Link = [&](int x, int y) -> void { fa[x] = y; };

    dfs(dfs, rt);

    // compute sdom in reversed DFS order
    for (int x = stamp - 1; x >= 0; --x) {
        for (int y : radj[x]) {
            // sdom[x] = min({y | (y, x) in E(G), y < x}, {sdom[z] |
            // (y, x) in E(G), z > x && z is y's ancestor})
            chmin(sdom[x], sdom[Eval(y, true)]);
        }
        if (x > 0) buckets[sdom[x]].pb(x);
        for (int u : buckets[x]) {
            int p = Eval(u, true);
            if (sdom[p] == x) dom[u] = x;
            else dom[u] = p;
        }
        if (x > 0) Link(x, pa[x]);
    }

    // idom[x] = -1 if x is unreachable from rt
    vector<int> idom(n, -1);
    idom[rt] = rt;
    rep(x, 1, stamp) {
        if (sdom[x] != dom[x]) dom[x] = dom[dom[x]];
    }
    rep(i, 1, stamp) idom[rev[i]] = rev[dom[i]];
    return idom;
}

```

### 6.4 Enumerate Planar Face [ac7b47]

```

// 0-based
struct PlanarGraph {
    int n, m, id;
    vector<Pt> v;
    vector<vector<pair<int, int>>> adj;
    vector<int> conv, nxt, vis;

    PlanarGraph(int n, int m, vector<Pt> _v) :
        n(n), m(m), id(0),

```

```

    v(_v), adj(n),
    conv(m << 1), nxt(m << 1), vis(m << 1) {}

```

```

void add_edge(int x, int y) {
    adj[x].push_back({y, id << 1});
    adj[y].push_back({x, id << 1 | 1});
    conv[id << 1] = x;
    conv[id << 1 | 1] = y;
    id++;
}

```

```

vector<int> enumerate_face() {
    for (int i = 0; i < n; i++) {
        sort(all(adj[i]), [&](const auto &a, const auto &b) {
            return argcmp((v[a.first] - v[i]), (v[b.first] - v[i]));
        });
        int sz = adj[i].size(), pre = sz - 1;
        for (int j = 0; j < sz; j++) {
            nxt[adj[i][pre].second] = adj[i][j].second ^ 1;
            pre = j;
        }
    }
}

```

```

vector<int> ret;
for (int i = 0; i < m * 2; i++) {
    if (!vis[i]) {
        int area = 0, now = i;
        vector<int> pt;
        while (!vis[now]) {
            vis[now] = true;
            pt.push_back(conv[now]);
            now = nxt[now];
        }
        pt.push_back(pt.front());
        for (int i = 0; i + 1 < ssize(pt); i++) {
            area -= (v[pt[i]] ^ v[pt[i + 1]]);
        }
        // pt = face boundary
        if (area > 0) {
            ret.push_back(area);
        } else {
            // pt is outer face
        }
    }
}
return ret;
}

```

### 6.5 Manhattan MST [98280c]

```

// {w, u, v}
vector<tuple<int, int, int>> ManhattanMST(vector<Pt> P) {
    vector<int> id(P.size());
    iota(all(id), 0);
    vector<tuple<int, int, int>> edg;
    for (int k = 0; k < 4; k++) {
        sort(all(id), [&](int i, int j) {
            return (P[i] - P[j]).ff < (P[j] - P[i]).ss;
        });
        map<int, int> sweep;
        for (int i : id) {
            auto it = sweep.lower_bound(-P[i].ss);
            while (it != sweep.end()) {
                int j = it->ss;
                Pt d = P[i] - P[j];
                if (d.ss > d.ff) {
                    break;
                }
                edg.emplace_back(d.ff + d.ss, i, j);
                it = sweep.erase(it);
            }
            sweep[-P[i].ss] = i;
        }
        for (Pt &p : P) {
            if (k % 2) {
                p.ff = -p.ff;
            } else {
                swap(p.ff, p.ss);
            }
        }
    }
    return edg;
}

```

## 6.6 Matroid Intersection [c3d412]

```

/*
M1 = xx matroid, M2 = xx matroid
y<-s if I+y satisfies M1
y->t if I+y satisfies M2
x<-y if I-x+y satisfies M2
x->y if I-x+y satisfies M1
交換點權：
-w[e] if e \in I
w[e] otherwise
*/
vector<int> I(, 0);
while (true) {
    vector<vector<int>> adj();
    int s = , t = s + 1;
    auto M1 = [&]() -> void { // xx matroid
        { // y<-s
        }
        { // x->y
        }
    };
    auto M2 = [&]() -> void { // xx matroid
        { // y->t
        }
        { // x<-y
        }
    };
    auto augment = [&]() -> bool { // 註解掉的是帶權版
        vector<int> vis( + 2, 0), dis( + 2, IINF), from( + 2, -1);
        queue<int> q;
        vis[s] = 1;
        dis[s] = 0;
        q.push(s);
        while (!q.empty()) {
            int u = q.front(); q.pop();
            // vis[u] = 0;
            for (int v : adj[u]) {
                int w = ; // no weight -> 1, v == t -> 0
                if (chmin(dis[v], dis[u] + w)) {
                    from[v] = u;
                    // if (!vis[v]) {
                    //     vis[v] = 1;
                    //     q.push(v);
                    // }
            }
        }
        if (from[t] == -1) return false;
        for (int cur = from[t]; cur = from[cur]) {
            if (cur == -1 || cur == s) break;
            I[cur] ^= 1;
        }
        return true;
    };
    M1(), M2();
    if (!augment()) break;
}

```

## 6.7 Maximum Clique [3ca044]

```

constexpr size_t kN = 150;
using bits = bitset<kN>;
struct MaxClique {
    bits G[kN], cs[kN];
    int ans, sol[kN], q, cur[kN], d[kN], n;
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n; ++i) G[i].reset();
    }
    void addEdge(int u, int v) {
        G[u][v] = G[v][u] = 1;
    }
    void preDfs(vector<int> &v, int i, bits mask) {
        if (i < 4) {
            for (int x : v) d[x] = (G[x] & mask).count();
            sort(all(v), [&](int x, int y) {
                return d[x] > d[y];
            });
        }
        vector<int> c(v.size());

```

```

cs[1].reset(), cs[2].reset();
int l = max(ans - q + 1, 1), r = 2, tp = 0, k;
for (int p : v) {
    for (k = 1;
        (cs[k] & G[p]).any(); ++k);
    if (k >= r) cs[++r].reset();
    cs[k][p] = 1;
    if (k < l) v[tp++] = p;
}
for (k = l; k < r; ++k)
    for (auto p = cs[k].Find_first(); p < kN; p = cs[k]._Find_next(p))
        v[tp] = p, c[tp] = k, ++tp;
dfs(v, c, i + 1, mask);
}
void dfs(vector<int> &v, vector<int> &c, int i, bits mask) {
    while (!v.empty()) {
        int p = v.back();
        v.pop_back();
        mask[p] = 0;
        if (q + c.back() <= ans) return;
        cur[q++] = p;
        vector<int> nr;
        for (int x : v)
            if (G[p][x]) nr.push_back(x);
        if (!nr.empty()) preDfs(nr, i, mask & G[p]);
        else if (q > ans) ans = q, copy_n(cur, q, sol);
        c.pop_back();
        --q;
    }
}
int solve() {
    vector<int> v(n);
    iota(all(v), 0);
    ans = q = 0;
    preDfs(v, 0, bits(string(n, '1')));
    return ans;
}
} cliq;

```

## 6.8 Tree Hash [af0b82]

```

u64 shift(u64 x) {
    x ^= mask;
    x ^= x << 7;
    x ^= x >> 21;
    x ^= x << 11;
    x ^= mask;
    return x;
}
void hash(int u, int pa) {
    hsh[u] = 1;
    for (int v : adj[u]) {
        if (v == pa) continue;
        hash(hash, v, u);
        hsh[u] += shift(hsh[v]);
    }
}

```

## 6.9 Two-SAT [80853f]

```

struct TwoSat {
    int n;
    vector<vector<int>> G;
    vector<bool> ans;
    vector<int> id, dfn, low, stk;
    TwoSat(int n) : n(n), G(2 * n) {}
    void addClause(int u, bool f, int v, bool g) { // (u = f) or (v = g)
        G[2 * u + !f].push_back(2 * v + g);
        G[2 * v + !g].push_back(2 * u + f);
    }
    void addImply(int u, bool f, int v, bool g) { // (u = f) -> (v = g)
        G[2 * u + f].push_back(2 * v + g);
        G[2 * v + !g].push_back(2 * u + !f);
    }
    int addVar() {
        G.emplace_back();
        G.emplace_back();
        return n++;
    }
    void addAtMostOne(const vector<pair<int, bool>> &li) {
        if (ssize(li) <= 1) return;
        int pu; bool pf; tie(pu, pf) = li[0];

```

```

for (int i = 2; i < ssize(li); i++) {
    const auto &[u, f] = li[i];
    int nxt = addVar();
    addClause(pu, !pf, u, !f);
    addClause(pu, !pf, nxt, true);
    addClause(u, !f, nxt, true);
    tie(pu, pf) = make_pair(nxt, true);
}
addClause(pu, !pf, li[1].first, !li[1].second);
} // {b42333}
int cur = 0, scc = 0;
void dfs(int u) {
    stk.push_back(u);
    dfn[u] = low[u] = cur++;
    for (int v : G[u]) {
        if (dfn[v] == -1) {
            dfs(v);
            chmin(low[u], low[v]);
        } else if (id[v] == -1) {
            chmin(low[u], dfn[v]);
        }
    }
    if (dfn[u] == low[u]) {
        int x;
        do {
            x = stk.back();
            stk.pop_back();
            id[x] = scc;
        } while (x != u);
        scc++;
    }
}
bool satisfiable() {
    ans.assign(n, 0);
    id.assign(2 * n, -1);
    dfn.assign(2 * n, -1);
    low.assign(2 * n, -1);
    for (int i = 0; i < n * 2; i++)
        if (dfn[i] == -1) {
            dfs(i);
        }
    for (int i = 0; i < n; ++i) {
        if (id[2 * i] == id[2 * i + 1]) {
            return false;
        }
        ans[i] = id[2 * i] > id[2 * i + 1];
    }
    return true;
}
}; // [9fb62b] \ addVar, addAtMostOne

```

## 6.10 Virtual Tree [83c4da]

```

// need LCA
vector<vector<int>> vir(n);
auto clear = [&](auto self, int u) -> void {
    for (int v : vir[u]) self(self, v);
    vir[u].clear();
};
auto build = [&](vector<int> &v) -> void { // be careful of the
    changes to the array
    // maybe dont need to sort when do it while dfs
    sort(all(v), [&](int a, int b) {
        return dfn[a] < dfn[b];
    });
    clear(clear, 0);
    if (v[0] != 0) v.insert(v.begin(), 0);
    int k = v.size();
    vector<int> st;
    rep(i, 0, k) {
        if (st.empty()) {
            st.push_back(v[i]);
            continue;
        }
        int p = lca(v[i], st.back());
        if (p == st.back()) {
            st.push_back(v[i]);
            continue;
        }
        while (st.size() >= 2 && dep[st.end()[-2]] >= dep[p]) {
            vir[st.end()[-2]].push_back(st.back());
            st.pop_back();
        }
        if (st.back() != p) {

```

```

            vir[p].push_back(st.back());
            st.pop_back();
            st.push_back(p);
        }
        st.push_back(v[i]);
    }
    while (st.size() >= 2) {
        vir[st.end()[-2]].push_back(st.back());
        st.pop_back();
    }
};

```

## 6.11 Functional Graph [a9b3cd]

```

// bel[x]: x is belong bel[x]-th jellyfish
// len[x]: cycle length of x-th jellyfish
// ord[x]: order of x in cycle (x == root[x])
struct FunctionalGraph {
    int n, cnt = 0;
    std::vector<std::vector<int>> adj;
    std::vector<int> f, bel, dep, ord, root, in, out, len;
    FunctionalGraph(int n) : n(n), adj(n), root(n),
        bel(n, -1), dep(n), ord(n), in(n), out(n) {}
    void dfs(int u) {
        in[u] = cnt++;
        for (int v : adj[u]) {
            if (bel[v] == -1) {
                dep[v] = dep[u] + 1;
                root[v] = root[u];
                bel[v] = bel[u];
                dfs(v);
            }
        }
        out[u] = cnt;
    }
    void build(const auto &f_) {
        f = f_;
        for (int i = 0; i < n; i++) {
            adj[f[i]].push_back(i);
        }
        std::vector<int> vis(n, -1);
        for (int i = 0; i < n; i++) {
            if (vis[i] == -1) {
                int x = i;
                while (vis[x] == -1) {
                    vis[x] = i;
                    x = f[x];
                }
                if (vis[x] != i) {
                    continue;
                }
                int s = x, l = 0;
                do {
                    bel[x] = len.size();
                    ord[x] = l++;
                    root[x] = x;
                    x = f[x];
                } while (x != s);
                len.push_back(l);
            }
        }
        for (int i = 0; i < n; i++) {
            if (root[i] == i) {
                dfs(i);
            }
        }
    }
    int dist(int x, int y) { // x -> y
        if (bel[x] != bel[y]) {
            return -1;
        } else if (dep[x] < dep[y]) {
            return -1;
        } else if (dep[y] != 0) {
            if (in[y] <= in[x] and in[x] < out[y]) {
                return dep[x] - dep[y];
            }
            return -1;
        } else {
            return dep[x] + (ord[y] - ord[root[x]] + len[bel[x]]) %
                len[bel[x]];
        }
    }
};

```



## 7 Math

### 7.1 Combinatoric

```
vector<mint> fac, inv;

inline void init(int n) {
    fac.resize(n + 1);
    inv.resize(n + 1);
    fac[0] = inv[0] = 1;
    rep(i, 1, n + 1) fac[i] = fac[i - 1] * i;
    inv[n] = fac[n].inv();
    for (int i = n; i > 0; --i) inv[i - 1] = inv[i] * i;
}

inline mint Comb(int n, int k) {
    if (k > n || k < 0) return 0;
    return fac[n] * inv[k] * inv[n - k];
}

inline mint H(int n, int m) {
    return Comb(n + m - 1, m);
}

inline mint catalan(int n) {
    return fac[2 * n] * inv[n + 1] * inv[n];
}

inline mint excatalan(int n, int m, int k) {
    if (k > m) return Comb(n + m, m);
    if (k > m - n) return Comb(n + m, m) - Comb(n + m, m - k);
    return 0;
}
```

### 7.2 Discrete Log [442909]

```
int power(int a, int b, int p, int res = 1) {
    for (; b; b /= 2, a = 1LL * a * a % p) {
        if (b & 1) {
            res = 1LL * res * a % p;
        }
    }
    return res;
}

int exbsgs(int a, int b, int p) {
    a %= p;
    b %= p;
    if (b == 1 || p == 1) {
        return 0;
    }
    if (a == 0) {
        return b == 0 ? 1 : -1;
    }

    i64 g, k = 0, t = 1; // t : a ^ k / sum{d}
    while ((g = std::gcd(a, p)) > 1) {
        if (b % g) {
            return -1;
        }
        b /= g;
        p /= g;
        k++;
        t = t * (a / g) % p;
        if (t == b) {
            return k;
        }
    }

    const int n = std::sqrt(p) + 1;
    std::unordered_map<int, int> mp;
    mp[b] = 0;

    int x = b, y = t;
    int mi = power(a, n, p);
    for (int i = 1; i < n; i++) {
        x = 1LL * x * a % p;
        mp[x] = i;
    }

    for (int i = 1; i <= n; i++) {
        t = 1LL * t * mi % p;
        if (mp.contains(t)) {
            return 1LL * i * n - mp[t] + k;
        }
    }

    return -1; // no solution
}
```

### 7.3 Div Floor Ceil

```
// b > 0!!!!
int CEIL(int a, int b) {
    return (a >= 0 ? (a + b - 1) / b : a / b);
}

int FLOOR(int a, int b) {
    return (a >= 0 ? a / b : (a - b + 1) / b);
}
```

### 7.4 exCRT [fccd2c]

```
i64 exgcd(i64 a, i64 b, i64 &x, i64 &y) {
    if (b == 0) {
        x = 1;
        y = 0;
        return a;
    }
    i64 g = exgcd(b, a % b, y, x);
    y -= a / b * x;
    return g;
}

// return {x, T}
// a: moduli, b: remainders
// x: first non-negative solution, T: minimum period
std::pair<i64, i64> exCRT(auto &a, auto &b) {
    auto [m1, r1] = std::tie(a[0], b[0]);
    for (int i = 1; i < ssize(a); i++) {
        auto [m2, r2] = std::tie(a[i], b[i]);
        i64 x, y;
        i64 g = exgcd(m1, m2, x, y);
        if ((r2 - r1) % g) { // no solution
            return {-1, -1};
        }
        x = (i128(x) * (r2 - r1) / g) % (m2 / g);
        if (x < 0) {
            x += (m2 / g);
        }
        r1 = m1 * x + r1;
        m1 = std::lcm(m1, m2);
    }
    r1 %= m1;
    if (r1 < 0) {
        r1 += m1;
    }
    return {r1, m1};
}
```

### 7.5 Factorization [cd95b9]

```
ull modmul(ull a, ull b, ull M) {
    i64 ret = a * b - M * ull(1.L / M * a * b);
    return ret + M * (ret < 0) - M * (ret >= (i64)M);
}

ull modpow(ull b, ull e, ull mod) {
    ull ans = 1;
    for (; e; b = modmul(b, b, mod), e /= 2) {
        if (e & 1) ans = modmul(ans, b, mod);
    }
    return ans;
}

bool isPrime(ull n) {
    if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
    ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
        s = __builtin_ctzll(n - 1), d = n >> s;
    for (ull a : A) {
        ull p = modpow(a % n, d, n), i = s;
        while (p != 1 && p != n - 1 && a % n && i--) {
            p = modmul(p, p, n);
            if (p != n - 1 && i != s) return 0;
        }
        return 1;
    }
    // [94d8b8]
}

ull pollard(ull n) {
    uniform_int_distribution<ull> unif(0, n - 1);
    ull c = 1;
    auto f = [n, &c](ull x) { return modmul(x, x, n) + c % n; };
    ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
    while (t++ % 40 || __gcd(prd, n) == 1) {
        if (x == y) c = unif(rng), x = ++i, y = f(x);
        if ((q = modmul(prd, max(x, y) - min(x, y), n))) prd = q;
        x = f(x), y = f(f(y));
    }
}
```

```

    }
    return __gcd(prd, n);
} // [6a1cda]

vector<ull> factor(ull n) {
    if (n == 1) return {};
    if (isPrime(n)) return {n};
    ull x = pollard(n);
    auto l = factor(x), r = factor(n / x);
    l.insert(l.end(), r.begin(), r.end());
    return l;
}

```

## 7.6 Floor Sum [92460c]

```

// \sum_0^n floor((a * x + b) / c) in log(n + m + a + b)
int floor_sum(int a, int b, int c, int n) { // add mod if
    needed
    int m = (a * n + b) / c;
    if (a >= c || b >= c)
        return (a / c) * (n * (n + 1) / 2) + (b / c) * (n + 1) +
            floor_sum(a % c, b % c, c, n);
    if (n < 0 || a == 0)
        return 0;
    return n * m - floor_sum(c, c - b - 1, a, m - 1);
}

```

## 7.7 FWT [a0135a]

```

void fwt(vector<ll> &f, bool inv = false) { // xor-convolution
    const int N = 31 - __builtin_clz(ssize(f)),
        inv2 = (MOD + 1) / 2;
    rep(i, 0, N) rep(j, 0, 1 << N) {
        if (j >> i & 1 ^ 1) {
            ll a = f[j], b = f[j | (1 << i)];
            if (inv) {
                f[j] = (a + b) * inv2 % MOD;
                f[j | (1 << i)] = (a - b + MOD) * inv2 % MOD;
            } else {
                f[j] = (a + b) % MOD;
                f[j | (1 << i)] = (a - b + MOD) % MOD;
            }
        }
    }
}

```

## 7.8 Gauss Elimination [e45cbd]

```

using Z = ModInt<998244353>;
// using F = long double;
using Matrix = std::vector<std::vector<Z>>>;
// using Matrix = std::vector<std::vector<F>>>; (double)
// using Matrix = std::vector<std::bitset<5000>>>; (mod 2)

template <typename T>
auto gauss(Matrix &A, std::vector<T> &b, int n, int m) {
    assert(ssize(b) == n);
    int r = 0;
    std::vector<int> where(m, -1);
    for (int i = 0; i < m && r < n; i++) {
        int p = r; // pivot
        while (p < n && A[p][i] == T(0)) p++;
        if (p == n) continue;
        std::swap(A[r], A[p]), std::swap(b[r], b[p]);
        where[i] = r;
        // coef: mod 2 don't need this
        T inv = T(1) / A[r][i];
        for (int j = i; j < m; j++) A[r][j] *= inv;
        b[r] *= inv;
        for (int j = 0; j < n; j++) { // deduct: mod 2 don't need
            this
            if (j != r) {
                T x = A[j][i];
                for (int k = i; k < m; k++) {
                    A[j][k] -= x * A[r][k];
                }
                b[j] -= x * b[r];
            }
        }
        // for (int j = 0; j < n; ++j) { // (mod 2) -> coef and
        // deduct
        //     if (j != r && A[j][i]) {
        //         A[j] ^= A[r], b[j] ^= b[r];
        //     }
        // }
        r++;
    }
}

```

```

}
for (int i = r; i < n; i++) {
    if (ranges::all_of(A[i] | views::take(m), [](auto &x) {
        return x == T(0); }) && b[i] != T(0)) {
        return std::tuple(-1, std::vector<T>(), std::vector<std::
            vector<T>>()); // no solution
    }
    // if (A[i].none() && b[i]) { // (mod 2)
    //     return std::tuple(-1, std::vector<T>(), std::vector<
    //         std::vector<T>>());
    // }
}
// if (r < m) { // infinite solution
//     return ;
// }
std::vector<T> sol(m);
std::vector<std::vector<T>> basis;
for (int i = 0; i < m; i++) {
    if (where[i] != -1) {
        sol[i] = b[where[i]];
    } else {
        std::vector<T> v(m); v[i] = 1;
        for (int j = 0; j < m; j++) {
            if (where[j] != -1) {
                v[j] = A[where[j]][i] * T(-1);
                // v[j] = A[where[j]][i]; (mod 2)
            }
        }
        basis.push_back(std::move(v));
    }
}
return std::tuple(r, sol, basis);
};

```

## 7.9 Lagrange Interpolation [b70847]

```

struct Lagrange {
    int deg{};
    vector<int> C;
    Lagrange(const vector<int> &P) {
        deg = P.size() - 1;
        C.assign(deg + 1, 0);
        for (int i = 0; i <= deg; i++) {
            int q = inv[i] * inv[i - deg] % mod;
            if ((deg - i) % 2 == 1) {
                q = mod - q;
            }
            C[i] = P[i] * q % mod;
        }
    }
    int operator()(int x) { // 0 <= x < mod
        if (0 <= x and x <= deg) {
            int ans = fac[x] * fac[deg - x] % mod;
            if ((deg - x) % 2 == 1) {
                ans = (mod - ans);
            }
            return ans * C[x] % mod;
        }
        vector<int> pre(deg + 1), suf(deg + 1);
        for (int i = 0; i <= deg; i++) {
            pre[i] = (x - i);
            if (i) {
                pre[i] = pre[i] * pre[i - 1] % mod;
            }
        }
        for (int i = deg; i >= 0; i--) {
            suf[i] = (x - i);
            if (i < deg) {
                suf[i] = suf[i] * suf[i + 1] % mod;
            }
        }
        int ans = 0;
        for (int i = 0; i <= deg; i++) {
            ans += (i == 0 ? 1 : pre[i - 1]) * (i == deg ? 1 : suf[i
                + 1]) % mod * C[i];
            ans %= mod;
        }
        if (ans < 0) ans += mod;
        return ans;
    }
};

```

## 7.10 Linear Sieve [e7d01a]

```
const int C = 1e6 + 5;

int mo[C], lp[C], phi[C], isp[C];
vector<int> prime;

void sieve() {
    mo[1] = phi[1] = 1;
    rep(i, 1, C) lp[i] = 1;
    rep(i, 2, C) {
        if (lp[i] == 1) {
            lp[i] = i;
            prime.pb(i);
            isp[i] = 1;
            mo[i] = -1;
            phi[i] = i - 1;
        }
        for (int p : prime) {
            if (i * p >= C) break;
            lp[i * p] = p;
            if (i % p == 0) {
                phi[p * i] = phi[i] * p;
                break;
            }
            phi[i * p] = phi[i] * (p - 1);
            mo[i * p] = mo[i] * mo[p];
        }
    }
}
```

## 7.11 Lucas [5facf0]

```
// comb(n, m) % M, M = p^k
// O(M)-O(log(n))
struct Lucas {
    const int p, M;
    vector<int> f;
    Lucas(int p, int M) : p(p), M(M), f(M + 1) {
        f[0] = 1;
        for (int i = 1; i <= M; i++) {
            f[i] = f[i - 1] * (i % p == 0 ? 1 : i) % M;
        }
    }
    int CountFact(int n) {
        int c = 0;
        while (n) c += (n /= p);
        return c;
    }
    // (n! without factor p) % p^k
    int ModFact(int n) {
        int r = 1;
        while (n) {
            r = r * power(f[M], n / M % 2, M) % M * f[n % M] % M;
            n /= p;
        }
        return r;
    }
    int ModComb(int n, int m) {
        if (m < 0 || n < m) return 0;
        int c = CountFact(n) - CountFact(m) - CountFact(n - m);
        int r = ModFact(n) * power(ModFact(m), M / p * (p - 1) - 1, M) % M
            * power(ModFact(n - m), M / p * (p - 1) - 1, M) % M;
        return r * power(p, c, M) % M;
    }
};
```

## 7.12 Mod Int [5a3b5b]

```
using u32 = unsigned int;
using u64 = unsigned long long;
template <class T>
constexpr T power(T a, u64 b, T res = 1) {
    for (; b != 0; b /= 2, a *= a) {
        if (b & 1) {
            res *= a;
        }
    }
    return res;
}

template <u32 P>
struct ModInt {
    u32 v;
    const static ModInt G;
```

```
constexpr ModInt &norm(u32 x) {
    v = x < P ? x : x - P;
    return *this;
}
constexpr ModInt(i64 x = 0) { norm(x % P + P); }
constexpr ModInt inv() const { return power(*this, P - 2); }
constexpr ModInt operator-(const ModInt &r) const { return ModInt() - *this; }
constexpr ModInt operator+(const ModInt &r) const { return ModInt().norm(v + r.v); }
constexpr ModInt operator-(const ModInt &r) const { return ModInt().norm(v + P - r.v); }
constexpr ModInt operator*(const ModInt &r) const { return ModInt().norm(u64(v) * r.v % P); }
constexpr ModInt operator/(const ModInt &r) const { return *this * r.inv(); }
constexpr ModInt &operator+=(const ModInt &r) { return *this = *this + r; }
constexpr ModInt &operator-=(const ModInt &r) { return *this = *this - r; }
constexpr ModInt &operator*=(const ModInt &r) { return *this = *this * r; }
constexpr ModInt &operator/=(const ModInt &r) { return *this = *this / r; }
constexpr bool operator==(const ModInt &r) const { return v == r.v; }
constexpr bool operator!=(const ModInt &r) const { return v != r.v; }
explicit constexpr operator bool() const { return v != 0; }
friend std::ostream &operator<<(std::ostream &os, const ModInt &r) {
    return os << r.v;
}
};
using mint = ModInt<998244353>;
template <> const mint mint::G = mint(3);
```

## 7.13 Primitive Root [bebd30]

```
ull primitiveRoot(ull p) {
    auto fac = factor(p - 1);
    sort(all(fac));
    fac.erase(unique(all(fac)), fac.end());
    auto test = [p, fac](ull x) {
        for(ull d : fac)
            if (modpow(x, (p - 1) / d, p) == 1)
                return false;
        return true;
    };
    uniform_int_distribution<ull> unif(1, p - 1);
    ull root;
    while(!test(root = unif(rng)));
    return root;
}
```

## 7.14 Simplex [2e718d]

```
// max{cx} subject to {Ax<=b, x>=0}
// n: constraints, m: vars !!!
// x[] is the optimal solution vector
// usage :
// x = simplex(A, b, c); (A <= 100 x 100)
vector<double> simplex(
    const vector<vector<double>>& a,
    const vector<double>& b,
    const vector<double>& c) {

    int n = (int)a.size(), m = (int)a[0].size() + 1;
    vector<val(n + 2, vector<double>(m + 1));
    vector<int> idx(n + m);
    iota(all(idx), 0);
    int r = n, s = m - 1;
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < m - 1; ++j)
            val[i][j] = -a[i][j];
        val[i][m - 1] = 1;
        val[i][m] = b[i];
        if (val[r][m] > val[i][m])
            r = i;
    }
    copy(all(c), val[n].begin());
    val[n + 1][m - 1] = -1;
    for (double num; ; ) {
        if (r < n) {
            swap(idx[s], idx[r + m]);
```

```

    val[r][s] = 1 / val[r][s];
    for (int j = 0; j <= m; ++j) if (j != s)
        val[r][j] *= -val[r][s];
    for (int i = 0; i <= n + 1; ++i) if (i != r) {
        for (int j = 0; j <= m; ++j) if (j != s)
            val[i][j] += val[r][j] * val[i][s];
        val[i][s] *= val[r][s];
    }
}
r = s = -1;
for (int j = 0; j < m; ++j)
    if (s < 0 || idx[s] > idx[j])
        if (val[n + 1][j] > eps || val[n + 1][j] > -eps && val[
n][j] > eps)
            s = j;
if (s < 0) break;
for (int i = 0; i < n; ++i) if (val[i][s] < -eps) {
    if (r < 0
        || (num = val[r][m] / val[r][s] - val[i][m] / val[i][s]
        ) < -eps
        || num < eps && idx[r + m] > idx[i + m])
        r = i;
}
if (r < 0) {
    // Solution is unbounded.
    return vector<double>{};
}
}
if (val[n + 1][m] < -eps) {
    // No solution.
    return vector<double>{};
}
vector<double> x(m - 1);
for (int i = m; i < n + m; ++i)
    if (idx[i] < m - 1)
        x[idx[i]] = val[i - m][m];
return x;
}

```

## 7.15 Sqrt Mod [4e4b23]

```

// the Jacobi symbol is a generalization of the Legendre symbol
// such that the bottom doesn't need to be prime.
// (n|p) -> same as legendre
// (n|ab) = (n|a)(n|b)
// work with long long
int Jacobi(int a, int m) {
    int s = 1;
    for (; m > 1; ) {
        a %= m;
        if (a == 0) return 0;
        const int r = __builtin_ctz(a);
        if ((r & 1) && ((m + 2) & 4)) s = -s;
        a >>= r;
        if (a & m & 2) s = -s;
        swap(a, m);
    }
    return s;
} // [00fa11]

// 0: a == 0
// -1: a isn't a quad res of p
// else: return X with X^2 p == a
// doesn't work with long long
int QuadraticResidue(int a, int p) {
    if (p == 2) return a & 1;
    if (int jc = Jacobi(a, p); jc <= 0) return jc;
    int b, d;
    for (; ; ) {
        b = rand() % p;
        d = (1LL * b * b + p - a) % p;
        if (Jacobi(d, p) == -1) break;
    }
    int f0 = b, f1 = 1, g0 = 1, g1 = 0, tmp;
    for (int e = (1LL + p) >> 1; e; e >>= 1) {
        if (e & 1) {
            tmp = (1LL * g0 * f0 + 1LL * d * (1LL * g1 * f1 % p)) % p;
            ;
            g1 = (1LL * g0 * f1 + 1LL * g1 * f0) % p;
            g0 = tmp;
        }
        tmp = (1LL * f0 * f0 + 1LL * d * (1LL * f1 * f1 % p)) % p;
        f1 = (2LL * f0 * f1) % p;
        f0 = tmp;
    }
}

```

```

}
return g0;
}

```

## 7.16 LinearSolve [1c7d11]

```

// ax + b = 0 (mod m)
std::pair<i64, i64> sol(i64 a, i64 b, i64 m) {
    assert(m > 0);
    b *= -1;
    i64 x, y;
    i64 g = exgcd(a, m, x, y);
    if (g < 0) {
        g *= -1, x *= -1, y *= -1;
    }
    if (b % g != 0) return {-1, -1};
    x = x * (b / g) % (m / g);
    if (x < 0) {
        x += m / g;
    }
    return {x, m / g};
}

```

## 7.17 PiCount [b9ce98]

```

i64 PrimeCount(i64 n) { // n ~ 10^13 => < 2s
    if (n <= 1) return 0;
    int v = sqrt(n), s = (v + 1) / 2, pc = 0;
    vector<int> smalls(v + 1), skip(v + 1), roughs(s);
    vector<i64> larges(s);
    for (int i = 2; i <= v; ++i) smalls[i] = (i + 1) / 2;
    for (int i = 0; i < s; ++i) {
        roughs[i] = 2 * i + 1;
        larges[i] = (n / (2 * i + 1) + 1) / 2;
    }
    for (int p = 3; p <= v; ++p) {
        if (smalls[p] > smalls[p - 1]) {
            int q = p * p;
            ++pc;
            if (1LL * q * q > n) break;
            skip[p] = 1;
            for (int i = q; i <= v; i += 2 * p) skip[i] = 1;
            int ns = 0;
            for (int k = 0; k < s; ++k) {
                int i = roughs[k];
                if (skip[i]) continue;
                i64 d = 1LL * i * p;
                larges[ns] = larges[k] - (d <= v ? larges[smalls[d] -
pc] : smalls[n / d]) + pc;
                roughs[ns++] = i;
            }
            s = ns;
            for (int j = v / p; j >= p; --j) {
                int c = smalls[j] - pc, e = min(j * p + p, v + 1);
                for (int i = j * p; i < e; ++i) smalls[i] -= c;
            }
        }
    }
    for (int k = 1; k < s; ++k) {
        const i64 m = n / roughs[k];
        i64 t = larges[k] - (pc + k - 1);
        for (int l = 1; l < k; ++l) {
            int p = roughs[l];
            if (1LL * p * p > m) break;
            t -= smalls[m / p] - (pc + l - 1);
        }
        larges[0] -= t;
    }
    return larges[0];
}

```

## 7.18 Triangular

- Cosine Law (餘弦定理)
$$c^2 = a^2 + b^2 - 2ab \cos C$$

$$b^2 = a^2 + c^2 - 2ac \cos B$$

$$a^2 = b^2 + c^2 - 2bc \cos A$$
- Weierstrass Substitution (t-代換)
 設  $t = \tan \frac{\theta}{2}$ , 則有:
 
$$\sin \theta = \frac{2t}{1+t^2}, \quad \cos \theta = \frac{1-t^2}{1+t^2}, \quad d\theta = \frac{2}{1+t^2} dt$$
- Brahmagupta's Formula (海龍公式, 四邊形版本)
 若四邊形為圓內接, 邊長  $a, b, c, d$ , 半周長  $s = \frac{a+b+c+d}{2}$ , 則:
 
$$A = \sqrt{(s-a)(s-b)(s-c)(s-d)}$$

一般四邊形 (Bretschneider's formula) :

$$A = \sqrt{(s-a)(s-b)(s-c)(s-d) - abcd \cos^2\left(\frac{A+C}{2}\right)}$$

## 7.19 ModMin [79217f]

```
// min{k | l <= ((ak) mod m) <= r}, no solution -> -1
int mod_min(int a, int m, int l, int r) {
    if (a == 0) return l ? -1 : 0;
    if (int k = (l + a - 1) / a; k * a <= r)
        return k;
    int b = m / a, c = m % a;
    if (int y = mod_min(c, a, a - r % a, a - l % a))
        return (l + y * c + a - 1) / a + y * b;
    return -1;
}
```

## 7.20 FFT [474566]

```
template<typename C = complex<double>>
void FFT(vector<C> &P, C w, bool inv = 0) {
    int n = P.size(), lg = __builtin_ctz(n);
    assert(__builtin_popcount(n) == 1);

    for (int j = 1, i = 0; j < n - 1; ++j) {
        for (int k = n >> 1; k > (i ^ k); k >= 1); // !!!
        if (j < i) swap(P[i], P[j]);
    }

    vector<C> ws = {inv ? C{1} / w : w};

    rep (i, 1, lg) ws.pb(ws[i - 1] * ws[i - 1]);
    reverse(all(ws));

    rep (i, 0, lg) {
        for (int k = 0; k < n; k += 2 << i) {
            C base = C{1};
            rep (j, k, k + (1 << i)) {
                auto t = base * P[j + (1 << i)];
                auto u = P[j];
                P[j] = u + t;
                P[j + (1 << i)] = u - t;
                base = base * ws[i];
            }
        }
    }

    if (inv) rep (i, 0, n) P[i] = P[i] / C(n);
}

const int N = 1 << 21;
const double PI = acos(-1);
const auto w = exp(-complex<double>(0, 2.0 * PI / N));
```

## 7.21 NTT [ff4101]

```
// add sub mul
struct ntt {
    vector<int> ws;
    ntt(int N) : ws(N) {
        int wb = fpow(3, (MOD - 1) / N, MOD);
        ws[0] = 1;
        rep (i, 1, N) ws[i] = mul(ws[i - 1], wb);
    }
    void operator()(vector<int> &P, bool inv = 0) {
        int n = P.size(), lg = __builtin_ctz(n);
        assert(__builtin_popcount(n) == 1);
        for (int j = 1, i = 0; j < n - 1; ++j) {
            for (int k = n >> 1; k > (i ^ k); k >= 1); // !!!
            if (j < i) swap(P[i], P[j]);
        }
        for (int L = 2; L <= n; L <= 1) {
            int dx = n / L, dl = L >> 1;
            for (int k = 0; k < n; k += L) {
                for (int j = k, x = 0; j < k + dl; j++, x += dx) {
                    int t = mul(ws[x], P[j + dl]);
                    P[j + dl] = sub(P[j], t);
                    P[j] = add(P[j], t);
                }
            }
        }
        if (inv) {
            reverse(1 + all(P));
            int invn = fpow(n, MOD - 2, MOD);
            rep (i, 0, n) P[i] = mul(P[i], invn);
        }
    }
}
```

```
}
};
const int N = 1 << 20;
ntt NTT(N);
```

## 7.22 NTT prime

• P: 7681, Rt: 17	P: 12289, Rt: 11
• P: 40961, Rt: 3	P: 65537, Rt: 3
• P: 786433, Rt: 10	P: 5767169, Rt: 3
• P: 7340033, Rt: 3	P: 23068673, Rt: 3
• P: 469762049, Rt: 3	P: 2061584302081, Rt: 7
• P: 2748779069441, Rt: 3	P: 167772161, Rt: 3
• P: 104857601, Rt: 3	P: 985661441, Rt: 3
• P: 998244353, Rt: 3	P: 1107296257, Rt: 10
• P: 2013265921, Rt: 31	P: 2810183681, Rt: 11
• P: 2885681153, Rt: 3	P: 605028353, Rt: 3
• P: 1945555039024054273, Rt: 5	P: 9223372036737335297, Rt: 3

## 7.23 Polynomial

```
std::mt19937_64 rng(std::chrono::steady_clock::now().
    time_since_epoch().count());

template <class mint>
void nft(bool type, std::vector<mint> &a) {
    int n = int(a.size()), s = 0;
    while ((1 << s) < n) {
        s++;
    }
    assert(1 << s == n);
    static std::vector<mint> ep, iep;
    while (int(ep.size()) <= s) {
        ep.push_back(power(mint::G, mint(-1).v / (1 << int(ep.size())
            )));
        iep.push_back(ep.back().inv());
    }
    std::vector<mint> b(n);
    for (int i = 1; i <= s; i++) {
        int w = 1 << (s - i);
        mint base = type ? iep[i] : ep[i], now = 1;
        for (int y = 0; y < n / 2; y += w) {
            for (int x = 0; x < w; x++) {
                auto l = a[y << 1 | x];
                auto r = now * a[y << 1 | x | w];
                b[y | x] = l + r;
                b[y | x | n >> 1] = l - r;
            }
            now *= base;
        }
        std::swap(a, b);
    }
}

template <class mint>
std::vector<mint> multiply(const std::vector<mint> &a, const
    std::vector<mint> &b) {
    int n = int(a.size()), m = int(b.size());
    if (!n || !m) return {};
    if (std::min(n, m) <= 8) {
        std::vector<mint> ans(n + m - 1);
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < m; j++) {
                ans[i + j] += a[i] * b[j];
            }
        }
        return ans;
    }
    int lg = 0;
    while ((1 << lg) < n + m - 1) {
        lg++;
    }
    int z = 1 << lg;
    auto a2 = a, b2 = b;
    a2.resize(z);
    b2.resize(z);
    nft(false, a2);
    nft(false, b2);
    for (int i = 0; i < z; i++) {
        a2[i] *= b2[i];
    }
    nft(true, a2);
    a2.resize(n + m - 1);
```



```

mint iz = mint(z).inv();
for (int i = 0; i < n + m - 1; i++) {
    a2[i] *= iz;
}
return a2;
}

template <class D>
struct Poly {
    std::vector<D> v;
    Poly(const std::vector<D> &v_) : v(v_) { shrink(); }
    void shrink() {
        while (v.size() > 1 && !v.back()) {
            v.pop_back();
        }
    }
    int size() const { return int(v.size()); }
    D freq(int p) const { return (p < size()) ? v[p] : D(0); }
    Poly operator+(const Poly &r) const {
        auto n = std::max(size(), r.size());
        std::vector<D> res(n);
        for (int i = 0; i < n; i++) {
            res[i] = freq(i) + r.freq(i);
        }
        return res;
    }
    Poly operator-(const Poly &r) const {
        int n = std::max(size(), r.size());
        std::vector<D> res(n);
        for (int i = 0; i < n; i++) {
            res[i] = freq(i) - r.freq(i);
        }
        return res;
    }
    Poly operator*(const Poly &r) const { return multiply(v, r.v); }
    Poly operator*(const D &r) const {
        int n = size();
        std::vector<D> res(n);
        for (int i = 0; i < n; i++) {
            res[i] = v[i] * r;
        }
        return res;
    }
    Poly operator/(const D &r) const { return *this * r.inv(); }
    Poly operator/(const Poly &r) const {
        if (size() < r.size()) return {};
        int n = size() - r.size() + 1;
        return (rev().pre(n) * r.rev().inv(n)).pre(n).rev();
    }
    Poly operator%(const Poly &r) const { return *this - *this / r * r; }
    Poly operator<<(int s) const {
        std::vector<D> res(size() + s);
        for (int i = 0; i < size(); i++) {
            res[i + s] = v[i];
        }
        return res;
    }
    Poly operator>>(int s) const {
        if (size() <= s) {
            return Poly();
        }
        std::vector<D> res(size() - s);
        for (int i = 0; i < size() - s; i++) {
            res[i] = v[i + s];
        }
        return res;
    }
    Poly &operator+=(const Poly &r) { return *this = *this + r; }
    Poly &operator-=(const Poly &r) { return *this = *this - r; }
    Poly &operator*=(const Poly &r) { return *this = *this * r; }
    Poly &operator*=(const D &r) { return *this = *this * r; }
    Poly &operator/=(const Poly &r) { return *this = *this / r; }
    Poly &operator/=(const D &r) { return *this = *this / r; }
    Poly &operator%=(const Poly &r) { return *this = *this % r; }
    Poly &operator<<=(const size_t &n) { return *this = *this << n; }
    Poly &operator>>=(const size_t &n) { return *this = *this >> n; }
    Poly pre(int le) const {
        return {{v.begin(), v.begin() + std::min(size(), le)}};
    }
};

```

```

Poly rev(int n = -1) const {
    std::vector<D> res = v;
    if (n != -1) {
        res.resize(n);
    }
    std::reverse(res.begin(), res.end());
    return res;
}

Poly diff() const {
    std::vector<D> res(std::max(0, size() - 1));
    for (int i = 1; i < size(); i++) {
        res[i - 1] = freq(i) * i;
    }
    return res;
}

Poly inte() const {
    std::vector<D> res(size() + 1);
    for (int i = 0; i < size(); i++) {
        res[i + 1] = freq(i) / (i + 1);
    }
    return res;
}

// f * f.inv() = 1 + g(x)x^m
Poly inv(int m) const {
    Poly res = Poly({D(1) / freq(0)});
    for (int i = 1; i < m; i *= 2) {
        res = (res * D(2) - res * res * pre(2 * i)).pre(2 * i);
    }
    return res.pre(m);
}

Poly exp(int n) const {
    assert(freq(0) == 0);
    Poly f({1}), g({1});
    for (int i = 1; i < n; i *= 2) {
        g = (g * 2 - f * g * g).pre(i);
        Poly q = diff().pre(i - 1);
        Poly w = (q + g * (f.diff() - f * q)).pre(2 * i - 1);
        f = (f + f * (*this - w.inte()).pre(2 * i)).pre(2 * i);
    }
    return f.pre(n);
}

Poly log(int n) const {
    assert(freq(0) == 1);
    auto f = pre(n);
    return (f.diff() * f.inv(n - 1)).pre(n - 1).inte();
}

Poly pow(int n, i64 k) const {
    int m = 0;
    while (m < n && freq(m) == 0) m++;
    Poly f(std::vector<D>(n, 0));
    if (k && m && (k >= n || k * m >= n)) return f;
    f.v.resize(n);
    if (m == n) return f.v[0] = 1, f;
    int le = m * k;
    Poly g({v.begin() + m, v.end()});
    D base = power<D>(g.freq(0), k, inv = g.freq(0).inv());
    g = ((g * inv).log(n - m) * D(k)).exp(n - m);
    for (int i = le; i < n; i++) f.v[i] = g.freq(i - le) * base;
    return f;
}

Poly Getsqrt(int n) const {
    if (size() == 0) return {{0}};
    int z = QuadraticResidue(freq(0).v, 998244353);
    if (z == -1) return Poly{};
    Poly f = pre(n + 1);
    Poly g({z});
    for (int i = 1; i < n; i *= 2) {
        g = (g + f.pre(2 * i) * g.inv(2 * i)) / 2;
    }
    return g.pre(n + 1);
}

Poly sqrt(int n) const {
    int m = 0;
    while (m < n && freq(m) == 0) m++;
    if (m == n) return {{0}};
    if (m & 1) return Poly{};
    Poly s = Poly(std::vector<D>(v.begin() + m, v.end()));
    Getsqrt(n);
    if (s.size() == 0) return Poly{};
    std::vector<D> res(n);
    for (int i = 0; i + m / 2 < n; i++) res[i + m / 2] = s.freq(i);
}

```

```

    return Poly(res);
}
Poly modpower(u64 n, const Poly &mod) {
    Poly x = *this, res = {{1}};
    for (; n; n /= 2, x = x * x % mod) {
        if (n & 1) {
            res = res * x % mod;
        }
    }
    return res;
}
friend std::ostream &operator<<(std::ostream &os, const Poly
&p) {
    if (p.size() == 0) {
        return os << "0";
    }
    for (auto i = 0; i < p.size(); i++) {
        if (p.v[i]) {
            os << p.v[i] << "x^" << i;
            if (i != p.size() - 1) {
                os << "+";
            }
        }
    }
    return os;
}
};
template <class mint>
struct MultiEval {
    using NP = MultiEval *;
    NP l, r;
    int sz;
    Poly<mint> mul;
    std::vector<mint> que;
    MultiEval(const std::vector<mint> &que_, int off, int sz_) :
        sz(sz_) {
        if (sz <= 100) {
            que = {que_.begin() + off, que_.begin() + off + sz};
            mul = {{1}};
            for (auto x : que) {
                mul *= {-x, 1};
            }
            return;
        }
        l = new MultiEval(que_, off, sz / 2);
        r = new MultiEval(que_, off + sz / 2, sz - sz / 2);
        mul = l->mul * r->mul;
    }
    MultiEval(const std::vector<mint> &que_) : MultiEval(que_, 0,
        int(que_.size())) {}
    void query(const Poly<mint> &pol_, std::vector<mint> &res)
        const {
        if (sz <= 100) {
            for (auto x : que) {
                mint sm = 0, base = 1;
                for (int i = 0; i < pol_.size(); i++) {
                    sm += base * pol_.freq(i);
                    base *= x;
                }
                res.push_back(sm);
            }
            return;
        }
        auto pol = pol_ % mul;
        l->query(pol, res);
        r->query(pol, res);
    }
    std::vector<mint> query(const Poly<mint> &pol) const {
        std::vector<mint> res;
        query(pol, res);
        return res;
    }
};
template <class mint>
Poly<mint> berlekampMassey(const std::vector<mint> &s) {
    int n = int(s.size());
    std::vector<mint> b = {mint(-1)}, c = {mint(-1)};
    mint y = mint(1);
    for (int ed = 1; ed <= n; ed++) {
        int l = int(c.size()), m = int(b.size());
        mint x = 0;
        for (int i = 0; i < l; i++) {
            x += c[i] * s[ed - l + i];
        }
    }

```

```

        b.push_back(0);
        m++;
        if (!x) {
            continue;
        }
        mint freq = x / y;
        if (l < m) {
            // use b
            auto tmp = c;
            c.insert(begin(c), m - l, mint(0));
            for (int i = 0; i < m; i++) {
                c[m - 1 - i] -= freq * b[m - 1 - i];
            }
            b = tmp;
            y = x;
        } else {
            // use c
            for (int i = 0; i < m; i++) {
                c[l - 1 - i] -= freq * b[m - 1 - i];
            }
        }
    }
    return c;
}
template <class E, class mint = decltype(E().f)>
mint sparseDet(const std::vector<std::vector<E>> &g) {
    int n = int(g.size());
    if (n == 0) {
        return 1;
    }
    auto randV = [&]() {
        std::vector<mint> res(n);
        for (int i = 0; i < n; i++) {
            res[i] = mint(std::uniform_int_distribution<i64>(1, mint
                (-1).v)(rng)); // need rng
        }
        return res;
    };
    std::vector<mint> c = randV(), l = randV(), r = randV();
    // l * mat * r
    std::vector<mint> buf(2 * n);
    for (int fe = 0; fe < 2 * n; fe++) {
        for (int i = 0; i < n; i++) {
            buf[fe] += l[i] * r[i];
        }
        for (int i = 0; i < n; i++) {
            r[i] *= c[i];
        }
        std::vector<mint> tmp(n);
        for (int i = 0; i < n; i++) {
            for (auto e : g[i]) {
                tmp[i] += r[e.to] * e.f;
            }
        }
        r = tmp;
    }
    auto u = berlekampMassey(buf);
    if (u.size() != n + 1) {
        return sparseDet(g);
    }
    auto acdet = u.freq(0) * mint(-1);
    if (n % 2) {
        acdet *= mint(-1);
    }
    if (!acdet) {
        return 0;
    }
    mint cdet = 1;
    for (int i = 0; i < n; i++) {
        cdet *= c[i];
    }
    return acdet / cdet;
}

```

## 7.24 Theorem

- Pick's Theorem  
 $A = i + \frac{b}{2} - 1$   
 $A$ : Area ·  $i$ : grid number in the inner ·  $b$ : grid number on the side
- Matrix-Tree theorem  
 undirected graph  
 $D_{ii}(G) = \deg(i), D_{ij} = 0, i \neq j$   
 $A_{ij}(G) = A_{ji}(G) = \#e(i, j), i \neq j$   
 $L(G) = D(G) - A(G)$   
 $t(G) = \det L(G) \binom{1, 2, \dots, i-1, i+1, \dots, n}{1, 2, \dots, i-1, i+1, \dots, n}$

- leaf to root  
 $D_{ij}^{out}(G) = \deg^{out}(i), D_{ij}^{out} = 0, i \neq j$   
 $A_{ij}(G) = \#e(i, j), i \neq j$   
 $L^{out}(G) = D^{out}(G) - A(G)$   
 $t^{root}(G, k) = \det L^{out}(G)_{(1,2,\dots,k-1,k+1,\dots,n)}^{(1,2,\dots,k-1,k+1,\dots,n)}$   
 root to leaf  
 $L^{in}(G) = D^{in}(G) - A(G)$   
 $t^{leaf}(G, k) = \det L^{in}(G)_{(1,2,\dots,k-1,k+1,\dots,n)}^{(1,2,\dots,k-1,k+1,\dots,n)}$
- Derangement  
 $D_n = (n-1)(D_{n-1} + D_{n-2}) = nD(n-1) + (-1)^n$
- Möbius Inversion  
 $f(n) = \sum_{d|n} g(d) \Leftrightarrow g(n) = \sum_{d|n} \mu\left(\frac{n}{d}\right) f(d)$
- Euler Inversion  
 $\sum_{i|n} \varphi(i) = n$
- Binomial Inversion  
 $f(n) = \sum_{i=0}^n \binom{n}{i} g(i) \Leftrightarrow g(n) = \sum_{i=0}^n (-1)^{n-i} \binom{n}{i} f(i)$
- Subset Inversion  
 $f(S) = \sum_{T \subseteq S} g(T) \Leftrightarrow g(S) = \sum_{T \subseteq S} (-1)^{|S|-|T|} f(T)$
- Min-Max Inversion  
 $\max_{i \in S} x_i = \sum_{T \subseteq S} (-1)^{|T|-1} \min_{j \in T} x_j$
- Ex Min-Max Inversion  
 $\text{kthmax}_{i \in S} x_i = \sum_{T \subseteq S} (-1)^{|T|-k} \binom{|T|-1}{k-1} \min_{j \in T} x_j$
- Lcm-Gcd Inversion  
 $\text{lcm}_{i \in S} x_i = \prod_{T \subseteq S} \left( \gcd_{j \in T} x_j \right)^{(-1)^{|T|-1}}$
- Sum of powers  
 $\sum_{k=1}^n k^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k^+ n^{m+1-k}$   
 $\sum_{j=0}^m \binom{m+1}{j} B_j^- = 0$   
 note:  $B_1^+ = -B_1^-, B_i^+ = B_i^-$
- Cayley's formula  
 number of trees on  $n$  labeled vertices:  $n^{n-2}$   
 Let  $T_{n,k}$  be the number of labelled forests on  $n$  vertices with  $k$  connected components, such that vertices  $1, 2, \dots, k$  all belong to different connected components. Then  $T_{n,k} = kn^{n-k-1}$ .
- High order residue  
 $[d^{\frac{p-1}{(n,p-1)}} \equiv 1]$
- Packing and Covering  
 $|\text{maximum independent set}| + |\text{minimum vertex cover}| = |V|$
- Koňig's theorem  
 $|\text{maximum matching}| = |\text{minimum vertex cover}|$
- Dilworth's theorem  
 $\text{width} = |\text{largest antichain}| = |\text{smallest chain decomposition}|$
- Mirsky's theorem  
 $\text{height} = |\text{longest chain}| = |\text{smallest antichain decomposition}| = |\text{minimum anticlique partition}|$
- Lucas' Theorem  
 For  $n, m \in \mathbb{Z}^*$  and prime  $P$ ,  $\binom{m}{n} \pmod P = \prod \binom{m_i}{n_i}$  where  $m_i$  is the  $i$ -th digit of  $m$  in base  $P$ .
- Stirling approximation  
 $n! \approx \sqrt{2\pi n} \left(\frac{n}{e}\right)^n e^{\frac{1}{12n}}$
- 1st Stirling Numbers(permutation  $|P| = n$  with  $k$  cycles)  
 $S(n, k) = \text{coefficient of } x^k \text{ in } \prod_{i=0}^{n-1} (x+i)$   
 $S(n+1, k) = nS(n, k) + S(n, k-1)$
- 2nd Stirling Numbers(Partition  $n$  elements into  $k$  non-empty set)  
 $S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$   
 $S(n+1, k) = kS(n, k) + S(n, k-1)$
- Catalan number  
 $C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n-1}$   
 $\binom{n+m}{n} - \binom{n+m}{n+1} = \frac{(m+n)!}{n!} \frac{n-m+1}{n+1}$  for  $n \geq m$   
 $C_n = \frac{1}{n+1} \binom{2n}{n} = \frac{(2n)!}{(n+1)n!}$   
 $C_0 = 1$  and  $C_{n+1} = 2 \binom{2n+1}{n+2} C_n$   
 $C_0 = 1$  and  $C_{n+1} = \sum_{i=0}^n C_i C_{n-i}$  for  $n \geq 0$
- Extended Catalan number  
 $\frac{1}{(k-1)n+1} \binom{kn}{n}$
- Calculate  $c[i-j]+ = a[i] \times b[j]$  for  $a[n], b[m]$   
 1.  $a = \text{reverse}(a); c = \text{mul}(a, b); c = \text{reverse}(c);$   
 2.  $b = \text{reverse}(b); c = \text{mul}(a, b); c = \text{rshift}(c, m-1);$

- Eulerian number (permutation  $1 \sim n$  with  $m$   $a[i] > a[i-1]$ )  
 $A(n, m) = \sum_{i=0}^m (-1)^i \binom{n+1}{i} (m+1-i)^n$   
 $A(n, m) = (n-m)A(n-1, m-1) + (m+1)A(n-1, m)$
- Hall's theorem  
 Let  $G = (X + Y, E)$  be a bipartite graph. For  $W \subseteq X$ , let  $N(W) \subseteq Y$  denotes the adjacent vertices set of  $W$ . Then,  $G$  has a  $X'$ -perfect matching (matching contains  $X' \subseteq X$ ) iff  $\forall W \subseteq X', |W| \leq |N(W)|$ .
- Tutte Matrix:  
 For a graph  $G = (V, E)$ , its maximum matching =  $\frac{rank(A)}{2}$  where  $A_{ij} = ((i, j) \in E ? (i < j ? x_{ij} : -x_{ji}) : 0)$  and  $x_{ij}$  are random numbers.
- Erdoš–Gallai theorem  
 There exists a simple graph with degree sequence  $d_1 \geq \dots \geq d_n$  iff  $\sum_{i=1}^n d_i$  is even and  $\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k), \forall 1 \leq k \leq n$
- Euler Characteristic  
 planar graph:  $V - E + F - C = 1$   
 convex polyhedron:  $V - E + F = 2$   
 $V, E, F, C$ : number of vertices, edges, faces(regions), and components
- Burnside Lemma  
 $|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$
- Polya theorem  
 $|Y^x/G| = \frac{1}{|G|} \sum_{g \in G} m^{c(g)}$   
 $m = |Y|$ : num of colors,  $c(g)$ : num of cycle
- Cayley's Formula  
 Given a degree sequence  $d_1, \dots, d_n$  of a labeled tree, there are  $\frac{(n-2)!}{(d_1-1)! \dots (d_n-1)!}$  spanning trees.
- Find a Primitive Root of  $n$ :  
 $n$  has primitive roots iff  $n = 2, 4, p^k, 2p^k$  where  $p$  is an odd prime.  
 1. Find  $\phi(n)$  and all prime factors of  $\phi(n)$ , says  $P = \{p_1, \dots, p_m\}$   
 2.  $\forall g \in [2, n)$ , if  $g^{\frac{\phi(n)}{p_i}} \neq 1, \forall p_i \in P$ , then  $g$  is a primitive root.  
 3. Since the smallest one isn't too big, the algorithm runs fast.  
 4.  $n$  has exactly  $\phi(\phi(n))$  primitive roots.
- Taylor series  
 $f(x) = f(c) + f'(c)(x-c) + \frac{f''(c)}{2!}(x-c)^2 + \frac{f'''(c)}{3!}(x-c)^3 + \dots$
- Lagrange Multiplier  
 $\min f(x, y)$ , subject to  $g(x, y) = 0$   
 $\frac{\partial f}{\partial x} + \lambda \frac{\partial g}{\partial x} = 0$   
 $\frac{\partial f}{\partial y} + \lambda \frac{\partial g}{\partial y} = 0$   
 $g(x, y) = 0$
- Calculate  $f(x+n)$  where  $f(x) = \sum_{i=0}^{n-1} a_i x^i$   
 $f(x+n) = \sum_{i=0}^{n-1} a_i (x+n)^i = \sum_{i=0}^{n-1} x^i \cdot \frac{1}{i!} \sum_{j=i}^{n-1} \frac{a_j}{j!} \cdot \frac{n^{j-i}}{(j-i)!}$
- Bell 數 (有  $n$  個人, 把他們拆組的方法總數)  
 $B_0 = 1$   
 $B_n = \sum_{k=0}^n s(n, k)$  (second - stirling)  
 $B_{n+1} = \sum_{k=0}^n \binom{n}{k} B_k$
- Wilson's theorem  
 $(p-1)! \equiv -1 \pmod p$   
 $(p^q!)_p \equiv \begin{cases} 1, & (p=2) \wedge (q \geq 3), \\ -1, & \text{otherwise.} \end{cases} \pmod{p^q}$
- Fermat's little theorem  
 $a^p \equiv a \pmod p$
- Euler's theorem  
 $a^b \equiv \begin{cases} a^{b \bmod \varphi(m)}, & \gcd(a, m) = 1, \\ a^b, & \gcd(a, m) \neq 1, b < \varphi(m), \\ a^{(b \bmod \varphi(m)) + \varphi(m)}, & \gcd(a, m) \neq 1, b \geq \varphi(m). \end{cases} \pmod m$
- 環狀著色 (相鄰塗異色)  
 $(k-1)(-1)^n + (k-1)^n$

## 8 Stringology

### 8.1 Aho–Corasick AM [1f3003]

```
struct ACM {
    int idx = 0;
    vector<array<int, 26>> tr;
    vector<int> cnt, fail;

    void clear() {
        tr.resize(1, array<int, 26>{});
        cnt.resize(1, 0);
        fail.resize(1, 0);
    }
};
```

```

}

ACM() {
    clear();
}

int newnode() {
    tr.push_back(array<int, 26>{});
    cnt.push_back(0);
    fail.push_back(0);
    return ++idx;
}

void insert(string &s) {
    int u = 0;
    for (char c : s) {
        c -= 'a';
        if (tr[u][c] == 0) tr[u][c] = newnode();
        u = tr[u][c];
    }
    cnt[u]++;
}

void build() {
    queue<int> q;
    rep (i, 0, 26) if (tr[0][i]) q.push(tr[0][i]);
    while (!q.empty()) {
        int u = q.front(); q.pop();
        rep (i, 0, 26) {
            if (tr[u][i]) {
                fail[tr[u][i]] = tr[fail[u]][i];
                cnt[tr[u][i]] += cnt[fail[tr[u][i]]];
                q.push(tr[u][i]);
            } else {
                tr[u][i] = tr[fail[u]][i];
            }
        }
    }
}

int query(string &s) {
    int u = 0, res = 0;
    for (char c : s) {
        c -= 'a';
        u = tr[u][c];
        res += cnt[u];
    }
    return res;
}
};

```

## 8.2 Double String [1cdb3b]

```

// need zvalue
int ans = 0;
auto dc = [&](auto self, string cur) -> void {
    int m = cur.size();
    if (m <= 1) return;
    string _s = cur.substr(0, m / 2), _t = cur.substr(m / 2, m);
    self(self, _s);
    self(self, _t);
    rep (T, 0, 2) {
        int m1 = _s.size(), m2 = _t.size();
        string s = _t + "$" + _s, t = _s;
        reverse(all(t));
        zvalue z1(s), z2(t);
        auto get_z = [&](zvalue &z, int x) -> int {
            if (0 <= x && x < z.z.size()) return z[x];
            return 0;
        };
        rep (i, 0, m1) if (_s[i] == _t[0]) {
            int len = m1 - i;
            int L = m1 - min(get_z(z2, m1 - i), len - 1);
            R = get_z(z1, m2 + 1 + i);
            if (T == 0) R = min(R, len - 1);
            R = i + R;
            ans += max(0, R - L + 1);
        }
        swap(_s, _t);
        reverse(all(_s));
        reverse(all(_t));
    }
};
dc(dc, str);

```

## 8.3 Lyndon Factorization [822807]

```

// partition s = w[0] + w[1] + ... + w[k-1],
// w[0] >= w[1] >= ... >= w[k-1]
// each w[i] strictly smaller than all its suffix
// min rotate: last < n of duval_min(s + s)
// max rotate: last < n of duval_max(s + s)
// min suffix: last of duval_min(s)
// max suffix: last of duval_max(s + -1)
vector<int> duval(const auto &s) {
    int n = s.size(), i = 0;
    vector<int> pos;
    while (i < n) {
        int j = i + 1, k = i;
        while (j < n and s[k] <= s[j]) { // >=
            if (s[k] < s[j]) k = i; // >
            else k++;
            j++;
        }
        while (i <= k) {
            pos.push_back(i);
            i += j - k;
        }
    }
    pos.push_back(n);
    return pos;
}

```

## 8.4 Manacher [ad2217]

```

/* center i: radius z[i * 2 + 1] / 2
   center i, i + 1: radius z[i * 2 + 2] / 2
   both aba, abba have radius 2 */
vector<int> manacher(const string &tmp) { // 0-based
    string s = "%";
    int l = 0, r = 0;
    for (char c : tmp) s += c, s += '%';
    vector<int> z(ssize(s));
    for (int i = 0; i < ssize(s); i++) {
        z[i] = r > i ? min(z[2 * l - i], r - i) : 1;
        while (i - z[i] >= 0 && i + z[i] < ssize(s) && s[i - z[i]]
            == s[i + z[i]])
            ++z[i];
        if (z[i] + i > r) r = z[i] + i, l = i;
    }
    return z;
}

```

## 8.5 SA-IS [72a941, a9701f]

```

auto sais(const auto &s) {
    const int n = (int)s.size(), z = ranges::max(s) + 1;
    if (n == 1) return vector{0LL};
    vector<int> c(z); for (int x : s) ++c[x];
    partial_sum(all(c), begin(c));
    vector<int> sa(n); auto I = views::iota(0, n);
    vector<bool> t(n); t[n - 1] = true;
    for (int i = n - 2; i >= 0; i--)
        t[i] = (s[i] == s[i + 1] ? t[i + 1] : s[i] < s[i + 1]);
    auto is_lms = views::filter([&t](int x) {
        return x && t[x] & !t[x - 1];
    });
    auto induce = [&] {
        for (auto x = c; int y : sa)
            if (y-- and !t[y]) sa[x[s[y] - 1]++] = y;
        for (auto x = c; int y : sa | views::reverse())
            if (y-- and t[y]) sa[--x[s[y]]] = y;
    };
    vector<int> lms, q(n); lms.reserve(n);
    for (auto x = c; int i : I | is_lms) {
        q[i] = int(lms.size());
        lms.push_back(sa[--x[s[i]]] = i);
    }
    induce(); vector<int> ns(lms.size());
    for (int j = -1, nz = 0; int i : sa | is_lms) {
        if (j >= 0) {
            int len = min({n - i, n - j, lms[q[i] + 1] - i});
            ns[q[i]] = nz += lexicographical_compare(
                s.begin() + j, s.begin() + j + len,
                s.begin() + i, s.begin() + i + len
            );
        }
        j = i;
    }
    ranges::fill(sa, 0); auto nsa = sais(ns);
}

```

```

for (auto x = c; int y : ns | views::reverse)
    y = lms[y], sa[--x[s[y]]] = y;
return induce(), sa;
} // 1
// sa[i]: sa[i]-th suffix is the
// i-th lexicographically smallest suffix.
// lcp[i]: LCP of suffix sa[i] and suffix sa[i + 1].
struct Suffix {
    int n;
    vector<int> sa, rk, lcp;
    Suffix(const auto &s) : n(s.size()),
        lcp(n - 1), rk(n) {
        vector<int> t(n + 1); // t[n] = 0
        copy(all(s), t.begin()); // s shouldn't contain 0
        sa = sais(t); sa.erase(sa.begin());
        for (int i = 0; i < n; i++) rk[sa[i]] = i;
        for (int i = 0, h = 0; i < n; i++) {
            if (!rk[i]) { h = 0; continue; }
            for (int j = sa[rk[i] - 1];
                i + h < n and j + h < n
                and s[i + h] == s[j + h];) ++h;
            lcp[rk[i] - 1] = h ? h - 1 : 0;
        }
    }
}; // 2

```

## 8.6 Suffix Array [5455bf]

```

struct SA {
    int n;
    std::vector<int> sa, rk;

    SA(std::string s) {
        n = s.size();
        sa.resize(n);
        rk.resize(n);
        std::iota(all(sa), 0);
        std::sort(all(sa), [&](int a, int b) {
            return s[a] < s[b];
        });
        rk[sa[0]] = 0;
        for (int i = 1; i < n; i++) {
            rk[sa[i]] = rk[sa[i - 1]] + (s[sa[i]] != s[sa[i - 1]]);
        }
        int k = 1;
        std::vector<int> tmp, cnt(n);
        tmp.reserve(n);
        while (rk[sa[n - 1]] < n - 1) {
            tmp.clear();
            for (int i = 0; i < k; i++) {
                tmp.push_back(n - k + i);
            }
            for (auto i : sa) if (i >= k) {
                tmp.push_back(i - k);
            }
            std::fill(all(cnt), 0);
            for (int i = 0; i < n; i++) {
                cnt[rk[i]]++;
            }
            for (int i = 1; i < n; i++) {
                cnt[i] += cnt[i - 1];
            }
            for (int i = n - 1; i >= 0; i--) {
                sa[--cnt[rk[tmp[i]]]] = tmp[i];
            }
            std::swap(rk, tmp);
            rk[sa[0]] = 0;
            for (int i = 1; i < n; i++) {
                rk[sa[i]] = rk[sa[i - 1]] + (tmp[sa[i - 1]] < tmp[sa[i]
            ] ||
                sa[i - 1] + k == n || tmp[sa[i - 1]] + k < tmp[sa[i]
                + k]);
            }
            k *= 2;
        }
    }
};

```

## 8.7 SuffixAutomaton [c59c1d]

```

struct SAM {
    int ch[2 * N][C], len[2 * N], link[2 * N], pos[2 * N], cnt[2
        * N], _id;
    // node -> strings with the same endpos set
    // length in range [len(link) + 1, len]

```

```

// node's endpos set -> pos in the subtree of node
// link -> longest suffix with different endpos set
// len -> longest suffix
// pos -> end position
// cnt -> size of endpos set
SAM () { reset(); }
int newnode() {
    fill_n(ch[_id], C, 0);
    len[_id] = link[_id] = pos[_id] = cnt[_id] = 0;
    return _id++;
}
void build(string s) {
    int lst = 0;
    for (int i = 0; i < s.size(); ++i) {
        char c = s[i];
        int cur = newnode();
        len[cur] = len[lst] + 1, pos[cur] = i + 1;
        int p = lst;
        while (~p && !ch[p][c - 'a'])
            ch[p][c - 'a'] = cur, p = link[p];
        if (p == -1) link[cur] = 0;
        else {
            int q = ch[p][c - 'a'];
            if (len[p] + 1 == len[q]) {
                link[cur] = q;
            } else {
                int nxt = newnode();
                len[nxt] = len[p] + 1, link[nxt] = link[q];
                pos[nxt] = 0;
                for (int j = 0; j < C; ++j)
                    ch[nxt][j] = ch[q][j];
                while (~p && ch[p][c - 'a'] == q)
                    ch[p][c - 'a'] = nxt, p = link[p];
                link[q] = link[cur] = nxt;
            }
        }
        cnt[cur]++, lst = cur;
    }
}
// void build_count() {
//     vector<int> p(_id);
//     iota(all(p), 0);
//     sort(all(p),
//         [&](int i, int j) {return len[i] > len[j];});
//     for (int i = 0; i < _id; ++i) if (~link[p[i]])
//         cnt[link[p[i]]] += cnt[p[i]];
// }
void reset() { _id = 0, newnode(), link[0] = -1; }
} sam;

```

## 8.8 Z-value [a39b66]

```

struct zvalue {
    vector<int> z;
    int operator[] (const int &x) const {
        return z[x];
    }
    zvalue(string s) {
        int n = s.size();
        z.resize(n);
        z[0] = 0;
        for (int i = 1, l = 1, r = 0; i < n; i++) {
            z[i] = min(z[i - l], max<int>(0, r - i));
            while (i + z[i] < n && s[i + z[i]] == s[z[i]]) z[i]++;
            if (i + z[i] > r) l = i, r = i + z[i];
        }
    }
};

```





