



# Introduction to Go

Kevin W. Gisi

Twin Cities Code Camp 8—April 10, 2010

## Summary

Go is a brand-spanking-new systems language that Google released in November, 2009. Every wonder how awesome C would be if it was garbage-collected, concurrent, and didn't take a few weeks to compile? Wake up; it's here! We'll take a look at this new language that steals some of the dynamic flexibility of Python and Ruby, the performance of C, and a compile time that you'll miss if you blink.

## Hello, world

```
package main

import "fmt"

func    () {
    fmt.Printf("Hello, world\n")
}
```

code/hello\_world.go

## Why Go?

- It's a systems language
- It's fun, like dynamic languages

## We Already Have a Systems Language!

Like C

```
void    (int m, int t, int
c) {
    ((t / m) <= 1) ?
primes(m,t+1,c) : !(t % m) ?
primes(m,t+1, t % m) :
    ((t % m)==(t / m) && !c) ?
    (printf("%d\t", (t / m)),
primes(m,t+1,c)) :
    ((t % m)> 1 && (t % m) < (t /
m)) ? primes(m,t+1,c + !((t /
m) % (t % m))) :
    (t < m * m) ? primes(m,t+1,c)
: 0;
}
```

code/c.c

## We Already Have Fun Languages!


```
module
    def    (    *    )
        args.    ? cmd.    :
    "#{cmd} #{args.    (" ")}"
    end
end

puts this is terrible code


x = [1,2,3]
(x.    ('+'))
```

code/ruby.rb

## Fun Languages are Slow at Runtime



## Fast Languages are Slow to Compile



## Alternative: Go

Go is slow at runtime AND at compile time!

- 1/2—1/3 LOC for C++ benchmarks
- 1—1/16 of the speed (libraries?)


Priorities:

- Compile time
- Performance
- Readability

---

## It Runs on Linux

---



---

## It Runs on OS X!

---



---

## It Runs on Virtual Machines!

---



---

## Specifications

---

- Compiled
- Imperative, structured
- Concurrent
- Strongly typed (explicit or inferred)

---

## Variables & Types

---

- int, float
- int8, int32, float64
- uint, ufloat
- string
- struct

---

## Variables: Pointers and Arrays

---

### Pointers

- Use them for reference
- DON'T manipulate them!

### Arrays

```
var arrayOfInt [10]int
```

code/variables.go

## Variables: Slices and Maps

### Slices

- "Pointers" for arrays
- Contains pointers to each object in a range of the array
- Used for passing array values by reference

### Maps

```
var m map = map[string] int{}
m["price"] = 5
```

code/variables.go

## Variable Declaration

```
// Declare a variable
var s string = ""

// Go infers the type
var s2 = ""

// Syntactic shorthand -
// initializing declaration
s3 := ""
```

code/variables.go

## Variable Allocation

### new()

- allocates heap space
- zero-initializes the space
- returns the address

### make()

- allocates heap space
- creates the object (and underlying data structure)
- returns the value

## Go ≠ C

- Semicolons optional (implied)
- Curly braces MUST start on the same line
- No parentheses in `ifs` and `fors`
- Garbage collected
- Arrays aren't pointers

## Functions

- CamelCase - public
- camelCase - package-level
- Pass by value
- Multiple return values

## What? Multiple Return Values?!

```
func      () (int, string) {
    return 5, "thanks for asking!"
}
```

code/functions.go

How do we access them?

```
x, message := gimmeFive()
```

code/functions.go

## Why Multiple Return Values?

```

    if text, err :=
readFile('foo.txt'); err == nil
{
    // Read the file
} else {
    // Handle the error
}

    for key, value := range
my_map {

    }

    // ...or
    for _, value := range my_map
{ // Discard the first returned
value

    }

```

code/functions.go

## Named Results

```

func      () (value int, err
string) {
    // value and err are set to
nil
    value = 5
    return // implicitly returns
5, nil
}

```

code/functions.go

## Methods

Write functions that operate on particular data

```

type Mongoose int

    func (          ) Pluck()
string {
    return "The mongoose was
plucked"
}

```

code/functions.go

## Interfaces

- Similar to Java
- Definition of acceptable types
- Types don't "implement" anything

## Interfaces

```

type Duck interface {
    Quack()
    Waddle()
    Swim()
}

func (i int)      () {}
func (i int)      () {}
func (i int)      () {}

func (d Duck)      () {} //
We can pass this an int

```

code/interfaces.go

## Interface Embedding

```
type Spider interface {
    CreateWebs()
}

type Man interface {
    MissUncleBen()
}

type SpiderMan interface {
    Spider
    Man
}

func (m SpiderMan)
    () {} // Target
must CreateWebs() and
MissUncleBen()
```

code/interfaces.go

## Struct Embedding

```
struct Spider interface {
    CreateWebs()
}

struct Man interface {
    MissUncleBen()
}

struct SpiderMan interface {
    Spider
    Man
}

func (m Man)
    () {} //
Can pass a Man or a SpiderMan
```

code/interfaces.go

## Concurrency



## Goroutines

- NOT threads
- Independent code
- Communication over shared memory

## Threads

- Exist
- Span across multiple cores
- Go load-balances them
- Don't worry about it

## Goroutine Example


```
go gimmeFive()

go func() {
    time.Sleep(5)
    fmt.Println("Computer over.
Virus = very yes")
}()
```

code/concurrency.go

- No access to spawned goroutines
- No thread.join equivalent

## Channels



- Like Unix pipes
- Communicate across goroutines
- Optionally blocking/non-blocking

## Channel Example: Communication

```
func      () {
    output := make(chan string)
    go log(output)
    for true {
        output <- "Hey. Hey. Listen"
    }
}

func      (                ) {
    for true {
        data := <- input
        fmt.Println(data)
    }
}
```

code/concurrency.go

## Channel Example: Asynchronous

```
func      () {
    output := make(chan string,
10)
    go log(output)
    output <- "Hey. Hey. Listen"
    // Chatter terminates almost
immediately
}
```

code/concurrency.go



---

## Channel Example: Semaphore

---

```
func      (      ) {  
    for true {  
        <- input  
        // Do something  
        input <- 1  
    }  
}
```

[code/concurrency.go](#)

---

## Channel Example: Thread.join

---

```
func      () {  
    gui_dead := make(chan int)  
    go gui()  
  
    // Do some stuff  
    <- gui_dead  
}
```

[code/concurrency.go](#)

---

## Packages and Libraries

---

- os
- net
- websocket
- math
- strings
- bufio
- encoding
- json
- testing
- regexp

---

## What Should You Use It For?

---

- Not yet ready for production use
- Systems work
- High performance
- Fun!

Help develop libraries you want to see!

---

## Additional Information

---

- <http://golang.org>
- Go Wiki
- Google Tech Talk

---

## Questions? Comments?

---



Thank you!

Kevin W. Gisi

<kevin@kevingisi.com>