

Bashmatic Usage Docs (v2.7.0)

Table of Contents

File <code>lib/yarn.sh</code>	6
<code>yarn_install()</code>	6
<code>yarn_sha()</code>	6
File <code>lib/dropbox.sh</code>	6
function <code>dropbox.ignore {</code>	6
See also.....	6
<code>dropbox.unignore()</code>	6
See also.....	6
File <code>lib/file.sh</code>	6
<code>file.temp()</code>	7
<code>file.normalize-files()</code>	7
Example.....	7
<code>file.first-is-newer-than-second()</code>	7
<code>file.ask.if-exists()</code>	7
<code>file.install-with-backup()</code>	7
Example.....	7
Arguments.....	7
File <code>lib/pids.sh</code>	7
<code>pids.stop-by-listen-tcp-ports()</code>	8
Example.....	8
<code>pid.stop-if-listening-on-port()</code>	8
Example.....	8
File <code>lib/bashit.sh</code>	8
<code>bashit-prompt-terraform()</code>	8
<code>bashit-install()</code>	8
File <code>lib/array.sh</code>	8
<code>array.has-element()</code>	9
Example.....	9
<code>array.includes()</code>	9
<code>array.join()</code>	9
Example.....	9
Arguments.....	9
<code>array.sort()</code>	9
Example.....	10
<code>array.sort-numeric()</code>	10
Example.....	10

array.min()	10
Example	10
array.force-range()	10
Example	10
array.max()	10
Example	11
array.uniq()	11
Example	11
array.from.command()	11
Example	11
File lib/asciidoc.sh	11
asciidoc.rouge-themes()	11
File lib/output-utils.sh	11
is-dbg()	12
dbg()	12
File lib/audio.sh	12
lib/audio.sh	12
File lib/brew.sh	14
package.is-installed()	14
File lib/output.sh	14
section()	14
Arguments	14
File lib/usage.sh	14
usage-widget()	14
Example	14
File lib/file-helpers.sh	15
.file.make_executable()	16
File lib/video.sh	16
lib/video.sh	16
File lib/path.sh	17
path.strip-slash()	18
path.dirs()	18
Arguments	18
path.dirs.size()	18
path.dirs.uniq()	18
path.dirs.delete()	18
Arguments	18
path.uniq()	18
PATH.uniqify()	18
path.append()	18
path.prepend()	19

path.mutate.uniq()	19
path.mutate.delete()	19
path.mutate.append()	19
path.mutate.prepend()	19
PATH_add()	19
path.absolute()	19
File lib/osx.sh	19
osx.app.is-installed()	19
Example	19
Arguments	20
Exit codes	20
File lib/db.sh	20
db.config.parse()	20
Example	20
db.psql.connect()	21
Example	21
db.psql.connect.just-data()	21
Example	21
db.psql.connect.table-settings-set()	21
Example	21
db.psql.db-settings()	21
Example	21
db.psql.connect.db-settings-pretty()	21
Example	21
Arguments	22
db.psql.connect.db-settings-toml()	22
Example	22
Arguments	22
db.actions.run-multiple()	22
Example	22
db.actions.pga()	22
File lib/shdoc.sh	22
lib/shdoc.sh	22
File lib/git.sh	23
git.cfgu()	23
Example	23
git.open()	23
Example	23
Arguments	23
File lib/package.sh	23
package.ensure.is-installed()	24

package.ensure.command-available()	24
Example	24
File lib/time.sh	24
time.with-duration.start()	24
Example	24
time.a-command()	24
Arguments	24
File lib/shasum.sh	25
shasum.set-command()	25
shasum.set-algo()	25
Example	25
shasum.sha()	25
shasum.sha-only()	25
shasum.sha-only-stdin()	25
shasum.to-hash()	26
Example	26
shasum.all-files()	26
Example	26
shasum.all-files-in-dir()	26
Example	26
sha()	26
File lib/runtime-config.sh	26
is.dry-run.on()	27
Example	27
is.dry-run.off()	27
Example	27
set.dry-run.on()	27
Example	27
set.dry-run.off()	27
Example	27
File lib/color.sh	27
color.current-background()	28
File lib/pg.sh	28
pg.is-running()	28
pg.running.server-binaries()	28
pg.running.data-dirs()	28
pg.server-in-path.version()	28
File lib/dir.sh	28
dir.short-home()	28
File lib/config.sh	28
config.get-format()	29

<code>config.set-file()</code>	29
<code>config.get-file()</code>	29
<code>config.dig()</code>	29
Arguments	29
<code>config.dig.pretty()</code>	29
File <code>lib/flatten.sh</code>	29
<code>flatten-file()</code>	29
Example	29
File <code>lib/nvm.sh</code>	30
<code>nvm.is-valid-dir()</code>	30
<code>nvm.detect()</code>	30
<code>nvm.install()</code>	30
<code>nvm.load()</code>	30
File <code>lib/net.sh</code>	30
<code>net.is-host-port-protocol-open()</code>	31
Arguments	31
File <code>lib/is.sh</code>	31
<code>__is.validation.error()</code>	31
Arguments	31
Exit codes	31
<code>is-validations()</code>	31
<code>__is.validation.ignore-error()</code>	31
<code>__is.validation.report-error()</code>	32
<code>whenever()</code>	32
Example	32
File <code>lib/util.sh</code>	32
File <code>lib/runtime.sh</code>	32
<code>run.inspect-vars()</code>	32
File <code>lib/pdf.sh</code>	32
Bashmatic Utilities for PDF file handling	32
File <code>bin/install-direnv</code>	33
<code>direnv.register()</code>	33
File <code>bin/regen-usage-docs</code>	33
File <code>bin/pdf-reduce</code>	33
<code>pdf.do.shrink()</code>	33
File <code>bin/scheck</code>	33
<code>manual-install()</code>	34
Copyright & License	34

NOTICE: [shdoc](#) documentation is auto-extracted from the Bashmatic Sources.

File `lib/yarn.sh`

- `yarn_install()`
- `yarn_sha()`

`yarn_install()`

Installs YARN via npm if not found; then runs yarn install Note that yarn install is skipped if package.json and yarn.lock haven't changed since the last run of yarn install.

`yarn_sha()`

Prints to STDOUT the SHA based on package.json and yarn.lock

File `lib/dropbox.sh`

- `function dropbox.ignore {`
- `dropbox.unignore()`

`function dropbox.ignore {`

Set file to be ignored by Dropbox

See also

- <https://help.dropbox.com/files-folders/restore-delete/ignored-files>

`dropbox.unignore()`

Set a file or directorhy to be ignored by Dropbox

See also

- <https://help.dropbox.com/files-folders/restore-delete/ignored-files>
-

File `lib/file.sh`

- `file.temp()`
 - `file.normalize-files()`
 - `file.first-is-newer-than-second()`
 - `file.ask.if-exists()`
-

- [file.install-with-backup\(\)](#)

file.temp()

Creates a temporary file and returns it as STDOUT shellcheck disable=SC2120

file.normalize-files()

This function will rename all files passed to it as follows: spaces are replaced by dashes, non printable characters are removed, and the filename is lower cased.

Example

```
file.normalize-files "My Word Document.docx"  
# my-word-document.docx
```

file.first-is-newer-than-second()

A super verbose shortcut to `[[file -nt file2]]`

file.ask.if-exists()

Ask the user whether to overwrite the file

file.install-with-backup()

Installs a given file into a provided destination, while making a copy of the destination if it already exists.

Example

```
file.install-with-backup conf/.psqlrc ~/.psqlrc backup-strategy-function
```

Arguments

- @arg1 File to backup
- @arg2 Destination
- @arg3 [optional] Shortname of the optional backup strategy: 'bak' or 'folder'.

File lib/pids.sh

- [pids.stop-by-listen-tcp-ports\(\)](#)
- [pid.stop-if-listening-on-port\(\)](#)

pid.stop-by-listen-tcp-ports()

Finds any PID listening on one of the provided ports and stop them.

Example

```
pid.stop-by-listen-tcp-ports 4232 9578 "${PORT}"
```

pid.stop-if-listening-on-port()

Finds any PID listening the one port and an optional protocol (tcp/udp)

Example

```
pid.stop-if-listening-on-port 3000 tcp  
pid.stop-if-listening-on-port 8126 udp
```

File lib/bashit.sh

- [bashit-prompt-terraform\(\)](#)
- [bashit-install\(\)](#)

bashit-prompt-terraform()

Possible Bash It Powerline Prompt Modules

aws_profile battery clock command_number cwd dirstack gcloud go history_number hostname
in_toolbox in_vim k8s_context last_status node python_venv ruby scm shlvl terraform user_info wd

bashit-install()

Installs Bash-It Framework

File lib/array.sh

- [array.has-element\(\)](#)
- [array.includes\(\)](#)
- [array.join\(\)](#)
- [array.sort\(\)](#)
- [array.sort-numeric\(\)](#)

- `array.min()`
- `array.force-range()`
- `array.max()`
- `array.uniq()`
- `array.from.command()`

`array.has-element()`

Returns "true" if the first argument is a member of the array passed as the second argument:

Example

```
$ declare -a array=("a string" test2000 moo)
if [[ $(array.has-element "a string" "${array[@]}") == "true" ]]; then
    ...
fi
```

`array.includes()`

Similar to `array.has-elements`, but does not print anything, just returns 0 if includes, 1 if not.

`array.join()`

Joins a given array with a custom string.

Example

```
$ declare -a array=(one two three)
$ array.join "," "${array[@]}"
$ array.join " -> " true "${array[@]}"
-> one
-> two
-> three
```

Arguments

- `@arg1`
- `@arg2`
- `@arg3 .`

`array.sort()`

Sorts the array alphanumerically and prints it to STDOUT

Example

```
declare -a unsorted=(hello begin again again)
local sorted="$(array.sort "${unsorted[@]}")"
```

array.sort-numeric()

Sorts the array numerically and prints it to STDOUT

Example

```
declare -a unsorted=(1 2 34 45 6)
local sorted="$(array.sort-numeric "${unsorted[@]}")"
```

array.min()

Returns a minimum integer from an array. Non-numeric elements are ignored and skipped over. Negative numbers are supported, but non-integers are not.

Example

```
$ declare -a array=(10 20 30 -5 5)
$ array.min "," "${array[@]}"
-5
```

array.force-range()

Given a numeric argument, and an additional array of numbers, determines the min/max range of the array and prints out the number if it's within the range of array's min and max. Otherwise prints out either min or max.

Example

```
$ array.force-range 26 0 100
# => 26
$ array.force-range 26 60 100
# => 60
```

array.max()

Returns a maximum integer from an array. Non-numeric elements are ignored and skipped over. Negative numbers are supported, but non-integers are not.

Example

```
$ declare -a array=(10 20 30 -5 5)
$ array.min "," "${array[@]}"
30
```

array.uniq()

Sorts and uniqs the array and prints it to STDOUT

Example

```
declare -a unsorted=(hello hello hello goodbye)
local uniqed="$(array.sort-numeric "${unsorted[@]}")"
```

array.from.command()

Creates an array variable, where each element is a line from a command output, which includes any spaces.

Example

```
array.from.command music_files "find . -type f -name '*.mp3'"
echo "You have ${#music[@]} music files."
```

File **lib/asciidoc.sh**

Provides helper functions for dealing with asciidoc format.

- [asciidoc.rouge-themes\(\)](#)

asciidoc.rouge-themes()

Installs gem "rouge" and prints all available themes

File **lib/output-utils.sh**

- [is-dbg\(\)](#)
- [dbg\(\)](#)

is-dbg()

Checks if we have debug mode enabled

dbg()

Local debugging helper, activate it with `export BASHMATIC_DEBUG=1`

File `lib/audio.sh`

lib/audio.sh

Audio conversions routines.

- `audio.file.frequency()`
- `audio.make.mp3s()`
- `audio.make.mp3()`
- `audio.file.mp3-to-wav()`
- `audio.dir.mp3-to-wav()`
- `.audio.karaoke.format()`
- `audio.dir.rename-wavs()`
- `audio.dir.rename-karaoke-wavs()`

audio.file.frequency()

Given a music audio file, determine its frequency.

audio.make.mp3s()

Given a folder of MP3 files, and an optional KHz specification, perform a sequential conversion from AIF/WAV format to MP3.

Example

```
audio.wav-to-mp3 [ file.wav | file.aif | file.aiff ] [ file.mp3 ]
```

audio.make.mp3()

Converts one AIF/WAV file to high-rez 320 Kbps MP3

audio.file.mp3-to-wav()

Decodes a folder with MP3 files back into WAV

audio.dir.mp3-to-wav()

assume a folder with a bunch of MP3s in subfolders

Example

```
same folder structure but under /Volumes/SDCARD.
```

.audio.karaoke.format()

Rename function for one filename to another. This particular function deals with files of this format: Downloaded from karaoke-version.com:

Example

```
.audio.karaoke.format  
"Michael_Jackson_Billie_Jean(Drum_Backing_Track_(Drum_only))_248921.wav"  
=> michael_jackson_billie_jean—drum_backing_track-drum_only.wav
```

audio.dir.rename-wavs()

This function receives a format specification, and an optional directory as a second argument. Format specification is meant to map to a function `.audio.<format>.format` that's used as follows: `.audio.<format>.format "file-name" => "new file name"</format></format>`

Example

```
audio.dir.rename-wavs karaoke ~/Karaoke
```

audio.dir.rename-karaoke-wavs()

Renames wav files in the current folder (or the folder passed as an argument, based on the naming scheme downloaded from karaoke-version.com

Example

```
audio.dir.rename-karaoke-wavs "~/Karaoke"
```

File `lib/brew.sh`

- `package.is-installed()`

`package.is-installed()`

For each passed argument checks if it's installed.

File `lib/output.sh`

- `section()`

`section()`

Prints a "arrow-like" line using powerline characters

Arguments

- `@arg1` Width (optional) — only interpreted as width if the first argument is a number.
 - `@args` Text to print
-

File `lib/usage.sh`

- `usage-widget()`

`usage-widget()`

This is a massive hack and I am ashamed to have written it. With that out of the way, here we go. This command generates a pretty usage box for a tool or another command.

Example

```

usage-widget [-]<width> \                                # box width. If it starts with "-"
forces cache wipe.                                     #
    "command [flags] <arg1 ... >" \                    # <-- USAGE
    "This command is beyond description." \            # <-- DESCRIPTION
    "[@]string" \                                       # <-- This and subsequent lines may
optionally start with "@" symbol,                        #
    "[@]string" \                                       #      which will turn them into sub-
headings:                                                #
    "[@]string" \
    "[@]string"
usage-widget 90 \
    "command [flags] <arg1 ... >" \
    "This command is beyond description." \
    "@examples" \
    "Some examples will follow" \
    "And others won't."

```

```

|  USAGE:          command [flags] <arg1 ... >
|
|
|

```

```

|  DESCRIPTION:    This command is beyond description.
|
|
|

```

```

|  EXAMPLES:
|
|
|

```

```

|          Some examples will follow
|
|

```

```

|          And others won't.
|
|

```

File `lib/file-helpers.sh`

- `.file.make_executable()`

.file.make_executable()

Makes a file executable but only if it already contains a "bang" line at the top.

File lib/video.sh

lib/video.sh

Video conversions routines.

- [.video.install-deps\(\)](#)
- [.video.convert.compress-shrinkwrap\(\)](#)
- [.video.convert.compress-11\(\)](#)
- [.video.convert.compress-12\(\)](#)
- [.video.convert.compress-13\(\)](#)
- [.video.convert.compress-21\(\)](#)
- [.video.convert.compress-22\(\)](#)
- [.video.convert.compress-23\(\)](#)
- [.video.convert.compress-3\(\)](#)
- [video.convert.compress\(\)](#)

.video.install-deps()

Installs ffmpeg

.video.convert.compress-shrinkwrap()

Named after the author of a similar tool that does this:

.video.convert.compress-11()

Given two arguments (from), (to), performs a video recompression

.video.convert.compress-12()

Given two arguments (from), (to), performs a video recompression

.video.convert.compress-13()

Given two arguments (from), (to), performs a video recompression

.video.convert.compress-21()

Given two arguments (from), (to), performs a video recompression

.video.convert.compress-22()

Given two arguments (from), (to), performs a video recompression

.video.convert.compress-23()

Given two arguments (from), (to), performs a video recompression

.video.convert.compress-3()

Given two arguments (from), (to), performs a video recompression

video.convert.compress()

Given two arguments (from), (to), performs a video recompression according to the algorithm in the second argument.

Example

```
video.convert.compress bigfile.mov 13
```

File lib/path.sh

Utilities for managing the \$PATH variable

- [path.strip-slash\(\)](#)
- [path.dirs\(\)](#)
- [path.dirs.size\(\)](#)
- [path.dirs.uniq\(\)](#)
- [path.dirs.delete\(\)](#)
- [path.uniq\(\)](#)
- [PATH.uniqify\(\)](#)
- [path.append\(\)](#)
- [path.prepend\(\)](#)
- [path.mutate.uniq\(\)](#)
- [path.mutate.delete\(\)](#)
- [path.mutate.append\(\)](#)

- `path.mutate.prepend()`
- `PATH_add()`
- `path.absolute()`

`path.strip-slash()`

Removes a trailing slash from an argument path

`path.dirs()`

Prints a new-line separated list of paths in PATH

Arguments

- @arg1 A path to split, defaults to \$PATH

`path.dirs.size()`

Prints the total number of paths in the path argument, which defaults to \$PATH

`path.dirs.uniq()`

Prints all folders in \$PATH, one per line, removing any duplicates, Does not mutate the \$PATH

`path.dirs.delete()`

Deletes any number of folders from the PATH passed as the first string argument (defaults to \$PATH). Does not mutate the \$PATH, just prints the result to STDOUT

Arguments

- @arg1 String representation of a PATH, eg `"/bin:/usr/bin:/usr/local/bin"`
- @arg2 An array of paths to be removed from the PATH

`path.uniq()`

Removes duplicates from the \$PATH (or argument) and prints the results in the PATH format (column-joined). DOES NOT mutate the actual \$PATH

`PATH.uniqify()`

Using sed and tr uniq the PATH without re-sorting it.

`path.append()`

Appends a new directory to the \$PATH and prints the result to STDOUT, Does NOT mutate the actual \$PATH

path.prepend()

Prepends a new directory to the \$PATH and prints to STDOUT, If one of the arguments already in the PATH its moved to the front. DOES NOT mutate the actual \$PATH

path.mutate.uniq()

Removes any duplicates from \$PATH and exports it.

path.mutate.delete()

Deletes paths from the PATH provided on the command line

path.mutate.append()

Appends valid directories to those in the PATH, and exports the new value of the PATH

path.mutate.prepend()

Prepends valid directories to those in the PATH, and exports the new value of the PATH

PATH_add()

This function exists within direnv, but since we are sourcing in .envrc we need to have this defined to avoid errors.

path.absolute()

Returns an absolute version of a given path

File lib/osx.sh

OSX Specific Helpers and Utilities

- [osx.app.is-installed\(\)](#)

osx.app.is-installed()

Checks if a given parameter matches any of the installed applications under /Applications and ~/Applications

By the default prints the matched application. Pass **-q** as a second argument to disable output.

Example

```
❏ osx.app.is-installed safari
Safari.app
❏ osx.app.is-installed safari -q && echo installed
installed
❏ osx.app.is-installed microsoft -c
6
```

Arguments

- **\$1** (a): string value to match (case insentively) for an app name
- **\$2..** additional arguments to the last invocation of **grep**

Exit codes

- **0**: if match was found
- **1**: if not

File **lib/db.sh**

- **db.config.parse()**
- **db.psql.connect()**
- **db.psql.connect.just-data()**
- **db.psql.connect.table-settings-set()**
- **db.psql.db-settings()**
- **db.psql.connect.db-settings-pretty()**
- **db.psql.connect.db-settings-toml()**
- **db.actions.run-multiple()**
- **db.actions.pga()**

db.config.parse()

Returns a space-separated values of db host, db name, username and password

Example

```
db.config.set-file ~/.db/database.yml
db.config.parse development
#=> hostname dbname dbuser dbpass
declare -a params=( $(db.config.parse development) )
echo ${params[0]} # host
```

db.psql.connect()

Connect to one of the databases named in the YAML file, and optionally pass additional arguments to psql. Informational messages are sent to STDERR.

Example

```
db.psql.connect production
db.psql.connect production -c 'show all'
```

db.psql.connect.just-data()

Similar to the db.psql.connect, but outputs just the raw data with no headers.

Example

```
db.psql.connect.just-data production -c 'select datname from pg_database;'
```

db.psql.connect.table-settings-set()

Set per-table settings, such as autovacuum, eg:

Example

```
db.psql.connect.table-settings-set prod users autovacuum_analyze_threshold 1000000
db.psql.connect.table-settings-set prod users autovacuum_analyze_scale_factor 0
```

db.psql.db-settings()

Print out PostgreSQL settings for a connection specified by args

Example

```
db.psql.db-settings -h localhost -U postgres appdb
```

db.psql.connect.db-settings-pretty()

Print out PostgreSQL settings for a named connection

Example

```
db.psql.connect.db-settings-pretty primary
```

Arguments

- @arg1 dbname database entry name in ~/.db/database.yml

db.psql.connect.db-settings-toml()

Print out PostgreSQL settings for a named connection using TOML/ini format.

Example

```
db.psql.connect.db-settings-toml primary > primary.ini
```

Arguments

- @arg1 dbname database entry name in ~/.db/database.yml

db.actions.run-multiple()

Executes multiple commands by passing them to psql each with -c flag. This allows, for instance, setting session values, and running commands such as VACUUM which can not run within an implicit transaction started when joining multiple statements with ";"

Example

```
$ db -q run my_database 'set default_statistics_target to 10; show
default_statistics_target; vacuum users'
ERROR: VACUUM cannot run inside a transaction block
```

db.actions.pga()

Installs (if needed) pg_activity and starts it up against the connection

File lib/shdoc.sh

lib/shdoc.sh

Helpers to install gawk and shdoc properly.0

see `${BASHMATIC_HOME}/lib/shdoc.md` for an example of how to use SHDOC. and also [project's github page](#).

- [gawk.install\(\)](#)

gawk.install()

Installs gawk into /usr/local/bin/gawk

File lib/git.sh

- [git.cfgu\(\)](#)
- [git.open\(\)](#)

git.cfgu()

Sets or gets user values from global gitconfig.

Example

```
git.cfgu email
git.cfgu email kigster@gmail.com
git.cfgu
```

git.open()

Reads the remote of a repo by name provided as an argument (or defaults to "origin") and opens it in the browser.

Example

```
git clone git@github.com:kigster/bashmatic.git
cd bashmatic
source init.sh
git.open
git.open origin # same thing
```

Arguments

- **\$1** (optional): name of the remote to open, defaults to "origin"
-

File lib/package.sh

- [package.ensure.is-installed\(\)](#)
- [package.ensure.command-available\(\)](#)

package.ensure.is-installed()

fr

package.ensure.command-available()

Example

```
In this example we skip installation if `gem` exists and in the PATH.  
Otherwise we install the package and retry, and return if not found
```

File lib/time.sh

- `time.with-duration.start()`
- `time.a-command()`

time.with-duration.start()

Starts a time for a given name space

Example

```
time.with-duration.start moofie  
# ... time passes  
time.with-duration.end   moofie 'Moofie is now this old: '  
# ... time passes  
time.with-duration.end   moofie 'Moofie is now very old: '  
time.with-duration.clear moofie
```

time.a-command()

This function receives a command to execute as an argument. The command is executed as 'eval "\$@"'; meanwhile the start/end times are measured, and the following string is printed at the end:
eg. "4 minutes 24.345 seconds"

Arguments

- @args Command to run

File lib/shasum.sh

SHA Functions

SHASUM related functions, that compute SHA for a single file, collection of files, or entire directories.

- [shasum.set-command\(\)](#)
- [shasum.set-algo\(\)](#)
- [shasum.sha\(\)](#)
- [shasum.sha-only\(\)](#)
- [shasum.sha-only-stdin\(\)](#)
- [shasum.to-hash\(\)](#)
- [shasum.all-files\(\)](#)
- [shasum.all-files-in-dir\(\)](#)
- [sha\(\)](#)

shasum.set-command()

Override the default SHA command and algorithm Default is shasum -a 256

shasum.set-algo()

Override the default SHA algorithm

Example

```
$ shasum.set-algo 256
```

shasum.sha()

Compute SHA for all given files, ignore STDERR NOTE: first few arguments will be passed to the shasum command, or whatever you set via shasum.set-command.

shasum.sha-only()

Print SHA ONLY removing the file components

shasum.sha-only-stdin()

Print SHA ONLY removing the file components

shasum.to-hash()

This function populates a pre-declare associative array with filenames mapped to their SHAs, but only in the current directory Call **dbg-on** to enable additional debugging info.

Example

```
$ declare -A file_shas
$ shasum.to-hash file_shas $(find . -type f -maxdepth 2)
$ echo "Total of ${#file_shas[@]} files in the hash"
```

shasum.all-files()

For a given array of files, sort them, take a SHA of each file, and return a single SHA finger-printing this set of files. # NOTE: the files are sorted prior to hashing, so the return SHA should ONLY change when files are either changed, or added/removed. Only computes SHA of the files provided, does not recurse into folders

Example

```
$ shasum.all-files *.cpp
```

shasum.all-files-in-dir()

For a given directory and an optional file pattern, use **find** to grab every single file (that matches optional pattern) and return a single SHA

Example

```
$ shasum.all-files-in-dir . '*.pdf'
cc35aad389e61942c75e111f1eddb634d74b4b1
```

sha()

sha256

File lib/runtime-config.sh

- [is.dry-run.on\(\)](#)
- [is.dry-run.off\(\)](#)
- [set.dry-run.on\(\)](#)

- [set.dry-run.off\(\)](#)

is.dry-run.on()

Returns 0 when dry-run flag was set, 1 otherwise.

Example

```
set.dry-run.on  
is.dry-run.on || rm -f ${temp}
```

is.dry-run.off()

Returns 0 when dry-run flag was set, 1 otherwise.

Example

```
set.dry-run.off  
is.dry-run.on || rm -f ${temp}
```

set.dry-run.on()

Returns 0 when dry-run flag was set, 1 otherwise.

Example

```
set.dry-run.on  
is.dry-run.on || run "ls -al"
```

set.dry-run.off()

Returns 1 when dry-run flag was set, 0 otherwise.

Example

```
set.dry-run.on  
is.dry-run.on || run "ls -al"
```

File [lib/color.sh](#)

- [color.current-background\(\)](#)

color.current-background()

Prints the background color of the terminal, assuming terminal responds to the escape sequence. More info: <https://stackoverflow.com/questions/2507337/how-to-determine-a-terminals-background-color>

File lib/pg.sh

- [pg.is-running\(\)](#)
- [pg.running.server-binaries\(\)](#)
- [pg.running.data-dirs\(\)](#)
- [pg.server-in-path.version\(\)](#)

pg.is-running()

Returns true if PostgreSQL is running locally

pg.running.server-binaries()

if one or more PostgreSQL instances is running locally, prints each server's binary postgres file path

pg.running.data-dirs()

For each running server prints the data directory

pg.server-in-path.version()

Grab the version from `postgres` binary in the PATH and remove fractional sub-version

File lib/dir.sh

- [dir.short-home\(\)](#)

dir.short-home()

Replaces the first part of the directory that matches `${HOME}` with `'~/`

File lib/config.sh

- [config.get-format\(\)](#)

- `config.set-file()`
- `config.get-file()`
- `config.dig()`
- `config.dig.pretty()`

`config.get-format()`

Get current format

`config.set-file()`

Set the default config file

`config.get-file()`

Get the file name

`config.dig()`

Reads the value from a two-level configuration hash

Arguments

- @arg1 hash key
- @arg2 hash sub-key

`config.dig.pretty()`

Uses `jq` utility to format JSON with color, supports partial

File `lib/flatten.sh`

- `flatten-file()`

`flatten-file()`

Given a long path to a file, possibly with spaces in cluded and a desintation as a second argument, generates a flat pathname and copies the first argument there.

Example

```
❯ tree -Q "33 Retro Synth/"
"33 Retro Synth/"
├── "001 Retro Synth - A Synth Primer.en.srt"
├── "001 Retro Synth - A Synth Primer.mp4"
├── "002 Retro Synth - Oscillator.en.srt"
└── "002 Retro Synth - Oscillator.mp4"
❯
flatten-file "33 Retro Synth/001 Retro Synth - A Synth Primer.mp4"
@arg1 -n | --dry-run (optional)
@arg2 source path
@arg3 dest paths
```

File **lib/nvm.sh**

- [nvm.is-valid-dir\(\)](#)
- [nvm.detect\(\)](#)
- [nvm.install\(\)](#)
- [nvm.load\(\)](#)

nvm.is-valid-dir()

Returns true if NVM_DIR is correctly set, OR if a directory passed as an argument contains nvm.sh

nvm.detect()

Returns success and exports NVM_DIR whenever nvm.sh is found underneath any of the possible locations tried.

nvm.install()

Installs NVM via Curl if not already installed.

nvm.load()

Loadd

File **lib/net.sh**

- [net.is-host-port-protocol-open\(\)](#)

net.is-host-port-protocol-open()

Uses pingless connection to check if a remote port is open Requires sudo for UDP

Arguments

- @arg1 host
 - @arg2 port
 - @arg3 [optional] protocol (defaults to "tcp", supports also "udp")
-

File lib/is.sh

Various validations and asserts that can be chained and be explicit in a DSL-like way.

- <<isvalidationerror,is.validation.error()>>
- [is-validations\(\)](#)
- <<isvalidationignore-error,is.validation.ignore-error()>>
- <<isvalidationreport-error,is.validation.report-error()>>
- [whenever\(\)](#)

__is.validation.error()

Invoke a validation on the value, and process the invalid case using a customizable error handler.

Arguments

- @arg1 func Validation function name to invoke
- @arg2 var Value under the test
- @arg4 error_func Error function to call when validation fails

Exit codes

- 0: if validation passes

is-validations()

Returns the list of validation functions available

__is.validation.ignore-error()

Private function that ignores errors

`__is.validation.report-error()`

Private function that ignores errors

`whenever()`

a convenient DSL for validating things

Example

```
whenever /var/log/postgresql.log is.an-empty-file && {  
  touch /var/log/postgresql.log  
}
```

File `lib/util.sh`

Miscellaneous utilities.

File `lib/runtime.sh`

- [run.inspect-vars\(\)](#)

`run.inspect-vars()`

Prints values of all variables starting with prefixes in args

File `lib/pdf.sh`

Bashmatic Utilities for PDF file handling

Install and uses GhostScript to manipulate PDFs.

- [pdf.combine\(\)](#)

`pdf.combine()`

Combine multiple PDFs into a single one using ghostscript.

Example

```
pdf.combine ~/merged.pdf 'my-book-chapter*'
```

Arguments

- **\$1** (pathname): to the merged file
 - ... (the): rest of the PDF files to combine
-

File **bin/install-direnv**

Add direnv hook to shell RC files

- [direnv.register\(\)](#)

direnv.register()

Add direnv hook to shell RC files

File **bin/regen-usage-docs**

Regenerates USAGE.adoc && USAGE.pdf

File **bin/pdf-reduce**

- [pdf.do.shrink\(\)](#)

pdf.do.shrink()

shrinks PDF

File **bin/scheck**

- [manual-install\(\)](#)
-

manual-install()

Manually Download and Install ShellCheck

Copyright & License

- Copyright © 2017-2022 Konstantin Gredeskoul, All rights reserved.
- Distributed under the MIT License.