



## 6. Character Segmentation, Language Models and Beam Search

The heart of Tesseract

*Ray Smith, Google Inc.*

# Approaches to Segmentation

- Segment first using only geometry.
- Maximally chop, then combine with a beam search. (Over-segmentation.)
- Sliding window to "avoid" segmentation altogether.
- Tesseract: Chop only as needed, then combine as needed.



## Over-Segmentation

- Aim is to maximize recall of chops with the compromise of reduction in precision.




# Segmentation Graph


- Segmentation possibilities and classifier results form a directed graph




# Searching the Segmentation Graph



# Searching the Segmentation Graph



higher



}uglier

## Integration of Language Models (General Methods)

- Implement Language Model as Finite State Machine.
- Search Language Model and Segmentation Graph in parallel.
- Combine “probabilities” in some sensible way.
- Hidden Markov Model methods are good example.

## Segmentation Free = Extreme Over-Segmentation

- Slide over the word/textline with a classifier/HMM.
- Beam search + shape model probs + language model probs solves the segmentation internally.
- Really just mega-over-segmentation.



## Tesseract Segmentation Approach based on observations:

- Initial segmentation is often correct or close.
- Classifier generally doesn't like incorrectly segmented text.
- Over-segmentation often leads to poor results., eg m->iii

## Tesseract Segmentation Approach

Classify Initial Segmentation

Search Word: OK? Yes => Done

while any Bad Blob has any Chops available

    Chop and classify pieces of Worst Choppable Blob

    Search Word: OK? Yes => Done

while any fixable “Pain point”



    Associate adjacent blobs and classify

    Search Word: OK? Yes => Done

## Types of Pain Point

- Initial: Join each adjacent pair
- Ambiguity: Eg  $m/rn$
- Path: Neighbors of blobs in the current best path

# Ratings MATRIX = Segmentation Graph



Each entry holds a BLOB\_CHOICE\_LIST providing classifier choices with rating and certainty.

# Live Demo of Segmentation Search

## Chopper demo

```
api/tesseract unlv/mag.3B/2/8022_028.3B.tif test1 inter segdemo chopdebug3
```

Col 2, line 6, word 1

## Associator demo

```
api/tesseract unlv/doe3.3B/4/2214_007.3B.tif test1 inter segdemo
```

Col 2, line 8, word 2

## Evaluation of a WORD\_CHOICE (no params-model)

Word Rating = word\_factor  $\sum_{\text{segmentation}} \text{blob\_choice} \rightarrow \text{rating}()$   
word\_factor =

| Condition          | base word_factor                 | Add-ons   |
|--------------------|----------------------------------|---|
| Frequent dawg word | 1.0                              | Inconsistent case +0.1  |
| Other dawg word    | 1.1                              | Inconsistent case +0.1  |
| Non-dawg word      | 1.25 +0.01 for each char over 3. | Inconsistent case +0.1<br>Inconsistent punc +0.2<br>Inconsistent chartype +0.3<br>Inconsistent script +0.5<br>Inconsisted char spacing +0.01<br>All except script +0.01 for each additional occurrence. |


## Evaluation of a WORD\_CHOICE (with params-model)

Word Rating = word\_factor  $\sum$  outline length

word\_factor = weighted sum of word features:







- mean blob rating
- num inconsistent spaces
- num inconsistent char type
- num x-height inconsistencies
- num case inconsistencies
- word length (in type categories)

# Tesseract Word Recognizer





# Example of Chopping (unlv/mag.3B/2/8022\_028.3B.tif Col 2, line 6, word 1)

|   | Word     | Distance | Worst blob |
|---|----------|----------|------------|
|    | Momm     | 212.2    | 7.7        |
|    | Mommn    | 186.3    | 8.3        |
|    | Momtfln  | 178.0    | 9.2        |
|   | Momtain  | 124.9    | 5.3        |
|  | Mounm    | 184.0    | 7.7        |
|  | Mountain | 80.6     | 3.1        |
|   |          |          | ACCEPT!    |

# Example of Combining (unlv/dae3.3B/4/2214\_007.3B.tif, col 2, line 8, word 2)

Word Distance

lillit- 77.58

limit57.1

Emit 89.7

Unfit 95.4

Hulk 122.7

Bulk 136.8

Word Distance

HUM 120.6

MUM 127.0

BUM 134.7

1mm 112.8

Milk147.2

huh 137.1

fink 140.7

Emu 129.7

BMW 140.3

Thanks for Listening!

Questions?