Computer Science & Engineering Department

Arhitectura Sistemelor de Calcul

Curs 12
cs.pub.ro
cs.curs.pub.ro

University Politehnica of Bucharest



In cursul anterior

- Nevoia de a compara sisteme de calcul
- Cum masuram Performanta?
- Benchmark-uri pentru masini “seriale”
- Benchmark-uri pentru masini “paralele”



Cuprins

- Top 500 List
- Arhitecturi si Aplicatii Relevante
- Trend de dezvoltare



Top 500 List


top500.org

- Proiect demarat in Iunie 1993
- Lista actualizata a celor mai puternice 500 de sisteme de calcul de uz general, disponibile comercial in lume si folosite la aplicatii complexe
- Statisticile referitoare la supercalculatoare sunt interesante pentru
  - Dezvoltatorii de sisteme (producatorii de HW & SW)
  - Utilizatori
  - Potentialii viitori utilizatori
- Se doreste cunoasterea
  - Numarului si locatiei sistemelor
  - Domeniilor de aplicatie ale sistemelor → facilitarea unor potentiale colaborari

top500.org

- Lista este publicata de 2 ori pe an
- Benchmark – versiune paralela a Linpack – HPL (Jack Dongarra @ ICL, University of Tennessee)
  - http://www.netlib.org/benchmark/hpl/
  - Rezolvarea unui sistem dens de ecuatii liniare Ax = b
  - Nu reflecta intr-un mod exhaustiv performanta intregului sistem!
  - Dimensiunea problemei poate fi modificata pentru a se potrivi cel mai bine pe arhitectura sistemului masurat
- Listele sunt prezentate la @Supercomputing Conference – US si International Supercomputing Conference – Germania





Arhitecturi si Aplicatii Relevante

Motivatie - HW Then…


- Cylindrical so wires are short
- Freon Cooling
- 8M Pounds
- Aldermaston Atomic Weapons Establishment







Motivatie - Aplicatii






No (more) Kaboom…

Motivatie - The Earth-Simulator

- Simulari atmosferice pentru Agentia Aerospatiala a Japoniei
- Simulari oceanice pentru Centrul Japonez de Stiinte si Tehnologii Marine
- Simulari industriale
- Simulari atomice pentru Insititutul Japonez de **Cercetari Atomice**




Sistemul NEC Earth Simulator

- Site: The Earth Simulator Center
- Familia de sisteme: NEC Vector
- Model: SX6
- Procesor: NEC 1000MHz
- OS: Super-UX
- Arhitectura: MPP
- Aplicatii: Studiul mediului, Cercetari Atomice
- Anul instalarii: 2002
- Numar de procesoare: 5120
- Rmax(TFlops): **35**.86
- Rpeak(TFlops): **40**.96
- Interconectare: Multi-stage crossbar
- No 1 intre 2002-2004




Procesoare Vectoriale SX6




- Unitate Scalara (SU)
- Unitate Vectoriala (VU)
- Frecventa – 500 MHz
- SU – procesor super-scalar: 64Kb instr cache; 64Kb data cache; 128 registrii de uz general
- VU – 72 registrii vectoriali cu 256 elemente & 8 seturi de 6 benzi de asamblare pentru operatii logice si aritmetice
- Tehnologie de fabricaţie: LSI, 0.15µm CMOS, 60 mil. tranzistori
- Consum 140 W

Arhitectura HW Earth-Simulator



Consum & Structura Earth Simulator

- Fiecare 2 noduri sunt instalate într-un container (1x1.4x2m)
- Fiecare container consumă 20 KW → 8MW
- Memoria sistemului este de 10TB
- Spatiu de stocare pe disc 700 TB
- Stocare in masa pe banda 1.6 PB







Columbia / SGI Altix @NASA

- Site: NASA/Ames Research Center/NAS
- Familia de sisteme: SGI® Altix™
- Model: SGI® Altix™ 3700, Voltaire Infiniband
- Procesoare: Intel IA-64 Itanium 2 1.5 GHz
- OS: SuSE Linux Enterprise Server 9
- Arhitectura: MPP
- Aplicatii: Cercetari aerospatiale
- Anul instalarii: 2004
- Numar de procesoare: 10240
- Rmax(TFlops): **51**.870
- Rpeak(TFlops): **60**.960
- Interconectare: Numalink/Infiniband




Arhitectura Columbia

- Numele sistemului
  - In memoria echipajului de pe Columbia - 1 februarie 2001
- 20 superclustere Altix™ din seria 3000
  - 8 SGI Altix 3700 si 12 Altix 3700 Bx2
  - 4 din Bx2-uri formeaza un 2048-PE (Processor Shared Memory Environment)
- Procesoare Intel Itanium 2
  - 1.5GHz, 6MB Cache
- Pana la 24 TB de Global Shared Memory pe fiecare cluster




Interconectare Columbia

- Nodurile sunt conectate
  - Voltaire InfiniBand
  - Ethernet de 1 si 10 Gb/s
- Columbia este conectat la un on-line RAID printr-o conexiune Fibre Channel → 440TB
- Conectarea procesoarelor prin SGI®NUMAlink™ → design modular
  - 2048 de procesoara folosesc NumaLink si pentru conectarea dintre noduri
  - Singura tehnologie care ofera global shared memory si intre noduri, nu doar in cadrul unui nod




Software Columbia





- OS: SGI ProPack 4 – bazat pe SUSE Linux
- Compilatoare Intel® Fortran/C/C++ & Gnu
- Fiecare nod de 512 procesoare ofera
  - Latenţă mică la accesul mem (<1 ms) → reduce overheadul in comunicatie
  - Global shared mem de 1TB → procesele mari rămân rezidente
- Optim pentru aplicatii cu comunicatie masiva intre procesoare
  - Simulari fizice in care domeniul este discretizat → CFD
  - Prognoza meteo & Nanotehnologii
  - N-Body simulations → Astrofizica


Aplicatii Columbia



- Cart3D
  - Prezice traiectoria unei buc e in timpul ascensiu
  - Culorile reprezinta presiune
- Debris
  - Calculeaza traiectoriile rest icolul orbital in timp
  - Evalueaza periculozitatea a
- Overflow
  - CFD utilizat pentr vehiculelor aerosp
  - Campul de presi za de 2.46Mach, la
  - Culorile reprezint n jurul vehiculului, c
- Phantom
  - CFD utilizat pentr re in motoare cu rea
  - Presiunea in pom navetei spatiale utili








MareNostrum JS20 Cluster

- Site: Barcelona Supercomputing Center
- Familia de sisteme: IBM Cluster
- Model: BladeCenter JS20 Cluster
- Procesoare: PowerPC 970 2.3 GHz
- OS: SuSE Linux Enterprise Server 9
- Arhitectura: Cluster
- Aplicatii: Medicina
- Anul instalarii: 2006
- Numar de procesoare: 10240
- Rmax(TFlops): **62**.63
- Rpeak(TFlops): **94**.21
- Interconectare: Red Myrinet




Arhitectura MareNostrum

- Memorie totala 20TB
- Capacitate de stocare: 370TB
- Este format din 44 de rack-uri ce ocupa 120m^2




Arhitectura MareNostrum







Aplicatii MareNostrum


- Computational Sciences
  - Computer Architecture
  - Performance Tools
  - Grid Computing & Clusters
- Earth Sciences
  - Air Quality
  - Meteorological Modelling
  - Mineral Dust
  - Climate Change
- Life Sciences
  - Molecular Modelling & Bioinformatics
  - Computational Genomics
  - Electronic & Atomic Protein Modelling












IBM RoadRunner

- Site: DOE/NNSA/Los Alamos NL
- Familia de sisteme:
- Model: BladeCenter QS22 Cluster
- Procesoare: PowerXCell 8i 3.2 GHz
- OS: Linux
- Arhitectura: Cluster
- Memorie: 104TB
- Aplicatii: Cercetare
- Anul instalarii: 2008
- Numar de procesoare: 122.400
- Rmax(PFlops): **1**,042 (NMax 2,25M)
- Rpeak(PFlops): **1**,376
- Consum: 2345 KW
- Interconectarea: Voltaire Infiniband






Cell processor (2007, ~100 GF)




CM-5 board with vector units (1994, 1 GF)

Arhitectura RoadRunner




8,640 dual-core Opterons
⇨ **76 TeraFlops**
16,560 Cell eDP chips
⇨ **1.7 PetaFlops**



Los Alamos NATIONAL LABORATORY


Programare RoadRunner

- **Computational Library (ALF w/ IBM)**
  - Task & work block queuing & management
  - Streaming & user-defined data partitioning
  - Process management
  - Error handling
- **Communication Library (DaCS w/ IBM)**
  - Data movement & synchronization
  - Process management & synchronization
  - Topology description
  - Error handling
  - First implementation may leverage OpenMPI
- **Longer term**
  - ALF & DaCS support in tools
  - ALF from Opteron ⇒ Cell directly
  - Compilers supporting some of this



Los Alamos NATIONAL LABORATORY

Programare Hibrida RoadRunner



- Hybrid programming will be a challenge!
  - No compiler switches to "just use the Cells"
  - Not even a single compiler – 3 of them
  - Code developer/architect must decompose application and create cooperative program pieces

JuQueen BlueGene/Q

- Site: Forschungszentrum Juelich (FZJ)
- Model: IBM-BG/Q – 28 Racks
- Procesor: IBM PowerA2, 1.6 GHz
- OS: CNK/Linux
- Arhitectura: MPP
- Aplicatii: Cercetare
- Anul instalarii: 2012
- Numar de core-uri: 458.752
- Rmax(PFlops): **5**,009
- Rpeak(PFlops): **5**,872
- Memorie: 448 TB
- Interconectare: Custom 5D Torus






ASC@UPB: Monica Bugeanu & Alex Calotoiu


Arhitectura IBM BlueGene

- Program initiat de IBM in 1999 pentru a construi “a petaflop scale machine”
- BlueGene/L – primul pas, bazat pe procesoare PowerPC
  - Spatiu de adresare mare
  - Compilatoare standard
  - Bazat pe middleware de “message passing” deja existent
  - A necesitat adaugiri semnificative fata de sistemul PowerPC standard
- Un nod computational = computer-on-a-chip – ASIC
  - Procesoare IBM PowerPC
  - Memorie DRAM embedded
  - L1-3 cache embedded
  - Multiple module de interconectare folosind retele de comutare de mare viteza




Arhitectura IBM BlueGene


- Memorie
  - 1GB DDR RAM / core – 16GB pe nod
  - Doua controlere de memorie externa de tip DDR integrat on-chip la 1.33GHz
- Procesor
  - 18C @ 1.6GHz: 16 computationale, unul pentru OS, unul de backup
  - 32MB DRAM L2 Cache: transactional memory & executie speculativa
  - Quad SIMD floating point unit
  - 45nm cu performanta maxima de 204.8 GFLOPS
  - Consuma 55W la 19.19mm si 1.47 B tranzistoare
- Interconectare
  - Tor 5D cu un router pe nod cu 11 link-uri
  - Procesor I/O extern dedicat – 2GB/s
  - Core-urile legate printr-un crossbar
- I/O Extern
  - Noduri dedicate pentru I/O extern
  - Reteaua este de tip arborescent
- OS - CNK/Linux
- Software: MPI, OpenMP, Charm++, GlobalArrays, Posix IO



Arhitectura IBM BlueGene




Arhitectura IBM BlueGene




Retele de Comunicatie IBM BlueGene


- Nodurile sunt atasate la 5 retele de comunicatie
  - Retea toroidala 5D pentru comunicatii intre noduri
  - Retea colectiva de comunicatii
  - Retea globala de intreruperi si bariere
  - Pentru I/O – Gigabit Ethernet
  - Joint Test Access GroupGigabit Ethernet – pentru control si monitorizare
- Favorizeaza aplicatii care comunica cu vecinii imediati
- BG e dezvoltat pentru aplicatii cu volum mare de date




I/O IBM BlueGene



IBM BlueGene Software Stack





IBM BlueGene – Mod de executie



Aplicatii IBM BlueGene


- Analiza proteinelor
- Interactiunea intre medicamente si proteine
- Data Mining
- Fizica atomica: similar cu ASC Purple
- Dinamica moleculara (inclusiv ab-initio)
- Hidrodinamica steady state si turbulenta
- Astrofizica






K Computer SPARC64

- Site: RIKEN Advanced Institute for Computational Science
- Familia de sisteme: Fujistu – SPARC64 VIIIfx 2.0GHz
- Procesor: SPARC64 VIIIfx 2.0GHz (8-core)
- OS: Linux
- Arhitectura: Cluster
- Aplicatii: Cercetare
- Anul instalarii: 2011
- Numar de core-uri: 705.024
- Rmax(PFlops): **10**,510
- Rpeak(PFlops): **11**,280
- HPCG(TFlops): **602**,5
- Memorie: 1,410 TB
- Consum: 12.660 kW
- Interconectare: Custom – Tofu














K Computer Processor

- 8C @ 2GHz – SoC design
- Embedded Memory Controller
- Shared 5M L2 Cache
- 45nm – 760M tranzistori
- 128GFlops (peak)
- 64GB/s transfer la memorie
- 58W si racire cu apa
- Set de registri mare 192 int / 256 fp
- Unitati SIMD
- Software Managed Cache




K Computer 6D Mesh/Torus Tofu Interconnect






K Computer Fujitsu Exabyte File System

- Date foarte multe: 100PB~1EB
- Foarte multi clienti: 100k~1M
- Foarte multe servere: 1k~10k
- Reducerea latentei la fisiere: ~10k ops



K Computer Performance Tuning




8/2022 - Perlmutter


- Site: LBNL
- Familia de sisteme: HPE Cray EX235n
- Procesor: AMD EPYC 7763 64C 2.45GHz, NVIDIA A100 SXM4 40 GB
- OS: HPE Cray OS
- Arhitectura: MPP
- Aplicatii: Research
- Anul instalarii: 2021
- Numar de core-uri: 761,865
- Rmax(PFlops): **70**,90
- Rpeak(PFlops): **93**,75
- HPCG(TFlops): **1,905**
- Memorie: **421** TB
- Consum: **2.58** kW / **27.37** GFlop/W
- Interconectare: GBEth / Slingshot-10 (274 GB)



Perlmutter Architecture




Arhitectura Cray XC Series – 1





Arhitectura Cray XC Series – 2






Cray XC – Software Stack


Cray HPC Cluster Software Stack						
HPC Programming Tools	Development & Performance Tools	Cray PE on CS	Intel® Cluster Studio	PGI Cluster Development Kit®	GNU Toolchain	NVIDIA® CUDA®
	Application Libraries	Cray® LibSci™, LibSci_ACC	Intel® MPI	IBM Platform MPI	MVAPICH2	OpenMPI
	Debuggers	Rogue Wave TotalView®	Allinea DDT, MAP	Intel® IDB	PGI PGDBG®	GNU GDB
Schedulers File Systems and Management	Resource Management / Job Scheduling	SLURM	Adaptive Computing Moab®, Maui, Torque	Altair PBS Professional	IBM Platform™ LSF®	Grid Engine
	File Systems	Lustre®	NFS	GPFS	Panasas PanFS®	Local (ext3, ext4, XFS)
	Cluster Management	Cray® Advanced Cluster Engine (ACE™) Management Software				
Operating Systems and Drivers	Drivers & Network Mgmt.	Accelerator Software Stack & Drivers		OFED		
	Operating Systems	Linux® (Red Hat, CentOS)				


Arhitectura Sisteme Cray














Arhitectura Sisteme Cray








Retele de conectare Cray









Cray - Aplicatii

WL-LSMS
Role of material disorder, statistics, and fluctuations in nanoscale materials and systems.






LAMMPS
A multiple capability molecular dynamics code.





S3D
Combustion simulations to enable the next generation of diesel/bio fuels to burn more efficiently.

CAM-SE
Answers questions about specific climate change adaptation and mitigation scenarios.



NRDF
Radiation transport – important in astrophysics, laser fusion, combustion, atmospheric dynamics, and medical imaging – computed on AMR grids.






Denovo
High-fidelity radiation transport calculations that can be used in a variety of nuclear energy and technology applications.


7/2022 - Sunway TaihuLight

- Site: National Super Computer Center in Wuxi
- Model: NRCPC MPP
- Procesor: Sunway SW26010 260C 1.45GHz
- OS: Sunway RaiseOS 2.0.5
- Arhitectura: MPP
- Aplicatii: Cercetare
- Anul instalarii: 2016-2018
- Numar de core-uri: 10.649.600
- Rmax(PFlops): **93**,02
- Rpeak(PFlops): **125**,44
- HPCG(TFlops): **481**
- Memorie: **1,311** TB
- Consum: **15,371** kW
- Interconectare: Custom Sunway




Arhitectura Sunway TaihuLight






Node Architecture Sunway TaihuLight

1 Node (of 40 960) of Sunway TaihuLight




Arhitectura Sunway TaihuLight

- Performance / Watt: 6.05 GFLOPS/W - 4th Top500 Green
- 40960 Processors, each with 260 Cores having:
  - Scratchpad Memory: 64kB Data / 16kB Instruction
- Memory Bandwith: 5591 TB/s
- Network link Bandwith: 14GB/s
- System Storage: 20PB
- I/O Bandwidth: 288GB/s
- NoC Interconnect



Software Stack Sunway TaihuLight



Software Sunway TaihuLight

- Simulation/Modeling Packages:
  - ANSYS: Fluent, CFX, Multiphysics
  - Comet
  - Star CD / CCM+
  - MSC Nastran
  - LS-Dyna
- Pre/post processing utilities:
  - HyperMesh
  - Tecplot
  - Gambit
  - MSC Patran




6/2022 - Sierra Power System S922

- Site: DOE/NNSA/LLNL
- Familia de sisteme: IBM Power Systems
- Procesor: IBM POWER9 22C 3.1GHz, NVIDIA Volta V100
- OS: Red Hat Enterprise Linux
- Arhitectura: Cluster
- Aplicatii: Cercetare
- Anul instalarii: 2018
- Numar de core-uri: 1,572,480
- Rmax(PFlops): **94**,64
- Rpeak(PFlops): **125**,71
- HPCG(PFlops): **1,796**
- Memorie: **1.382** TB
- Consum: **7.438** kW
- Interconectare: Dual-rail Mellanox EDR Infiniband




Application Highlight




- Nuclear Security Administration's stockpile stewardship mission
- 3D Simulation instead of underground testing
- Performance of nuclear weapon systems
- Understand key issues of nuclear physics

Future Trends Processors

- New processors & accelerators:
  - Multi-core to many-core: 8, 16, 32, ... 80, 128, 1000?
  - IBM Cell , AMD Fusion, Intel Polaris, NVidia G8800
  - Distributed memory & caches at core level
  - FPGAs, GPGPU, Clearspeed CSX600, IBM Cell, XtremeData XD1000, Nvidia G80, AMD Stream Processor
- Connection standards
  - AMD Torrenza, Intel/IBM Geneseo, AMD HyperTransport Initiative
- Programming
  - IBM Roadrunner Cell libraries, RapidMind, Peakstream, Impulse C, Standford's Sequoia, NVidia CUDA, Clearspeed C, Mercury MFC, stream programming
- Heterogeneous architectures
  - Clusters of mixed node
  - Hybrid accelerated node (e.g. Roadrunner, Clearspeed, FPGA)
  - Hybrid on the same bus (e.g. CPU+GPUs, Intel's Geneseo, AMD's Torrenza)
  - Within processor itself (e.g. Cell, AMD Fusion)



Future Trends System Architecture



ASCR Roadmap Example

ASCR Computing Upgrades At a Glance

System attributes	NERSC Now	OLCF Now	ALCF Now	NERSC Upgrade	OLCF Upgrade	ALCF Upgrades	
Name Planned Installation	Edison	TITAN	MIRA	Cori 2016	Summit 2017-2018	Theta 2016	Aurora 2018-2019
System peak (PF)	2.6	27	10	> 30	200	>8.5	180
Peak Power (MW)	2	9	4.8	< 3.7	13.3	1.7	13
Total system memory	357 TB	710TB	768TB	~1 PB DDR4 + High Bandwidth Memory (HBM)+1.5PB persistent memory	> 2.4 PB DDR4 + HBM + 3.7 PB persistent memory	>480 TB DDR4 + High Bandwidth Memory (HBM)	> 7 PB High Bandwidth On-Package Memory Local Memory and Persistent Memory
Node performance (TF)	0.460	1.452	0.204	> 3	> 40	> 3	> 17 times Mira
Node processors	Intel Ivy Bridge	AMD Opteron Nvidia Kepler	64-bit PowerPC A2	Intel Knights Landing many core CPUs Intel Haswell CPU in data partition	Multiple IBM Power9 CPUs & multiple Nvidia Voltas GPUS	Intel Knights Landing Xeon Phi many core CPUs	Knights Hill Xeon Phi many core CPUs
System size (nodes)	5,600 nodes	18,688 nodes	49,152	9,300 nodes 1,900 nodes in data partition	~4,600 nodes	>2,500 nodes	>50,000 nodes
System Interconnect	Aries	Gemini	5D Torus	Aries	Dual Rail EDR-IB	Aries	2nd Generation Intel Omni-Path Architecture
File System	7.6 PB 168 GB/s, Lustre®	32 PB 1 TB/s, Lustre®	26 PB 300 GB/s GPFS™	28 PB 744 GB/s Lustre®	120 PB 1 TB/s GPFS™	10PB, 210 GB/s Lustre initial	150 PB 1 TB/s Lustre®

Rank	System	Cores	Rmax (PFlop/s)	Rpeak (PFlop/s)	Power (kW)
1	**Frontier** - HPE Cray EX235a, AMD Optimized 3rd Generation EPYC 64C 2GHz, AMD Instinct MI250X, Slingshot-11, **HPE** DOE/SC/Oak Ridge National Laboratory **United States**	8,699,904	1,194.00	1,679.82	22,703
2	**Supercomputer Fugaku** - Supercomputer Fugaku, A64FX 48C 2.2GHz, Tofu interconnect D, **Fujitsu** RIKEN Center for Computational Science **Japan**	7,630,848	442.01	537.21	29,899
3	**LUMI** - HPE Cray EX235a, AMD Optimized 3rd Generation EPYC 64C 2GHz, AMD Instinct MI250X, Slingshot-11, **HPE** EuroHPC/CSC **Finland**	2,220,288	309.10	428.70	6,016
4	**Leonardo** - BullSequana XH2000, Xeon Platinum 8358 32C 2.6GHz, NVIDIA A100 SXM4 64 GB, Quad-rail NVIDIA HDR100 Infiniband, **Atos** EuroHPC/CINECA **Italy**	1,824,768	238.70	304.47	7,404
5	**Summit** - IBM Power System AC922, IBM POWER9 22C 3.07GHz, NVIDIA Volta GV100, Dual-rail Mellanox EDR Infiniband, **IBM** DOE/SC/Oak Ridge National Laboratory **United States**	2,414,592	148.60	200.79	10,096

The Current Top 5 @Top 500

Ce am invatat in aces curs?

- Top 500 List
- Arhitecturi si Aplicatii Relevante
- Trend de dezvoltare



Thank you for your attention.





emil.slusanschi@cs.pub.ro
cs.pub.ro