

Machine Learning for 3-Coloring


Solving NP-Complete Graph Problems with Message Passing Neural Networks

Francesco Tartaglia

1. Dataset Design

Building a heterogeneous and balanced training environment is crucial to prove the model can generalize 3-COL rules:

-  Random Variety (Phase Transition): Focus on "borderline" Erdős-Rényi graphs—the hardest to solve even for classical algorithms.
-  Topological Diversity: Inclusion of Regular, Planar, and Special graphs (cliques, bipartite) to learn true geometry, not just statistical patterns.
-  Balanced Labels (50/50 Split): Exactly 50% "3-Colorable" (YES) and 50% "Non 3-Colorable" (NO) to prevent prediction bias.
-  Size Generalization: Training on small graphs (10-30 nodes) and testing on large ones (50-100 nodes) to verify true algorithmic learning.



Architecture: MPNN Design

How the Graph Neural Network shares and processes topological information:

1

Node Feature & Message Passing

Nodes exchange vector messages along edges for consecutive layers k .

Each node updates its latent state by incorporating the structure of its k -hop neighborhood, identifying cycles and local constraints.

2

Global Readout Layer

Moving from a local view to a global graph-level representation.

A Global Pooling operator (e.g., Mean or Sum Pooling) condenses all node representations into a single global state vector .

h_G

3

Binary Output Layer

A final Multi-Layer Perceptron (MLP) with a Sigmoid activation function produces a binary decision.

Trained end-to-end guided by Binary Cross-Entropy Loss to predict true 3-colorability.

Input Representation & Graph Encoding



Transforming graph topology into zero-knowledge predictions:

-  **Structural Features:** The model receives the adjacency matrix and node features like degree and local clustering coefficient. No edge features are provided.
-  **Zero-Knowledge Initialization:** No chromatic hints or partial colorings are given. The network must deduce the answer entirely from pure geometric topology.
-  **K-Hop Message Passing:** We run rounds of information sharing. This allows each node's receptive field to detect odd cycles and cliques up to 4 hops away.

Readout & Decision Boundary

Global Readout

We use Sum Pooling to combine node vectors into a Graph-Level Vector.

Scientific Motivation: It guarantees permutation invariance (node order doesn't matter) and allows dynamic processing of graphs of varying sizes (10 to 100 nodes) with a fixed architecture.

Output Layer

The global vector is compressed via a Sigmoid activation into a continuous value .
 $P \in [0, 1]$

$$\hat{y} = P (\text{Graph is 3-Colorable})$$

Using a strict threshold: if the $\hat{y} \geq 0.5$ graph is predicted 3-colorable, otherwise not.

Evaluation Protocol & Validation

Integrating modern Machine Learning with classical search methodologies.

Size Generalization

We train the MPNN solely on small graphs (15-30 nodes) and test it on much larger, complex instances (50-100 nodes).

Motivation: Solving unseen large instances mathematically proves the model has learned general topological rules, completely ruling out overfitting.

ML-Guided Search

The network's output is not used as a "blind" final solution. Instead, its probabilities act as a heuristic to guide an exact algorithm (Backtracking).

This merges the mathematical correctness guarantee of backtracking with the deep statistical intuition of Machine Learning.

The Scientific Claim

”

Graph Neural Networks can extract latent topological invariants, acting as a "super-heuristic" capable of drastically reducing resolution times for NP-Complete problems in the critical Phase Transition area.

Evaluated against classical heuristics (e.g., DSatur) by measuring Number of Backtracks (nodes explored) and Time-to-Solution, proving the ML overhead is vastly outweighed by pruned search trees.

Open Questions & Future Directions



Scalability Limits

The GNN generalizes well from 30 to 100 nodes, but what about industrial scale (10,000+ nodes)? Does Message Passing become too expensive or suffer from oversmoothing?



Transfer Learning

If the model learns 3-COL topology, can this knowledge transfer to related NP-Complete problems like Maximum Clique or K-Coloring without training from scratch?



Explainable AI

When assigning high probabilities to a color, what geometric structures is the network looking at? "Reading" the black box could unveil new human-understandable heuristics.

The Hybrid Future of Search

Synergy, Not Substitution

ML cannot replace exact algorithms for NP-Complete problems due to the lack of absolute guarantees. However, it excels as a guiding super-heuristic.

Breaking the Phase Transition Wall

Training in the zone of maximum difficulty prevents trivial learning and generates true topological comprehension.

Key Takeaway

The true scientific value of ML applied to graphs is not guessing the perfect solution, but intuiting the right path for classical algorithms to explore—transforming exponential calculation times into manageable ones.

