

IT1100
Internet and Web technologies

Lecture 07 - part I PHP - Superglobal variables and Form Handling

Mr. Jagath Wickramarathne

**Faculty of Computing** 







### Lecture 07 – part I PHP - Superglobal variables and Form Handling

IT1100 Internet and Web technologies



#### Content

1. Superglobal variables and Form handling

### 1. Superglobal variables

• There are some built-in variables in PHP environment, which provides some special features, they are called **superglobal** variables.

They are basically associative arrays

 You will learn different types of supergloabal variables throughout the module

# 1. Superglobal variables Reading forms

 HTML form on a web page allows a user to enter data that is sent to a server for processing.

#### \$\_GET["index"]

 An array of variables passed to the current script via the URL parameters.

#### \$\_POST["index"]

 An array of variables passed to the current script via the HTTP POST method. 1. Superglobal variables Reading forms

#### Methods to read forms

1. HTML form (frond end) + PHP backend to read form inputs

2. PHP form + PHP backend to read form inputs

# 1. Superglobal variables Reading forms (HTML + PHP)

# 1. Superglobal variables Reading forms (HTML + PHP)

#### process.php

```
<!DOCTYPE html>
<html>
<body>
<form method="post" action="<?php echo htmlspecialchars($_SERVER["PHP_SELF"]);?>">
  Name: <input type="text" name="txtName">
  <br>
  <input type="submit" value="Submit" name="btnSubmit">
</form>
<?php
            if(isset($_POST["btnSubmit"])){
                        echo "<h1> Hi " . $ POST["txtName"];
```

- htmlspecialchars Convert special characters to HTML entities
- \$\_SERVER["PHP\_SELF"] a super global variable that returns the filename of the currently executing script

# Superglobal variables Reading forms - textbox

```
<!DOCTYPE html>
<html>
<body>
<form method="post" action="php-html-form-textbox-example.php">
Name: <input type="text" name="fname">
      <input type="submit">
</form>
</body>
</html>
                                                    <?php
                                                      $name = $ REQUEST['fname'];
                                                      echo $name;
```

### Superglobal variables Reading forms - textarea


```
<html>
<ht><h2>PHP HTML Form textarea Example</h2>
<form name="php-html-form-textarea-example" method="POST" action="php-html-form-textarea-example.php">
    Enter Your Full Name :
        <input name="Fullname" type="text" value=""><br/>Enter Your Address :
        <textarea name="UserAddress" rows="3" cols="20"></textarea>
        <br/>><br/><input name="BtnSubmit" type="submit" value="Submit">
        </form>
        </html>
```

isset — Determine if a variable is declared and is different than NULL

```
<?php
if(isset($_POST['BtnSubmit']))
{
   echo "<h2>Bellow is the form data</h2>";
   echo "<hr>";
   echo "</br>Your Name :{$_POST['Fullname']}";
   echo "</br>Your Address :{$_POST['UserAddress']}";
   echo "<hr>";
}
?>
```

#### Output








## Superglobal variables Reading forms - radio


```
<html>
<h3>PHP HTML Form radio button Example</h3>
     <form name="UserInformationForm" method="POST" action="php-html-form-radio-button-example.php">
        Enter Your Full Name:
        <input name="FullName" type="text" value=""><br/><br/>
        You are:
        <input name="YourGender" type="radio" value="male"> Male
        <input name="YourGender" type="radio" value="female" checked=checked"> Female<br/>br/>
        <input name="BtnSubmit" type="submit" value="Submit">
     </form>
</html>
                                                                     <?php
                                                                      if(isset($ POST['BtnSubmit']))
   Output
  PHP HTML Form radio button Example
                                                                        echo "<h3>Your form data as bellow</h3>";
  Enter Your Full Name : Saman Gamage
                                                                        echo "</br>Your Name :{$ POST['FullName']}";
                               Your form data as bellow
                                                                        echo "</br>Your are :{$_POST['YourGender']}";
  You are: 
Male Female
                                                                        echo "<hr>";
   Submit
                                Your Name :Saman Gamage
                                Your are a:Male
    FACULTY OF COMPUTING
```

### Superglobal variables Reading forms – checkbox

empty — Determine whether a variable is empty



#### Output







## Superglobal variables Reading forms - Select

```
<html>
<h3>PHP HTML Form select box Example</h3>
<form name="UserInformationForm" method="POST" action="php-html-form-select-box-example.php">
  Enter Your Full Name:
  <input name="FullName" type="text" value=""><br/><br/>
  I like:
  <select name="I like">
    <option value="java">JAVA</option>
    <option value="php">PHP</option>
    <option value="asp">ASP .Net</option>
  </select>
  <br/><br/>
  <input name="BtnSubmit" type="submit" value="Submit">
</form>
</html>
```

```
<?php
if(isset($_POST['BtnSubmit']))
{
  echo "<h3>Your submitted form data as bellow</h3>";
  echo "Your Name : {$_POST['FullName']}</br>";
  echo "I like : <h2>{$_POST['I_like']} </h2> Programming...!</br>";
  echo "<hr>";
}
```

#### Output





### Summary

1. Superglobal variables and Form handling