# 02\_Modelling.ipynb

### September 23, 2021

[]: # Importations

```
import sys
     sys.path.append('..')
     import pandas as pd
     import numpy as np
     from sklearn.model_selection import train_test_split
     from sklearn.model_selection import StratifiedKFold, RepeatedStratifiedKFold
     from sklearn.model_selection import cross_validate
     from imblearn.pipeline import Pipeline
     from sklearn.linear_model import SGDClassifier
     from sklearn.ensemble import RandomForestClassifier
     from lightgbm import LGBMClassifier
     from sklearn.metrics import confusion_matrix, classification_report
     from imblearn.combine import SMOTETomek
     from imblearn.under_sampling import TomekLinks
     from preprocessing import preprocessor as prep
     from preprocessing import preprocessor_no_scaler as prep_no_scl
     from styles import *
[]: # Initialisation
     train = pd.read_csv('../02_data/application_train.csv')
     test = pd.read_csv('../02_data/application_test.csv')
     id_error_msg = lambda x: '`SK_ID_CURR` is not unic for {} set!'.format(x)
     assert len(train.SK ID CURR.unique()) == train.shape[0], id error msg('train')
     assert len(test.SK_ID_CURR.unique()) == test.shape[0], id_error_msg('test')
     train.set_index('SK_ID_CURR', inplace=True)
     test.set_index('SK_ID_CURR', inplace=True)
     print('Training set dimensions :', train.shape)
     cls_size = train.TARGET.value_counts()
     cls_freq = train.TARGET.value_counts(normalize=True)
     print(pd.DataFrame({'size': cls_size,
                         'freq': cls_freq.apply(lambda x: '%.3f' % x)}))
```

```
Training set dimensions: (307511, 121)
         size
                freq
    0
      282686 0.919
        24825 0.081
[]: train_sample = train[::10]
     print('Sampled training set dimensions :', train_sample.shape)
     cls_size = train.TARGET.value_counts()
     cls_freq = train.TARGET.value_counts(normalize=True)
     print(pd.DataFrame({'size': cls_size,
                         'freq': cls_freq.apply(lambda x: '%.3f' % x)}))
    Sampled training set dimensions: (30752, 121)
         size
                freq
      282686 0.919
        24825 0.081
[]: X, y = train.iloc[:, 1:], train.iloc[:, 0].values.reshape(-1,1)
     Xs, ys = train_sample.iloc[:, 1:], train_sample.iloc[:, 0].values.reshape(-1.1)
     X train, X test, y train, y test = train_test_split(Xs, ys, test_size=.2)
     print('X_train:', X_train.shape)
     print('y_train:', y_train.shape)
     print('X test:', X test.shape)
     print('y_test:', y_test.shape)
    X train: (24601, 120)
    y_train: (24601, 1)
    X_test: (6151, 120)
    y_test: (6151, 1)
        Modèle 1 : SGD Classifier
[]: sgd = Pipeline([('p', prep), ('m', SGDClassifier())])
     cv = StratifiedKFold(n_splits=6, shuffle=True, random_state=42)
     #cv = RepeatedStratifiedKFold(n splits=5, n repeats=3, random state=42)
     scoring = ['precision_macro', 'recall_macro']
     sgd scor = cross validate(sgd, X train, y train, scoring=scoring, cv=cv)
     print('Model 1\n' + line_decor)
     print(sgd_scor['test_precision_macro'])
     print(sgd_scor['test_recall_macro'])
     #print('Mean Accuracy: %.4f' % np.mean(sgd_scores['test_accuracy']))
     print('Mean Precision: %.4f' % np.nanmean(sgd_scor['test_precision_macro']))
     print('Mean Recall: %.4f' % np.nanmean(sgd_scor['test_recall_macro']))
    Model 1
```

Γ

nan

nan

nan 0.4602439 0.46036585 0.46036585]

```
Mean Precision: 0.4603
    Mean Recall: 0.5000
[]: resampler = SMOTETomek(tomek=TomekLinks(sampling_strategy='majority'))
     sgd_imb = Pipeline([('p', prep), ('r', resampler), ('m', SGDClassifier())])
     cv = StratifiedKFold(n_splits=6, shuffle=True, random_state=42)
     #cv = RepeatedStratifiedKFold(n_splits=5, n_repeats=3, random_state=42)
     scoring = ['precision_macro', 'recall_macro']
     sgd_imb_scor = cross_validate(sgd_imb, X_train, y_train, scoring=scoring, cv=5)
     print(sgd_scor['test_precision_macro'])
     print(sgd_scor['test_recall_macro'])
     print('Model 1 - with imbalance handling\n' + line_decor)
     #print('Mean Accuracy: %.4f' % np.mean(sgd_imb_scores['test_accuracy']))
     print('Mean Precision: %.4f' % np.nanmean(sgd_imb_scor['test_precision_macro']))
     print('Mean Recall: %.4f' % np.nanmean(sgd_imb_scor['test_recall_macro']))
    Γ
                                  nan 0.4602439 0.46036585 0.46036585]
            nan
                       nan
    [nan nan nan 0.5 0.5 0.5]
    Model 1 - with imbalance handling
    Mean Precision: 0.5517
    Mean Recall: 0.6540
[]: model1 = Pipeline([('p', prep), ('m', SGDClassifier())])
     model1.fit(X_train, y_train)
     y_pred = model1.predict(X_test)
     conf_mat = confusion_matrix(y_test, y_pred)
     print('Model 1\n' + line_decor)
     print('Score: %.4f' % model1.score(X_test, y_test))
     print(line_decor + '\nConfusion matrix\n' + str(conf mat))
     print(classification_report(y_test, y_pred))
    Model 1
    _____
    Score: 0.9190
    Confusion matrix
    [[56522
                0]
     [ 4981
                0]]
                  precision
                               recall f1-score
                                                   support
               0
                       0.92
                                 1.00
                                           0.96
                                                     56522
                       0.00
                                 0.00
               1
                                            0.00
                                                      4981
                                           0.92
                                                     61503
        accuracy
       macro avg
                       0.46
                                 0.50
                                            0.48
                                                     61503
    weighted avg
                       0.84
                                 0.92
                                           0.88
                                                     61503
```

[nan nan nan 0.5 0.5 0.5]

## 2 Modèle 2 : Random Forest Classifier

```
[]: model2 = Pipeline([('p', prep_no_scl), ('m', RandomForestClassifier())])
     cv = RepeatedStratifiedKFold(n_splits=10, n_repeats=3, random_state=1)
     scoring = ['accuracy','precision_macro','recall_macro']
     scores_model2 = cross_validate(model2, X_train, y_train, scoring=scoring, cv=cv,
                                    n_jobs=-1)
     print('Model 2\n' + 8 * '-')
     print('Mean Accuracy: %.4f' % np.mean(scores_model2['test_accuracy']))
     print('Mean Precision: %.4f' % np.mean(scores_model2['test_precision_macro']))
     print('Mean Recall: %.4f' % np.mean(scores_model2['test_recall_macro']))
[]: model2 = Pipeline([('p', prep_no_scl), ('m', RandomForestClassifier())])
     model2.fit(X_train, y_train)
     y_pred = model2.predict(X_test)
     conf_mat = confusion_matrix(y_test, y_pred)
     print('Model 2\n' + 8 * '-')
     print('Score: %.4f' % model2.score(X_test, y_test))
     print(8 * '-' + '\nConfusion matrix\n' + str(conf_mat))
     print(classification_report(y_test, y_pred))
    Model 1
    _____
    Score: 0.9185
    -----
    Confusion matrix
    ΓΓ56485
                41
     [ 5011
                311
                  precision
                               recall f1-score
                                                  support
               0
                       0.92
                                 1.00
                                           0.96
                                                     56489
               1
                       0.43
                                 0.00
                                           0.00
                                                      5014
                                           0.92
                                                     61503
        accuracy
       macro avg
                       0.67
                                 0.50
                                           0.48
                                                     61503
                       0.88
                                 0.92
                                           0.88
                                                     61503
    weighted avg
[]: y_pred = model2.predict(X_test)
     conf_mat = confusion_matrix(y_test, y_pred)
     print(conf_mat)
    [[56512
                5]
     Γ 4979
                711
```

```
[]: model2.get_params()
[]: {'memory': None,
      'steps': [('columntransformer',
        ColumnTransformer(remainder='passthrough',
                          transformers=[('simpleimputer-1',
                                          SimpleImputer(strategy='median'),
                                          ['CNT_CHILDREN', 'AMT_INCOME_TOTAL',
                                           'AMT_CREDIT', 'AMT_ANNUITY',
                                           'AMT_GOODS_PRICE',
                                           'REGION POPULATION RELATIVE', 'DAYS BIRTH',
                                           'DAYS_EMPLOYED', 'DAYS_REGISTRATION',
                                           'DAYS_ID_PUBLISH', 'OWN_CAR_AGE',
                                           'CNT_FAM_MEMBERS', 'REGION_RATING_CLIENT',
                                           'REGION_RAT...
     SimpleImputer(fill_value='Unknown',
     strategy='constant')),
                                                          ('value_formatter',
     FunctionTransformer(func=<function <lambda> at 0x7f1e9f7aa790>)),
                                                          ('encoder',
     OneHotEncoder())]),
                                          ['NAME_TYPE_SUITE', 'NAME_INCOME_TYPE',
                                           'NAME_EDUCATION_TYPE',
     'NAME_FAMILY_STATUS',
                                           'NAME_HOUSING_TYPE', 'OCCUPATION_TYPE',
                                           'ORGANIZATION TYPE', 'FONDKAPREMONT MODE',
                                           'HOUSETYPE MODE',
     'WALLSMATERIAL_MODE'])])),
       ('randomforestclassifier', RandomForestClassifier())],
      'verbose': False,
      'columntransformer': ColumnTransformer(remainder='passthrough',
                        transformers=[('simpleimputer-1',
                                        SimpleImputer(strategy='median'),
                                        ['CNT_CHILDREN', 'AMT_INCOME_TOTAL',
                                         'AMT_CREDIT', 'AMT_ANNUITY',
                                         'AMT_GOODS_PRICE',
                                         'REGION_POPULATION_RELATIVE', 'DAYS_BIRTH',
                                         'DAYS_EMPLOYED', 'DAYS_REGISTRATION',
                                         'DAYS_ID_PUBLISH', 'OWN_CAR_AGE',
                                         'CNT_FAM_MEMBERS', 'REGION_RATING_CLIENT',
                                         'REGION_RAT...
     SimpleImputer(fill value='Unknown',
     strategy='constant')),
                                                        ('value formatter',
    FunctionTransformer(func=<function <lambda> at 0x7f1e9f7aa790>)),
                                                        ('encoder',
     OneHotEncoder())]),
```

```
['NAME_TYPE_SUITE', 'NAME_INCOME_TYPE',
                                   'NAME_EDUCATION_TYPE', 'NAME_FAMILY_STATUS',
                                   'NAME_HOUSING_TYPE', 'OCCUPATION_TYPE',
                                   'ORGANIZATION_TYPE', 'FONDKAPREMONT_MODE',
                                   'HOUSETYPE_MODE', 'WALLSMATERIAL_MODE'])]),
'randomforestclassifier': RandomForestClassifier(),
'columntransformer_n_jobs': None,
'columntransformer__remainder': 'passthrough',
'columntransformer sparse threshold': 0.3,
'columntransformer transformer weights': None,
'columntransformer transformers': [('simpleimputer-1',
 SimpleImputer(strategy='median'),
  ['CNT CHILDREN',
   'AMT_INCOME_TOTAL',
   'AMT CREDIT',
   'AMT_ANNUITY'
   'AMT_GOODS_PRICE',
   'REGION_POPULATION_RELATIVE',
   'DAYS_BIRTH',
   'DAYS_EMPLOYED',
   'DAYS_REGISTRATION',
   'DAYS ID PUBLISH',
   'OWN_CAR_AGE',
   'CNT FAM MEMBERS',
   'REGION RATING CLIENT',
   'REGION_RATING_CLIENT_W_CITY',
   'HOUR_APPR_PROCESS_START',
   'EXT SOURCE 1',
   'EXT_SOURCE_2',
   'EXT_SOURCE_3',
   'OBS_30_CNT_SOCIAL_CIRCLE',
   'DEF_30_CNT_SOCIAL_CIRCLE',
   'OBS_60_CNT_SOCIAL_CIRCLE',
   'DEF_60_CNT_SOCIAL_CIRCLE',
   'DAYS_LAST_PHONE_CHANGE',
   'AMT_REQ_CREDIT_BUREAU_HOUR',
   'AMT REQ CREDIT BUREAU DAY',
   'AMT REQ CREDIT BUREAU WEEK',
   'AMT REQ CREDIT BUREAU MON',
   'AMT REQ CREDIT BUREAU QRT',
   'AMT REQ CREDIT BUREAU YEAR']),
 ('simpleimputer-2',
 SimpleImputer(),
  ['APARTMENTS_AVG',
   'BASEMENTAREA_AVG',
   'YEARS_BEGINEXPLUATATION_AVG',
   'YEARS_BUILD_AVG',
```

```
'COMMONAREA_AVG',
  'ELEVATORS_AVG',
  'ENTRANCES_AVG',
  'FLOORSMAX_AVG',
  'FLOORSMIN_AVG',
 'LANDAREA_AVG',
  'LIVINGAPARTMENTS_AVG',
 'LIVINGAREA_AVG',
  'NONLIVINGAPARTMENTS AVG',
  'NONLIVINGAREA AVG']),
('simpleimputer-3',
SimpleImputer(strategy='median'),
['APARTMENTS_MEDI',
  'BASEMENTAREA_MEDI',
  'YEARS_BEGINEXPLUATATION_MEDI',
  'YEARS_BUILD_MEDI',
  'COMMONAREA_MEDI',
  'ELEVATORS_MEDI',
  'ENTRANCES_MEDI',
  'FLOORSMAX_MEDI',
  'FLOORSMIN_MEDI',
 'LANDAREA_MEDI',
  'LIVINGAPARTMENTS_MEDI',
  'LIVINGAREA MEDI',
  'NONLIVINGAPARTMENTS_MEDI',
  'NONLIVINGAREA MEDI']),
('simpleimputer-4',
SimpleImputer(strategy='most_frequent'),
['APARTMENTS_MODE',
  'BASEMENTAREA_MODE',
  'YEARS_BEGINEXPLUATATION_MODE',
  'YEARS_BUILD_MODE',
  'COMMONAREA_MODE',
  'ELEVATORS_MODE',
  'ENTRANCES_MODE',
  'FLOORSMAX_MODE',
  'FLOORSMIN MODE',
 'LANDAREA_MODE',
  'LIVINGAPARTMENTS MODE',
  'LIVINGAREA MODE',
  'NONLIVINGAPARTMENTS MODE',
  'NONLIVINGAREA_MODE',
  'TOTALAREA MODE']),
('pipeline-1',
Pipeline(steps=[('nan_imputer', SimpleImputer(strategy='most_frequent')),
                 ('xna_imputer',
                  SimpleImputer(missing_values='XNA',
```

```
strategy='most_frequent')),
                   ('encoder',
                    OrdinalEncoder(categories=[['Cash loans', 'Revolving
loans'],
                                                 ['N', 'Y'], ['N', 'Y'],
                                                 ['No', 'Yes'], ['M', 'F'],
                                                 ['MONDAY', 'TUESDAY',
'WEDNESDAY',
                                                  'THURSDAY', 'FRIDAY',
'SATURDAY',
                                                  'SUNDAY']]))]),
   ['NAME_CONTRACT_TYPE',
    'FLAG_OWN_CAR',
    'FLAG_OWN_REALTY',
    'EMERGENCYSTATE_MODE',
    'CODE_GENDER',
    'WEEKDAY_APPR_PROCESS_START']),
  ('pipeline-2',
   Pipeline(steps=[('imputer', SimpleImputer(strategy='most_frequent'))]),
   ['FLAG_MOBIL',
    'FLAG_EMP_PHONE',
    'FLAG_WORK_PHONE',
    'FLAG_CONT_MOBILE',
    'FLAG PHONE',
    'FLAG EMAIL',
    'REG REGION NOT LIVE REGION',
    'REG_REGION_NOT_WORK_REGION',
    'LIVE_REGION_NOT_WORK_REGION',
    'REG_CITY_NOT_LIVE_CITY',
    'REG_CITY_NOT_WORK_CITY',
    'LIVE_CITY_NOT_WORK_CITY',
    'FLAG_DOCUMENT_2',
    'FLAG_DOCUMENT_3',
    'FLAG_DOCUMENT_4',
    'FLAG_DOCUMENT_5',
    'FLAG_DOCUMENT_6',
    'FLAG_DOCUMENT_7',
    'FLAG_DOCUMENT_8',
    'FLAG DOCUMENT 9',
    'FLAG_DOCUMENT_10',
    'FLAG_DOCUMENT_11',
    'FLAG_DOCUMENT_12',
    'FLAG_DOCUMENT_13',
    'FLAG_DOCUMENT_14',
    'FLAG_DOCUMENT_15',
    'FLAG_DOCUMENT_16',
    'FLAG_DOCUMENT_17',
```

```
'FLAG_DOCUMENT_18',
    'FLAG DOCUMENT 19',
    'FLAG_DOCUMENT_20',
    'FLAG_DOCUMENT_21']),
  ('pipeline-3',
  Pipeline(steps=[('imputer',
                    SimpleImputer(fill value='Unknown', strategy='constant')),
                   ('value_formatter',
                    FunctionTransformer(func=<function <lambda> at
0x7f1e9f7aa790>)),
                   ('encoder', OneHotEncoder())]),
   ['NAME_TYPE_SUITE',
    'NAME INCOME TYPE',
    'NAME_EDUCATION_TYPE',
    'NAME_FAMILY_STATUS',
    'NAME_HOUSING_TYPE',
    'OCCUPATION_TYPE',
    'ORGANIZATION_TYPE'
    'FONDKAPREMONT_MODE',
    'HOUSETYPE_MODE',
    'WALLSMATERIAL_MODE'])],
 'columntransformer__verbose': False,
 'columntransformer_simpleimputer-1': SimpleImputer(strategy='median'),
 'columntransformer simpleimputer-2': SimpleImputer(),
 'columntransformer_simpleimputer-3': SimpleImputer(strategy='median'),
 'columntransformer simpleimputer-4': SimpleImputer(strategy='most frequent'),
 'columntransformer__pipeline-1': Pipeline(steps=[('nan_imputer',
SimpleImputer(strategy='most_frequent')),
                 ('xna_imputer',
                  SimpleImputer(missing_values='XNA',
strategy='most_frequent')),
                 ('encoder',
                  OrdinalEncoder(categories=[['Cash loans', 'Revolving loans'],
                                              ['N', 'Y'], ['N', 'Y'],
                                              ['No', 'Yes'], ['M', 'F'],
                                              ['MONDAY', 'TUESDAY', 'WEDNESDAY',
                                               'THURSDAY', 'FRIDAY', 'SATURDAY',
                                               'SUNDAY']]))]),
 'columntransformer pipeline-2': Pipeline(steps=[('imputer',
SimpleImputer(strategy='most_frequent'))]),
 'columntransformer pipeline-3': Pipeline(steps=[('imputer',
                  SimpleImputer(fill_value='Unknown', strategy='constant')),
                 ('value formatter',
                  FunctionTransformer(func=<function <lambda> at
0x7f1e9f7aa790>)),
                 ('encoder', OneHotEncoder())]),
 'columntransformer__simpleimputer-1__add_indicator': False,
```

```
'columntransformer_simpleimputer-1_copy': True,
 'columntransformer__simpleimputer-1__fill_value': None,
 'columntransformer_simpleimputer-1_missing_values': nan,
 'columntransformer_simpleimputer-1_strategy': 'median',
 'columntransformer_simpleimputer-1_verbose': 0,
 'columntransformer__simpleimputer-2__add_indicator': False,
 'columntransformer simpleimputer-2 copy': True,
 'columntransformer__simpleimputer-2__fill_value': None,
 'columntransformer simpleimputer-2 missing values': nan,
 'columntransformer simpleimputer-2 strategy': 'mean',
 'columntransformer__simpleimputer-2__verbose': 0,
 'columntransformer__simpleimputer-3__add_indicator': False,
 'columntransformer_simpleimputer-3_copy': True,
 'columntransformer_simpleimputer-3_fill_value': None,
 'columntransformer_simpleimputer-3_missing_values': nan,
 'columntransformer_simpleimputer-3_strategy': 'median',
 'columntransformer_simpleimputer-3_verbose': 0,
 'columntransformer_simpleimputer-4_add_indicator': False,
 'columntransformer_simpleimputer-4_copy': True,
 'columntransformer__simpleimputer-4__fill_value': None,
 'columntransformer__simpleimputer-4__missing_values': nan,
 'columntransformer_simpleimputer-4_strategy': 'most_frequent',
 'columntransformer__simpleimputer-4__verbose': 0,
 'columntransformer pipeline-1 memory': None,
 'columntransformer_pipeline-1_steps': [('nan_imputer',
  SimpleImputer(strategy='most_frequent')),
  ('xna imputer',
  SimpleImputer(missing_values='XNA', strategy='most_frequent')),
  ('encoder',
  OrdinalEncoder(categories=[['Cash loans', 'Revolving loans'], ['N', 'Y'],
                              ['N', 'Y'], ['No', 'Yes'], ['M', 'F'],
                              ['MONDAY', 'TUESDAY', 'WEDNESDAY', 'THURSDAY',
                               'FRIDAY', 'SATURDAY', 'SUNDAY']]))],
 'columntransformer__pipeline-1__verbose': False,
 'columntransformer_pipeline-1_nan_imputer':
SimpleImputer(strategy='most_frequent'),
 'columntransformer pipeline-1 xna imputer':
SimpleImputer(missing_values='XNA', strategy='most_frequent'),
 'columntransformer__pipeline-1__encoder': OrdinalEncoder(categories=[['Cash
loans', 'Revolving loans'], ['N', 'Y'],
                            ['N', 'Y'], ['No', 'Yes'], ['M', 'F'],
                            ['MONDAY', 'TUESDAY', 'WEDNESDAY', 'THURSDAY',
                             'FRIDAY', 'SATURDAY', 'SUNDAY']]),
 'columntransformer__pipeline-1__nan_imputer__add_indicator': False,
 'columntransformer_pipeline-1_nan_imputer_copy': True,
 'columntransformer_pipeline-1_nan_imputer_fill_value': None,
 'columntransformer__pipeline-1__nan_imputer__missing_values': nan,
```

```
'columntransformer_pipeline-1_nan_imputer_strategy': 'most_frequent',
 'columntransformer_pipeline-1_nan_imputer_verbose': 0,
 'columntransformer_pipeline-1_xna_imputer_add indicator': False,
 'columntransformer__pipeline-1__xna_imputer__copy': True,
 'columntransformer pipeline-1 xna imputer fill value': None,
 'columntransformer_pipeline-1_xna_imputer_missing_values': 'XNA',
 'columntransformer pipeline-1 xna imputer strategy': 'most frequent',
 'columntransformer__pipeline-1__xna_imputer__verbose': 0,
 'columntransformer pipeline-1 encoder categories': [['Cash loans',
   'Revolving loans'],
  ['N', 'Y'],
  ['N', 'Y'],
  ['No', 'Yes'].
  ['M', 'F'],
  ['MONDAY',
   'TUESDAY'
   'WEDNESDAY',
   'THURSDAY',
   'FRIDAY',
   'SATURDAY',
   'SUNDAY']],
 'columntransformer pipeline-1 encoder dtype': numpy.float64,
 'columntransformer_pipeline-1_encoder_handle_unknown': 'error',
 'columntransformer pipeline-1 encoder unknown value': None,
 'columntransformer__pipeline-2__memory': None,
 'columntransformer pipeline-2 steps': [('imputer',
  SimpleImputer(strategy='most_frequent'))],
 'columntransformer pipeline-2 verbose': False,
 'columntransformer__pipeline-2__imputer':
SimpleImputer(strategy='most_frequent'),
 'columntransformer_pipeline-2_imputer_add_indicator': False,
 'columntransformer_pipeline-2_imputer_copy': True,
 'columntransformer_pipeline-2_imputer_fill_value': None,
 'columntransformer__pipeline-2__imputer__missing_values': nan,
 'columntransformer_pipeline-2_imputer_strategy': 'most_frequent',
 'columntransformer__pipeline-2__imputer__verbose': 0,
 'columntransformer__pipeline-3__memory': None,
 'columntransformer_pipeline-3_steps': [('imputer',
  SimpleImputer(fill value='Unknown', strategy='constant')),
  ('value formatter',
  FunctionTransformer(func=<function <lambda> at 0x7f1e9f7aa790>)),
  ('encoder', OneHotEncoder())],
 'columntransformer__pipeline-3__verbose': False,
 'columntransformer__pipeline-3__imputer': SimpleImputer(fill_value='Unknown',
strategy='constant'),
 'columntransformer__pipeline-3__value_formatter':
FunctionTransformer(func=<function <lambda> at 0x7f1e9f7aa790>),
```

```
'columntransformer_pipeline-3_encoder': OneHotEncoder(),
 'columntransformer_pipeline-3_imputer_add_indicator': False,
 'columntransformer__pipeline-3__imputer__copy': True,
 'columntransformer_pipeline-3_imputer_fill_value': 'Unknown',
 'columntransformer_pipeline-3_imputer_missing_values': nan,
 'columntransformer__pipeline-3__imputer__strategy': 'constant',
 'columntransformer__pipeline-3__imputer__verbose': 0,
 'columntransformer__pipeline-3__value_formatter__accept_sparse': False,
 'columntransformer__pipeline-3__value_formatter__check_inverse': True,
 'columntransformer__pipeline-3__value_formatter__func': <function</pre>
preprocessing.<lambda>(x)>,
 'columntransformer__pipeline-3__value_formatter__inv_kw_args': None,
 'columntransformer__pipeline-3__value_formatter__inverse_func': None,
 'columntransformer_pipeline-3_value_formatter_kw_args': None,
 'columntransformer pipeline-3 value formatter validate': False,
 'columntransformer_pipeline-3_encoder_categories': 'auto',
 'columntransformer_pipeline-3_encoder_drop': None,
 'columntransformer_pipeline-3_encoder_dtype': numpy.float64,
 'columntransformer__pipeline-3__encoder__handle_unknown': 'error',
 'columntransformer__pipeline-3__encoder__sparse': True,
 'randomforestclassifier_bootstrap': True,
 'randomforestclassifier__ccp_alpha': 0.0,
 'randomforestclassifier__class_weight': None,
 'randomforestclassifier criterion': 'gini',
 'randomforestclassifier__max_depth': None,
 'randomforestclassifier max features': 'auto',
 'randomforestclassifier__max_leaf_nodes': None,
 'randomforestclassifier max samples': None,
 'randomforestclassifier_min_impurity_decrease': 0.0,
 'randomforestclassifier__min_impurity_split': None,
 'randomforestclassifier_min_samples_leaf': 1,
 'randomforestclassifier__min_samples_split': 2,
 'randomforestclassifier_min_weight_fraction_leaf': 0.0,
 'randomforestclassifier__n_estimators': 100,
 'randomforestclassifier__n_jobs': None,
 'randomforestclassifier__oob_score': False,
 'randomforestclassifier random state': None,
 'randomforestclassifier_verbose': 0,
 'randomforestclassifier warm start': False}
```

## 3 Modèle 3 : LightGBM

```
[]: model3 = Pipeline([('p', prep), ('m', LGBMClassifier())])
model3.fit(X_train, y_train)
print('Score:', model3.score(X_test, y_test))
```

#### Score: 0.9192071931450498

```
[]: y_pred = model3.predict(X_test)
conf_mat = confusion_matrix(y_test, y_pred)
print(conf_mat)
```

[[56447 81] [4888 87]]

## []: print(classification\_report(y\_test, y\_pred))

	precision	recall	f1-score	support
0 1	0.92 0.52	1.00 0.02	0.96 0.03	56528 4975
accuracy macro avg weighted avg	0.72 0.89	0.51 0.92	0.92 0.50 0.88	61503 61503 61503

```
# smote tomek
# random search precision des deux classes (privilégier light_gbm)
#
# choisir optimisation recall(classe 1)
# fonction coût : manque à gagner pour chaque treshold
# treshold = + = + precision - recall
# precision élevée = on accepte tout le monde
# recall élevée = on refuse tout le monde
# regarder crer une colonne intérêts (amt credit - good price),
# optimiser mon threshold % de ça
```