

Design & Implementation of Smart Traffic Light Controller

U.Jyothi

Department of Information
Technology

G.Narayanamma Institute of
Technology and Science for
Women Hyderabad,India
Jyothi.uppari@gnits.ac.in

B.Priyanka

Department of Information
Technology

G.Narayanamma Institute of
Technology and Science for
Women Hyderabad,India
priyabendalam@gmail.com

B.Namitha Reddy

Department of Information
Technology

G.Narayanamma Institute of
Technology and Science for
Women Hyderabad,India
namitha.band30@gmail.com

M.Jyothirmai

Department of Information
Technology

G.Narayanamma Institute of
Technology and Science for
Women Hyderabad,India
jyothirmai609@gmail.com

Abstract— Overcrowding of urban sites visitors is an increasing menace in contemporary towns that follow through with increased delays, consumption of fuel and environmental pollution. The traditional visitors signaling structures operate on a fixed time scale, which is currently failing to adjust to actual-time site visitor variations, leading to an inefficient management of site visitors. This project is about the design and development of a Smart Traffic Light Controller the application of car density analysis within a python-based SUMO simulator environment. Each direction is initially given a predetermined inexperienced period of 10 seconds at an intersection. The generation always monitors vehicle queues, and when the lane is facing a high traffic, the inexperienced signal period is mechanically extended to 15 seconds. On the other hand, the period changes to the default setting when the visitors are reduced. The simulation shows real-time version, which improves the allocation of signals and reduces unnecessary delays on unused lanes. Compared to hardware or IoT-based solutions, this software program-based solution provides a framework that is available and scalable to educational and research programs. Findings indicate that there has been a large enhancement in visitors wafts to sites, reduction in mean waits, and better intersection throughput in comparison with conventional constant-time law. Such an overview highlights the potential of intelligent, information-based traffic management systems to enhance urban mobility and provides a basis on the future intelligent transportation solutions.

Keywords— Smart Traffic Light Controller, Traffic Congestion, Adaptive Signal Control, Vehicle Density Analysis, SUMO Simulation, Urban Traffic Management, Dynamic Green Signal Timing, Intelligent Transportation Systems.

I. INTRODUCTION

City shipping systems play a significant role in the functioning of innovative towns, and they help to support movement, transformation, and interpersonal relations[1]. With the growth of city population and the rise in ownership of cars, congestion by visitors has become a huge problem, primary to the increased duration of the trip, better fuel consumption, and the increased environmental pollutants[2]. Traffic control is the key to maximizing the use of courses, improving safety, and reducing delays of commuters[3]. Traffic sign manipulate, which is a very important element of the traffic visitors

control, has long been based on a fixed-time schedule, assigning each lane signal time without consideration of actual visitor events [4]. Although these systems are simple to build, they lack the functionality to dynamically adjust to fluctuating site visitors numbers, often resulting in underutilised lanes, extended automobile waits, and suboptimal junction performance [5]. With the escalation of urban traffic complexity, there may be an increasing need for sensible visitors control systems that can provide responsive and adaptive manage.

Notwithstanding progress in adaptive visitors management, several issues persist. Traditional constant-time and semi-actuated signal structures fail to recollect the unpredictable stochastic traits of urban visitors, as car arrivals and congestion patterns range inconsistently at some stage in the day [6]. Numerous present day adaptive structures rely on substantial hardware infrastructures, such as IoT sensors, cameras, and embedded devices, which might be costly to implement and keep [7]. Moreover, a sizable portion of the studies is constrained to theoretical modelling or restricted demonstrations, resulting in a deficiency of scalable, fee-efficient, and software program-based totally solutions for simulating real-international traffic conditions [8]. This underscores the want for pragmatic frameworks that can dynamically beautify visitors waft whilst retaining available for scholarly and research programs [9]. Moreover, modern-day studies regularly lacks gadgets that allow adaptable testing with numerous site visitors situations and junction configurations [10].

This undertaking pursuits to expand and execute a software program framework for adaptive traffic sign manage that adjusts green sign periods relying on real-time vehicle density at junctions. The gadget is aiming to reduce wait times and improve congestion and use of lanes and this is within a simulation-based framework mostly as it avoids using costly hardware. The research is valuable as it demonstrates how the dynamic sign timing can maximize the throughput of the junction and provide the simulation platform that is scalable to evaluate the traffic strategies and create the realistic foundation on the development of the intelligent transportation organization in the future. It is a framework

that uses a more bendy, software program-convenient methodology, which allows teachers and planners to assess site visitors control techniques under a wide range of simulated conditions without the need to physically implement them.

This matrix of consideration is monumental because it has the potential of making an impact as far as mobility of cities, environmental sustainability, and transportation planning are concerned. The warned device can reduce time wasted in crossings, decrease consumption of the gasoline, and reduce the vehicle pollution through the dynamically changing naive mild periods according to the city traffic volume, and thus contribute to more sustainable city environments. The simulation platform provides an understanding of the flow styles and congestion dynamics of site visitors, which can be used to make decisions based on data to improve the infrastructure and urban planning. The study also highlights the significance of scalable, software based entirely solutions in enhancing smart spiders visitors control, which provides a basis in incorporation of adaptive visitors control on the intelligent city tasks. The appearance shows that adaptive, information driven traffic signal control may also optimise the overall performance of street network, reduce economic loss caused by congestion and enhance general first-class existence of the city residents.

II. RELATED WORK

The growing desire of proper visitor management has created a number of studies on viable visitor signs manipulate designs. Bhatia et al. [11] presented a clever traffic mild device aimed at the reduction of congestion through a responsive increase in signal periods in response to visitor events. Their approach verified monolithic advances in automobile throughput and wait lengths in comparison with the unchanging time designs, which highlights the effectiveness of flexible visitors management. Nevertheless, the studies usually targeted on conceptual layout and become deficient in a complete simulation framework for verifying performance across diverse traffic conditions. Mohamed and Radwan [12] executed a thorough evaluation of visitors light manage layout methodologies, classifying the to be had structures into constant-time, actuated, and adaptive techniques. Their thorough research revealed that several adaptive systems hold to depend upon hardware and stumble upon implementation problems in actual urban settings.

Numerous studies investigated rule-based and logic-driven traffic signal control systems. Albatish and Abu-Naser [13] added a rule-based totally smart traffic sign machine, displaying efficient control in simulated site visitors eventualities. Their technique prioritised simplicity and simplicity of implementation, even though it become constrained in scalability at junctions with rather dynamic visitors styles. Gadawe and Qaddoori [14] created a clever traffic light controller with VHDL, emphasising hardware implementation for real-time signal management. Their methodology provided correct timing changes however required specialized hardware and lacked flexibility for simulation or software program-different checking out. Hawi et al. [15] used fuzzy logic with wireless sensor networks to enhance visitors float management. Their machine successfully treated diverse traffic volumes; although, dependence on bodily sensors heightened deployment complexity and renovation burdens.

Research has also been conducted on density-based and surveillance-integrated site visitors manage structures. Udoakah and Okure [16] evolved a visitors mild machine that uses car density evaluation at the side of a surveillance machine to decorate inexperienced sign distribution. The approach, although a hit, become hardware-extensive and limited to sure crossings geared up with monitoring sensors. Albagul et al. [17] advanced and built a smart visitors signal gadget with a focal point on practical use. The era had concrete blessings in alleviating congestion but turned into deficient in its ability to regulate to real-time versions in site visitors glide. Karakuzu and Demirci [18] created a fuzzy common sense-primarily based simulator for clever visitors lighting with hardware integration, turning in precise sign management but necessitating huge infrastructure expenditure.

Subsequent investigations have tested implementations primarily based on FPGA and embedded structures. Singh and Badwaik [19] advanced an FPGA-based totally adaptive dynamic traffic mild controller that efficaciously changed sign timings according to fluctuating visitors instances. Notwithstanding its effectiveness, the method trusted specialised generation, proscribing scalability and accessibility. Chavan et al. [20] evolved an smart visitors signal controller the usage of embedded structures, emphasising low in cost hardware solutions for minor junctions. The machine, albeit yielding promising results, changed into confined in actual-time edition and simulation flexibility due to its hardware-centric architecture.

Current research shows that adaptive and shrewd visitors management can also extensively improve junction performance and alleviate congestion. Common drawbacks include reliance on specialized technology, confined scalability, and a lack of adaptable simulation frameworks suitable for studies and trying out in numerous city contexts. The recognized inadequacies necessitate the modern research, which introduces a software-based totally simulation framework for wise visitors sign control. This observe utilises vehicle density evaluation in a simulated environment to provide a scalable, hardware-unbiased platform for assessing adaptive signal strategies, making sure realistic applicability for real-global traffic management.

III. MATERIALS AND METHODS

The proposed system seeks to decorate city site visitors glide the usage of a Smart Traffic Light Controller constructed in a Python-primarily based SUMO simulation surroundings. The system uses real-time records of vehicle density at intersections to dynamically control the duration of green signals to ensure that the lanes with a high level of critically packed are provided with extended inexperience at the same time as lanes that are less congested have standard timings. The workflow integrates the process of collecting traffic data, simulated processing, and dynamic signal control in an endless cycle, allowing instantly versioning changing users of the site to situate. Innovative factors to answer that include density-pushed sensory timing and movable queue tracking enhance life and augment intersection throughput devoid of relying on hardware or internet of things devices. The structure can support the flexible experimenting and testing of manipulate methods through simulating various visitors scenarios. The expected outcomes include fewer cases of car

wait, less congestion, and better gas economy, which demonstrates the effectiveness of software-based adaptive traffic management as the scalable and low-cost transportation solution in cities.




Fig.1 System Architecture

Fig.1 indicates the design of the devices shows a Python-based mostly Smart Traffic Light Controller which would be connected to a simulator called SUMO to festoon the visitors of the city riding on the highway. The simulator will take the conditions of the traffic, which the user enters to replicate the actions of cars. Automobile density analysis in real-time at crossings establishes the degree of congestion, which is used in adaptive manipulate good judgment to adjust the visitors sign timings dynamically. The current system of comments makes sure that busier lanes of the site are given a longer green cycle, despite the fact that much less congested lanes remain on a normal time frame. The design allows to push the simulation-based optimisation of software programs with the visitors without the necessity of physical sensors and IoT devices, enhancing performance and reducing delays.

A) Traffic Network Modeling and Vehicle Generation:

The layout of the site visitors community is the first step which includes the junctions, lanes, and the placement of signals in the SUMO simulation environment. Hooked up are vehicle classifications, lane potential and standard green mild intervals (10 seconds). Vehicles are dynamically generated mainly using the arrival fees to emulate the actual traffic scenarios which contain both top and stale-height phenomena. This modelling and automobile technology, phase bureaucracy forms the foundation of the simulation and allows particular evaluation of the traffic waft and adaptive sign management.

B) Traffic Density Detection:

In this section, the actual-time observation of car queues on each junction will be highlighted by SUMO lane or edge detectors. The method measures the number of desk bound cars and the use of lanes to measure the density of the visitors to the site. High density lanes are unique in prioritised processing. This specific identity of congestion is essential so that the adaptive controller can make informed decisions and ensure that the timing of the sign changes reduce the number of waits and ensure that the less trafficked lanes are not unfairly slowed. This is the much needed enter of the dynamic manage algorithm.

C) Adaptive Signal Control Algorithm:

The method of adaptive manage, written in Python is a dynamically changing period of green mild based on the observed density of site visitors. In case of automobile waits exceeding installed standards the green lights are extended with up to 15 seconds followed by returning to 10 seconds as the traffic reduces. This action will improve the efficiency of traffic, reduce the number of waits, and will reduce fuel consumption. The constant changes during each stage of simulation ensure impartiality of lanes and the skillful response to the instances of variable visitors.

D) Integration and Simulation Execution:

The manage approach mostly built in Python is coupled with SUMO through TraCI API to modify signals in real-time. Traffic images can adjust in real-time to vehicles as congestion in each intersection and the simulation functions in a never-ending cycle to simulate continuous traffic flow at the sites. SUMO GUI provides visualisation of the signal changes and drift of vehicles in real-time. This phase authenticates the gadget interior a controlled virtual putting before any actual-global deployment so as to ensure robust and reconfigurable traffic control.

E) Performance Evaluation and Iterative Testing:

To measure performance, simulation effects, which include automobile waiting times, queue lengths and green signal intervals are analyzed. There are different traffic scenarios such as low, medium and excessive traffic and the thresholds are used and readjusted multiple times to achieve maximum glide. Measures of performance and average put off and throughput are calculated to measure the gadget efficacy. This constituent ensures that the adaptive traffic controller is resilient, scalable and gifted in improving the urban visitors flow with the traffic compared with the traditional fixed signal or non-adaptable systems.

IV. EXPERIMENTAL RESULTS

To execute the simulation, double-click on the 'run.bat' file to see the following page shown in Fig.2.



Fig.2 SUMO Simulation Environment

Click the 'Run Propose SUMO Simulation' button on the top screen to access the subsequent page shown in Fig.3.




Fig.3 SUMO Simulation Environment in 1st Iteration

on the simulation seen above, the green signal duration values decrease from 10 to 0 at each light. As traffic increases, the time subsequently rises to 15, as illustrated in Fig.4.





Fig.4 SUMO Simulation Environment in High Traffic Density

In the screen above, the upper right corner indicates that more cars are waiting, resulting in an increase of the green time to 15 seconds, which decreases by one second until it reaches 12. Once it reaches zero, the opposing direction will get the green time, as seen on Fig.5.



Fig.5 SUMO Simulation Environment in Further Iterations

The screen displays another signal that has a green indication.



In the screen's bottom right, further cars are queued, causing the green signal duration to decrease from 15 to 14 to 0 until all vehicles have departed. During the execution of the aforementioned scenario, the duration of the green signal fluctuates dynamically between 10 and 15 seconds as seen on Fig.6.

The aforementioned simulation will execute in an indefinite loop; to terminate the program, just click the 'Windows' key on the keyboard and thereafter quit the application.

V. CONCLUSION

The suggested Smart Traffic Light Controller efficaciously optimises urban visitors waft through simulation-primarily based adaptive sign law. In assessment to standard static site visitors mild structures that characteristic on predetermined time cycles, regularly main to extended wait times and excessive fuel use, the newly created gadget dynamically modifies inexperienced sign lengths consistent with real-time traffic density. The controller, advanced in Python and paired with the SUMO simulation surroundings, oversees vehicle queues at junctions, extending green light period for busy lanes and returning to traditional timings whilst visitors diminishes. The outcomes of simulation have significant enhancement of car throughput, waiting time, and stepped forward lane utilisation balance, which highlights the effectiveness of adaptive manipulate in realistic site visitors control. The modular design of the device allows it to adjust to different visitor conditions of the site, including top and stale-height, and provides a scalable foundation to introduce future upgrades, as well as the integration of IoT-based devices of the sensors primarily of the traffic or machine gaining knowledge of algorithms. This measure provides an effective, green and green solution to congestion of people at the urban visitor levels, contributes to the enhancement of additional wiser and adaptive transport systems.

The Smart Traffic Light Controller may also be enhanced with such means as real-time IoT sensors, camera-based vehicle identification, as those may be used to support the precision of traffic monitoring. The next improvements can include the mingling of device getting to know algorithms to foresee visitor control of emergency automobiles, adaptive prioritisation of metropolis massive optimisation in a significant number of crossroads. Moreover, more extensive expansion of the gadget to accommodate multimodal site users, such as pedestrians, bicycles, and public transport, can further significantly enhance mobility of the city, reduce traffic jams, and environmental impact, hence visitors management can become more reasonable and sustainable.

REFERENCES

- [1] Lee, W. H., & Chiu, C. Y. (2020). Design and implementation of a smart traffic signal control system for smart city applications. *Sensors*, 20(2), 508.
- [2] Shenbagavalli, S., Priyadharshini, T., Sowtharya, S., Manikandan, P., & Saravanan, D. S. (2020). Design and implementation of smart traffic controlling system. *International Journal of Engineering Technology Research & Management*, 4(4), 28-36.
- [3] De Oliveira, L. F. P., Manera, L. T., & Da Luz, P. D. G. (2020). Development of a smart traffic light control system with real-time monitoring. *IEEE Internet of Things Journal*, 8(5), 3384-3393.
- [4] Alaidi, A., Aljazeera, I., Alrikabi, H., Mahmood, I., & Abed, F. (2020). Design and implementation of a smart traffic light management system controlled wirelessly by arduino.

- [5] Oliveira, L. F. P. D., Manera, L. T., & Luz, P. D. G. (2019, October). Smart traffic light controller system. In 2019 Sixth International Conference on Internet of Things: Systems, Management and Security (IOTSMS) (pp. 155-160). IEEE.
- [6] Alkawgani, A. H. M., & Alkawgani, A. H. M. (2018). Design of real time smart traffic light control system. *Int. J. Ind. Electron. Electr. Eng.*, 6(4), 43-47.
- [7] Díaz, N., Guerra, J., & Nicola, J. (2018, October). Smart traffic light control system. In 2018 IEEE Third Ecuador Technical Chapters Meeting (ETCM) (pp. 1-4). IEEE.
- [8] Ghazal, B., ElKhatib, K., Chahine, K., & Kherfan, M. (2016, April). Smart traffic light control system. In 2016 third international conference on electrical, electronics, computer engineering and their applications (EECEA) (pp. 140-145). IEEE.
- [9] Bhairi, M. N., Kangle, S. S., Edake, M. S., Madgundi, B. S., & Bhosale, V. B. (2017, May). Design and implementation of smart solar LED street light. In 2017 International Conference on Trends in Electronics and Informatics (ICEI) (pp. 509-512). IEEE.
- [10] Bobyr, M. V., Khrapova, N. I., & Lamonov, M. A. (2021). Smart traffic light control system based on fuzzy logic. *Юго-Западного государственного университета*, 163.
- [11] Bhatia, M. S., Aggarwal, A., & Kumar, N. (2020). Smart traffic light system to control traffic congestion. *PalArch, s journal of Archaeology of Egypt/Egyptology (PJAEE)*.
- [12] Mohamed, N. E., & Radwan, I. I. (2022). Traffic light control design approaches: a systematic literature review. *International Journal of Electrical & Computer Engineering* (2088-8708), 12(5).
- [13] Albatish, I. M., & Abu-Naser, S. S. (2019, October). Modeling and controlling smart traffic light system using a rule based system. In 2019 International Conference on Promising Electronic Technologies (ICPET) (pp. 55-60). IEEE.
- [14] Gadawe, N. T., & Qaddoori, S. L. (2019). Design and implementation of smart traffic light controller using VHDL language. *International Journal of Engineering & Technology*, 8(4), 596-602.
- [15] Hawi, R., Okeyo, G., & Kimwele, M. (2017, July). Smart traffic light control using fuzzy logic and wireless sensor network. In 2017 Computing Conference (pp. 450-460). IEEE.
- [16] Udoakah, Y. N., & Okure, I. G. (2017). Design and implementation of a density-based traffic light control with surveillance system. *Nigerian Journal of Technology*, 36(4), 1239-1248.
- [17] Albagul, A., Hamed, H., Naji, M., Asseni, A., & Zaragoun, A. (2012). Design and fabrication of a smart traffic light control system. In 3rd International conference Informatics and Computing Theory (AICT'12). Barcelona, Spain.
- [18] Karakuzu, C., & Demirci, O. (2010). Fuzzy logic based smart traffic light simulator design and hardware implementation. *Applied Soft Computing*, 10(1), 66-73.
- [19] Singh, S., & Badwaik, S. C. (2011, April). Design and implementation of FPGA-based adaptive dynamic traffic light controller. In 2011 International Conference on Emerging Trends in Networks and Computer Communications (ETNCC) (pp. 324-330). IEEE.
- [20] Chavan, S. S., Deshpande, R. S., & Rana, J. G. (2009, December). Design of intelligent traffic light controller using embedded system. In 2009 Second International Conference on Emerging Trends in Engineering & Technology (pp. 1086-1091). IEEE.