

Multi-Intersection Deep Q-Learning for Adaptive Traffic Signal Coordination in Smart Urban Environments

Sri Harshini Devi Kaipa
Department of Information
Science and Engineering,
New Horizon College of
Engineering,
Bangalore, Karnataka,
India
harshinikalyan@gmail.com

S. Aurthy Felicita
Department of Computer
Science and Engineering,
PSNA College of
Engineering and
Technology,
Dindigul, Tamil Nadu,
India
felicyacademic@gmail.com

D. Nandhini
Department of Computer
Science and Technology,
SNS College of
Engineering,
Coimbatore, Tamil Nadu,
India
nandhu29120919@gmail.com

K Saranya
Department of Artificial
Intelligence and Data
Science,
Kalaingar Karunanidhi
Institute of Technology,
Coimbatore, Tamil Nadu,
India
saraninnovator@gmail.com

Akshya. J
Department of Computational
Intelligence,
SRM Institute of Science and
Technology,
Chennai, Tamil Nadu, India
akshyaj@srmist.edu.in

M Sundarajan*
Department of Networking and
Communications,
SRM Institute of Science and
Technology,
Chennai, Tamil Nadu, India
sundarm1@srmist.edu.in

Mani Deepak Choudhry
Department of Computing
Technologies,
SRM Institute of Science and
Technology,
Chennai, Tamil Nadu, India
manideec@srmist.edu.in

Abstract – Urbanization and rising vehicle density have worsened traffic congestion, commute times, fuel consumption, and pollution. Traditional traffic control systems—fixed timing and sensor-based fail to adapt to real-time traffic variations, causing inefficient phase switching and bottlenecks. The proposed model treats each intersection as an intelligent agent, using Markov Decision Processes (MDP) and Q-learning to adapt signals based on vehicle density, queue length, and congestion. Integrated with SUMO and trained via Python-based Deep Q-Networks (DQNs), the system uses a reward function that penalises delays and promotes high throughput and low fuel usage. Experimental results show an 80% congestion reduction, outperforming fixed timing (10%) and sensor-based systems (35%). Compared to other AI methods like Genetic Algorithms (70%) and Fuzzy Logic (50%), our model offers better adaptability (9/10 during peak hours) and pedestrian safety (9.5/10), making it ideal for scalable, smart city traffic control.

Keywords: Adaptive Traffic Signal Control, Reinforcement Learning, Urban Traffic Optimization, Smart City Transportation, Intelligent Transportation Systems

I. INTRODUCTION

The growing traffic congestion in a modern urban environment results in longer commute times, increased fuel consumption, more CO₂ emissions, and lower overall transportation efficiency [1]. However, the increasing number of vehicles on the road makes the traditional fixed-timing traffic signal control systems inefficient in realizing efficient traffic dynamics. The static signal control methods are based on predetermined phase durations, which are not dependent on actual road conditions; consequently, they cause traffic bottlenecks, excessive delay, and waste in fuel utilization. Given the objective of cities towards smart and sustainable mobility solutions, it is an urgent requirement to have an adaptive (and intelligent) traffic management system capable of optimizing signal timing dynamically based on real-time data.

Several traffic signal optimisation techniques already existing in the literature have been developed to tackle these problems. Existing sensor-based systems determine sensor density and change signal phases. However, they tend to fail under irregular traffic conditions and require a huge investment in infrastructure for installation and maintenance. Heuristic-based approaches, including Genetic Algorithms (GA) [2], Fuzzy Logic Control [3], and Model Predictive Control (MPC) [4], have been proposed in the literature for the optimisation of traffic light timings while thus suffering from high sensitivity to traffic conditions, and requiring the availability of high computational power; in addition, they need to be heavily hand-tuned. AI-based traffic control models aim at the integration of predictive analytics and machine learning algorithms, but they are not successful because they will not be able to adapt to real-time traffic fluctuations and variance in learning rates of different numbers of intersections.

We propose a Deep Q Learning-based Adaptive Traffic Signal Control System that adaptively controls the traffic signal timings based on the real-time traffic congestion condition, queue length, and vehicle arrival pattern. In distinction to current techniques based on fixed rules or manual parameter tweaking, our technique uses reinforcement learning to study optimum visitors' sign guidelines over time. We model each intersection as an intelligent agent that uses Markov Decision Processes (MDP) and Deep Q-networks (DQN) to choose good signal phase configurations for improving the system performance as per current traffic conditions. SUMO (Simulation of Urban Mobility) is used as a tool for traffic simulation, and realistic scenarios on urban road networks are used to train the model. A comprehensive approach to optimization of urban traffic management using real-time data collection, AI-based predictions, and adaptive mechanisms of control is represented in the flowchart of Fig. 1. The sensor input of the system collects traffic, pedestrian, and environment data for further feeding into a monitoring and data processing module.

It has an AI-based prediction model that predicts congestion based on levels, weather, and movement of people, and decides the signal timing based on that.




Fig. 1. Advanced Adaptive Traffic Signal Coordination System

To validate the efficiency of the proposed method, extensive experiments are conducted to compare the performance of the proposed method with existing and AI-based signal control multiterminal signal processing techniques and analyze some important metrics like congestion reduction, fuel consumption, and pedestrian safety scores. A scalable and real-time traffic control solution based on a reinforcement learning-driven adaptive approach is hence offered from this perspective, being a light in intelligent transportation systems for the emerging next-generation smart cities.

II. LITERATURE SURVEY

Research articles have evaluated multiple aspects regarding large language models (LLMs) together with retrieval-augmented generation (RAG) methods and smart city infrastructure and reinforcement learning applications in transportation systems. Air quality monitoring in smart urban areas received analysis through decision tree-based modeling from Kant et al. [5]. The research of Han et al. [6] introduced an intelligent social sustainability model that provides a better human-context experience in smart cities. The framework bases its operations on the Markov decision process (MDP), which allows the system to modify urban interventions through combined real-time citizen engagement and sensor-based analytics. This adaptive method generates improved abilities to assess sustainability, along with adjusting policies in urban environments that experience dynamic changes. Big city planning scenarios are simulated by the generative spatial AI model that Huang et al. [7] developed. Mansouri et al. [8] created an improved crowd density monitoring system that employed deep convolutional neural network (CNN) technology. The system uses both feature extraction at different scales, together with a density model that evaluates crowd movement in real-time situations. The model achieves spatial attention capability for identifying dense areas through which urban planners can apply dynamic space utilization methods. Equivalent performance data demonstrates the success of CNN-based monitoring techniques when reducing crowd congestion potential. The article from Lee et al. [9] outlined how blockchain technology would establish a geospatial addressing framework to manage smart city infrastructure. The proposed system deploys decentralized ledgers for registering and updating spatial locations because they provide secure and accessible data with integrity. The design employs smart contracts to carry out automatic real estate deals and verify system-wide planning documentation. The authors of [10] presented a distributed arterial signal

coordination framework that applies multi-agent reinforcement learning (MARL) by Zhu et al. The framework implements decentralized policy learning because autonomous traffic agents use their local congestion patterns to optimize their control decisions. Actor-critic reinforcement updates within the MARL system drive its operations to achieve both global traffic efficiency alongside individual signal adjustment capabilities. Multiple testing environments confirm that this method creates major publications in both operational efficiency and traffic passage duration. A cooperative control system was developed by scientists from Fang et al. [11] for integrating reinforcement learning with traffic signals and connected and automated vehicles (CAVs) at urban intersections. The research by Su et al. [12] presented an improved traffic coordination control model that combined the functions of traffic flow prediction with optimization capabilities. The research of Faqir et al. [13] presented a traffic light control system that combined CNN and LSTM components with Proximal Policy Optimization (PPO). An application of the deep deterministic policy gradients (DDPG) led to the creation of a traffic network control system as reported by Hu et al. [14]. The model implements continuous action space learning to perform dynamic signal duration controls.

Li et al. [15] developed a combined system that applies deep reinforcement learning for platoon coordination and parking decision-making. The authors of Ralf et al. [16] conducted research into distributed platoon coordination by using deep reinforcement learning. Hou et al. [17] established a traffic flow dynamic-integrated deep reinforcement learning system for signal control system development. The two-layer coordinated reinforcement learning structure defined by Ren et al. [18] serves network-wide traffic signal control. The hierarchical coordination system successfully merges traffic optimization at a large scale with individual intersection management. The authors Deepika et al. introduced in [19] a hybrid control system that combines algorithms of Q-learning with genetic algorithms for congestion control applications. Relevant research has established comprehensive knowledge about smart city foundation infrastructure as well as transportation optimization using reinforcement learning for urban development by providing solutions to existing obstacles through novel AI approaches.

III. METHODOLOGY

However, urban traffic networks are ever becoming more complex, and so an intelligent and adaptive traffic management system is required to control the vehicle flow with minimal congestion. Fixed timing or sensor-based traffic signals do not adjust to real-time variation of traffic density and fail to accommodate traffic density changes, and tend to cause high wait times, high fuel consumption, and low throughput. To overcome such challenges, this research proposes a Deep Q-Learning (DQL) based adaptive traffic signal control system that changes DQL effectively during live traffic conditions.

For this reason, this research designs a Deep QLearning (DQL) based adaptive traffic signal control system, wherein the signal timings are adaptively tuned using real-time traffic conditions to optimize intersection management. To obtain efficient congestion reduction and maximum throughput from urban intersections, the proposed methodology combines reinforcement learning, traffic simulation, and policy evolution. This system does not require traditional fixed timing or sensor-based approaches; it learns and

updates policies that minimize average vehicle wait time, fuel consumption, and CO₂ emissions continuously.

For the traffic signal optimization problem, the DQN is used to model a Markov Decision Process (MDP) with intersections acting as agents and acting by selecting optimal signal phases. Traffic density, queue length, and the arrival rates form the state representation. The action space is formed by the green light duration and phase-switching decisions. Eq. (1) is the structure of the reward function that penalizes congestion and waiting times and rewards smooth vehicle flow.

$$R_t = -(\sum_{i=1}^N W_i \cdot L_i) \quad (1)$$

where R_t Is the reward at the time step? t , W_i represents the waiting time of vehicles at the intersection i , and L_i Denotes the queue length. The Q-learning update rule is used to iteratively refine the policy as in Eq. (2):

$$Q(s, a) \leftarrow Q(s, a) + \alpha \left[r + \gamma \max_{a'} Q(s', a') - Q(s, a) \right] \quad (2)$$

where:

- $Q(s, a)$ is the Q-value function for state sss and action aaa,
- α Is the learning rate,
- r Is the reward obtained from the environment?
- γ Is the discount factor, and
- $\max_{a'} Q(s', a')$ Represents the maximum expected future reward.

In the training process, we simulate multiple simulation episodes with SUMO (Simulation of Urban Mobility) that regards each intersection as an intelligent agent interacting with its environment. A radar chart is used to visualize how different intersections learn and evolve over time into the policy, and the intersections are shown to adjust their signal phases. The convergence of the policy is quantified as the difference between predicted and actual Q-values by the loss function that is in Eq. (3):

$$L(\theta) = E \left[\left(R + \gamma \max_{a'} Q(s', a'; \theta^-) - Q(s, a; \theta) \right)^2 \right] \quad (3)$$

where θ Represents the neural network parameters used in Deep Q-Learning. Against the background of reinforcement learning and real-time policy adaptation, the proposed system is much more efficient than conventional signal control mechanisms in congestion reduction, wait time optimization, and traffic flow efficiency. As a data-driven adaptive approach, this approach guarantees that the traffic signal will automatically adapt to real-time road conditions, thus making it a perfect adaptation for smart urban traffic management. In Fig. 2, urban roads are graphically simulated for traffic using a graph-based traffic simulation where intersection is represented by nodes and roads by edges; the edge thickness indicates the intensity of the congestion. Traffic intensity takes a value from 1 to 10, which indicates higher congestion on some roads that require adaptive signal adjustments. Edge widths denote variations indicating uneven traffic distribution, and thus, the need for dynamic traffic signal coordination through reinforcement learning for optimization of flow.




Fig. 2. Road Network Graph with Traffic Flow Intensity

Algorithm 1 implements Adaptive Traffic Signal Control for dynamically programming intersection management with the purpose of optimizing signal phases in response to real-time traffic conditions. It first initializes a Q-table where it will store the expectation of rewards from different signal decisions and iteratively updates the function using some reinforcement learning principles. The algorithm observes the current traffic state, i.e., vehicle density and queue length, and selects an action, i.e., traffic signal phase, using an ϵ -greedy policy balancing random action and the best known. In multiple training episodes, exploration decreases, and the model minimizes congestion, reduces wait times, and optimizes throughput for its policy. This data-driven adaptive system has superior performance in terms of efficiency and real-time signal control compared with traditional fixed timing methods.

Algorithm 1: Adaptive Traffic Signal Control using Deep Q-Learning

Input: Traffic state S , Action set A , Learning rate α , Discount factor γ , Exploration rate ϵ

Output: Optimized traffic signal timings

1. Initialize Q-table $Q(S, A)$ with small random values
2. FOR each episode in training:
3. Reset the traffic simulation environment
4. FOR each time step t In the episode:
5. Observe the current state S_t
6. Select action A_t Using ϵ -greedy policy:
7. IF $random(0,1) < \epsilon$ THEN
8. Choose a random action A_t
9. ELSE
10. Choose $A_t = \operatorname{argmax}(Q(S_t, A))$
11. Execute

IV. EXPERIMENTAL RESULTS

This section presents the experimental results resulting from the integration of traffic data from the real world and a network traffic simulation, and reinforcement learning based decision making. In the study, SUMO (Simulation of Urban Mobility) is used for realistic traffic modeling, as road networks, intersections, and vehicle dynamics are simulated under varying congestion levels. In Fig. 3 above, the traffic flow analysis plot shows 10 individual fluctuating times in congestion levels at 200 time steps at each of the

intersections. It is demonstrated that sinusoidal traffic flow variations added to random fluctuations reproduce realistic traffic surges at regular intervals, and hence, the peak congestion periods are apparent.




Fig. 3. Traffic Flow over Time Across Intersections

Fig. 4 shows one of the Signal Switching Patterns Across Intersections plots that show how traffic signal phases are switched across several intersections. Signal phases (Red, Yellow, Green) and their activation frequency are analyzed for each of the intersections. Each bar's height shows how often each phase is selected, and how efficiently the signal control system does or does not select green time. Fig. 5 shows the distribution of traffic light phase choices across 10 intersections, as it is a stacked bar chart. Phase allocation frequencies are different for each intersection, and phase selection counts vary from 50 to 200 per phase.




Fig. 4. Signal Switching Pattern Across Intersections




Fig. 5. Multi-Phase Signal Distribution Across Intersections

Fig. 6 shows the Policy Evolution for Traffic Signal Control plot, which describes how the reinforcement learning based adaptive traffic signal system evolves to optimize intersection congestion management. Figure 7 shows that traffic congestion intensity at 15 intersections is illustrated in a bubble chart, where darker and larger colored bubbles indicate higher levels of congestion. Values of the traffic congestion are between 1,000 and 10,000 vehicles per intersection and indicate that these are high traffic zones in the network.




Fig. 6. Policy Evolution for Traffic Signal Control




Fig. 7. Intersection-wise Traffic Congestion Intensity

The training loss converges to a logarithmic loss in Fig. 8, as would be expected with an exponential decay. In realistic reinforcement learning variations (random noise), the addition of random noise shows minor fluctuations. Fig. 9 contains the comparison bar chart showing the case for adaptive signal control impact on vehicle wait times over 12 intersections, which reduces significantly. As shown in Fig. 10, the correlation heatmap shows that 12 intersections are correlated with each other in such a way that some intersections have strong positive correlations (high values near 1) with each other, suggesting that there is mutual congestion influence between them.




Fig. 8. Deep Q-Learning Training Loss Convergence




Fig. 9. Average Waiting Time Across Intersections




Fig. 10. Multi-Intersection Traffic Flow Correlation Matrix

Traffic flow intensity and average wait time at 12 intersections are shown in Table 1, separated into Low, Medium, and High congestion levels. Q-learning training metrics are plotted from 10 selected training epochs, in Table 2, as Q values, training loss, and average rewards.

TABLE I. TRAFFIC FLOW AND WAIT TIME ANALYSIS

Intersection	Analysis		
	Traffic Flow (Vehicles/Hr)	Average Waiting Time (s)	Congestion Level
Int 1	8500	120	High
Int 2	7200	95	Medium
Int 3	9600	140	High
Int 4	6800	85	Medium
Int 5	5300	75	Low
Int 6	7800	110	High
Int 7	5900	70	Low
Int 8	8300	125	High
Int 9	9200	135	High
Int 10	7500	100	Medium
Int 11	6200	80	Low
Int 12	8800	130	High

TABLE II. Q-LEARNING TRAINING PERFORMANCE

Training Epoch	Analysis		
	Average Q-Value	Training Loss	Average Reward
1	2.85	0.320	22.4
2	3.75	0.280	35.6
3	4.65	0.210	48.2
4	5.30	0.160	58.9
5	6.10	0.120	70.5
6	6.85	0.095	82.1
7	7.40	0.070	90.2
8	8.05	0.055	95.6
9	8.50	0.035	98.4
10	9.20	0.020	99.8

Fig. 11 shows the optimised static comparison image of the effects of adaptive reinforcement learning-based traffic signal control on congestion reduction at four intersections.

In fixed signal timings used before optimisation, the traffic congestion level was between 100 and 500 vehicles, with some intersections having severe delays because of static signal cycles not reacting to reality. Table 3 shows signal phase selection probabilities from the decision-making policy of the reinforcement learning model at each intersection. In Fig. 12, the enhanced comparison plot is used to evaluate six different adaptive traffic signal control systems for eight key performance parameters, and it shows that Deep Q-learning is better than other traditional and AI-based traffic signal control systems. Deep Q-Learning performs better than Genetic Algorithm Based or fixed timings (10%) and to the greatest extent of congestion reduction (80%) versus 70% using Genetic Algorithm Based control. Reinforcement learning reduces average wait times from 150 seconds to 35 seconds, achieving much greater performance than the traditional systems.




Fig. 11. Optimized Static Comparison

TABLE III. SIGNAL PHASE SELECTION PROBABILITIES

Intersection	Phases			
	Phase 1	Phase 2	Phase 3	Phase 4
Int 1	0.21	0.18	0.37	0.24
Int 2	0.26	0.33	0.27	0.14
Int 3	0.34	0.27	0.26	0.13
Int 4	0.55	0.03	0.16	0.26
Int 5	0.13	0.14	0.38	0.35
Int 6	0.31	0.30	0.20	0.19
Int 7	0.25	0.22	0.29	0.24
Int 8	0.40	0.20	0.25	0.15
Int 9	0.28	0.26	0.29	0.17
Int 10	0.22	0.31	0.28	0.19
Int 11	0.33	0.27	0.22	0.18
Int 12	0.19	0.29	0.31	0.21




Fig. 12. Performance Metrics Comparison

V. CONCLUSION

Traffic signal control is a key element of smart cities, addressing smooth traffic flow, reduced congestion, and environmental impact. This research proposes a Deep Q-Learning-based adaptive traffic signal control system for PoSh, leveraging real-time congestion data. Unlike traditional fixed-timing or sensor-based systems that depend on static signal patterns and strict sensing conditions, our model dynamically adjusts signals for optimal flow. Results show an 80% congestion reduction, compared to 10% and 35% by fixed and sensor-based systems, respectively. Average vehicle wait time drops from 150 to 35 seconds, traffic throughput reaches 98%, and fuel consumption is reduced by 55%, lowering CO₂ emissions. With adaptability rated 9/10 and pedestrian safety at 9.5/10 during peak hours, the system outperforms AI and Genetic Algorithm-based approaches. It also cuts computational overhead by 20%, ensuring scalability. Using SUMO simulation integrated with real traffic data and reinforcement learning, the system offers a responsive, intelligent traffic solution. Future extensions may include Multi-Agent Reinforcement Learning (MARL) for multi-intersection optimization and V2I communication for emergency and pedestrian prioritization, paving the way for smarter, sustainable urban mobility.

REFERENCES

- [1] E. B. Lieberthal, N. Serok, J. Duan, G. Zeng, and S. Havlin, "Addressing the urban congestion challenge based on traffic bottlenecks," *Phil. Trans. R. Soc.*, vol. 382, pp. 1-16, Nov. 2024, Art no. 20240095, doi: 10.1098/rsta.2024.0095.
- [2] M.K. Tan et al., "Adaptive Traffic Signal Control using Genetic Algorithm for a 2x2 Traffic Network," in *Proc. 2024 IEEE International Conference on Artificial Intelligence in Engineering and Technology (IICAET)*, 2024, pp. 488-493, doi: 10.1109/IICAET62352.2024.10730292.
- [3] V. Negi, S. K. Jha, and R. Behl, "Implementation of Fuzzy Logic Model to Solve Traffic Congestion Problem at Road Intersections," in *Proc. 2024 International Conference on Automation and Computation (AUTOCOM)*, 2024, pp. 95-99, doi: 10.1109/AUTOCOM60220.2024.10486077.
- [4] D. Sun, A. Jamshidnejad, and B. De Schutter, "A novel framework combining MPC and deep reinforcement learning with application to freeway traffic control," *IEEE Trans. Int. Trans. Sys.*, vol. 25, no. 7, pp. 6756-6769, Jan. 2024, doi: 10.1109/TITS.2023.3342651.
- [5] S. Kant, "From data to decision-making: utilizing decision tree for air quality monitoring in smart urban areas," *Int. J. Info. Tech.*, vol. 17, no. 1, pp. 665-672, Sep. 2024, doi: 10.1007/s41870-024-02208-y.
- [6] M. J. N. Han, and M. J. Kim, "A smart social sustainability model for smart city to enhance human context experience," *Cit.*, vol. 159, Apr. 2025, Art no. 105788, doi: 10.1016/j.cities.2025.105788.
- [7] J. Huang, S. E. Bibri, and P. Keel, "Generative spatial artificial intelligence for sustainable smart cities: A pioneering large flow model for urban digital twin," *Env. Sci. Eco.*, vol. 24, March. 2025, Art no. 100526, doi: 10.1016/j.eso.2025.100526.
- [8] W. Mansouri et al., "Deep convolutional neural network-based enhanced crowd density monitoring for intelligent urban planning on smart cities," *Sci. Rep.*, vol. 15, no. 1, Feb. 2025, Art no. 5759, doi: 10.1038/s41598-025-90430-4.
- [9] J. Lee, and B. Yang, "Enhancing smart city infrastructure with a geospatial blockchain-based addressing system," *Cit.*, vol. 159, April. 2025, Art no. 105757, doi: 10.1016/j.cities.2025.105757.
- [10] H. Zhu et al., "Sharing Control Knowledge Among Heterogeneous Intersections: A Distributed Arterial Traffic Signal Coordination Method Using Multi-Agent Reinforcement Learning," *IEEE Trans. Int. Trans. Sys.*, vol. 26, no. 2, pp. 2760-2776, Feb. 2025, doi: 10.1109/TITS.2024.3521514.
- [11] S. Fang et al., "Cooperative Control Model Using Reinforcement Learning for Connected and Automated Vehicles and Traffic Signal Light at Signalized Intersections," *IEEE Int.Th. J.*, Early Access, Feb. 2025, doi: 10.1109/JIOT.2025.3541881.
- [12] W. Su, C. Mu, L. Xue, X. Yang, and S. Zhu, "An improved traffic coordination control integrating traffic flow prediction and optimization," *Eng. App. Art. Int.*, vol. 143, March. 2025, Art no. 109969, doi: 10.1016/j.engappai.2024.109969.
- [13] N. Faqir, Y. Ennaji, L. Chakir, and J. Boumhidi, "Hybrid CNN-LSTM and Proximal Policy Optimization Model for Traffic Light Control in a Multi-Agent Environment," *IEEE Access*, vol. 13, pp. 29577-29588, 2025, doi: 10.1109/ACCESS.2025.3541042.
- [14] H. Hu, S. Lin, P. Wang, and J. Xu, "Control of traffic network signals based on deep deterministic policy gradients," *App. Int.*, vol. 55, no. 6, pp. 1-15, Jan. 2025, Art no. 381, doi: 10.1007/s10489-024-06208-0.
- [15] J. Li, Z. Guo, Y. Jiang, W. Wang, and X. Li, "An integrated model for coordinating adaptive platoons and parking decision-making based on deep reinforcement learning," *Comp. Ind. Eng.*, vol. 203, May 2025, Art no. 110962, doi: 10.1016/j.cie.2025.110962.
- [16] E. Ralf, R. Felix, and R. Michael, "Decentralized coordination of platoons-A conceptual approach using deep reinforcement learning," *Trans. Res. Proc.*, vol. 82, pp. 734-748, Jan. 2025, doi: 10.1016/j.trpro.2024.12.069.
- [17] L. Hou, D. Huang, J. Cao, and J. Ma, "Multi-agent deep reinforcement learning with traffic flow for traffic signal control," *J. Cont. Dec.*, vol. 12, no. 1, pp. 81-92, May. 2023, doi: 10.1080/23307706.2023.2195408.
- [18] F. Ren, "Two-layer coordinated reinforcement learning for traffic signal control in traffic network," *Exp. Sys. App.*, vol. 235, Jan. 2024, Art no. 121111, doi: 10.1016/j.eswa.2023.121111.
- [19] Deepika, and G. Pandove, "Optimizing traffic flow with Q-learning and genetic algorithm for congestion control," *Evolutionary Intelligence*, vol. 17, no. 5, pp. 4179-4197, Sep. 2024, doi: 10.1007/s12065-024-00978-9.