



```
GNU nano 7.2 /etc/elasticsearch/elasticsearch.yml
# The following settings, TLS certificates, and keys have been automatically
# generated to configure Elasticsearch security features on 21-03-2025 18:12:19
#
# -----

# Enable security features
xpack.security.enabled: false

xpack.security.enrollment.enabled: true

# Enable encryption for HTTP API client connections, such as Kibana, Logstash, and Agents
xpack.security.http.ssl:
  enabled: false
  keystore.path: certs/http.p12

# Enable encryption and mutual authentication between cluster nodes
xpack.security.transport.ssl:
  enabled: true
  verification_mode: certificate
  keystore.path: certs/transport.p12
  truststore.path: certs/transport.p12
# Create a new cluster with the current node only
# Additional nodes can still join the cluster later
cluster.initial_master_nodes: ["elasticsearch1"]

# Allow HTTP API connections from anywhere
# Connections are encrypted and require user authentication
http.host: 0.0.0.0

# Allow other nodes to join the cluster from anywhere
# Connections are encrypted and mutually authenticated
#transport.host: 0.0.0.0

#----- END SECURITY AUTO CONFIGURATION -----
█

^G Help      ^O Write Out ^W Where Is  ^K Cut       ^I Execute   ^C Location  M-U Undo     M-A Set Mark M-J To Bracket M-Q Previous
^X Exit      ^R Read File ^\ Replace   ^U Paste     ^J Justify   ^_ Go To Line M-E Redo     M-G Copy      ^Q Where Was  M-W Next
```