CS 3205 COMPUTER NETWORKS

JAN-MAY 2020

LECTURE 9: 6TH FEB 2020

Text book and section(s) covered in this lecture:
Book Kurose and Ross – Sections 5.3, 5.4

Cable networks

Section 5.3.4

Cable access network

Data-Over-Cable Service Interface Specification (DOCSIS)



- *multiple* 40Mbps downstream (broadcast) channels – FDM used
  - single CMTS transmits into channels – no multi access problem
- *multiple* 30 Mbps upstream channels – FDM
  - *multiple access: all* users contend for certain upstream channel time slots (others assigned) – TDM within a channel.

Cable access network



DOCSIS: data over cable service interface spec

- FDM over upstream, downstream frequency channels
- TDM upstream: some slots assigned, some have contention
  - downstream MAP frame: assigns upstream slots
  - request for upstream slots (and data) transmitted random access (binary backoff) in selected slots

ARP – some additional aspects

Section 5.4.1

A typical ARP Table

Internet Address	Physical Address	Type
169.254.19.59	a4-93-4c-dd-a7-cd	dynamic
172.30.61.129	a4-93-4c-dd-a7-cd	dynamic
172.30.61.255	ff-ff-ff-ff-ff-ff	static
224.0.0.22	01-00-5e-00-00-16	static
224.0.0.251	01-00-5e-00-00-fb	static
224.0.0.252	01-00-5e-00-00-fc	static
239.255.255.250	01-00-5e-7f-ff-fa	static
255.255.255.255	ff-ff-ff-ff-ff-ff	static

- Address 224.0.0.22 – IGMPv3 protocol
- Address 224.0.0.251 – Multicast DNS
- Address 224.0.0.252 – Link local multicast name resolution protocol (LLMNR)
- Address 239.255.255.250 – Simple Service Discovery Protocol – A protocol for advertise and discovery of network services and presence information.
- Address 255.255.255.255 – Broadcast to all nodes in that network
- STATIC address type are fixed. They don't need ARP. ARP is used for addresses, which are dynamic

ARP Wireshark – check / Demo

Link Layer - Ethernet

Section 5.4.2

Ethernet

"dominant" wired LAN technology:

- cheap $20 for NIC
- first widely used LAN technology
- simpler, cheaper than token LANs and ATM
- kept up with speed race: 10 Mbps – 10 Gbps



Metcalfe's Ethernet sketch

Ethernet: physical topology

- *bus:* popular through mid 90s
  - all nodes in same collision domain (can collide with each other)
- *star:* prevails today
  - active *switch* in center
  - each "spoke" runs a (separate) Ethernet protocol (nodes do not collide with each other)



bus: coaxial cable



star

Ethernet frame structure

sending adapter encapsulates IP datagram (or other network layer protocol packet) in Ethernet frame

preamble:

- 7 bytes with pattern 10101010 followed by one byte with pattern 10101011
- used to synchronize receiver, sender clock rates

Ethernet frame structure (more)

- *addresses:* 6 byte source, destination MAC addresses
  - if adapter receives frame with matching destination address, or with broadcast address (e.g. ARP packet), it passes data in frame to network layer protocol
  - otherwise, adapter discards frame
- *type:* indicates higher layer protocol (mostly IP but others possible, e.g., Novell IPX, AppleTalk)
- *CRC:* cyclic redundancy check at receiver
  - error detected: frame is dropped

Ethernet: unreliable, connectionless

- *connectionless:* no handshaking between sending and receiving NICs
- *unreliable:* receiving NIC doesnt send acks or nacks to sending NIC
  - data in dropped frames recovered only if initial sender uses higher layer rdt (e.g., TCP), otherwise dropped data lost
- Ethernet's MAC protocol: unslotted *CSMA/CD wth binary backoff*

802.3 Ethernet standards: link & physical layers

- *many* different Ethernet standards
  - common MAC protocol and frame format
  - different speeds: 2 Mbps, 10 Mbps, 100 Mbps, 1Gbps, 10G bps
  - different physical layer media: fiber, cable



Link layer, LANs: outline

5.1 introduction, services

5.2 error detection, correction

5.3 multiple access protocols

5.4 LANs

- addressing, ARP
- Ethernet
- switches
- VLANS

5.5 link virtualization: MPLS

5.6 data center networking

5.7 a day in the life of a web request

Link Layer Switches

Section 5.4.3

Ethernet switch

- link-layer device: takes an *active* role
  - store, forward Ethernet frames
  - examine incoming frame's MAC address, selectively forward frame to one-or-more outgoing links when frame is to be forwarded on segment, uses CSMA/CD to access segment
- *transparent*
  - hosts are unaware of presence of switches
- *plug-and-play, self-learning*
  - switches do not need to be configured

Switch: *multiple* simultaneous transmissions

- hosts have dedicated, direct connection to switch
- switches buffer packets
- Ethernet protocol used on *each* incoming link, but no collisions; full duplex
  - each link is its own collision domain
- *switching:* A-to-A' and B-to-B' can transmit simultaneously, without collisions



switch with six interfaces (1,2,3,4,5,6)

Switch forwarding table

Q: how does switch know A' reachable via interface 4, B' reachable via interface 5?

- A: each switch has a switch table, each entry:
  - (MAC address of host, interface to reach host, time stamp)
  - looks like a routing table!

Q: how are entries created, maintained in switch table?

- something like a routing protocol?



switch with six interfaces (1,2,3,4,5,6)

Switch: self-learning

- switch *learns* which hosts can be reached through which interfaces
  - when frame received, switch "learns" location of sender: incoming LAN segment
  - records sender/location pair in switch table



MAC addr	interface	TTL
A	*1*	*60*

Switch table (initially empty)

Switch: frame filtering/forwarding

when frame received at switch:

1. record incoming link, MAC address of sending host
2. index switch table using MAC destination address
3. if entry found for destination
   then {
   if destination on segment from which frame arrived
   then drop frame
   else forward frame on interface indicated by entry
   }
   else flood /* forward on all interfaces except arriving interface */

Self-learning, forwarding: example

- frame destination, A', locaton unknown: *flood*
- destination A location known: selectively send on just one link



MAC addr	interface	TTL
A	*1*	*59*
A'	*4*	*60*

switch table (initially empty)

Interconnecting switches

- switches can be connected together



Q: sending from A to G - how does S_1 know to forward frame destined to F via S_4 and S_3?

- A: self learning! (works exactly the same as in single-switch case!)

Self-learning multi-switch example

Suppose C sends frame to I, I responds to C



- Q: show switch tables and packet forwarding in S_1, S_2, S_3, S_4

Institutional network