

GitButler CLI Cheat Sheet

Essential commands for working with GitButler

GitButler is a Git client that allows you to work on multiple branches simultaneously. This cheat sheet features the most important and commonly used GitButler CLI commands for easy reference.

Setup and Teardown

Switching to and from GitButler branch management

```
but setup
```

Switch to GitButler in the current repository

```
but teardown
```

Go back to vanilla git branch management

Branch Management

Create and manage parallel and stacked branches

```
but branch
```

List all branches available

```
but branch new [name]
```

Create a new parallel branch

```
but branch new [name] --anchor [branch]
```

Create a new stacked branch from an existing branch

```
but apply [branch]
```

Apply (enable) a branch to your working directory

```
but unapply [branch|id]
```

Unapply (disable) a branch from your working directory

Inspection

View your workspace state and changes

```
but status
```

Show uncommitted changes, applied branches, and commits

```
but status -fv
```

Show committed files, IDs, authors, and timestamps

```
but diff
```

Show uncommitted changes and their file and hunk IDs

```
but show [id]
```

Show details for a commit or branch

Committing Changes

Create commits on your branches

```
but commit -b [branch] -m "[message]"
```

Commit all uncommitted changes; create the branch if needed

```
but commit -b [branch] -m  
"[message]" [change-id]...
```

Commit selected files or hunks from but diff

GitButler CLI Cheat Sheet

Remote Operations

Push changes and interact with forges

```
but push [branch]
```

Push one branch to its remote

```
but pull
```

Update the target and rebase all applied branches

```
but pr new [branch] -t
```

Push a branch or stack and create its reviews

```
but config forge
```

View and modify forge authentications

Conflict Management

Resolve conflicts in commits

```
but resolve [commit]
```

Enter resolution mode for a conflicted commit

Operations Log

View and restore workspace history

```
but undo
```

Undo the last operation

```
but oplog
```

Show operation history of workspace

```
but oplog restore [oplog-sha]
```

Restore workspace to a specific snapshot

Helper Commands

Open GitButler and configure terminal integrations

```
but gui
```

Open the GUI to the current project

```
but alias
```

Create and manage aliases for commonly used commands

```
but config
```

View and modify GitButler configuration settings